

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
L 6331

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Public Lands Exploration Co., Inc.	8. Farm or Lease Name State
3. Address of Operator P. O. Box 29119, Dallas, Texas 75229	9. Well No. 3
4. Location of Well UNIT LETTER C 500 FEET FROM THE North LINE AND 2310 FEET FROM THE West LINE, SECTION 15 TOWNSHIP 11N RANGE 25E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, KT, GR, etc.) 4515.8' GL	12. County Guadalupe

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOBS ☒ OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 11" hole at 1:30 PM 3-12-80. TD 30'. Ran 30' of 8 5/8" 32# casing and cemented from TD to surface with 10 sacks of neat cement containing 2% calcium chloride. Drilled 7 7/8" hole to 431' TD. Ran 429.98' of 4 1/2" 10.5# K-55 casing. Installed notched guide shoe on bottom of casing. Cemented casing as follows: Pumped 20 bbls. of gelled 2% KCl water containing 1 gallon of marflow, 75 sacks of Class "H" cement containing 0.5% Halad 9 and 75 sacks of Class "H" cement containing 2% calcium chloride. Landed plug at 10:00 PM. Circulated out 30 sacks. Pressure tested casing to 600 psig for 30 minutes. Casing held OK.

10311
MAY 23 1980
C. J. JOY
SANTA FE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles C. Joy TITLE Agent DATE May 16, 1980

APPROVED BY Carl Velazquez TITLE STAFF, REGIONAL GEOLOGIST DATE 5/23/80

CONDITIONS OF APPROVAL, IF ANY: