

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-73

5a. Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.  
L 6331

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-401) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐  
2. Name of Operator  
Public Lands Exploration Co., Inc.  
3. Address of Operator  
P. O. Box 29119, Dallas, Texas 75229  
4. Location of Well  
UNIT LETTER D 330 FEET FROM THE North LINE AND 990 FEET FROM  
THE West LINE, SECTION 15 TOWNSHIP 11N RANGE 25E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name  
State

9. Well No.  
5

10. Field and Pool, or Wildcat  
Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)  
4495.5 GL

12. County  
Guadalupe

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐  
PLUG AND ABANDON ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIATION WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOBS ☒  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded an 11" hole at 2:00 PM 4-15-80. TD 27'. Ran 27' of 8 5/8" 32# casing and cemented from TD to surface with 10 sacks of neat cement containing 2% calcium chloride. Drilled 7 7/8" hole to 454' TD. Ran 450.37' of 4 1/2" 10.5# K-55 casing. Installed notched collar on bottom of casing. Cemented casing as follows: Pumped 20 bbls. of gelled 2% KCl water containing 1 gallon of marflow, 15 bbls. of 2% KCl water, 100 sacks of Class "H" cement containing 0.5% Halad-9 and 140 sacks of Class "H" cement containing 2% calcium chloride. Landed plug at 2:30 PM April 23, 1980. Circulated out 45 sacks. Pressure tested casing to 600 psig for 30 minutes. Casing held OK.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles C. Jorg TITLE Agent DATE May 19, 1980

APPROVED BY Carl Vilvoog TITLE LOGGIST DATE 6/16/80  
CONDITIONS OF APPROVAL, IF ANY: