

DATE RECEIVED	
DISTRIBUTION	
SANTAFE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

1770-1771

54115

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
Name of Operator		8. Farm or Lease Name	
Public Lands Exploration Co., Inc.		Beryl	
Address of Operator		9. Well No.	
4835 LBJ Freeway, Suite 635, Dallas, Texas 75234		1	
Location of Well		10. Field and Pool, or Wildcat	
UNIT LETTER <u>K</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>1950</u> FEET FROM THE <u>West</u> LINE, SECTION <u>8</u> TOWNSHIP <u>11N</u> RANGE <u>26E</u> NMPM.		Wildcat	
11. Elevation (Show whether DF, RT, GR, etc.) 4762.0' GL		12. County	
		Guadalupe	

[illegible]

FORM REMEDIAL WORK	<input type="checkbox"/>	PLUG AND ABANDON	<input type="checkbox"/>	REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>			COMMENCE DRILLING OPNS.	<input type="checkbox"/>	PLUG AND ABANDONMENT	<input checked="" type="checkbox"/>
REPAIR OR ALTER CASING	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>	CASING TEST AND CEMENT JOBS	<input type="checkbox"/>		
OTHER _____	<input type="checkbox"/>			OTHER _____	<input type="checkbox"/>		

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 1:00 PM September 14, 1980. Drilled 11" hole to 26' TD. Ran 26' of 8 5/8" 23# casing and cemented with 5 sacks of neat cement containing 2% calcium chloride from TD to surface. Drilled well to 1050' TD with a 7 7/8" bit. Received permission to plug well from Mr. Carl G. Ulvog on January 15, 1981. His instructions were to set an 87 sack cement plug from 1050' TD back to 746' and a 12 sack plug from 40' to surface. Unable to get drill pipe below 1,000'. Set a 95 sack plug from 1000' back to 670' and a 12 sack plug from 40' to surface. Finished plugging operations March 7, 1981. Installed steel marker and covered pit. Location is ready for inspection.

Cored well as follows: 762'-788', 788'-814', 814'-840' and 921'-940'.

APPROVED

hereby certify that the information above is true and complete to the best of my knowledge and belief.

Charles @ Joy TITLE Agent DATE April 7, 1981

ROY E JOHNSON TITLE DATE 8-7-81

CONDITIONS OF APPROVAL, IF ANY: