

AS APPLIED RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSULTATION DIVISION  
P.O. BOX 18  
SANTA FE, N.M. 87501

NOV 08 1981

Form O-103  
Revised 10-1-79

SIGNATURE	
State <input type="checkbox"/>	File <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR FILL BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT TO DRILL OR FILL BACK TO A DIFFERENT RESERVOIR" FOR SUCH PROPOSALS.

OIL WELL <input checked="" type="checkbox"/>	CAB WELL <input type="checkbox"/>	OTHER <input type="checkbox"/>	7. Well Agreement Name
1. Name of Operator Public Lands Exploration Co., Inc.			8. Farm or Lease Name Beryl
3. Address of Operator 4835 LBJ Freeway, Suite 635, Dallas, Texas 75224			9. Well No. 2
4. Location of Well UNIT LETTER I 1650 FEET FROM THE South LINE AND 990 FEET FROM THE East LINE SECTION 8 TOWNSHIP 11N RANGE 26E NADP.			10. Field and Pool, or Wildcat Wildcat
11. Elevation (Show whether DE, RT, GR, etc.) 4759.0' GT			12. County Guadalupe

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 4:00 PM on October 27, 1980. Drilled 11" hole to 27'. Ran 27' of 8 5/8" 32# casing and cemented with 9 sacks of neat cement from TD to surface. Drilled well to 975' with a 7 7/8" bit. Received permission to plug well from Mr. Carl G. Ulvog on November 10, 1980. His instructions were to set a 50 sack cement plug from 950' back to 775' and a 14 sack from 40' to surface. Drill pipe was run to 950' and a 50 sack cement plug set from 950' back to 775'. A 14 sack plug was set from 40' to surface. Cementing operations completed Nov. 11, 1980. Installed steel marker and covered pit. Location is ready for inspection.

Cored well as follows: 815'-839', 839'-864', 864'-874', 874'-900' and 900'-921'.

APPROVED

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles C. [Signature]TITLE AgentDATE April 7, 1981APPROVED BY Roy E. JohnsonTITLE MINING ENGINEERDATE 8-7-81

CONDITIONS OF APPROVAL, IF ANY: