

OIL CONSERVATION DIVISION

P. O. BOX 2011

SANTA FE, NEW MEXICO 87501

Form O-103
Revised 10-1-70

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
MAY 01 1981

1. Title Type of Lease	
2. State Oil & Gas Lease No.	

LG 5209

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR THE RELEASE OF TITLE OR TO LEASE OR TO CONVEY TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO RE-LEASE OR TO RE-CONVEY TO A DIFFERENT RESERVOIR.)

3. Unit Agreement Name	
4. Field or Lease Name	Karen - State
5. Well No.	3
6. Field and Pool, or Wildcat	Wildcat
7. Unit Agreement Name	
8. Field or Lease Name	
9. Well No.	
10. Field and Pool, or Wildcat	
11. Elevation (Show whether DF, RT, GL, etc.)	4825.0' GL
12. County	Guadalupe

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK	<input type="checkbox"/>	PLUG AND ABANDON	<input type="checkbox"/>	REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>	COMMENCE DRILLING OPNS.	<input type="checkbox"/>	PLUG AND ABANDONMENT	<input checked="" type="checkbox"/>
NULL OR ALTER CASING	<input type="checkbox"/>	OTHER	<input type="checkbox"/>	CASING TEST AND CEMENT JOBS	<input type="checkbox"/>		
				OTHER			

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 2:00 P.M. on October 5, 1980. Drilled 11" hole to 16'. Ran 16' of 8 5/8" 23# casing and cemented with 5 sacks of neat cement from TD to surface. Drilled well to 900' TD with a 7 7/8" bit. Received permission to plug well from Mr. Carl G. Ulvog on October 13, 1980. His instructions were to set a 50 sack cement plug from 873' back to 696' and a 13 sack plug from 40' to surface. Ran drill pipe to 875' and set a 50 sack cement plug from 875' back to 698'. A 13 sack plug was set from 40' back to surface. Plugging operations completed October 15, 1980. Installed steel marker and covered pit. Location is ready for inspection.

Cored well as follows: 653'-675', 730'-755', 755'-768', 768'-795' and 795'-820'.

APPROVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

WITNESSED BY Charles E. Day TITLE Agent DATE April 7, 1981APPROVED BY Roy E. Johnson TITLE Anderson, Carl G. Jr. DATE 8-7-81

CONDITIONS OF APPROVAL IF ANY: