

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name Pooling Application Pending
2. Name of Operator O. H. Berry		8. Farm or Lease Name Tucumcari FNB
3. Address of Operator Suite 188, One Marienfeld Place, Midland, TX 79701		9. Well No. 1-X
4. Location of Well UNIT LETTER <u>P</u> <u>710</u> FEET FROM THE <u>East</u> LINE AND <u>660</u> FEET FROM THE <u>South</u> LINE, SECTION <u>20</u> TOWNSHIP <u>8-N</u> RANGE <u>22-E</u> NMPM.		10. Field and Pool, or Wildcat Wildcat
11. Elevation (Show whether DF, RT, GR, etc.) 4799 GL		12. County Guadalupe

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPER. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

It is proposed to set a wireline cast iron bridge plug at 2700' inside 5-1/2" casing and dump 30' of cement on top of bridge plug. A 10' cement plug will then be placed at the top of the 5-1/2" casing string and an appropriate metal marker will be installed at the surface. This work will be performed in consort with other operators plugging programs in this area as soon as possible.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED O. H. Berry TITLE Operator DATE 10 January 1986
APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 1/16/86
CONDITIONS OF APPROVAL, IF ANY: