

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<p align="center"><b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</p>		<p>5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/></p>
<p>1. Name of Operator McClellan Oil Corporation</p>		<p>5. State Oil &amp; Gas Lease No. Fee</p>
<p>2. Address of Operator P. O. Drawer 730, Roswell, New Mexico 88202</p>		<p>7. Unit Agreement Name</p>
<p>3. Location of Well UNIT LETTER <u>I</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>31</u> TOWNSHIP <u>11 N</u> RANGE <u>22 E</u> NMPM.</p>		<p>8. Farm or Lease Name Burner Fee</p>
<p>15. Elevation (Show whether DF, RT, GR, etc.)</p>		<p>9. Well No. 2</p>
<p>12. County Guadalupe</p>		<p>10. Field and Pool, or Wildcat Wildcat</p>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 5-2-84 Move in Cortez Cable Tool. Spud with 14" bit.
- 5-15-84 Ran 337' of 10-3/4" casing and mudded in to shut off water and cavings. Drilled with 10" bit.
- 5-25-84 Drilled to 687'. Pulled 10-3/4" casing. Ran 685' of 8-5/8", 24 lb/ft casing. Cemented with 250 sx Pace Setter Lite and 100 sx Class "C" with 2% CaCl<sub>2</sub>. Circulated 50 sx. WOC - 18 hrs. Drilled out with 8" bit.
- 6-04-84 Drilling at 1007'. Hole carrying 800' of water from Glorieta. Prep to rig down cable tools and move in Rotary.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Paul Kagsdale</u>	TITLE <u>Operations Manager</u>	DATE <u>June 5, 1984</u>
APPROVED BY <u>Roy E. Johnson</u>	TITLE <u>MANAGER</u>	DATE <u>6-11-84</u>

CONDITIONS OF APPROVAL, IF ANY: