

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator McClellan Oil Corporation	8. Form or Lease Name Burner Fee
3. Address of Operator P.O. Drawer 730, Roswell, NM 88202	9. Well No. 3
4. Location of Well UNIT LETTER <u>F</u> <u>2310</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>19</u> TOWNSHIP <u>11-N</u> RANGE <u>22-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4904' G.L.	12. County Guadalupe

### Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☒  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☒  
OTHER ☐

ALTERING CASING ☒  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6/13/85: Drilling to TD at 5411' with 7-7/8" bit. Ran Dresser Atlas Gamma Ray-Neutron Log to correlate zones. Circulate hole for logs.

6/14/85: Logged with Schlumberger CNL-LDT-DLL-MSFL.

6/15/85: Circulated hole for DST's.

6/16/85: Ran DST #1.

6/17/85: Ran DST #2. & #3.

6/18/85: Ran DST #4 & #5 & #6.

6/19/85: Ran D.P. in hole to 5410'. Set a 25 sx plug at TD. Layed down D.P. Ran 77 joints of 4-1/2" casing with formation packer shoe to 3215'. Set shoe (holding). Cemented using Halliburton with 410 sx Class "C" with 2% CaCl, 2/10 of 1% CFR-2, 2/10 of 1% Hallad 4. Plug down at 6:30 pm. Released rig. Waiting on completion unit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mitch Lee TITLE Production Engineer DATE 6/20/85  
APPROVED BY \_\_\_\_\_ TITLE FOR DATE 7-2-85  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_