

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1950, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-019-20096

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
LABRADOR OIL COMPANY

3. Address of Operator
400 NORTH ST. PAUL, SUITE 400, DALLAS TEXAS 75201

4. Well Location
Unit Letter F : 1795 Feet From The NORTH Line and 1895 Feet From The WEST Line

Section 32 Township 7N Range 23E NMPM SENW County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

GROUND-4642'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

DRILL 12-14" HOLE TO RKB 2889.' RAN 47 JTS N-80 47LB 9-5/8" CASING PLUS 26 JTS OF 47. 1
P-110 CAING BUTRESS TREAD. TOTAL LENGTH OF STRILG2885.76 PLUS FS AND FC2.75 OR TOTAL
OF 2888.51'. LAND CASING W/SHOE AT 2886. RKB FC AT 2804.39' CEMENT WITH 750 SAKS OF 35/65
002 H 12.4 PPG, TAIL WITH 300 SAKS C AT 14.8 PPG, DISPLACE WITH 205 BBLS WATER, BUMP
PLUG WITH 1200 PSI, FLOAT HELD CIP 4 HRS RELEASE AT 5 am 9-30-94 RECOVERED 161 SAKS AT
SURFACE-WOC 20 HRS. NIPPLE UP- RUND IN AND TAG CEMENT 2821' DRILL TO SHOE AT 2882'
CLOSE FRAMS AND PRESSURE UP TO 1300 PSI FOR 30 MIN.NO LOSS-DRILL SHOE AND I JT.
TEST SEAT AND FORMATION WITH EQUILANT 13 LBS MUD NO BREAKDOWN- DRILL ON

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Billy M. Johnson TITLE COMPANY MAN DATE 10-1-91

TYPE OR PRINT NAME BILLY M. JOHNSON TELEPHONE NO. 214-855-0111

This space for State Use

APPROVED BY Ry E. Johnson TITLE DISTRICT SUPERVISOR DATE 11-8-91

CONDITIONS OF APPROVAL, IF ANY