

...Depth Cleaned Out.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 6983 feet, and from feet to feet
 Cable tools were used from None feet to feet, and from feet to feet

PRODUCTION

Put to Producing Nonproductive, 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
 Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.		T. Devonian.		T. Ojo Alamo.	
T. Salt.		T. Silurian.		T. Kirtland-Fruitland.	
B. Salt.		T. Montoya.		T. Farmington.	
T. Yates.		T. Simpson.		T. Pictured Cliffs.	
T. 7 Rivers.		T. McKee.		T. Menefee.	
T. Queen.		T. Ellenburger.		T. Point Lookout.	
T. Grayburg.		T. Gr. Wash.		T. Mancos.	
T. San Andres.	1278	T. Pre-Cambrian	6832	T. Dakota.	
T. Glorieta.	1772	T.		T. Morrison.	
T. Yeso Yeso.	2040	T.		T. Penn.	
T. Tubbs.	3130	T.		T.	
T. Abo.		T.		T.	
T. Penn.	5258	T.		T.	
T. Miss.		T.		T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	660	660	Shale and sand	5990	6700	710	Shale, sand & dolomite
660	740	80	Shale and lime	6700	6815	115	Shale, sd., li. & dolomite
740	1105	365	Shale and sand	6815	6820	5	Shale, sand, & chert
1105	1120	15	Shale and lime	6820	6840	20	Shale, sand, li., & dolomite
1120	1278	158	Shale and sand	6840	6890	50	Shale, sd., li., dolo., & granite wash
1278	1660	382	Anhydrite, dolomite & Sh.	6890	6930	40	Shale, sd., dolo. & granite wash
1660	1772	112	Shale, sd., dolo., & anhy.	6930	6983	53	Shale, sd., & dolomite
1772	1950	178	Shale and sand				
1950	2145	195	Sand, anhy., sh., & dolo.				
2145	2400	255	Shale, dolomite & anhy.				
2400	2580	180	Shale, sand, & anhy.				
2580	2660	80	Shale, sd., dolo. & anhy.				
2660	2900	240	Shale and sand				
2900	3240	340	Shale, sd., anhy., & dolo.				
3240	4095	855	Shale and sand				
4095	4160	65	Shale, sd., dolo. & granite wash				
4160	4440	280	Shale and sand				
4440	4590	150	Shale, sd. & granite wash				
4590	4770	180	Shale and sand				
4770	5340	570	Shale, sd., dolo. & granite wash				
5340	5670	330	Shale and sand				
5670	5990	320	Shale, sand & granite wash				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

December 2, 1958

(Date)

Company or Operator General Crude Oil Company

Address 314 Commerce Bldg., Abilene, Texas

Name F. A. Hunter

Position or Title Area Production Superintendent