NO. OF COPIES RECEIVED			Form C-193
DISTRIBUTION			Supersedes Old
SANTA FE	NEW MEXICO OIL CONS	SERVATION COMMISSION	C-102 and C-103
FILE		2 3 1.62	Effective 1-1-65
U.S.G.S.		. W O 1810	5a. Indicate Type of Lease
LAND OFFICE	1	مومات والمتعم ومراك المحامد مصور وي	State Fee X
OPERATOR		and the second s	5. State Oil & Gas Lease No.
	J	A. 网络 66	5, State Off & Gas Lease No.
SUNDA	RY NOTICES AND REPORTS ON	WELLS	
USE "APPLICAT	OPOSALS TO DRILL OR TO DEEPEN OR PLUG I TON FOR PERMIT -" (FORM C-101) FOR SUC	BACK TO A DIFFERENT RESERVOIR. CH PROPOSALS.)	
OIL GAS WELL	other. Junked & Ab	andoned	7. Unit Agreement Name
2. Name of Operator			8. Farm or Lease Name
McClellan Oil Corporation			Driggers Fee
3. Address of Operator			9. Well No.
P.O. Drawer 730, F	Roswell, New Mexico	88202	1
	1000	• • • •	10. Field and Pool, or Wildcat
UNIT LETTER G 1980 FEET FROM THE NORTH LINE AND 1980 FEET FROM			Wildcat
THE East LINE, SECTION	DON 22 TOWNSHIP 11N	RANGE 21E NMPM.	
	15. Elevation (Show whether	DE RT CP ct-1	
	5091' D.F.	Dr, K1, GK, etc.)	12. County Guadalupe
Check A	Appropriate Box To Indicate N	lature of Notice Report of Orl	her Date
NOTICE OF IN	TENTION TO:	SUBSEQUENT	REPORT OF:
PERFORM REMEDIAL WORK		<u></u>	
TEMPORARILY ABANDON	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
PULL OR ALTER CASING		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	
OTHER		OTHER	
			• •
17. Describe Proposed or Completed Op	erations (Clearly state all pertinent deta	ils, and give pertinent dates, including	estimated date of starting any proposed
work) SEE RULE 1103.		, , , , , , , , , , , , , , , , , , , ,	starting any proposed
Duo to dunk du kal	1 1		
Due to junk in hole and drilling outside of existing 9-5/8" casing, this test			
was prugged and abandoned March 20, 1982 as per notice filed 3/19/82 and			
verbal permission	from OCD, Santa Fe.		•
	_	•	
Well was Plugged as follows:			
40 sx plug at T	.D. 2061'		
30 sx plug at 1760' (inside & outside 9-5/8" casing stub) 30 sx plug at 270' (inside and outside 13-3/8" casing.)			
30 sx plug at 2	70' (inside and out	side 13-3/8" casing.	
to sx plug at s	urtace.		
Heavy mud betwe	en all plugs. Will	set dry hole marker	and restore surface
as near possibl	e to original condit	ion.	and rescore surrace
			•
18 I hereby contifu that the 1-f			
18. I hereby certify that the information	above is true and complete to the best o	f my knowledge and belief.	
1.10/.1			÷
SIGNED BULL KUGS	Colimptitude Op	erations Manager	DATE 3/22/82
0 0/11	B. Carrier		
Carl C	reconstruction of the second o	en e	2 13 00
IPPROVED BY	TITLE		DATE 3-23-82
CONDITIONS OF APPROVAL, IF ANY:			