

NEW MEXICO OIL CONSERVATION COMMISSION
MISCELLANEOUS REPORTS ON WELLS

Form C-103
Driggers No. 1

Cities Service Production Company

Driggers No. 1 was drilled to 4578' Granite. PBTD 1849'. Nine Drill Stem Tests were run, the well was logged to T.D., 1812-1835 (23') Perf. and acidized w/2500 gal. Swabbed w/no evidence of oil or gas in commercial quantity. The hole was loaded w/approx. 10# mud. Set 25 sx plug 2240-2300' (base of 9 5/8" csg. @ 2275'), ran 9 5/8" cast iron drillable bridge plug set @ 1850'. Ran free point and shot off 9 5/8" csg. @ 1740'. Pulled 58 jts. and 1-10' nipple, 9 5/8" csg. (1740'). The following plugs were set: 30 sx cement 1712-1760' (Stub 9 5/8"); 30 sx cement 240-270' (base of 13 3/8"); and 15 sx cement @ top w/marker. Plugged was witnessed by Stanley E. Woodruff, Asst. Production Foreman, Box 126, Eunice, New Mexico (Cities Service Oil Co.), and E. G. Shivers, Tool Pusher, Makin Drlg. Co., P. O. Box 1628, Hobbs, New Mexico. Plugging was completed 5-21-58. The location has been cleared of all debris; cellar and pits have been filled; and the location is ready for inspection. Clean-up was completed October 23, 1958.