

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

May 21, 1958  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Cities Service Production Company

Driggers

Well No. 1

in G

(Company or Operator)

Lessee

(Unit)

SW 1/4 NE 1/4 of Sec. 22

T. 11-N

R. 21-E NMPM,

Wildcat

Pool

Guadalupe

County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was drilled to 4578' granite. It was plugged back to 1849'. Set 25 sx. plug 2240 to 2300 (base of 9 5/8" csg. @ 2275), ran 9 5/8" cast iron drillable bridge plug set @ 1850. Ran free point and shot off 9 5/8" csg. @ 1740'. Pulled 58 jts. and 1 -10' nipple, 9 5/8" csg. (1740').

Nine Drill Stem test were run, the well was logged to T.D., 1812-1835 (23') Perf. and acidized w/2500 gal. Swabbed w/no evidence of oil or gas in commercial quantity.

It is proposed to plug and abandon this well by spotting 30 sx cement plug 1712-1760 (Stub 9 5/8"), 30 sx cement plug 240-270 (base 13 3/8") and 15 sx cement top plug with a marker. It is proposed to clean-up the location in an approved manner when the pits are dry and the work can be done. Verbal approval received May 16, 1958.

Approved May 26, 1958  
Except as follows:

Cities Service Production Company

(Company or Operator)

By

Position

Dist. Supt.

Send Communications regarding well to:

Name

G. E. Ceyer

Address

Box 97, Hobbs, New Mexico

Approved

OIL CONSERVATION COMMISSION

By

Title