

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

RECEIVED

G 1972

5a. Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.

L-462

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- Dry hole

2. Name of Operator  
Glenn Oil Company 213-9859954

3. Address of Operator  
P. O. Box 2126 North Hollywood, California 91602

4. Location of Well  
UNIT LETTER \_\_\_\_\_ FEET FROM THE \_\_\_\_\_ LINE AND \_\_\_\_\_ FEET FROM  
THE SW $\frac{1}{4}$  of NW $\frac{1}{4}$  LINE, SECTION 2 TOWNSHIP 15N RANGE 32E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

State

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)

12. County

Harding

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Permission is requested to plug and abandon as a dry hole the above captioned well on or about the 15th day of February 1972.

Plugging procedure will be as follows: The well has 10-3/4" surface csg. set at 400' and cemented w/300 sacks which will be left in the hole. 8-5/8" casing is set at 625' the total depth of the hole, which will be pulled if possible. A 250' cement plug will be put in the bottom of the hole bringing the cement up into the surface casing at least 25' and then the hole will be bridged at 15' and cemented to the top. The rig will be removed from the location, pits filled, debris cleaned up and location leveled to the satisfaction of the NMOCC and the landowner.

*Fill space between cement plugs with heavy mud.*

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE Agent

DATE 2-12-72

APPROVED BY

TITLE

*Oil & Gas Inspector*  
*District IV*

DATE

2/17/72

CONDITIONS OF APPROVAL, IF ANY: