

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	<input checked="" type="checkbox"/>
CHGO.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

6. Name of Operator Conley & Associates, Inc.		7. Unit Agreement Name	
8. Farm or Lease Name Arthur Cain		9. Well No. # 3	
10. Field and Pool, or Wildcat Wildcat		11. County Harding	
12. Elevation (Show whether DF, RT, GR, etc.) 4320 GL. (topo)		13. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☒
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work, SEE RULE 1103.

Formerly permitted as New Mexico 30-201-20009
Spud date was March 9, 1976. The well was drilled with rotary to a depth of 1172'
no productive zones encountered. This well was to be plugged and abandoned June 9, 1976.
However on June 11, the contractor could not pull 3 1/2" NX casing 510 in the hole. Dowell
pumped 5 sacks of cement to 510' displaced with water cement set up below casing. Two
hours later they again pumped 5 sacks cement to 510', displaced with water, the cement went
up around the pipe and when pressure released some cement came back up inside the pipe there-
fore a plug is at 510'. K & K Drilling tore down and left hole open. On Aug, 19th 1976
150' of NX casing was pulled by Spencer well service. Then Dowell pumped 2 barrels of cement
to 150 feet followed with 6 barrels of water. Then a rubber plug was pushed 22 feet
and the hole filled with class A cement. The pits were filled on August 20, 1976.
The location was cleaned and leveled on August 20, 1976. Marker was made and set by
Jim Wright on August 20th.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Jack F. Conley</u>	TITLE <u>President</u>	DATE <u>8-21-76</u>
APPROVED BY <u>Carl Ulvog</u>	TITLE <u>SENIOR PETROLEUM GEOLOGIST</u>	DATE <u>7/7/77</u>
CONDITIONS OF APPROVAL, IF ANY:		