

CEMENTING SERVICE REPORT

DWL-496-J PRINTED IN U.S.A.

DOWELL

TREATMENT NUMBER

STAGE

DOWELL DISTRICT

DATE

Guymon

8-19-76

WELL NAME AND NO.

Conley State #3

LOCATION-POOL-FIELD

FORMATION

DOWELL REPRESENTATIVE

H.E. JOHNSON

COUNTY

Harding

STATE

New Mexico

NAME Conley Associates Inc

AND

ADDRESS

ZIP CODE

SPECIAL INSTRUCTIONS

Plug TO ABANDON

RIG NAME:

WELL DATA

HOLE SIZE	CASING OR LINER	A	B	C	D
DEPTH	SIZE-WEIGHT	7			
☐ RO ☐ CABLE	TOP				
BHST	BOTTOM				
BHCT	GRADE & THREAD				
BHCT	CAPACITY				

MUD: TYPE

WT.

VISC.

TYPE	DEPTH	TYPE	DEPTH
TYPE	DEPTH	TYPE	DEPTH

☒ TBG ☐ D.P.	HEAD & PLUGS	SQUEEZE JOB	
SIZE	☐ DOUBLE	TOOL	TYPE
WEIGHT	☐ SINGLE	DEPTH	
GRADE	☒ SWAGE	TAIL PIPE:	IN. FT.
THREAD	☒ KNOCKOFF	PERF INTERVAL	FT.
☐ NEW ☐ USED	TOP ☐ R ☐ W		TO
DEPTH	BOT ☐ R ☐ W		TO
CAPACITY	OTHER		TO

PRESSURE LIMIT

PSI

BUMP PLUG TO

PSI

MIN

☐ ROTATE

RPM

☐ RECIPROCAT

FT

☐ CENTRALIZERS NO

TIME	PRESSURE		VOLUME PUMPED	JOB SCHEDULED FOR		ARRIVED ON LOCATION		LEFT LOCATION	
	TBG. OR D.P.	CASING		TIME:	DATE:	TIME:	DATE:	TIME:	DATE:

TIME	TBG. OR D.P.	CASING	VOLUME PUMPED	INJECT. RATE	SERVICE LOG DETAIL
------	--------------	--------	---------------	--------------	--------------------

9:00	0	2	2	2	Rig TRUCK TO well
		60	2	2	START Cement Plug #1 150 FT. 130
					Water

7:20	1		2	2	Set Top Plug @ 22 FT
------	---	--	---	---	----------------------

REMARKS

SYSTEM CODE	NO. OF SACKS	YIELD CU. FT/SK	COMPOSITION OF CEMENTING SYSTEMS		SLURRY MIXED	
					VOL.	WT.
1.	660	1.18	CLASS A		3	15.8
2.						
3.						

BREAKDOWN FLUID	WT.	SACKS MIXED	PUMPED	PRESSURE MAX:	MIN:
☐ HESITATION SO.	☐ RUNNING SO.	CIRCULAT ON LOST	☐ YES ☐ NO	CEMENT CIRCULATED TO SURF.	☐ YES ☐ NO
BREAKDOWN	PSI	FINAL	PSI	CEMENT LEFT IN PIPE:	FT
WASHED THRU	☐ YES ☐ NO	TO	FT	MEASURED	☒ DISPLACEMENT ☐ WIRE LINE
TYPE OF WELL	☐ OIL ☐ GAS	☐ STORAGE ☐ BRINE/WATER	☐ WILDCAT	CUSTOMER REPRESENTATIVE	
DOES CUSTOMER CONSIDER SERVICE:				☐ SATISFACTORY ☐ UNSATISFACTORY ☐ UNKNOWN	

