NO. OF COPIES RECEIVED		Form C-103
DISTRIBUTION		Supersedes Old C-102 and C-103
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	
FILE	RECE	V F D
U.S.G.S.	~	VED Sa. Indicate Type of Lease
LAND OFFICE	.	State X Fee.
OPERATOR	OCT 3.1	1374 5. State Oil & Gas Lease No.
		L-5880
ING NOT USE THIS FORM FOR DAY	Y NOTICES AND REPORTS ON WELLS POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT HESENVICON FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS. A PTESIA -	c. ()))))))))
1.	ON TOWN OF TOTAL PROPERTY OF THE STATE OF TH	7. Unit Agreement Name
OIL X GAS WELL	OTHER-	
2. Name of Operator		8. Farm or Lease Name
Humble Oil & Refi	ning Company	New Mexico "CM" State
3. Address of Operator	Tilly Company	9. Well No.
P. O. Box 1600, Midland, Texas 79701		1
4, Location of Well		10. Field and Pool, or Wildcat
11711	3,040 FEET FROM THE North LINE AND 450	Wildcat
UNIT LETTER	FEET FROM THELINE AND	FEET FROM
East	14 18N 32F	
THE LINE, SECTION	N 14 TOWNSHIP 18N RANGE 32E	NMPM: \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	4,692' GR	Harding
16.		
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data		
NOTICE OF IN	TENTION TO: SUE	SSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUS AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	X PLUG AND ABANDONMENT X
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT .	IQB X
	OTHER	
OTHER		
17. Describe Proposed or Completed Op	erations (Clearly state all pertinent details, and give pertinent date	es. including estimated date of starting any proposed
work) SEE RULE 1103.		
MIRU Spudded 9-7/8" hole at 8:00 A.M. 9-29-71. Drilled to 460', rigged up and ran 448' of 7-5/8" OD 26.4# J-55 casing, set at 456', cemented with 215 sacks, circulated approximately 50 sacks of cement. WOC 18 hours. Tested 7-5/8" casing w/1000 psig		
	est O. K. Resumed drilling and drilled t	to 2,100' TD. Plugged and
abandoned hole as	follows:	
Plug No. 1 25 sx Class "H" Cement from 1,860' to 1,743'.		
Plug No. 2 25 sx Class "H" Cement from 1,550' to 1,443'.		
Plug No. 3 25 sx Class "H" Cement from 1,260' to 1,143'.		
	sx Class "H" Cement from 466' to 49'.	
Plug No. 5 2 s:	x Class "H" Cement from 15' to 0'.	
Placed mud laden	fluid between each plug, installed dry ho	ole marker.
	rang, and ballon dry me	
Job complete at 6	:00 P.M. 10-6-71 FRR & FRW.	
		·
18. I hereby certify that the information	above is true and complete to the best of my knowledge and belief.	
0 - 1 Star 20 1 11 01 11		
SIGNED J. W. Stovall TITLE Proration Specialist DATE 10-14-71		

__ TITLE ____

CONDITIONS OF APPROVAL, IF ANY: