

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
T. Salt _____
B. Salt _____
T. Yates _____
T. 7 Rivers _____
T. Queen _____
T. Grayburg _____
T. San Andres 1630
T. Glorieta 1902
T. ~~Simmons~~ 2377
T. Blinberry _____
T. Tubb 2396
T. Drinkard _____
T. Abo _____
T. Wolfcamp _____
T. Penn. _____
T. Cisco (Bough C) _____

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash 2625
T. Granite _____
T. Delaware Sand _____
T. Bone Springs _____
T. _____
T. _____

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn. "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Qtzte _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	297	297	Sand-Shale	<u>DEVIATION SURVEYS</u>			
297	689	392	Shale	<u>DEPTH</u>	<u>DEGREE</u>		
689	1779	1090	Sand, Shale	297	1/2		
1779	1833	54	Cole	825	1-		
1833	1867	34	Anhy-Lime	1478	1-		
1867	2270	403	Shale-Lime	2048	1 1/2		
2270	2400	130	Sand-Granite	2400	1 1/4		
2400	2670	270	Lime-Sand	The above are true to the best of my knowledge and belief.			
				AREA SUPERINTENDENT			
				Sworn to this date 2-24-72.			
				<u>Blanchard Lee Hunter</u> Notary Public in & for Lea Co. N.M. my Commission 2-5-74			