

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fed <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT WITH FEES FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> CO2 OTHER	7. Unit Agreement Name BDCDGU
2. Name of Operator Amoco Production Company	8. Form or Lease Name BDCDGU 2030
3. Address of Operator P. O. Box 68, Hobbs, New Mexico 88240	9. Well No. 181
4. Location of Well UNIT LETTER H 1980 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 18 TOWNSHIP 20-N RANGE 30-E N.M.P.M.	10. Field and Pool, or wildcat Und. Tubb
15. Elevation (Show whether OF, RT, GR, etc.) 5302' RDB	12. County Harding

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to squeeze non-productive perforations in San Andres, Glorieta, and Yeso formations as follows: Pull tubing, packer, tailpipe, and seating nipple. Set a retrievable bridge plug at approx. 2660' and cap with 10' sand. Set a cement retainer at 2420' and squeeze Yeso perms with 100 sacks class H cement with 2% CaCl₂. Sting out of retainer and dump excess cement on top of retainer. Set a cement retainer at 2010'. Squeeze Glorieta and San Andres perms with 200 sacks class H cement with 2% CaCl₂. Sting out of retainer and reverse out excess cement. Drill out cement retainers and cement. Circulate hole clean with 2% KCL water. Retrieve the retrievable bridge plug at 2660'. Run 2-3/8" tubing and seating nipple. Land tubing at approx. 2720'. Swab the well and shut-in.

0+2-NMOCD, SF 1-Hou 1-Susp 1-CLF 1-Amerada 1-UGI 1-Cities Serv.
1-Conoco 1-CO2 in Action 1-Excelsior 1-Sun. Tex.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Cathy L. Jorman TITLE Assist. Admin. Analyst DATE 4-1-82

APPROVED BY _____ TITLE _____ DATE 4-8-82
CONDITIONS OF APPROVAL, IF ANY: