

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- (CO ₂ Gas)		7. Unit Agreement Name
2. Name of Operator S.E.C. Corporation		8. Farm or Lease Name Mitchell
3. Address of Operator P.O. Box 9737, El Paso, Texas 79987		9. Well No. 16
4. Location of Well UNIT LETTER <u>J</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE. SECTION <u>5</u> TOWNSHIP <u>18 N</u> RANGE <u>30 E</u> NMPM.		10. Field and Pool, or Wildcat <u>So. Bueyeros</u> <u>(Mitchell CO₂)</u>
15. Elevation (Show whether DF, RT, GR, etc.) 4390' G.L. - 4397' K.B.		12. County Harding

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 6 P.M. April 2, 1975, drilled to 164'. Set 155', 8-5/8", 24# casing @ 164'. Cemented w/100 sax cement (Lone Star type "H") w/3% Cal. Chlor. Cement circulated to surface. Pressure plug to 200 psi for 8 hours. W.O.C. 12 hours, pressure test to 600 psi, held OK.

Drilled to 2060'. Set 2056' 4 1/2", 10.5# casing @ 2059'. Cemented w/525 sax cement (50/50 Howco Pozmix) w/4% gel. Cement circulated to surface. Pressure plug to 1000 psi, pressure held @ 1000, plug down @ 6:30 P.M. April 6, 1975. W.O.C. (to complete @ later date).

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>P. J. Bille</u>	TITLE <u>Manager-Tech. Services</u>	DATE <u>April 14, 1975</u>
APPROVED BY <u>Carl Ulvog</u>	TITLE <u>SENIOR PETROLEUM GEOLOGIST</u>	DATE <u>April 16, 1975</u>
CONDITIONS OF APPROVAL, IF ANY:		