

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		



Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-6320
7. Unit Agreement Name
8. Farm or Lease Name Olympic State
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Harding

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Astro-Tex Oil Corporation of New Mexico
3. Address of Operator P. O. Box 112, Cisco, Texas 76437
4. Location of Well UNIT LETTER <u>M</u> <u>660</u> FEET FROM THE <u>West</u> LINE AND <u>660</u> FEET FROM THE <u>South</u> LINE, SECTION <u>27</u> TOWNSHIP <u>16-N</u> RANGE <u>33-E</u> N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 4409 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-7-75 - Hole filled with 10.4 PPG mud - 1480 PPM chloride content 290 PPM calcium - 202 ft. 8-5/8" casing with 200 sacks Class "C" plus 2% KCL D-33 - 475 ft. 4-1/2" FH drill pipe and 5-1/2 FH drill collars - stem up. Squeezed 50 sacks Class "C" - 4% KCL to cement "K" type shoe 500 psi - 4" swedge to 8-5/8" 16# casinghead threads cemented. Marker information welded to head marker. No perforations present. Oil Conseration Commission representative absent at time of plugging.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Stanley J. Ditt TITLE President DATE 8-22-75

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: