

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER- CO ₂	7. Unit Agreement Name Bravo Dome Carbon Dioxide Gas Unit
2. Name of Operator Amoco Production Company	8. Form of Lease Name Bravo Dome Carbon Dioxide Gas Unit
3. Address of Operator P.O. Box 832, Brownfield, TX 79316	9. Well No. 2033 111G
4. Location of well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 11 TOWNSHIP 20N RANGE 33E NMPM.	10. Field and Pool or Block Bravo Dome Carbon Dioxide Gas Unit 640-Acre Area
11. Elevation (Show whether DF, RT, GR, etc.) 4920' GL	12. County Harding

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☒	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to fracture stimulate Tubb Formation to increase production. MIRU SU. Kill well with 2% KCL fresh water with additives. POOH with production equipment. RIH with treating packer and 2 7/8" workstring. Land treating packer at 2150'. Frac well with 40 lb HEC gel, liquid CO₂ and 8/16 Brady sand. Mix gel in 2% KCL fresh water. Shut well in for 1 hour after frac job. Flow well back to flow tank to recover load water overnight. Clean out sandfill to 2574' if necessary. RIH with production equipment. Set packer at 2310'. Load backside with packer fluid and pressure test annulus to 500 psi. Return well to production.

0+3-NMOCD, SF 1-R. A. Sheppard HOU. Rm 20.156 1-T. Thiel HOU. Rm. 3.167 1-DJH
1-Amerada Hess 1-Amerigas 1-Cities Service 1-Conoco 1-Shell 1-Exxon
1-WF, Brownfield 1-WF, Clayton

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED DD Holcomb TITLE Sr. Administrative Analyst DATE 9-17-87
APPROVED BY G. E. Johnson TITLE DISTRICT SUPERVISOR DATE 9-25-87
CONDITIONS OF APPROVAL, IF ANY: