- 1.		A					
. OF COPIC SACCIVED		. *	•				
NOITUBIRTZIO							
SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION					Form C-191		
FILE					Revised [4-6]	:	
U.S.G.S.			1 &	. 17	SA inglesia	Sype of France	
		ADI	30-021	20168		7 —	
LAND OFFICE		rir	311-021	- 0	STATE	i ree X	
OPERATOR			<i>)</i> •		-5. Store Ofi &	Gus Lease No.	
						•	
APPLICAT	ON FOR PERMIT T	O DRILL DEEEEN	02.01.110.014		Millill	THE STATE OF THE	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK							
peu l	ר.				7. Unit Agree	zeni iloze	
b. Type of Tell DRILL	J '	DEEFEN		PLUG BACK	BDCDG	iU	
WELL WELL X	CO2 OTHER				8. Farm or Les	ase Name	
2. Name at Operator	OOL STREE	·	ZUNC X	MULTIPLE Z TYE	BDCDG	11	
Amoco Production Company						9. Weil No.	
J. Accress of Operator						1933 101G	
P. O. Box 68, Hobbs, New Mexico 88240					10. Field and Pool, or Wildest		
	7.				Und.	Tuhh	
WHIT LETT		1650	FEET FROM THE	North	iiiiiii	Titte to	
1980	Esst	······································		FINE	HHHH		
	erme East	INE OF SEC. 10	19-N	. 33-E SMPM			
			imini	.33-E	12. County	aininini.	
	**************************************	X/////////////////////////////////////				illlill	
	W. TANKARTY	William Committee	Hillian Committee	Hillini I	Harding		
	77/////////////////////////////////////					illillilli	
	63/1/1061/11	Million Committee	19. Proposed Desin		77777777		
	//////////////////////////////////////	<i>XIIIIIIIIII</i>			1 2	O. HOLCEY OF C. L.	
4948' OIL CONS	EXVATION DIMANA	& Status Pluga rigori i	2900 1 215. Drilling Contra	Tubb		Rotary	
	SANTA FE Blank	ket on File		ctet	22. Approx. D	ate Wark will start	
			N/A		4th Qua	arter-1983	
	1	PROPOSED CASING AND	CEMENT PROGRA	MA			
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT			± 3 *		
12-1/4"	9-5/8"	THEIGHT PER FOOT	SETTING DEPTH SACKS OF		CEMENT	EST. TOP	
8-3/4"	7"	32.30#	700	Cir		Surface	
	i	15.#-20.#	2900		to 9-5/8'	Surface	
:	ļ				33 3 3/3	Suitace	
	•	•	i .	1	1	•	
Propose to drill and equip well in the Tubb formation. After reaching TD logs will be run							
and evaluated. Perforate and stimulate as necessary in attempting commercial production.							
	· ci ioiace and	scimulate as ne	cessary in a	ttempting co	mmercial c	roduction	
Mud Program:	0-700' Native				•		
		Spud Mud					
, ,	o -in KCL-291	lt Water Gel-St	arch		90	activities	
BOP program atta	ليمام			APPROVAL VALI PERMIT EXPIR	D FOR 10	DAYS	
Gas is not dedic	cnea	•		DEDMIT FXPIR	ES 11-6	79-8-S	
das is not dedic	ated			UNLESS DRI	LING UNDE	RWAY	
				Olych ber en			
O+2 NMOCD CE -	11011 -			· ·			
0+2-NMOCD, SF; 1 1-Cities Service	-HUU R. E. Ogde	n Rm 21.150: 1-	-SUSP: 1-P.19	1-Amerada	1 Ama:===		
1-Cities Service 1-Jim Russell, C	; I-Conoco; 1-C	02 in Action: 1	-Excelsion	1-Sun Too	Ameriga	5;	
1-Jim Russell, C	layton; 1-F. J.	Nash HOU Rm 4	206	- June 16x.	r-cxxon;		
	- •	,	. 200			-	
A HOVE SPACE DESCRIBE PRO	POSED PROGRAM: IF P	ROPASAL IS TO A				•	
TEDW costifus the con-	- PROLALM, IF AMY.		PLUG BACK, GIVE DAI	FA ON PRESENT PRODU	CHA BHOS BYITS	PROPOSED NEW PROPERT	
veny certify that the Information	alove is true and compl	rts to the best of my kno	wiedce and bellet				
ing little	P 1111					,	
		Till- Assistant	Administrati	ve Analyet-	RI	14/82	
(The spect for Se	ate Usen			- / III Y S COM	· Ule		
HOVED ON TOY	onnon	CIL AND	GAS INSPECTOR				
OLTIGHE OF APPROVAL		TITLE	- TOTOK		F	-31-73	
	ru t.t			DA.	TE		

OIL CONSERVATION COMMISSION TO BE NOTIFIED WITHIN 24 HOURS OF BEGINNING OPERATIONS

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C-102 Supersedes C-128 Effective 1-1-65

All distances must be from the outer boundaries of the Section. Operator Lease Well No. 1933101G AMOCO Unit Letter Section Township Range County 10 G T19N R33E HARDING Actual Footage Location of Well: 1650 feet from the NORTH line and feet from the EAST Ground Level Elev: 4948 Producing Formation Dedicated Acreage: Tubb Und. Tubb 160 Acres 1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc? □ No If answer is "yes," type of consolidation _ If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission. CERTIFICATION I hereby certify that the information coi tained herein is true and complete to the best of my knowledge and belief. OIL CONSERVATION DIVISION SANTA FE 1980 Position Assist Amoco Production Company August 29, 1983 I heraby certify that the well-location shows on this plat was plotted from field notes of actual surveys made by me or my supervision, and that the same 190 1320 1650 1980 2310 2000 1500 1000

STANDARD 2000 PS1 W.P. BOP STACK

- 1. Blow-out preventers may be manually operated.
- All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
- Bell nipple above blow-out preventer shall be same size as casing being drilled through.
- Kelly cock to be installed on kelly.
- Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
- Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
- Double or space saver type preventers may be used in lieu of two single preventers.
- BOP rams to be installed as follows:*

Drill pipe or casing rams

Bottom preventer Blind rams

- *Amoco District Superintendent may reverse location of rams. 9. Extensions and hand wheels to be installed and braced at all times.
- 10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

