

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals, and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I

P.O. Box 1983, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-021-20170

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

BRAVO DOME CO2 GAS UNIT

8. Well No.

1933-1616

9. Pool name or Wildcat

BRAVO DOME CO2 GAS UNIT - Tubb

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A

DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"

(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well

OIL WELL ☐

GAS WELL ☐

OTHER

CO2

2. Name of Operator

AMOCO PRODUCTION COMPANY

3. Address of Operator

P.O. Box 303, AMISTAD, NEW MEXICO 88410

4. Well Location

Unit Letter G : 1650 Feet From The NORTH Line and 1650 Feet From The EAST Line  
Section 16 Township 19N Range 33E NMPM HARDING County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

494'S GL

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations

SEE RULE 1103.

(Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)

4/13/98

MIRUSU, kill well with fresh water. Nipple up BOP. Pull and lay down 3-1/2" production tubing and packer. Pick up and run 2-3/8" workstring to 2450'.

4/14/98

Spot 35 sacks of Class C cement @ 2450'. Wait on cement. Lowered tubing and tag top of casing @ 2320'. Pressure tested to 500 psi. Circulate well with mud laden fluid with inhibitor fluid. Spot 25 sacks of Class C cement @ 2046' - 1901'. Spot 5 sacks of Class C cement @ 30'-3'. Cut off wellhead and anchors 3' below ground level. Cap well with steel plate. Install dry hole marker. RDMOSU. Clean and level location.

OK 8/4/98

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE D. J. Holcomb TITLE Field Team Leader

DATE 5/14/98

TYPE OR PRINT NAME D. J. Holcomb

TELEPHONE NO. (505) 374-3010

(This space for State Use)

APPROVED BY K. J. Johnson TITLE DISTRICT SUPERVISOR

DATE 8/10/98

CONDITIONS OF APPROVAL, IF ANY: