40. OF SPRICE RECEIVED		•	•				
OISTRIBUTION		W 1157155 on done-				••	
SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION				21014	Form C-191 Revised 1-1-65		
FILE							
U.S.C.S.					SAL INTICATE TYPE OF LEGUE		
LAND OFFICE 11 20173						Cus Losse No.	
OPERATOR		25	* *			Cus Coase No.	
AGDI IC TICN SOO DESIUE TO DOW						mismin	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK							
j	ד				7. Unii Agres	ment iteme	
b. Type of Well DRILL X		DEEPEN [PL	UG BACK	BDCDG		
WELL WELL IX COZ OTHER SINGLE V					8. Farm or Lease Name		
25 Notes at Operator Zine					9. Well No.	<u>U</u>	
Amoco Production Company 3. Accress of Operator						2640	
						1933 261G	
P. O. Box 68, Hobbs, New Mexico 88240						Und. Tubb	
MAIT LETTER G LOCATED 1650 North					innin	mmmmm	
1650 FEET FOOT							
THE STATE OF THE S	THE EDST	ve of sec. 26	-19-N 10E.	33-E KMP4			
					12. County	THILL	
				<u>illillil</u>	Harding	_ [[]]]]]]	
777777777777XXX	1888188 1890 <u>8</u>	XXX				HIIIIIII	
DESILLILIII			Proposed Depth	19A. Formution			
111111111111111111111111111111111111111	MOERUMON DIM			4	2	O. HOLERY OF C. C.	
4865	KT SANTA FEA- KIE	6 Status i'lug. Bond 21	S. Drilling Contracto	Tubb	122	Rotary	
4865'	Blan	ket on File	N/A	-	4th Ou	arter-1983	
. `	1	PROPOSED CASING AND			1 011 94	ar ter 1505	
SIZE OF HOLE		PROPOSED CASING AND					
12-1/4"	O E /OIL	WEIGHT PER FOOT	SETTING DEPT	H SACKS OF	CEMENT	EST. TOP	
8-3/4"	9-5/8" 7"	32.30#		<u>l</u> Cir	c.	Surface	
		15,#-20,#	2900*	<u> Tieback</u>	to 9-5/8	" Surface	
					İ	•	
Propose to drill and equip well in the Tubb formation. After reaching TD logs will be run and evaluated. Perforate and stimulate as necessary in attempting commercial production. Mud Program: 0-700' Native Spud Mud 700'-TD KCL-Salt Water Gel-Starch							
BOP program atta	chad		÷			70 DAYS	
Gas is not dedic	ated	•			XPIRES	11-29-83	
	a ccu			UNLESS	DRILLING T	JNDERWAY	
0+2-NMOCD, SF; 1 1-Cities Service 1-Jim Russell, C	layton; 1-F. J.	Nash, HOU Rm 4.	EXCEISION; I. 206	1-Amerada; -Sun. Tex.	1-Ameriga 1-Exxon	PROPOSED NEW PRODUC-	
1) from the same of the same o	angive is true and comp	icte to the best of my know	ledge and bellaf.				
and Tette	Sema	Tile Assistant A		_	01	acles	
(lbo sort in)	are the state	Tille Assistant A	dministrative	<u>Analys</u> toa	re _ &	39183	
(Val)							
PROVED BY TOY S JOHNSON TITLE CIL AND GAS INSPECTOR							
MOSTIONS OF APPROVAL		TITLE	O MA PECTOR	DA	TE_ & ~	31-83	
•	OII CONS	ERVATION COMM	USSION TO B	E NOTIFIED)	_	

OIL CONSERVATION COMMISSION TO BE NOTIFIED WITHIN 24 HOURS OF BEGINNING OPERATIONS

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

All distances must be from the outer boundaries of the Section Well No. _ease Leigit 1933261G County Frange R33E **HARDING** EAST 1650 NOR TH ieet irom the line ond Dedicated Acreage: Pool Producing Formation Ground Level Elev. Und. Tubb Acres 4865 Tubb 1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling. etc? If answer is "yes," type of consolidation _ If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission. CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief. 1650 Assist. Admin. Analyst Amoco Production Company August 29, 1983 I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same Certificate No 2000

STANDARD 2000 PS1 W.P. BOP STACK

- 1. Blow-out preventers may be manually operated.
- All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
- Bell nipple above blow-out preventer shall be same size as casing being drilled through.
- 4. Kelly cock to be installed on kelly.
- Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
- 6. Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
- Double or space saver type preventers may be used in lieu of two single preventers.
- 8. BOP rams to be installed as follows:*

Top preventer - Drill pipe or casing rams
Bottom preventer - Blind rams

*Amoco District Superintendent may reverse location of rams.

- 9. Extensions and hand wheels to be installed and braced at all times.
- 10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

:.

