STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

| TO THE OWN TOTAL | |
|------------------------|-----|
| NO. OF COPIED MECEIVED | 1 |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | V |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | - I |

| DISTRIBUTION | P. O. BO | | × 2088 Form C-103 | | |
|--|--|---|---|----------------------|--|
| SANTAFE | SANTA FE, NEW | MEXICO 87501 | | Revised 10-1-73 | |
| FILE | | | Sa. Indicate Type | | |
| U.S.G.S. | | | State | Fue X | |
| OPERATOR | | | 5. State Oil & Ga | s Lease No. | |
| | | | mmm | | |
| SUNDRY JOO NOT USE THIS FORM FOR PROPULE USE MARPILICATE | Y NOTICES AND REPORTS ON POSALS TO DELLE ON TO DELPHIN OF PLUG B | WELLS ACK TO A DIFFERENT RESERVOIR. H PROPOSALS.) | | | |
| CIL GAS | | | 7. Unit Agreemen | t Hanie | |
| WELL WELL WELL | other. Carbon Dioxid | <u>e</u> | 8. Farm or Lease | Name | |
| Etheldred T | . Ross | | Hayoz | | |
| 3. Assress of Operator | | | 9, Well No. | | |
| | <u>6 Panhandle, Texas 79</u> | 068 | #4 | el, or Walded | |
| G. Longtion of well D 66 | O FEET FROM THE North | LINE AND 660 FEET FRO | | | |
| i ! | | | | | |
| THE WEST LINE, SECTION | 14 TOWNSHIP 19N | RANGE JOD NMPH | . [[[[[]]]] | | |
| | 15. Elevation (Show whether | DF, RT, GR, etc.) | 12. County | | |
| | 4490 MSL | | Harding | <u> VIIIIIII</u> | |
| Check A | appropriate Box To Indicate N | | ther Data IT REPORT OF: | | |
| NOTICE OF IN | TENTION TO. | 33532432 | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | | |
| PERFORM REMEDIAL WORK | PLUG AND ABANDON | REMEDIAL WORK | | ING CASING | |
| TEMPGRAPILY ABANDON | | COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JQB | PLUG A | ND ABANDONMENT | |
| PULL OR ALTER CASING | CHANGE PLANS | OTHER Casing report | and cement | job | |
| CTHER | | | | | |
| 17. Describe Francised or Completed Ope | erations (Clearly state all pertinent dete | ails, and give pertinent dates, includin | g estimated date of s | narting any proposed | |
| work) SEE RULE 1103. | | | | | |
| Drilled 12¼ hole t | o a depth of 470 feet. | Set 455 feet of 9 5/8.3 | 61b. surface | pipe. | |
| Cemented with 350 | sacks of 2% Cal. Seal Ce | ement. Circulated approx | :. 20 bbls. in | nto pit. | |
| Drilled 8 3/4 hole | to depth of 2180 feet. | Set 2165.34 feet of / | inch casing. | nnrox. | |
| weight 26 lb. per | foot. Cemented with 500 . Ran Schlumberger Logs- | Compensated Neutron and | Dual Latera | log. | |
| .co ddekb imec pio | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | , | | |
| 16. I hereby certify that the information a | above is true and complete to the best o | f my knowledge and belief. | | | |
| P D R.A. | ^ | 100 A | | 10.06 | |
| SIGNED L J VIGIGIA | | peralor | | 18-86 | |
| - Long 8/2 | DI | STRICT SUPERVISOR | 1- | 27.86 | |