

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-021-20230
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	L5852
7. Lease Name or Unit Agreement Name	
West BDCDGU	
8. Well No.	19
9. Pool name or Wildcat	
West Bravo Dome	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER CO2 Supply	
2. Name of Operator OXY USA Inc.	
3. Address of Operator P.O. Box 50250 Midland, TX. 79710	
4. Well Location Unit Letter F : 1650 Feet From The North Line and 1650 Feet From The West Line Section 7 Township 18N Range 29E NMPM Harding County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5419.3'	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

(See other side)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Stewart TITLE Production Accountant DATE 1/14/91

TYPE OR PRINT NAME David Stewart TELEPHONE NO. 9156855717

(This space for State Use)

APPROVED BY Ry E Johnson TITLE _____ DATE 1-22-91

CONDITIONS OF APPROVAL, IF ANY:

Attachment C-103
OXY USA Inc.
West BDCDGU #19
Sec 7 T18N R29E
Harding County, New Mexico

MICU, Perf Granite Wash w/ 2 SPF @ 3175,76,77,78,97,98,99,3200,01-02,03,04,05,06,07,08,09,10,19,20,21,3222' Total 44 holes w/ .46" w/ 19" penetration. RIH w/ 5 1/2" RTTS, SN, & 2 7/8" tbg, tested tbg to 3000#. Set Rtts @ 3050'. Acidized perfs 3175-3222' w/ 2000 gal 7 1/2% NeFe HCl acid, Max pres-3200#, Min pres-700#, Avg pres-1200#, ISIP-340#, 5min-180#, 10min-150#, 15min SITP-40#. Open well to pit, well dead. Swabbed 37 BLW in 2 1/2 hrs, 400' fluid entry in 30 min, no show of gas. 14 hr SITP-0#, swabbed 24 BLW in 6 1/2 hrs, no show of gas. POOH w/ tbg & RTTS, RU WL & set 5 1/2 CIBP @ 3170', dump 4sx cmt on top, New PBTB-3135'.

Perf Tubb w/ 2 SPF @ 3039,40,41,42,43,44,45,46,47,48,49,50,51,52-53,54,55,56,57,58,59,75,76,77,78,79,3117,18,19,26,27,28,3129' Total 66 holes w/ .46" w/ 19" penetration. RIH w/ 5 1/2 Guiberson Uni VI, 1.781" F profile nipple, on/off tool, & 2 7/8" tbg, set pkr @ 2926'. Swabbed 17 BW in 6 hrs w/ 300-400' fluid entry/hr, no show of gas. 14hr SITP-0#, swabbed 5 BW in 2 hrs, no show of gas. Acidized perfs 3039-3129' w/ 2000 gal 7 1/2% NeFe HCl acid, Max pres-850#, Avg pres-800#, slight vacuum @ end of job. Swabbed 56 BLW in 3 hrs w/ 300-400' fluid entry/ 1/2hr, no show of gas. 40hr SITP-40#, swabbed 14 BLW & 20 BW in 8hrs w/ slight gas cut w/ each run, but no blow after each run. POOH w/ pkr & tbg, RU WL & set 5 1/2 CIBP @ 2980', dump 4sx cmt on top, New PBTB @ 2945'.

Perf Glorieta w/ 2 SPF @ 2403,04,05,06,07,11,12,13,14,15,16,31,35,-39,40,41,42,43,44,49,50,51,52,53,54,55,56,57,58,59,67,68,69,70,71,-72,73,74,75,76,77,78,79,80,81,82,83,84,85,86,2487' Total 102 holes w/ .46" w/ 19" penetration. RIH w/ pkr, prof nip, on/off tool & 2 7/8" tbg, set pkr @ 2306'. 17hr SITP-0#, swabbed 87 BW in 8 hrs, FL constant @ 2000', slight blow of gas after each run. POOH w/ pkr & tbg, RU WL & set 5 1/2 CIBP @ 2330', dump 5sx cmt on top, New PBTB @ 2295'. Spot 10sx cmt @ 2156' & 10sx cmt @ 610'. ND BOP & WH, spot 5sx cmt plug @ surface. Weld plate @ 9 5/8 csg, install dry hole marker, backfill cellar, RDPU. Roy Johnson w/ NMOCD-Santa Fe approved plugging procedure, but did not witness. Well P&A'd 12/6/90.