Submit 3 Copies	State of New Mexico Energy, Minerals, and Natural Resources Department		Form C-103 Revised 1-1-89
to Appropriate District Office	•		
DISTRICT I	OIL CONSERVATION DIVISION		WELL API NO.
P.O. Box 1980, Hobbs, NM 88240	P.O. Box 2088		30-021-20243
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico 87504-2088		5. Indicate Type of Lease STATE FEE
DISTRICT III			6. State Oil & Gas Lease No.
1000 Rio Brazos Rd., Aztec, NM 87410			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"			7. Lease Name or Unit Agreement Name
	(FORM C-101) FOR SUCH PROPOSALS.)		
1. Type of Well	GAS T		BRAVO DOME CO2 GAS UNIT
OL WELL	WELL OTHER	CO2	
2. Name of Operator			8. Well No.
AMOCO PRODUCTION COMPANY			2033-211G
3. Address of Operator P.O. Box 303, AMISTAD,	NEW MEXICO 88410		9. Pool name or Wildcat BRAYO DOME CO2 GAS UNIT
4. Well Location	NEW MEXICO COTTO	.	BRATE BONE OOF GAD ON!
Unit Letter G :	1980 Feet From The NORTH	Line and 1980	Feet From The EAST Line
Section 21	Township 20N	Range 33E NMP	M HARDING County
	10. Elevation (Show whe 5022	ther DF, RKB, RT, GR, etc.)	
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT X
PULL OR ALTER CASING] "	CASING TEST AND CEMENT JOB	
	, <u></u>		
OTHER: OTHER:			
12. Describe Proposed or Completed Operations (Clearly state all partinent details, and give pertinent datas, including estimated data of starting any proposed work) SEE RULE 1103.			
4/11/98			
Move in, rig up service unit. Kill well with fresh water. Nipple up BOP. Run 2-3/8" workstring to 2500'. Spot 15 sacks of			
class C cement @ 2500'.			
4/12/98			
Tag top of cement at 2340'. Circulate well with			
mud laiden fluid with inhibitor. Pressure test 4-1/2"			
fiberglass to 500 psi. Spot 10 sacks class C cement			
@ 1953' - 1806'. Spot 5 sacks of class C cement @ 30' - 3'. Cut off wellhead 3' below ground level. Dug up			
anchors. Cap well with steel plate. Install dry hole marker. Rig down, move out service unit. Clean and level location.			
I hereby certify that the information above is true	e and complete to the best of my knowledge and belief.	Field Team Leader	DATE 4/16/98
TYPE OR PRINT NAME D. J. Holcomb			TELEPHONE NO. (505) 374-3010
This areas for State Head			
APPROVED BY TY CONCULT TITLE DISTRICT SUPERVISOR DATE 8/10/98			
CONDITIONS OF APPROVAL, IF ANY:	/		<i>f</i> • • • • • • • • • • • • • • • • • • •