

OIL CONSERVATION COMMISSION

P. O. BOX 871

SANTA FE, NEW MEXICO

April 23, 1959

Mr. Robert F. Landis
Daly General Agency, Inc.
P. O. Box 1529
Denver 3, Colorado

Re: Powers Marshall Company
\$5,000 One Well Bond
NW/4 SE/4, Section 34,
Township 21 North, Range
30 East

Dear Mr. Landis:

We have your letter dated April 13, 1959, wherein you request cancellation of the above-captioned bond.

Please be advised that subject bond cannot be cancelled until the well located in the NW/4 SE/4 Section 34, Township 21 North, Range 30 East is properly plugged and abandoned. If the well is to be plugged and abandoned kindly furnish this office with the name of the person who is to perform the actual plugging work and we shall be happy to provide him with a plugging program and the proper forms for reporting the results of such plugging.

If we can be of further assistance in expediting this matter, please advise.

Very truly yours,

A. L. PORTER, Jr.
Secretary-Director

ALP/IRT/ir

C
O
P
Y

File
↓

WORKING METHOD USED TO
OBTAIN
STANDARD CURVES

The standard curves were obtained by plotting the logarithm of the ratio of the area under the peak to the area under the internal standard peak against the logarithm of the ratio of the concentration of the component to the concentration of the internal standard. The curves were then used to determine the concentration of the component in the sample.

The standard curves were obtained by plotting the logarithm of the ratio of the area under the peak to the area under the internal standard peak against the logarithm of the ratio of the concentration of the component to the concentration of the internal standard.

The standard curves were obtained by plotting the logarithm of the ratio of the area under the peak to the area under the internal standard peak against the logarithm of the ratio of the concentration of the component to the concentration of the internal standard. The curves were then used to determine the concentration of the component in the sample.

The standard curves were obtained by plotting the logarithm of the ratio of the area under the peak to the area under the internal standard peak against the logarithm of the ratio of the concentration of the component to the concentration of the internal standard. The curves were then used to determine the concentration of the component in the sample.