

New Mexico
OIL CONSERVATION COMMISSION

GOVERNOR EDWIN L. MECHEM
CHAIRMAN
LAND COMMISSIONER E.S. WALKER
MEMBER
STATE GEOLOGIST R.R. SPURRIER
SECRETARY AND DIRECTOR



P. O. BOX 871
SANTA FE, NEW MEXICO

INSPECTION REPORT

May 22, 1954

POWERS-MARSHALL COMPANY

RE: #1 Powers-Marshall
CNESE Sec. 34-T21N-R30E
Harding County

On this day I witnessed the casing job at the above captioned well which is located about three miles northeast of the village of Bueyeros on the Timmons lease.

The well has been drilled to a TD of 1915' in red sandy shale with limestone traces. 5 3/4" OD 17# casing was cemented at 1857.6' with 325 sacks of Portland cement. The job was done from 5:15 to 6:00 p.m. by Halliburton Oil Well Cementing Company, truck #2527 and T. E. Osborn of Texhoma, Oklahoma. Circulating pressure was 300 lbs. and maximum pressure of 1000 lbs. A HOWCO float shoe was used as well as a rubber type top plug. The slurry was mixed at a weight of 12.6 lbs. per gallon and cement was not circulated out.

The operator intends to wait on cement for at least 48 hours and then clean out and drill in with cable tools in what appears to be a high pressure carbon dioxide pay in the vicinity of 1890'.

Eugene A. Chavez
EUGENE A. CHAVEZ,
Oil & Gas Inspector
District #4

lgt