

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13 3/4	10	72	50	Halliburton		
9 5/8	7	1915	675	Halliburton		
6	5 1/2	2075	none	landed as bottom liner & perforated		

PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth Set \_\_\_\_\_  
Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from Surface feet to 1915 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
Cable tools were used from 1915 feet to 2075 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

PRODUCTION

Put to producing August, 1943  
The production of the first 24 hours was \_\_\_\_\_ barrels of fluid of which \_\_\_\_\_ % was oil; \_\_\_\_\_ % emulsion; \_\_\_\_\_ % water; and \_\_\_\_\_ % sediment. Gravity, Be \_\_\_\_\_  
If gas well, cu. ft. per 24 hours 710.000 Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_  
Rock pressure, lbs. per sq. in. 565

EMPLOYEES

E. D. Ackerman, Driller J. W. Jones, Driller  
\_\_\_\_\_, Driller \_\_\_\_\_, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this \_\_\_\_\_  
day of \_\_\_\_\_, 19\_\_\_\_

\_\_\_\_\_  
Notary Public \_\_\_\_\_  
My Commission expires \_\_\_\_\_

Copy - July 9 - 1955  
\_\_\_\_\_  
Place Date  
Name By A. C. Allen  
Position Mgr.  
Representing \_\_\_\_\_  
Company or Operator, \_\_\_\_\_  
Address \_\_\_\_\_