

**CARBONIC CHEMICALS CORPORATION**  
**MITCHELL NO. 8**

**LOCATION:**

C. SE 1/4, NE 1/4 Sec. 18  
T 19 N, R 30 E

**ELEVATION:**

4505 feet Ground  
4512 feet Top of Kelly Bushing

**DATE DRILLED:**

Spudded - June 1, 1950  
Completed - July 8, 1950

**TOTAL DEPTH:**

2076 feet - Driller  
2078 feet - Schlumberger

**HOLE SIZE:**

12-1/2 inch - 44 feet  
7-7/8 inch - 1920 feet  
6 inch - 2055 feet  
5-3/4 inch - 2076 feet

**BITS RUN:**

1	Reed	12-1/2 inch	Rock Bit
1 1/2	Hughes	7-7/8 inch	Rock Bits (1 re-tip)
2	Hughes	(6 & 5-3/4 inch)	Core heads

**CASING PROGRAM:**

Surface: 37 feet of 10-3/4 inch at 44 feet 7 inch  
with 16 sacks.  
Production: 1887.16 feet of 5-1/2 inch, 13 1/2, Lapwell,  
at 1893 feet w/378 sacks cement mixed w/16%  
Aqualag and 1/4 Floseal per sack. Halli-  
burton float shoe used. Cementing by  
Halliburton.