## NEW MEXICO OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

## AFFIDAVIT OF RESPONSIBILITY CONVERSION TO WATER-WELL

County of Hutchinson  Mr. Roy W. Resse
1. That he is Vice President of Service Drilling Company (Title) (Operator)  whose address is 1800 Fourth National Bank Building, Julsa, Oklahoma  2. That Service Drilling Co. (Operator)  longing to William Gruenerwald , whose address is Colorado Springs, CO. 80901  P. O. Box 126 (Landowner)  Wagon Mound, New Mexico , said well being drilled to test for hydrocarbons and/or carbon dioxide gas and described as the Gonzales-Pittman No. 1 , being located 660 feet from the South line and 660 feet from the West line of Section 24 , Township 21N , Range 21E , NMPM, Mora  County, New Mexico. 3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" cosing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of 490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40" set of 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23" casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
1. That he is Vice President of Service Drilling Compony (Title)  whose address is 1800 Fourth Notional Bank Building, Tulsa, Oklahoma  2. That Service Drilling Co. is the operator of a well drilled on land be- (Operator)  longing to William Gruenerwald (Landowner)  Wagon Mound, New Mexico , said well being drilled to test for hydrocarbons and/or carbon dioxide gas and described as the Gonzales-Pittman No. 1 , being located 660 feet from the South line and 660 feet from the West line of Section 24 , Township 21N , Range 21E , NMPM, Mora  County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" cosing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXXX to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of 490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40" set of 410' and cemented with 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
whose address is 1800 Fourth National Bank Building, Tulsa, Oklahama  2. That Service Drilling Co, is the operator of a well drilled on land be- (Operator)  longing to William Gruenerwald (Operator), whose address is Colorgdo Springs, CO. 80901  P. O. Box 126 (Landowner)  Wagon Mound, New Mexico, said well being drilled to test for hydrocarbons and/or carbon dioxide gas and described as the Gonzales-Pittman No. 1, being located 660 feet from the South line and 660 feet from the West line of Section 24, Township 21N, Range 21E, NMPM, Mora  County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" casing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXXXXXXXX to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of 490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
whose address is 1800 Fourth National Bank Building, Tulsa, Oklahama  2. That Service Drilling Co, is the operator of a well drilled on land be- (Operator)  longing to William Gruenerwald (Operator), whose address is Colorgdo Springs, CO. 80901  P. O. Box 126 (Landowner)  Wagon Mound, New Mexico, said well being drilled to test for hydrocarbons and/or carbon dioxide gas and described as the Gonzales-Pittman No. 1, being located 660 feet from the South line and 660 feet from the West line of Section 24, Township 21N, Range 21E, NMPM, Mora  County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" casing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXXXXXXXX to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of 490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
whose address is 1800 Fourth National Bank Building, Tulsa, Oklahoma  2. That Service Drilling Co, is the operator of a well drilled on land be- (Operator) P. O. Box 909  longing to William Gruenerwald , whose address is Colorgdo Springs, CO. 80901  P. O. Box 126 (Landowner)  Wagon Mound, New Mexico , said well being drilled to test for hydrocarbons and/or carbon dioxide gas and described as the Gonzales-Pittman No. 1 , being located 660 feet from the South line and 660 feet from the West line of Section 24 , Township 21N , Range 21E , NMPM, Mora  County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" casing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
2. That Service Drilling Co. (Operator)  (Operator)  P. O. Box 909  longing to William Gruenerwold  P. O. Box 126  (Landowner)  Wagon Mound, New Mexico  A said well being drilled to test for hydrocarbons and/or carbon dioxide gas and described as the Gonzales-Pittman  Fouth line and 660  Geet from the South line and 660  Geet from the West line of Section 24  Township 21N  Range 21E  NMPM, Mora  County, New Mexico  3. That said well was drilled to a total depth of 2916  Geet, and that casing has been set and cemented as follows: On October 12, 1975, 7" cosing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 sacks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jts 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
longing to William Gruenerwald , whose address is Colorado Springs, CO. 80901  P. O. Box 126 (Landowner)  Wagon Mound, New Mexico , said well being drilled to test for hydrocarbons and/or carbon dioxide gas and described as the Gonzoles-Pittman No. 1 , being located 660 feet from the South line and 660 feet from the West line of Section 24 , Township 21N , Range 21E , NMPM, Mora County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" casing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 cacks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XSXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of 1 feet and transfer well to landowner for his use as a water-well. Operator will 1 leave casing in the well as follows: (1) 13 jis 10-3/4", 40" set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23" casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
P. O. Box 126 (Landowner)  Wagon Mound, New Mexico , said well being drilled to test for hydrocarbons and/or carbon dioxide gas and described as the Gonzales-Pittman No. 1 , being located 660 feet from the South line and 660 feet from the West line of Section 24 , Township 21N , Range 21E , NMPM, Mora County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" casing was set at 1040 and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XSXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of 490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
Wagon Mound, New Mexico , said well being drilled to test for hydrocarbons and/or carbon dioxide gas and described as the Gonzales-Pittman No. 1 , being located 660 feet from the South line and 660 feet from the West line of Section 24 , Township 21N , Range 21E , NMPM, Mora  County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" casing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator further provides that operator is to plug said well back to a plugged-back total depth of feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
carbon dioxide gas and described as the feet from the South line and 660 feet from the South line and 660 feet from the West line of Section 24, Township 21N, Range 21E, NMPM, Mora  County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" casing was set at 1040 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of 490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40" set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23" casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
feet from the South line and 660 feet from the West line of Section 24.  Township 21N, Range 21E, NMPM, Mora  County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" cosing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of 490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40" set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23" casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
Township 21N, Range 21E, NMPM, Mora  County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" casing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
County, New Mexico.  3. That said well was drilled to a total depth of 2916 feet, and that casing has been set and cemented as follows: On October 12, 1975, 7" casing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 acks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
ing has been set and cemented as follows: On October 12, 1975, 7" casing was set at 1040' and cemented with 300 sacks common cement. On October 26, 1975, well was re-cemented with 300 sacks of flow-seal cement with good bond to 218'.  4. That operator and landowner have made an agreement whereby operator (is) (XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
4. That operator and landowner have made an agreement whereby operator (is) (XXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 jis 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
4. That operator and landowner have made an agreement whereby operator (is) (XXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of  490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 its 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
4. That operator and landowner have made an agreement whereby operator (is) (XXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of  490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 is 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
(is) (XXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of 490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 is 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
(is) (XXXXX) to back fill pits, level location, and clear it of all junk. The agreement further provides that operator is to plug said well back to a plugged-back total depth of 490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 is 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
further provides that operator is to plug said well back to a plugged-back total depth of  490 feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 its 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
feet and transfer well to landowner for his use as a water-well. Operator will leave casing in the well as follows: (1) 13 its 10-3/4", 40# set at 410' and cemented with 300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23# casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
300 sacks common cement and 150 sacks mixed cement (Halliburton). (2) 1040' 7", 23" casing 300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
300 sacks common cement (cement bonded to 218').  5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
5. That when operator has complied with the provisions of Paragraph 4 above it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
it will so notify the Oil Conservation Commission of the State of New Mexico on Com-
mission Form C-103, together with a signed statement from the landowner that the
provisions of Paragraph 4 above have been complied with to his satisfaction.
Service Drilling Company
(Operator)
By Hor W Lease
Subscribed and sworn to before me this 17th day of March , A. D. 1977 .
Wanda & Doede
Notary Public in and for the County of Hutchinson
STATE OF Colorado
County of El Paso
William Thursday, being first tuly sworn according to law, upon
his oath deposes and says that when the provisions of Paragraphs 4 and 5 above have been complied with, he will accept the above-described well for his use as a water-well, and
that he will assume all responsibility for the well, the location, and the conversion of the
well to a water-well.
(Landowner)
Subscribed and sworn to before me this ## day of Manager, A. D. 1977.
The factor of the state of the

\*Pits filled - location leveled