

GW - 21

REPORTS

YEAR(S):

2004



**Marathon
Oil Corporation**

**Groundwater Discharge Plan
GW-21
for
Indian Basin Gas Plant**

**329 Marathon Road
(Eddy County Road 401)
Lakewood, New Mexico**

Prepared For:

**Marathon Oil Company
Southern Business Unit
P.O. Box 3487
Houston, Texas 77253-3487**

Submitted to:

**State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division**

On behalf of:

Working Interest Owners

September 17, 2004



**Marathon
Oil Corporation**

**Groundwater Discharge Plan
GW-21
for
Indian Basin Gas Plant**

**329 Marathon Road
(Eddy County Road 401)
Lakewood, New Mexico**

Prepared For:

**Marathon Oil Company
Southern Business Unit
P.O. Box 3487
Houston, Texas 77253-3487**

Submitted to:

**State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division**

On behalf of:

Working Interest Owners

September 17, 2004

Groundwater Discharge Plan for Indian Basin Gas Plant

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
1.0 TYPE OF OPERATION	1
2.0 OPERATOR/LEGALLY RESPONSIBLE PARTY & LOCAL REPRESENTATIVE .	1
3.0 LOCATION OF FACILITY	1
4.0 LANDOWNER	1
5.0 FACILITY DESCRIPTION.....	2
6.0 MATERIALS STORED/USED AT THE FACILITY	2
7.0 SOURCES AND QUANTITIES OF EFFLUENTS & WASTE SOLIDS	2
7.1 Effluents	2
7.2 Solid and Liquid Wastes	3
7.3 Effluent and Solid Waste Quality Characteristics.....	3
7.3.1 Commingled Effluent.....	3
7.3.2 Wastewater and Treated Groundwater Quality Characteristics	4
7.3.3 Solid Waste Quality Characteristics.....	4
8.0 TRANSFER AND STORAGE OF PROCESS FLUIDS AND EFFLUENTS	4
8.1 Onsite Collection and Storage Systems	4
8.1.1 Open Drain System	5
8.1.2 Description of Integrity Test of Open Drain System	5
8.1.3 Closed Drain System.....	5
8.2 Inventory of Tanks and Vessels	6

TABLE OF CONTENTS

(Continued)

Section	Page
8.3 Measures to Prevent Unintentional and Inadvertent Discharges	6
8.3.1 Secondary Containment for Tanks	6
8.3.2 Chemical and Drum Storage Area Containment.....	6
8.3.3 New and Existing Sump Inspection	6
8.3.4 Aboveground Tank Inspection	6
8.3.5 Process Areas	6
8.3.6 Housekeeping.....	6
8.4 Underground Pipelines.....	7
8.5 Effluent Disposal.....	7
8.5.1 On-site Disposal.....	7
8.5.2 On-site Treatment.....	7
8.5.2.1 Treatment of Soils.....	7
8.5.2.2 Vadose Zone Monitoring, Sampling, and Notification.....	8
8.5.3 Off-site Disposal	8
8.5.3.1 Injection Wells.....	8
8.5.3.2 Commercial Disposal Facilities	8
9.0 PROPOSED MODIFICATIONS.....	8
10.0 INSPECTION, MAINTENANCE, AND REPORTING	9
10.1 Routine Inspection Procedures	9
10.2 Routine Maintenance Procedures.....	9
10.3 Routine Reporting Procedures	9
10.4 Stormwater Runoff and Flood Protection	9

TABLE OF CONTENTS

(Continued)

Section	Page
11.0 SPILL/LEAK PREVENTION & REPORTING (CONTINGENCY PLANS)	10
12.0 SITE CHARACTERISTICS	10
12.1 Geologic Description of Discharge Site	10
12.2 Hydrologic Features	10
13.0 OTHER COMPLIANCE INFORMATION.....	11

TABLES

Table 1.	Effluents and Estimated Volumes.
Table 2.	Waste Sources, Waste Classification, and Waste Treatment/Disposal Methods.
Table 3.	Inventory of Tanks.
Table 4.	Inventory of Process Vessels.
Table 5.	Underground Piping.
Table 6.	Soil Treatment Cleanup Standards.

FIGURES

Figure 1.	Topographic Map of Plant and Surrounding Area.
Figure 2.	Facility Diagram of the Plant.
Figure 3.	Process Flow Schematic.

APPENDICES

Appendix A.	Laboratory Results of Commingled Discharge Fluid.
Appendix B.	Spill Prevention and Control Plan.
Appendix C.	Stormwater Pollution Prevention Plan.

G r o u n d w a t e r D i s c h a r g e P l a n
for
I n d i a n B a s i n G a s P l a n t

1.0 TYPE OF OPERATION

The major purpose of the facility is gas processing. Although the components of the plant have been updated since it first began operations in 1966, the basic function and purpose of the plant have not changed. The plant owners have invested in new technology and replacement of aging equipment as necessary.

2.0 OPERATOR/LEGALLY RESPONSIBLE PARTY & LOCAL REPRESENTATIVE

The name of the operator is Marathon Oil Company. The mailing address for the Southern Business Unit is P.O. Box 3487, Houston, Texas 77253-3487. The telephone number for the Region office in Houston is (713) 629-6600.

The local Marathon Oil Company representative at the Indian Basin Gas Plant is Tom Breninger, Plant Superintendent. The street address of the plant is 329 Marathon Road (Eddy County Road 401), Lakewood, New Mexico. The mailing address is P.O. Box 1324, Artesia, New Mexico 88211. The plant telephone number is (505) 457-2621.

3.0 LOCATION OF FACILITY

The Indian Basin Gas Plant (facility) is located in the Northeast 1/4 of Section 23, T21S, R23E, NMPM, Eddy County, New Mexico, approximately 20 miles west of Carlsbad and 28 miles southwest of Artesia. Figure 1 is excerpted from the U.S.G.S. 7.5-minute topographic quadrangle, titled "Martha Creek", showing the location of the facility.

4.0 LANDOWNER

Marathon Oil Company is the landowner of record of a 160-acre site legally described as the Northeast 1/4 of Section 23, T21S, R23E, NMPM, Eddy County, New Mexico. The gas plant facility, which consists of approximately 60 acres, is located on the 160-acre property. Marathon's corporate headquarters address is P.O. Box 3128, Houston, Texas, 77253. Correspondence regarding the site should be directed to Tom Breninger, Plant Superintendent, at the plant address provided in Section 2.0.

5.0 FACILITY DESCRIPTION

The gas plant facility approximately occupies the Southwest 1/4 of the Northeast 1/4 of Section 23, T21S, R23E. Figure 1 shows the plant site, the boundary of the 160-acre property, and the adjacent property managed by the BLM. Figure 2 is a facility diagram of the gas plant site showing the plant perimeter fence, stormwater berms, primary facility tanks, cooling tower, landfarm, treatment cell, groundwater remediation system, sulfur pit, closed landfill, locations of chemical and fuel storage facilities, processing facilities, and drum storage areas.

6.0 MATERIALS STORED/USED AT THE FACILITY

A list of materials stored and used at the facility is included in Tables 3 and 4. See section 8.0 for more information.

7.0 SOURCES AND QUANTITIES OF EFFLUENTS & WASTE SOLIDS

Wastes that are generated at the gas plant consist of commingled effluent (Section 7.1) and solid and liquid wastes (Section 7.2). The commingled effluent is gathered by the drain and sump system and the solid and liquid wastes are generated at the plant but are not part of the commingled effluent.

7.1 Effluents

The commingled effluent consists of produced water and various other plant effluents. The individual waste effluent streams in the commingled effluent are identified in Table 1. The waste effluent streams from the various plant processes are collected and conveyed by the open drain piping system, the closed drain piping system, and several underground pipelines. Effluent volumes at the plant are variable and depend upon plant and field operations. Commingled effluent is normally discharged into a Marathon-operated Class II injection well – identified as the AGI #2 well -- located on adjacent Bureau of Land Management (BLM) property. (Note: Another formerly-used injection well located southeast of the plant has been plugged and abandoned.) The commingled effluent is also occasionally trucked off-site to commercial disposal facilities during emergencies.

Produced water, cooling tower blowdown, and boiler and condenser blowdowns consist of a combination of wastewater and chemical additives. The name and volume of additives in each effluent are listed on Table 1. These effluents, effluents from cleaning operations, and miscellaneous plant process effluents are commingled via the open drain piping system, which drains to the skimmer basin before being pumped to the steel saltwater tank.

The new Selexol unit has added two additional effluents. These effluents are outlined in Table 1. The Selexol effluent is drained via the open drain system, and is then sent to a Marathon-operated Class II injection well. It is commingled with the plant disposal system only during an emergency.

Reverse osmosis (RO) wastewater is disposed with plant wastewater. There is no treated groundwater (since January 2003), and no water is injected into the Lower Queen infiltration wells IW-1 and IW-2. During an emergency the effluents are commingled with the plant disposal system and are therefore listed on Table 1.

Domestic sewage is not commingled with other plant effluent and is therefore regulated by the New Mexico Environment Department. Sewage is conveyed through an underground pipeline to one of two underground septic tanks, which are designed to drain the sewage leachate. One of the septic systems was installed prior to December 1972, the other in April 1997.

7.2 Solid and Liquid Wastes

Solid and liquid wastes are generated at the plant that are not part of the commingled effluent or conveyed by underground piping. The waste classification, treatment/disposal methods, treatment/disposal/recycle locations, and waste storage areas are provided in Table 2.

Waste oil is collected from various plant equipment (Table 2) and stored in a 500-gallon waste oil storage tank located on the west side of the plant (Figure 2). The oil is stored in the tank until enough oil accumulates to warrant transport of the oil to a used oil recycling facility. Vehicle motor oil no longer is changed at the plant; rather it is performed off-site.

There are two Safety-Kleen parts cleaning units located in the pumper shack. One of the cleaning units is an open-top spray basin containing naptha solvent and the other unit is a self-contained cleaning unit that contains an aqueous solvent. Safety-Kleen services both units and recycles the solvent whenever the spent solvent is replaced. The naptha solvent is hazardous and the aqueous solvent is non-hazardous. The Environmental Protection Agency (EPA) small quantity generator number for hazardous waste generated at the Indian Basin Gas Plant is NMD 982760183-1235. The EPA hazardous waste site identification is NMO-1406.

Laboratory wastes are a starch and iodine mix, silver nitrate, and water test reagents. These liquids are temporarily stored in a 5-gallon container in the laboratory and later hand carried to a 55-gallon drum in the drum storage area on the west side of the plant. Waste paint is stored in a 55-gallon drum in the drum storage area. Both streams are stored until enough waste has accumulated for disposal/recycle by Safety-Kleen.

7.3 Effluent and Solid Waste Quality Characteristics

7.3.1 Commingled Effluent

On November 8, 1999, a grab sample of the commingled effluent was collected from a valve between the saltwater tank pump and the pipeline to the injection well. Total dissolved solids (TDS), pH, general chemistry, chlorinated hydrocarbons, aromatic hydrocarbons, and Resource Conservation and Recovery Act (RCRA) metals analysis of the effluent sample was conducted by Severn Trent Laboratories (STL). Laboratory results indicated that all commingled effluent constituents are below the WQCC 3-103 standards for groundwater except for benzene, toluene, ethylbenzene, total xylenes, chloride, sulfate, and TDS. The concentrations of benzene, toluene, ethylbenzene, and total xylenes were 4,300, 13,000, 700, and 7,000 µg/l, respectively.

The laboratory results are included in Appendix A.

Testing for polychlorinated biphenols (PCBs) was not necessary because PCB-contaminated transformers were removed from service at the gas plant before 1981. No other sources of PCB contamination have been identified to warrant testing for PCBs in the plant effluent.

Table 1 lists two plant effluents that contain one or more constituents as defined by WQCC Section 1101.TT. These effluents are the produced water and groundwater contaminated with condensate. It should be noted that the groundwater contaminated with condensate is transferred through an underground pipeline from the treatment compound to the fiberglass saltwater tank only in emergency situations. Treated groundwater is not an effluent anymore. The hazardous constituents that are likely contained in these effluents are benzene, toluene, ethylbenzene, meta-, para-, and ortho-xylenes, and naphthalene.

7.3.2 Wastewater Quality Characteristics

Marathon has been sampling the commingled reverse osmosis (RO) wastewater and the treated groundwater on a monthly basis for benzene, toluene, ethylbenzene and xylenes (BTEX), and on a quarterly basis for major cations/anions and polyaromatic hydrocarbons (PAHs) analysis using EPA approved methods. As described in Section 7.1, reverse osmosis wastewater is commingled with plant waste water and disposed off into the injection well. Pump and treat system, which was used to treat condensate contaminated groundwater was shut-in January 2003 after receiving approval from the OCD. Hence, above referenced monthly sampling of RO wastewater and treated groundwater has been discontinued since.

7.3.3 Solid Waste Quality Characteristics

Most solid wastes generated at the plant are not characterized by the definition in WQCC Section 1101.TT. Table 2, which has been updated to reflect new and modified waste sources, classifies each waste as either exempt, non-exempt (non-hazardous or potentially hazardous), or naturally occurring radioactive material (NORM). All non-exempt wastes will be characterized according to 40 CFR 261 to determine the appropriate method of disposal. After the waste stream has been characterized, the data will be kept on file at the gas plant. Solid wastes will be stored and handled in accordance with all applicable federal and state laws.

8.0 TRANSFER AND STORAGE OF PROCESS FLUIDS AND EFFLUENTS

8.1 Onsite Collection and Storage Systems

The open drain and closed drain systems are used to manage some of the effluents at the plant. Table 1 indicates which effluents are conveyed in the open drain system. These include two of the boiler and condenser blowdowns, cleaning operation effluents, and miscellaneous plant process effluents. Open drain system is used to collect commingled effluents. The closed drain system is used to collect effluent from pressurized vessels.

8.1.1 Open Drain System

The open drain system collects plant effluent under atmospheric conditions. The underground part of this system includes: four double-walled fiberglass sumps; one single-walled fiberglass sump at the air compressor building; two single-walled steel sumps (open-drain collection sump and LACT sump); steel collection pots; steel pipelines; and, polyethylene pipelines. The open drain system includes a total of seven underground sumps. The aboveground part of the system consists of concrete drainage and containment pads that collect and drain effluent into the underground part of the system for collection and disposal. All open drain sump pumps send their effluent to the open-drain collection sump where they are commingled. Commingled effluent collected in the open-drain collection sump is pumped to the skimmer basin gunbarrel tank, located on the skimmer basin pad.

8.1.2 Description of Integrity Test of Open Drain System

Seven separate sections of underground piping are tested by filling the piping to volumetric capacity and visually observing any fluctuations in fluid levels at the sump and manway locations. The test is performed at atmospheric conditions for 5 hours. In order to reduce the effects of temperature fluctuations that occur during the day, the test is conducted in the early morning or late evening hours. All sources for active drainage are isolated to prevent accidental introduction of non-test fluids into the system. A successful test has been conducted when the initial fluid levels remain constant throughout the 5-hour test period. The double walled fiberglass sumps are integrity tested by filling the inner chamber to capacity and observing any leaking of fluid from the inner chamber to the outer chamber. A successful test of the double-walled sumps has occurred if fluid does not leak to the outer chamber from the inner chamber during the 5-hour test period. The OCD will be notified at least 72 hours prior to all testing.

Successful integrity tests were conducted on the entire system during two testing periods. Initial testing was completed November 1999 on the majority of the system. Final integrity tests were completed February 2000. Records of all integrity tests are available at the Indian Basin Gas Plant office.

8.1.3 Closed Drain System

The closed drain was constructed in 1980 and modified in 1984 and 1996 and is mainly aboveground. This system is used to collect effluent from pressurized vessels. The maximum operating pressure is 200 psig. The closed drain system is connected to process vessels: inlet filter coalescer, four expander/compressors, three amine contactors, glycol contactor, Selexol contactor, three amine scrubbers, glycol overhead filter coalescer, Selexol scrubber, two amine flash tanks, amine still, Selexol still, glycol inlet filter coalescer, Selexol 3-phase separator, product contactor, new fuel gas scrubber, old fuel gas scrubber, two regen scrubbers, vertical inlet separator, cyclone separator and horizontal inlet separator. (See Figure 3 for a schematic of the process flow.) Steel piping leads from these process vessels to the closed drain scrubber, located near the generators. Collected liquids in the tank are sent to the skimmer basin gunbarrel for recovery and then to disposal via the wastewater injection system.

8.2 Inventory of Tanks and Vessels

Tables 3 and 4 are lists of tanks and vessels, respectively, with a potential to discharge. Table 3 lists the 55 tanks at the plant, and it has been updated to include 4 new storage tanks with liners that were put in service June 2003. Table 4 lists the separators, boilers, exchangers, condensers, scrubbers, and other vessels that are not constructed in impermeable secondary containment and would cause a discharge directly to the ground if the vessel leaked.

8.3 Measures to Prevent Unintentional and Inadvertent Discharges

8.3.1 Secondary Containment for Tanks

All storage tanks, except those that contain uncontaminated freshwater, are bermed to contain 133% of the volume of the largest tank. If two or more tanks are connected within the same containment, the berm contains 133% of the total volume of the interconnected tanks. New or existing tanks that undergo a major modification, as determined by the Division, will be placed within an impermeable enclosure.

8.3.2 Chemical and Drum Storage Area Containment

Drum storage areas are concrete paved and curbed to prevent a potential discharge to the ground of leaking or spilled drum contents. All tanks, drums, and containers will be clearly labeled to identify their contents and other emergency notification information.

8.3.3 New and Existing Sump Inspection

Construction plans for installing new sumps will be submitted to the Oil Conservation Division (OCD) for approval prior to project commencement. New sumps will incorporate secondary containment and leak-detection into the design prior to installation. The only below-grade tank at the plant is the sulfur underground storage tank.

8.3.4 Aboveground Tank Inspection

The glycol storage, 1200-barrel freshwater storage, and steel softwater tanks are on a concrete pad. Therefore, these tanks have leak detection. All other on-ground tanks are inspected every five years.

8.3.5 Process Areas

All process and maintenance areas which show evidence that leaks and spills are reaching the ground surface will be either paved and curbed or have some type of spill collection device incorporated into the design.

8.3.6 Housekeeping

All systems designed for spill collection/prevention will be inspected weekly and after each storm event to ensure proper operation and to prevent overtopping or system failure. A record of inspections will be retained on site for a period of five years.

8.4 Underground Pipelines

Table 5 lists underground pipelines that convey either process or waste effluents within the plant. The name of the pipeline, where the fluids are transferred from and to, year of construction or modification, piping diameter, fabrication material, average throughput during use, operating pressure, and the date of the last or next scheduled integrity test of each pipeline are indicated on Table 5. The Marathon procedures for mechanical integrity testing are on file at the plant. The procedures are based upon the third edition (dated December 1993) of the American Petroleum Institute document HP 1110 titled "Pressure Testing of Liquid Petroleum Pipelines."

8.5 Effluent Disposal

8.5.1 On-site Disposal

Surface impoundments or ponds, injection wells, leach fields (except for two septic tanks), drying beds, or other pits do not exist onsite. Onsite disposal of liquid and solid waste effluents is limited to the discharge of cooling tower effluent in the form of a mist onto the ground around the base of the cooling tower and solid sulfur that is discharged onto the ground on the west side of the plant. Marathon no longer uses the solid waste landfill onsite to dispose of exempt plant wastes and office trash. The landfill was closed in 1995.

8.5.2 Onsite Treatment

8.5.2.1 Treatment of Soils

Onsite treatment is limited to treatment of hydrocarbon-contaminated (e.g oil, glycol, and amine) soil. The treatment methods are landfarming, commercial soil shredding, or commercial incineration. The latter two treatment options will be performed by an environmental service company in the landfarm treatment cell. Soil will be treated to below the appropriate standards outlined in Table 6. Vadose zone monitoring will not be performed on the treatment cell if aboveground equipment is used for treatment. The confirmation sampling for the treated soils will be one sample per 50 yards of soil.

All soil is treated in an area on the west side of the plant (Figure 2). Soils from the plant are remediated in this landfarm area. Only soils from the plant presently are remediated in the landfarm area; however, other hydrocarbon-contaminated soils from nearby Marathon production sites may be remediated in this landfarm area. The landfarm area measures approximately 100 feet by 300 feet. The landfarm operates continuously throughout the year. The landfarm was originally constructed in 1989 with a 4-mil plastic liner with approximately 12-inch-high earthen berms on all four sides. Water needed for remediation of soils is trucked in periodically and applied to insure there is no runoff or standing water in the treatment area except during heavy rainfall events.

Soil to be placed in the landfarm will not contain polychlorinated biphenols (PCBs) or heavy metals in hazardous concentrations as defined by the Toxicity Characteristic Leaching Procedure (TCLP). Exempt soil will be directly loaded into the landfarm. Non-exempt soil will

be tested for RCRA metals and PCBs before loading into the landfarm unless process knowledge can be used to eliminate the need for testing.

Landfarmed soil is sampled periodically to determine whether cleanup standards have been achieved. Soil cleanup standards for TPH, total BTEX, and benzene are outlined in Table 6 in accordance with intended usage of the soils.

8.5.2.2 Vadose Zone Monitoring, Sampling, and Notification

In order to ensure that discharges to groundwater from the vadose zone beneath the landfarm will comply with standards in WQCC Section 3103 and Section 1101.TT, a randomly located grab sample will be collected each time treated soil is removed from the landfarm. The sample will be collected from six inches to one foot below grade.

If soil below the landfarm is found to contain TPH or total BTEX concentrations above 100 mg/kg and 50 mg/kg, respectively, the OCD will be notified according to the notification requirements of WQCC Section 1203. Marathon's seven-day written notification will contain a plan for the removal of soil from beneath the landfarm that exceeds these standards. If the soil below the landfarm is not found to contain TPH or total BTEX concentrations above the stated levels, then the landfarm will be reloaded and treatment of soil will continue. Laboratory analysis reports of the vadose zone sampling described above will be submitted to the OCD within 15 days of the transmittal date of the laboratory report.

8.5.3 Off-Site Disposal

8.5.3.1 Injection Wells

All exempt gas-plant waste effluents are collected by the open-drain system, closed-drain system, or other underground piping, and commingled at either the fiberglass or steel saltwater tanks (Figure 2). The commingled effluent is conveyed by underground pipeline and discharged at two off-site locations. This Marathon-operated Class II injection well is located on adjacent BLM property. The principal injection well is the Marathon Indian Basin Gas Well No. 1, located in the Northwest 1/4 of Section 23, T21S, R23E. Marathon Federal SWD Well No. 1, located in Unit K in the Southwest 1/4 of Section 24, T21S, R23E, is maintained as a backup well. The composition of the commingled effluent is identified in Table 1. Laboratory analysis of the commingled effluent is provided in Appendix A.

8.5.3.2 Commercial Disposal Facilities

Office refuse and other inert wastes are transported to the local municipal landfill for disposal. All other wastes are handled according to Table 2.

9.0 PROPOSED MODIFICATIONS

1. There are four new storage tanks in the southeast portion of the gas plant which were put in service last year. The new tanks are listed in Table 3.
2. Waste streams and different disposal facilities that are currently in use have been

updated. The changes are outlined in Table 2.

3. A Selexol process has been added to the plant to remove mercaptans from the gas stream. All of the tables have been updated accordingly to reflect the changes.
4. A new Glycol Inlet Filter Coalescer has been added to the plant to remove water and condensate from the gas stream. All of the tables have been updated accordingly to reflect the changes.

10.0 INSPECTION, MAINTENANCE, AND REPORTING

Marathon is actively involved in maintaining and improving spill and leak prevention procedures and good housekeeping practices. These goals are achieved by encouraging plant employees to be observant, to notify the appropriate persons of their observations, to correct problems quickly, and to prevent future spills and leaks by learning from problematic past practices.

10.1 Routine Inspection Procedures

Table 3 and 4 identify the aboveground storage tanks and process vessels (AST and APV; *i.e.*, those in-air tanks and vessels that allow 360 degree visual inspection) that are routinely inspected. The closed drain system is also routinely inspected. Plant employees routinely inspect plant equipment (*i.e.*, tanks, piping, pumps, fittings, valves, etc.) for leaks and spills during their daily work tasks. Four plant tours are conducted by plant personnel during each of two, twelve-hour shifts. A primary objective of these tours is to detect equipment leaks and spills. The current Best Management Plan for spills is provided in Appendix B.

10.2 Routine Maintenance Procedures

Employees are encouraged to identify and report potential spill situations. All plant employees have completed an 8-hour hazardous waste operations and emergency response (HAZWOPER) training session. In addition, all employees participate in an annual refresher training course which includes instruction on spill prevention and control measures as required by the Best Management Plan.

10.3 Routine Reporting Procedures

Small leaks or spills are reported and remediated immediately. A Marathon policy requires employees to complete a spill report upon discovery of a spill or leak. Spills or leaks are reported to the OCD according to the requirements of OCD Rule 116 and WQCC Regulations Section 1-203. BLM is notified if a spill or leak occurs on BLM land. The National Response Center is notified in accordance with 40 CFR 110.10. Spill reports are kept on file at the plant office.

10.4 Stormwater Runoff and Flood Protection

The potential for flooding of the plant is very low. Normally, flooding due to significant rainfall events is limited to the braided stream channels of Rocky Arroyo. The stream bed of Rocky Arroyo is approximately 10 feet lower than the elevation at the southern plant perimeter fence.

The last time Rocky Arroyo overran its banks was in 1986, but the water did not reach the plant.

Perimeter diversion berms consisting of dirt, piled two to three feet high, are located on the west and north sides of the plant to prevent upgradient stormwater from running onto the plant site. These stormwater berms prevent stormwater from contacting hydrocarbons or flooding the open-drain system which is designed to manage normal process flow only.

The Indian Basin Gas Plant Stormwater Pollution Prevention Plan (SWPPP), dated March 12, 1998, is included in Appendix C. This document describes the potential pollutant sources, stormwater measures and controls, stormwater runoff management, inspection and preventative maintenance, spill prevention and response procedures, employee stormwater training, and recordkeeping and internal reporting procedures. Select employees participate in stormwater pollution prevention training on an annual frequency according to the requirements in the SWPPP.

11.0 SPILL/LEAK PREVENTION & REPORTING (CONTINGENCY PLANS)

A contingency plan for potential occurrence of leaks and spills at the Indian Basin Gas Plant is located in the Best Management Plan which is included as Appendix B. The contingency plan describes the steps proposed to contain and remove spilled substances and mitigate the damage caused by the discharge, including protection from future migration to groundwater. The OCD notification threshold levels will be followed for discharges at the plant as defined by WQCC Regulations Section 1203 and significant leaks or spills as defined by OCD Rule 116.

12.0 SITE CHARACTERISTICS

12.1 Geologic Description of Discharge Site

The typical stratigraphic sequence beneath the gas plant is Queen Formation fractured sandstone, limestone, and dolomite bedrock at a depth of approximately 20 feet overlain by approximately 16 feet of silty, pebble to boulder gravel overlain by 4 feet of clayey silt and silt.

12.2 Hydrologic Features

Rocky Arroyo is a watercourse located approximately 600 feet south of the southern boundary of the site (Figure 1) that contains flowing water only during and for a period of time following heavy rainfall events. The main channel of Rocky Arroyo is 840 feet south of a fence at plant. South of the plant site, the stream channel of Rocky Arroyo trends southeast.

The first groundwater encountered below the plant site occurs within alluvium deposits. This shallow zone is perched above locally fractured, Permian sandstone, limestone, and dolomite of the Queen Formation. The presence of perched shallow groundwater is dependant on the amount of local rainfall. The flow direction of the perched shallow groundwater is generally southeast. A commercial supply well permitted by the State Engineer Office and completed in the shallow alluvial deposits is located approximately 2.5 miles east of the site boundary. The well is located where alluvial deposits are thick and downstream of the confluence of three

major drainage channels in the southern Seven Rivers embayment. These are Rocky Arroyo, Martha Creek, and Dunnaway Draw.

A rancher well (Lee well) is located approximately 0.7 miles west of the western boundary of the 160-acre property and approximately 100 feet north of County Road 401 (Figure 1). This active well is permitted by the State Engineer Office as a stock supply well and is completed in the Lower Queen regional aquifer which is the next saturated zone below the shallow groundwater zone.

13.0 OTHER COMPLIANCE INFORMATION

None to report.

Table 1. Effluents and Estimated Volumes

Effluent	Pathway	Waste Effluent Constituents	Volume	(Section 101.2 ZZ constituents)
PRODUCED WATER	Inlet separators to skimmer basin to saltwater tanks	Condensate, saltwater, Calgon pretest 32- 2 gal./day	2000 Bbls/day	none
COOLING TOWER BLOWDOWN	Aboveground piping to fiberglass saltwater tank	Softwater make-up Calgon conductor XLP-170 Van Waters Rogers sulfuric acid Calgon Tower Brom 960 (solid) Calgon H75	200 Bbls/day 2.1 gal/day 5 Bbls/mo 100 lbs/mo 3 gal/wk	none none none none none
BOILER AND CONDENSER BLOWDOWNS	Underground & aboveground steel pipeline to steel saltwater tank Underground & aboveground steel pipeline to steel saltwater tank Glycol sump of open drain to steel saltwater tank Open Drain System to skimmer basin Open Drain System to skimmer basin	Caustic Soda - Unichem Softwater make-up Calgon Ultra Amine 120 Calgon Burflook 2220 Calgon Conquer 3470	1.5 gal/day 95 Bbls/day 3.6 gal/day 4.5 gal/day 1.8 gal/day	none none none none none
CLEANING OPERATIONS	Steam cleaning Truck, tank, and drum washing	Water	50 Bbls/day	none
PLANT PROCESS EFFLUENTS	Open Drain to Skimmer Basin to Saltwater Tank to Injection	Huntsman diglycolamine (DGA) Triethylene glycol (TEG) Water	75 Bbls/day	none none none
SOFTWATER REGEN	Pumped from selexol unit to gunbarrel Selexol unit to open drain to injection	Dimethyl Ether of Polyethylene Glycol Mixture, Glycol Ethers	50 gal/day 120 Bbls	none
REVERSE OSMOSIS WASTEWATER*	Softwater building to saltwater tank via underground piping Primary: Water treatment to infiltration system via underground piping Secondary: Water treatment building to saltwater tank	Saltwater	75 Bbls/day	none
GROUNDWATER CONTAMINATED W/CONDENSATE* (Shut-in since January 2003)	Primary: Freshwater gathering to infl. Via underground piping Secondary: Freshwater gathering to saltwater tank	Freshwater Condensate (as TPH; EPA Mod. 8015)	300 Bbls/day 2375 Bbls/day <3,200 ug/L	none BTEX

* Denotes effluent is only commingled into disposal system in case of emergency or mechanical failure
Last Updated: 9/3/2004

Table 2. Waste Sources, Waste Classification, and Waste Treatment/Disposal Methods

Waste	Waste Classification	Treatment/Disposal Method	Disposal Location	Plant Storage Location
AEROSOL CANS (empty)	Non-exempt, Non-hazardous	Landfill	Southwest Disposal	Municipal waste stream
ANTIFREEZE (vehicle/glycol water bath)	Exempt & Non-exempt, Potentially hazardous	Disposal well	Safety Kleen	In original containers
BATTERIES, SPENT (generator, backup lighting, and CALCIUM SILICATE INSULATION	Non-exempt, Potentially hazardous	Recycle	Best-Buy	Drum storage area
CARBON, SPENT (Amine or Glycol System)	Non-exempt, Non-hazardous	Landfill	1) Southwest Disposal 2) Lea Land 3) Control Recovery, Inc.	Roll-off bin
CONCRETE, UNCONTAMINATED	Exempt	1) Exempt waste disposal facility 2) Non-hazardous industrial landfill	1) Exempt waste disposal facility 2) Control Recovery, Inc. 3) Lea Land	Roll-off bin when needed
COOLING TOWER CLEANING WASTE SOLIDS	Non-exempt, Non-hazardous	1) Leave on site OR 2) Municipal landfill	1) On site 2) Municipal landfill	NA
DEBRIS (Mercury Contaminated)	Non-exempt, Potentially hazardous	Injection; Off site Class II well	1) Control Recovery, Inc. 2) Lea Land	Frac tank until testing complete
DRUMS, SPENT	Non-exempt, Potentially hazardous	Recycle	Safety-Kleen	NA
EFFLUENTS (Spent DGA and TEG, washwater, boiler, condenser blowdown fluids, waste saltwater, Selexol)	Exempt, Non-hazardous	Recycle	U.S. Filter	Drum storage area
ELECTRICAL MATERIALS (Conduit, Panels, Etc.)	Non-exempt, Non-hazardous	Injection	MOC SWD Well	Saltwater Tank
FILTERS - AIR	Non-exempt, Non-hazardous	Recycle	U.S. Filter	Scrap metal recycling bin
FILTERS - NATURAL GAS FILTERS	Exempt	Landfill	Southwest Disposal	Dumpster
FILTERS - STABILIZER COMPRESSOR/AIR COMPRESSOR LUBE OIL FILTERS	Non-exempt	1) Recycle by incineration 2) Exempt waste disposal facility	1) Quell or U.S. Filter 2) exempt waste disposal facility	South east of plant
FILTERS - TURBINE LUBE OIL FILTERS	Non-exempt	Recycle by incineration	Quell or U.S. Filter	West side plant
FILTERS, GLYCOL & AMINE FILTERS & FILTER MEDIA (glycol sock filters, amine charcoal filters, amine bag filters)	Exempt	1) Recycle by incineration 2) Exempt waste disposal facility	1) Quell or U.S. Filter 2) Exempt waste disposal facility	South east of plant
FLUORESCENT LAMPS (Used)	Non-exempt, Hazardous	Recycle	Quell or U.S. Filter	South east of plant
GLYCOL CERAMIC SADDLES, SPENT	Exempt	Recycle	Safety Kleen	NA
HYDROBLASTING & SANDBLASTING MEDIA	Non-exempt, Potentially hazardous	1) Exempt waste disposal facility 2) Non-hazardous industrial landfill	1) Exempt waste disposal facility 2) Control Recovery, Inc. 3) Lea Land	Roll-off bin or drums when needed
LABORATORY WASTES (starch and iodine, silver nitrate, water test reagents)	Non-exempt, Potentially hazardous	As dictated by sampling Incinerated	As dictated by sampling Safety-Kleen determines	NA
METAL, SCRAP (NORM contaminated)	Non-exempt, Potentially hazardous	NORM disposal	Newpark Environmental	NORM storage area
METAL, SCRAP (not NORM contaminated)	Non-exempt, Non-hazardous	Recycle	U.S. Filter	Scrap metal recycling bin
METHANOL	Non-exempt, Hazardous	Recycle	Safety Kleen	Methanol storage area
MOLECULAR SIEVE, SPENT	Exempt	1) Exempt waste disposal facility 2) Non-hazardous industrial landfill	1) Exempt waste disposal facility 2) Control Recovery, Inc. 3) Lea Land	West side plant

Table 2. Waste Sources, Waste Classification, and Waste Treatment/Disposal Methods

Waste	Waste Classification	Treatment/Disposal Method	Disposal Location	Plant Storage Location
NATURALLY OCCURRING RADIOACTIVE MATERIAL (NORM)	NORM waste	NORM disposal	Newpark Environmental	NORM storage area
OFFICE AND PLANT TRASH	Non-exempt, Non-hazardous	Dumpster	Southwest Disposal	West side plant
OIL (vehicle motor, crankcase (chemical injection pumps, high pressure pumps), regen compressor, instrument air compressor, lube oil, stabilizer vapors compressor oil, turbine/expander compressor oil, inlet compressors oil.)	Non-exempt, Potentially hazardous	Recycle	U.S. Filter	Oil recycle storage area
PAINT, WASTE (non-empty cans, dried paints, waste paint)	Non-exempt, Potentially hazardous	Incinerated; Supplemental fuel	Safety-Kleen determines	Drum storage area
POLY-PIPE (Scrap Polyethylene)	Non-exempt, Non-hazardous	Landfill	Southwest Disposal	West Side of Plant
RAGS, OILY	Exempt & Non-exempt	Recycle by incineration	Quell or U.S. Filter	South east of plant
RAIN WATER, TANK BATTERY	Exempt (contaminated) & Non-exempt (clean), Non-hazardous	injection	MOC SWD Well	Bulk tank
RUBBER PRODUCTS (Belts, hoses, etc.)	Non-exempt, Non-hazardous	Landfill	Southwest Disposal	Roll-off bin
SOIL - AMINE CONTAMINATED, (spent)	Exempt	Landfarming/Bioremediation	Plant landfarm	Landfarm staging area
SOIL - AMINE CONTAMINATED, (virgin)	Non-exempt	Landfarming/Bioremediation	Plant landfarm	Landfarm staging area
SOIL - GLYCOL CONTAMINATED (spent)	Exempt	Landfarming/Bioremediation	Plant landfarm	Landfarm staging area
SOIL - GLYCOL CONTAMINATED (virgin)	Non-exempt	Landfarming/Bioremediation	Plant landfarm	Landfarm staging area
SOIL - HYDROCARBON CONTAMINATED (exempt)	Exempt	Landfarming/Bioremediation	Plant landfarm	Landfarm staging area
SOIL - LUBE OIL CONTAMINATED (non-exempt)	Non-exempt	Landfarming/Bioremediation	Plant landfarm	Landfarm staging area
SOIL - PRODUCED WATER CONTAMINATED (exempt)	Exempt	Bioremediation	In place	NA
SOIL - SULFUR CONTAMINATED	Exempt	Land discharge	1) Lea Land 2) Control Recovery, Inc.	West side of SRU, west of fence
SOLVENT, SPENT	Non-exempt, Potentially hazardous	Recycle	Safety Kleen	Naphtha 105 - pumper shack; 55-gallon drum Aquaworks - NA
SULFUR RECOVERY UNIT USED CATALYST & SUPPORT BALLS	Exempt	1) Exempt waste disposal facility 2) Non-hazardous industrial landfill	1) Exempt waste disposal facility 2) Control Recovery, Inc. 3) Lea Land	Roll-off bin when needed
SULFUR, OFF-SPEC	Exempt, Non-hazardous	1) Land discharge 2) Non-hazardous industrial landfill	1) West side of SRU, west of fence 2) Control Recovery, Inc. 3) Lea Land	Sulfur storage yard west of Sulfur Recovery Unit (SRU)
SULFURIC ACID	Non-exempt, Hazardous	Neutralized and landfilled	Safety-Kleen	NA
TIRES, VEHICLE USED	Non-exempt, Non-hazardous	Recycle	The Tire Co. - Carlsbad, NM	NA

Table 3. Inventory of Tanks

Name	Tank Volume	Type	Containment	Storage Contents
Condensate tank (bullet)/SE plant	1700 Bbl	npASST	Earthen dike	NA
Condensate tank (bullet)/SE plant	1700 Bbl	npASST	Earthen dike	NA
Tank (bullet)/SE plant (not in service)	1700 Bbl	npASST	Earthen dike	NA
Tank (bullet)/SE plant tank	1700 Bbl	npASST	Earthen dike	NGL
Tank (bullet)/SE plant tank	1700 Bbl	npASST	Earthen dike	NGL
Tank (bullet)/SE plant tank	1700 Bbl	npASST	Earthen dike	NGL
Gun Barrel Storage Tank	750 Bbl	npASST	Earthen dike	Condensate and Produced Water
Condensate Storage Tank	1000 Bbl	npASST	Earthen dike	Stabilized Condensate
Condensate Storage Tank	1000 Bbl	npASST	Earthen dike	Stabilized Condensate
Water Storage Tank	500 Bbl	npASST	Earthen dike	Water
Lube oil tank/recompressor	210 Bbl	npASST	Earthen dike	NA
Lube oil saddle tank/inlet compressor	52 Bbl	npASST	Concrete	NA
Open-top skimmer tank/skimmer pit	437 Bbl	npAST	Earthen dike	Wastewater
Saltwater tank (steel)/SW plant area(not in serv)	1000 Bbl	npASST	No	To injection
Saltwater tank (fiberglass)/SW plant area	500 Bbl	npAST	Concrete	To injection
Lube oil saddle tank/stabilizer compressor	11.9 Bbl	npASST	Steel	NA
Diesel tank/north plant area	10 Bbl	npASST	Concrete	Diesel
Meropa tank/SW plant area	100 gal	npASST	Steel	Meropa oil
Waste oil tank/west plant area	500 gal	npASST	Concrete	Waste & slop oils
Condensate tank/treatment compound	210 Bbl	npAST	Earthen dike	Cond. Contaminated Water
Condensate tank/treatment compound	210 Bbl	npAST	Earthen dike	Cond. Contaminated Water
Freshwater steel tank/NE plant area	1200 Bbl	npAST	No	Freshwater
Freshwater fiberglass tank/NE plant area	125 Bbl	npAST	No	Freshwater
Softwater tank/SW plant area	90 Bbl	npAST	Concrete	Freshwater
Reverse osmosis freshwater tank/SW plant	280	npAST	No	Freshwater
Glycol steel tank/SW plant area	90 Bbl	npAST	Concrete	Softwater
Sulfur tank/NW plant area	47,000 gal	npUST	No	Liquid sulfur
Large DGA Slop Tank*	200 Bbl	npASST	Earthen dike	Used DGA; Royal Purple oil
Small DGA Slop Tank*	70 Bbl	npASST	Earthen dike	Used DGA; Royal Purple oil
Burolock 2220 Storage Tank	1000 Bbl	npASST	Earthen dike	Calgon Burolock 2220
Ultramine 120 Storage Tank	1000 Bbl	npASST	Earthen dike	Calgon Ultramine 120
Conquor 3470 Storage Tank	1000 Bbl	npASST	Earthen dike	Calgon Conquor 3470
DEA Storage Tank #8	3000 gal	npASST	Earthen dike	New DEA
DEA Storage Tank #9*	4200 gal	npASST	Earthen dike	New DEA
TEG Storage Tank	750 g	npASST	Concrete	TEG
TEG Storage Tank	500 gal	npASST	Concrete	TEG
Methanol Storage Tank	500 gal	npASST	No	Methanol
Methanol Storage Tank	650 g	npASST	No	Methanol
Varsol Storage Tank	400 g	npASST	Concrete	Varsol
Kerosene Storage Tank	400 g	npASST	Concrete	Kerosene
Antifreeze Storage Tank	500 g	npASST	Concrete	Ethylene Glycol antifreeze
Selexol Storage Tank	210 Bbl	npAST	Concrete	Selexol
Caustic soda tank	500 gal	npASST	Steel	Caustic soda
Anti-foam tank	250 gal	npASST	Steel	Coastal Chem. 1017-F
Gun Barrel/treatment compound	500 bbl	npAST	Earthen dike	Cond. Contaminated water
Frac Tank	200 bbl	npAST	No	Fresh water
Frac Tank	200 bbl	npAST	No	Fresh water
Skimmer Oil tank	210 bbl	npAST	Concrete	Oil/water
Skimmer gun barrel	500 bbl	npAST	Concrete	Water/oil
Saltwater tank (east)	500 bbl	npAST	Concrete	Produced water/oil
Saltwater tank (middle)	500 bbl	npAST	Concrete	Produced water/oil
Saltwater tank (west)	500 bbl	npAST	Concrete	Produced water/oil
Calgon Pre-tect 32	500 gal	npASST	Steel	Calgon pre-tect 32
Gibraltar A-105 Tank (AGC)	500 gal		Steel	Oil

npASST = nonpressurized aboveground saddle storage tank (i.e. 360 degree inspection possible)

npAST = nonpressurized aboveground storage tank (i.e. 360 degree inspection possible)

npUST = nonpressurized underground storage tank

NA = not applicable

Table 4. Inventory of Process Vessels

Source location	Volume (Bbls)	Vessel Type	Vessel Bottom Lined Ground Underneath Paved	Contents	Fluids Drained to
Water exchanger/gas inlet	28	APV	In air/no	Cooling tower water	Abandoned OD
Inlet gas separator #1/gas inlet	90	APV	In air/no	Produced water	CD
Inlet gas separator #2/gas inlet	32	APV	In air/yes, conc. foundation pad	Produced water	CD
Air receiver/gas inlet	1	APV	In air/yes, conc. foundation pad	Atmospheric water	Bucket
Inlet separator/inlet compressor	75	APV	In air/no	Produced water	OD
Suction scrubber/inlet compressor	58	APV	In air/yes, conc. foundation pad	Produced water	OD
Air receiver/inlet compressor	3	APV	In air/yes, conc. foundation pad	Atmospheric water	Bucket
Amine contactor/amine sweetening	324	APV	In air/yes, conc. foundation pad	Produced water, amine	CD
Amine contactor overhead gas scrubber/amine sweetening	8	APV	In air/yes, conc. foundation pad	Produced water, amine	CD
Rich amine flash tank/amine sweetening	76	APV	In air/no	Produced water, amine	CD
Amine bag filter/amine sweetening	2	APV	In air/yes	Produced water, amine	Amine bag filter
Condensate stabilizer overhead condenser/amine sweetening	2	APV	In air/yes	Produced water, amine	OD & rich-lean amine exchanger
Amine still condenser/amine sweetening	2	APV	In air/no	Produced water	Aerial cooler to stabilizer reflux dru
Lean amine-water plate exchanger/amine sweetening	2	APV	In air/no	Produced water	Aerial cooler to reflux accumulator
Rich-lean amine exchanger/amine sweetening	2	APV	In air/yes	Produced water, amine	OD
Amine still/amine sweetening	22	APV	In air/no	Produced water, amine	OD
Amine reflux accumulator/amine sweetening	300	APV	In air/yes conc. foundation pad	Amine	Amine still
Amine still reboiler/amine sweetening	8	APV	In air/yes conc. foundation pad	Reflux water, amine	CD
Steam condensate surge tank/amine sweetening	19	APV	In air/yes conc. foundation pad	Reflux water, amine	CD
Amine charcoal filter/amine sweetening	50	APV	In air/no	Reflux water, amine	CD
Glycol water exchanger/glycol dehydration	60	APV	In air/yes, conc. pad	Condensed steam water	CD
Glycol contactor/glycol dehydration	2	APV	In air/no	Amine	Slp amine tank
Glycol contactor overhead scrubber/glycol dehydration	205	APV	In air/yes, conc. foundation pad	Produced water, glycol	CD
Glycol regenerator/glycol dehydration	8	APV	In air/yes, conc. foundation pad	Produced water, glycol	CD
Rich-lean glycol exchanger/glycol dehydration	73	APV	In air/no	Produced water, glycol	Atmosphere
Glycol surge tank/glycol dehydration	59	APV	In air/no	Produced water, glycol	Glycol contactor
Water collection drum/glycol dehydration	16	APV	In air/no	Glycol	OD
Inlet water separator/inlet condensate	3	APV	In air/yes	Produced water, glycol	OD
Stabilizer feed tank/inlet condensate	291	APV	In air/no	Steam, glycol	Abandoned OD
Regeneration gas scrubber/regeneration gas	291	APV	In air/yes	Produced water, cond.	CD
Product contactor/product treating	10	APV	In air/no	Produced water, cond.	CD
Product solvent separator/product treating	128	APV	In air/yes, conc. foundation pad	Produced water, cond.	Buckets
Acid gas scrubber #1/SRU	16	APV	In air/yes, conc. foundation pad	Amine, KOH	Rich amine flash tank
Acid gas scrubber #2/SRU	11	APV	In air/no	Amine, KOH	Amine reflux accumulator
Small condenser/SRU	11	APV	In air/no	Reflux water	Amine reflux accumulator
Large condenser/SRU	20	APV	In air/no	Reflux water	OD
Line 1, 3-phase separator/inlet pit	59	APV	In air/no	Cooling tower water	CD
Line 3, 3-phase separator/inlet pit	20	APV	In air/no	Cooling tower water	Skimmer basin
Line 4, 3-phase separator/inlet pit	14	APV	In air/no	Produced water, cond.	Skimmer basin
Cond.stabilizer feed-bottoms exchanger/cond.stabilization	36	APV	In air/no	Produced water, cond.	Skimmer basin
Condensate stabilizer reboiler/cond.stabilization	5	APV	On ground/no	Condensate	Cond.stabilizer tower or cooler
Condensate stabilizer/cond.stabilization	10	APV	In air/no	Condensate, steam	OD
Stabilizer reflux drum/cond. Stabilization	119	APV	On ground/yes, concrete pad	Condensate	OD
Stabilizer bottoms cooler/cond. Stabilization	10	APV	On ground/yes, concrete pad	Cond. Reflux water	OD
	1	APV	In air/no	Condensate	Condensate stabilizer tower or cooler

Table 4. Inventory of Process Vessels

Source location	Volume (Bbls)	Vessel Type	Vessel Bottom Lined/ Ground Underneath Paved	Contents	Fluids Drained to
Steam waste heat boiler #1/steam system	71.4	APV	In air/no	Softwater w/ additives	OD
Steam waste heat boiler #2/steam system	71.4	APV	In air/no	Softwater w/ additives	OD
Steam waste heat boiler #3/steam system	71.4	APV	In air/no	Softwater w/ additives	OD
Blowdown drum/steam system	11.9	APV	In air/no	Softwater w/ additives	OD
Main boiler/steam system	35.7	APV	In air/no	Softwater w/ additives	OD
Utility flare drum/plant flare system		APV	In air/no	Gas	Flare
Inlet gas flare drum/plant flare system	61	APV	In air/no	Produces water, cond.	Condensate
Stabilizer compressor suction scrubber	2	APV	In air/concrete pad	Condensate	OD
Stabilizer compressor suction scrubber		APV	Concrete pad with berm	Water/lube oil	OD
Inlet compressor		Comp	Concrete pad with berm	Water/lube oil	OD
A-2 Amine contactor	55	APV	In air/yes, conc. foundation pad	Produced water/Amine	CD
A-2 Amine contactor overhead scrubber	8	APV	In air/yes, conc. foundation pad	Produced water/Amine	CD
A-2 Rich Amine Flash tank	35	APV	In air/yes, steel skid	Amine/Produced water	CD
A-2 Amine Pre-bag filter	3	APV	In air/yes, steel skid	Amine	Bag filter
A-2 Amine Charcoal Filter	12	APV	In air/yes, steel skid	Amine	Amine charcoal filter
A-2 Amine Post-bag filter	3	APV	In air/yes, steel skid	Amine	Amine Post-bag filter
A-2 Rich/Lean Amine Exchanger	10	APV	In air/yes, steel skid	Amine	High pressure pumps
A-2 Amine Reboiler/Surge Tank	46	APV	In air/yes, steel skid	Reflux water/Amine	Amine still
A-2 Lean Amine/water heat exchanger	8	APV	In air/yes, steel skid	Reflux water/Amine	CD
A-2 Lean Amine cooler	2	APV	In air / no	Produced water/Amine	Pre-bag filter
A-2 Amine condensor fans	2	APV	In air / no	Amine	Lean Amine/ water exchanger
A-2 Amine Reflux Accumulator	9	APV	In air/yes, conc. foundation pad	Produced water	Aerial cooler to reflux accumulator
A-2 Amine Still	48	APV	In air/yes, conc. foundation pad	Reflux water/Amine	CD
A-2 Rich Bag Filter	5	APV	In air/yes, steel skid	Amine/Produced water	CD
Field Fuel Gas Scrubber South side	7	APV	In air/yes, conc. foundation pad	Fuel gas	OD rich/ lean amine exchanger
Inlet Gas Filter Separator South side	29	APV	In air/no	Produced water, cond.	Closed drain
Gas/water heat exchanger South side	35	APV	In air/no	Water/gas	Condensate system
Selexol Contactor	27	APV	In air/yes, conc. foundation pad	In air/yes, conc. foundation pad	Cooling tower
Selexol Overhead Filter Coalescer	1	APV	In air/yes, conc. foundation pad	In air/yes, conc. foundation pad	Selexol Flash Tank
Selexol Flash Tank	22	APV	In air/yes, steel skid	R.O. Water/Selexol (95%)	Selexol Flash Tank
Selexol (Rich) Filter	3	APV	In air/yes, steel skid	R.O. Water/Selexol (95%)	Rich Selexol Filter
Selexol Lean/Rich Heat Exchanger	94	APV	In air/yes, conc. foundation pad	R.O. Water/Selexol (95%)	L/R HEX / OD
Selexol Still Column	34	APV	In air/yes, conc. foundation pad	R.O. Water/Selexol (95%)	Selexol Still Column
Selexol Surge Tank	35	APV	In air/yes, steel skid	R.O. Water/Selexol (95%)	Selexol Surge Tank/Gun Barrel
Selexol Cooler	5	APV	In air/no	R.O. Water/Selexol (95%)	L/R HEX / OD
Selexol Charcoal Filter	2	APV	In air/yes, steel skid	R.O. Water/Selexol (95%)	Charcoal Filter
Selexol (Lean) Filter	3	APV	In air/yes, steel skid	R.O. Water/Selexol (95%)	Lean Selexol Filter / OD
Selexol Reflux Cooler	1	APV	In air/no	Process Water/ Selexol (<1%)	Reflux Accumulator / OD
Selexol Reflux Accumulator	2	APV	In air/yes, conc. foundation pad	Process Water/ Selexol (<1%)	Selexol Still Column / OD
Selexol Anti-Foam Pot	0.05	APV	In air/yes, steel skid	Silicone Based Anti-Foam	Selexol Contactor / Still / OD

APV = aboveground process vessel (i.e. 360 degree inspection possible)
 comp = compressor
 cond. = condensate

OD=Open Drain
 CD=Closed Drain


Table 5. Underground Piping


Piping Name	Pathway	Category or Modifier	Flow Rate (bbl/day)	Pressure (psig)	Diameter (in.)	Piping Type	Install. Date
Open drain system	Various plant units to open drain collection sump	2002	15	no	3.2	IC Steel	Sept 2019
Softwater regeneration	Water softener in water treatment building to fiberglass SWD tank	Before 1990	385	15	2	PVC	Jan 2015
Reverse osmosis wastewater piping (Out of service due to permit)	RO unit in water treatment building to air stripper outlet to infiltration	1991	200	60	2	Poly	Jan 2016
Untreated groundwater bypass piping	Division valve at treatment compound to Skimmer Basin	1995	2676	50	2	Poly	Jan 2016
Treated groundwater piping	Air stripper at treatment compound to skimmer basin SWD tank	1995	125	20	6	Poly	Jan 2020
Piping to Marathon Federal SWD Well No.1 (Sec.24) (Not in service)	Fiberglass saltwater tank to injection well	1977	Minimal	2000	3	Steel	Jan 2002
Piping to A.G.I. #1 well	Saltwater tank to injection well	2000	3000	2000	6	Fiberglass	-
Waste effluent transfer piping	Open drain collection sump to skimmer basin	1996	80	<10	4	IC Steel	Jan 2011
Co-production line to skimmer basin gunbarrel	Co-production line outside plant to skimmer basin gunbarrel	1996	2000	<10	6	Fiberglass	Jan 2016
Condensate Delivery Sales	Condensate bullet storage tanks(1) to condensate loading area (LA)	1993	300	<10	4	Poly	Mar 2018
SRU waste heat boiler & large condenser blowdown discharge piping (OOS)	Waste heat boiler and large condenser to steel saltwater tank	1985/1992	10	70	2	Steel	Jan 2017
Condensate make line	Stabilizer to condensate bullet storage tanks	1989	300	<20	2	Steel	Jan 2014
Condensate rerun line	Condensate bullet storage tanks to overhead pipe rack	1989	10;100 max	<20	2	Steel	Jan 2014
LACT sump pump to main boiler sump	LACT sump pump to main boiler sump	1966/1989	1	<35	2	Steel/Poly	Jan 2014
Inlet condensate line	Inlet valve pit to overhead pipe rack	1990	350	<30	4	Steel	Jan 2015
Divert line	Inlet valve pit to condensate bullet storage tanks	1993	1	40	2	Poly	Jan 2018
Produced water line	Inlet valve pit to skimmer basin gunbarrel	1996	1500	15	6	Poly	Jan 2018
Product skimmer recovery line	Skimmer basin oil transfer pump to inlet condensate line	1996	20	40	2	Steel	Jan 2011
Dump line	Stabilizer feed tank to skimmer basin	1996	50	40	4	Poly	Jan 2017
Injection line	Fiberglass saltwater tank to pump suction header	1996	3000	30	10	Steel	Jan 2013
Open top tank to skimmer basin gunbarrel	Open top transfer pump to skimmer basin gunbarrel	1996	50	10	2	Steel	Jan 2021
Cooling tower blowdown to skimmer basin	Cooling tower blowdown to skimmer basin SWD tank	1999	200	<10	2	Poly	Jan 2024
Morrow gas separator dump line	Morrow gas separator to closed drain	1996	0	<5	2	Steel	Jan 2021
Closed drain scrubber dump line	Closed drain scrubber to skimmer basin gunbarrel	1996	5	40	2	Poly	Jan 2021
Inlet filter/separator closed drain connection	Inlet filter/separator to inlet condensate line	1998	20	<10	2	Steel	Jan 2023
Inlet filter/separator closed drain connection	Inlet filter/separator to closed drain header	1998	0	40	2	Steel	Jan 2023
Blow down collection header	Open drain collection sump area to boiler blow down bottle	1996	80	40	2	Steel	Jan 2021
SRU Steam Condensate Return	SRU Steam Condensate Return	2001	10	0	2	Stainless	Jan 2009
Horizontal H.P. Inlet Scrubber Closed Drain	WHB's to open drain collection sump area	1994	1	40	2	Steel	Dec 2019
WHB Blowdown	Main boiler to blow down collection header	1991	65	100	2	Steel	Jan 2016
Main boiler blowdown to sump	Open drain collection sump pump to skimmer basin gunbarrel	1996	15	100	2	Steel	Jan 2015
Open drain collection sump pump to skimmer basin gunbarrel	Open drain collection sump pump to skimmer basin gunbarrel	1980	80	100	4	IC Steel	Jan 2005
Stabilizer Compressor Dump	Inlet Condensate Divert Line to the Transfer Tank	1982	15	30	1	Steel	Jan 2007
Inlet Condensate Divert Line to the Transfer Tank (OOS)	Line 3 & 4 Metering Separator Oil Dump Line to Inlet Cond. Line	1986	1	270	2	Steel	Jan 2011
Line 3 & 4 Metering Separator Oil Dump Line to Inlet Condensate Line	Inlet Compr. Suction Scrubber (H&V) Dump Lines to Inlet Metering Separator	1996	200	40	3	Steel	Jan 2014
Inlet Compressor Suction Scrubber (H&V) Dump Lines to Inlet Metering Separator	Recompressor & Expander Lube Oil Makeup Line	1989	3	30	2	Steel	Jan 2014
Recompressor & Expander Lube Oil Makeup Line	Underground Amine Lines Tied to Valve "Octopus" From:	1980	<1	150	1	Steel	Jan 2005
Underground Amine Lines Tied to Valve "Octopus" From:	Little stop	1988	1	5	2	Steel	Jan 2013
Flash tank	1988	1	80	2	2	Steel	Jan 2013
Bag filters	1988	<1	80	2	2	Steel	Jan 2013
Charcoal filters	1988	<1	80	2	2	Steel	Jan 2013
Reflux pumps	1988	1	20	2	2	Steel	Jan 2013
Amine Storage Tank 8	1988	1	5	2	2	Steel	Jan 2013
Amine Storage Tank 9	1988	1	5	2	2	Steel	Jan 2013
Glycol Storage Tank Discharge	Storage Tank transfer pump to glycol flash tank	1999	1	70	2	Poly	Dec 2019
Acid Gas Compressor Suction Line	SRU to Acid Gas Compressor	1996	1MMSCF/d	6	10	Steel	Jan 2021
Acid Gas Compressor Sweet Purge Gas	Pipe rack at Glycol Unit to Acid Gas Compressor	1996	80	2	2	Steel	Jan 2021
Acid Gas Compressor Instrument Air	Pipe rack at Glycol Unit to Acid Gas Compressor	1996	80	2	2	Steel	Jan 2021
Selexol reflux water	Selexol unit to gunbarrel	2002	1	25	2	Steel	None scheduled
Selexol underground pipeline	Selexol storage tank to Selexol Unit	2002	As needed	25	2	Steel	None scheduled
Glycol flash gas to Closed Drain	Glycol flash tank to closed drain scrubber	2003	1 MMSCF/d	100	2"	steel	-
Cyclone dump to Closed Drain	Cyclone to Closed drain scrubber	2003	1000	1000	2 7/8"	steel	-

Table 6. Soil Treatment Cleanup Standards

Use of Treated Soil	Cleanup Standards (mg/kg)		
	TRPH (EPA 418.1)	Total BTEX	Benzene
Reburied	100	50	10
Stormwater control dikes	1000	50	10
Secondary containment berms in the gas plant	3000	50	10
Roadspread or patching lease roads	3000	50	10
Pad dirt on production locations	3000	50	10

FIGURE 1





- NATURAL GASOLINE 3A
- NATURAL GASOLINE 3B
- BUTANE 2A
- BUTANE 2B
- PROPANE 1A
- PROPANE 1B
- PROPANE 1C



Marathon Oil Company

Midland, Texas 79701

DATE	BY	REVISIONS
8/17/92	JLS	MINOR REVISIONS
5/31/00	VHR	UPDATED BY AL COMPTON
3/22/02	OH	ADDED SELEXOL UNIT & DEHY "D"
7/19/02	SMJ	REVISED FOR AUDIT
1/22/04	DGS	REVISED FOR MOC 04-006 Ethanol Tank

FIGURE 2

INDIAN BASIN GAS PLANT

PLOT PLAN

PRELIMINARY APP.	DATE	FINAL APP.	DATE

SCALE: 40'=1"

APPENDIX A

LABORATORY RESULTS OF COMMINGLED DISCHARGE FLUID

NOV 21 1999

Environmental & Safety

ANALYTICAL REPORT

JOB NUMBER: 912816

Prepared For:

Marathon Oil Company
125 West Missouri Street
P.O. Box 552
Midland, TX 79702-0552

Attention: Mr. Paul Peacock

Date: 11/16/99



Signature

Name: Les Arnold

Title: Laboratory Manager

11/16/99

Date

Severn Trent Laboratories
2400 Cumberland Drive
Valparaiso, IN 46383

PHONE: 219-464-2389

FAX...: 219-462-2953



SAMPLE INFORMATION

Date: 11/16/99

Job Number.: 912816
Customer...: Marathon Oil Company
Attn.....: Mr. Paul Peacock

Project Number.....: 96000651
Customer Project ID....: INDIAN BASIN GAS PLT
Project Description....: Marathon Oil Co., Midland, Tx

Laboratory Sample ID	Customer Sample ID	Sample Matrix	Date Sampled	Time Sampled	Date Received	Time Received
912816-1	COMINGLED GAS PLT WASTE EFFLUENT	Aqueous	11/08/1999	10:00	11/09/1999	15:25



LABORATORY TEST RESULTS

Job Number: 912816

Date: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: INDIAN BASIN GAS PLT

ATTN: Mr. Paul Peacock

Customer Sample ID: COMINGLED GAS PLT WASTE EFFLUENT
 Date Sampled.....: 11/08/1999
 Time Sampled.....: 10:00
 Sample Matrix.....: Aqueous

Laboratory Sample ID: 912816-1
 Date Received.....: 11/09/1999
 Time Received.....: 15:25

TEST METHOD	PARAMETER/TEST DESCRIPTION	SAMPLE RESULT	REPORTING LIMIT	UNITS	DATE	TECH
EPA 160.1	Solids, Total Dissolved (TDS)	21000	10	mg/L	11/10/99	lam
EPA 300.0	Chloride	6600	1000	mg/L	11/10/99	kso
EPA 300.0	Fluoride (F)	<50	50	mg/L	11/10/99	kso
EPA 300.0	Nitrogen, Nitrate as N (NO3-N)	<1.0	1.0	mg/L	11/10/99	kso
EPA 300.0	Sulfate (SO4)	1460	100	mg/L	11/10/99	kso
EPA 420.2	Phenol, Total Recoverable	0.18	0.05	mg/L	11/11/99	dmw
SM 4500 CN	Cyanide, Total	0.08	0.05	mg/L	11/15/99	jdb
EPA 3010	Acid Digestion, Metals (ICP)	Complete			11/10/99	amw
EPA 7470	Mercury (Hg)	<0.001	0.001	mg/L	11/11/99	pal
EPA 3510	Separatory Funnel Liq/Liq Extraction	Complete			11/12/99	bjl
EPA 6010B	Metals Analysis (ICAP)					
	Aluminum (Al)	<0.1	0.1	mg/L	11/11/99	pal
	Arsenic (As)	<0.02	0.02	mg/L	11/10/99	amw
	Barium (Ba)	0.06	0.01	mg/L	11/10/99	chh
	Boron (B)	1.67	0.05	mg/L	11/11/99	pal
	Cadmium (Cd)	<0.005	0.005	mg/L	11/10/99	chh
	Chromium (Cr)	0.01	0.01	mg/L	11/10/99	chh
	Cobalt (Co)	<0.03	0.03	mg/L	11/10/99	chh
	Copper (Cu)	0.02	0.01	mg/L	11/10/99	chh
	Iron (Fe)	6.83	0.05	mg/L	11/10/99	chh
	Lead (Pb)	<0.05	0.05	mg/L	11/10/99	chh
	Manganese (Mn)	0.23	0.01	mg/L	11/10/99	chh
	Molybdenum (Mo)	<0.05	0.05	mg/L	11/10/99	chh
	Nickel (Ni)	0.03	0.01	mg/L	11/10/99	chh
	Selenium (Se)	<0.02	0.02	mg/L	11/10/99	amw
	Silver (Ag)	<0.01	0.01	mg/L	11/10/99	amw
	Zinc (Zn)	0.21	0.01	mg/L	11/10/99	chh
EPA 8310	Polynuclear Aromatic Hydrocarbons-HPLC					
	Acenaphthene	ND	5.0	ug/L	11/16/99	rm
	Acenaphthylene	ND	5.0	ug/L	11/16/99	rm
	Anthracene	ND	1.0	ug/L	11/16/99	rm
	Benzo(b)fluoranthene	ND	0.10	ug/L	11/16/99	rm
	Benzo(k)fluoranthene	ND	0.10	ug/L	11/16/99	rm
	Benzo(a)anthracene	ND	0.10	ug/L	11/16/99	rm
	Benzo(a)pyrene	ND	0.10	ug/L	11/16/99	rm
	Benzo(ghi)perylene	ND	0.10	ug/L	11/16/99	rm
	Chrysene	ND	1.0	ug/L	11/16/99	rm



LABORATORY TEST RESULTS

Job Number: 912816

Date: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: INDIAN BASIN GAS PLT

ATTN: Mr. Paul Peacock

Customer Sample ID: COMINGLED GAS PLT WASTE EFFLUENT
 Date Sampled.....: 11/08/1999
 Time Sampled.....: 10:00
 Sample Matrix.....: Aqueous

Laboratory Sample ID: 912816-1
 Date Received.....: 11/09/1999
 Time Received.....: 15:25

TEST METHOD	PARAMETER/TEST DESCRIPTION	SAMPLE RESULT	REPORTING LIMIT	UNITS	DATE	TECH	
EPA 8260B	Dibenzo(a,h)anthracene	ND	0.10	ug/L	11/16/99	rm	
	Fluoranthene	ND	1.0	ug/L	11/16/99	rm	
	Fluorene	ND	1.0	ug/L	11/16/99	rm	
	Indeno(1,2,3-cd)pyrene	ND	0.10	ug/L	11/16/99	rm	
	Naphthalene	<5.0	5.0	ug/L	11/16/99	rm	
	Phenanthrene	ND	1.0	ug/L	11/16/99	rm	
	Pyrene	ND	1.0	ug/L	11/16/99	rm	
	Volatile Organic Compounds						
	Vinyl chloride	ND	500	ug/L	11/15/99	weh	
	1,1-Dichloroethene	ND	200	ug/L	11/15/99	weh	
	Methylene chloride	ND	200	ug/L	11/15/99	weh	
	Benzene	4300	200	ug/L	11/15/99	weh	
	Carbon tetrachloride	ND	200	ug/L	11/15/99	weh	
	Chloroform	ND	200	ug/L	11/15/99	weh	
	1,2-Dibromoethane (EDB)	ND	200	ug/L	11/15/99	weh	
	1,1-Dichloroethane	ND	200	ug/L	11/15/99	weh	
	1,2-Dichloroethane	ND	200	ug/L	11/15/99	weh	
	Ethylbenzene	700	200	ug/L	11/15/99	weh	
	1,1,2,2-Tetrachloroethane	ND	200	ug/L	11/15/99	weh	
	Tetrachloroethene	ND	200	ug/L	11/15/99	weh	
	Toluene	13000	200	ug/L	11/15/99	weh	
	1,1,1-Trichloroethane	ND	200	ug/L	11/15/99	weh	
	1,1,2-Trichloroethane	ND	200	ug/L	11/15/99	weh	
	Trichloroethene	ND	200	ug/L	11/15/99	weh	
	Xylenes (total)	7000	500	ug/L	11/15/99	weh	



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Test Method.....: EPA 300.0
 Method Description.: Ion Chromatography Analysis
 Parameter.....: Chloride

Batch.....: 49213
 Units.....: mg/L

Analyst....: kso
 Test Code.: CHL

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
ICV		V199269C	9.197		10		92.0	%	85-115	11/10/1999	1149
ICB			0.274							11/10/1999	1202
CCV		V199269C	9.602		10		96.0	%	85-115	11/10/1999	1253
CCB			0.277							11/10/1999	1306
CCV		V199269C	9.760		10		97.6	%	85-115	11/10/1999	1358
CCB			0.317							11/10/1999	1411
MD	912816-1		6.777	2.69		6.645604	2.0	R	20	11/10/1999	1436
MS	912816-1	V199269B	17.954		10.000000	6.645604	113.1	%	75-125	11/10/1999	1449
CCV		V199269C	9.837		10		98.4	%	85-115	11/10/1999	1502
CCB			0.320							11/10/1999	1515

Test Method.....: SM 4500 CN
 Method Description.: Cyanide
 Parameter.....: Cyanide, Total

Batch.....: 49471
 Units.....: mg/L

Analyst....: jdb
 Test Code.: CNT

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
ICV		V199237D	0.000461							11/15/1999	1857
ICB			0.100252		0.1		100.3	%	85-115	11/15/1999	1857
MB			-0.000704							11/15/1999	1858
LCS		V199237C	0.081533		0.080000		101.9	%	80-120	11/15/1999	1859
MD	912698-4		0.006644			0.001112	0.005532	A	0.005000	11/15/1999	1901
MS	912698-4	V199237C	0.217930		0.200000	0.001112	108.4	%	75-125	11/15/1999	1901
CCV		V199237D	0.103436		0.1		103.4	%	85-115	11/15/1999	1906
CCB			0.000040							11/15/1999	1907
CCV		V199237D	0.098843		0.1		98.8	%	85-115	11/15/1999	1916
CCB			0.001002							11/15/1999	1917
CCV		V199237D	0.096158		0.1		96.2	%	85-115	11/15/1999	1927
CCB			0.001337							11/15/1999	1929
CCV		V199237D	0.098777		0.1		98.8	%	85-115	11/15/1999	1931
CCB			0.001160							11/15/1999	1932

Test Method.....: EPA 300.0
 Method Description.: Ion Chromatography Analysis
 Parameter.....: Fluoride (F)

Batch.....: 49213
 Units.....: mg/L

Analyst....: kso
 Test Code.: FL

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
ICV		V199269C	1.063		1		106.3	%	85-115	11/10/1999	1149
ICB			0.0000							11/10/1999	1202
CCV		V199269C	1.071		1		107.1	%	85-115	11/10/1999	1253
CCB			0.000							11/10/1999	1306
MD	912816-1		0.00			0.00	0.00	A	0.50	11/10/1999	1332
MS	912816-1	V199269B	0.952		1.000000	0.00	95.2	%	75-125	11/10/1999	1345
CCV		V199269C	0.965		1		96.5	%	85-115	11/10/1999	1358
CCB			0.000							11/10/1999	1411
CCV		V199269C	0.973		1		97.3	%	85-115	11/10/1999	1502
CCB			0.000							11/10/1999	1515



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Test Method.....: EPA 300.0
 Method Description.: Ion Chromatography Analysis
 Parameter.....: Nitrogen, Nitrate as N (NO3-N)
 Batch.....: 49213
 Units.....: mg/L
 Analyst...: kso
 Test Code.: NO3

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
ICV		V199269C	0.944		1		94.4	%	85-115	11/10/1999	1149
ICB			0.010							11/10/1999	1202
MD	912816-1		0.0158			0.000	0.0158	A	0.1000	11/10/1999	1228
MS	912816-1	V199269B	0.890		1.000000	0.000	89.0	%	75-125	11/10/1999	1241
CCV		V199269C	0.986		1		98.6	%	85-115	11/10/1999	1253
CCB			0.010							11/10/1999	1306
CCV		V199269C	1.007		1		100.7	%	85-115	11/10/1999	1358
CCV		V199269C	0.999		1		99.9	%	85-115	11/10/1999	1502
CCB			0.011							11/10/1999	1515

Test Method.....: EPA 420.2
 Method Description.: Phenolics, Total Recoverable (Auto.)
 Parameter.....: Phenol, Total Recoverable
 Batch.....: 49279
 Units.....: mg/L
 Analyst...: dmw
 Test Code.: PHENTR

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
		V199270G	0.198905		0.2000		99.5	%	85-115	11/11/1999	1451
			-0.002587							11/11/1999	1452
LCS		V199268C	0.089323		0.100000		89.3	%	80-120	11/11/1999	1453
MB			-0.003807							11/11/1999	1453
MS	912777-2	V199268C	0.095418		0.100000	-0.005935	101.4	%	75-125	11/11/1999	1455
MD	912777-2		-0.004557			-0.005935	0.001378	A	0.005000	11/11/1999	1455
CCV		V199270G	0.198366		0.2000		99.2	%	85-115	11/11/1999	1502
CCB			-0.002379							11/11/1999	1503
CCV		V199270G	0.200532		0.2000		100.3	%	85-115	11/11/1999	1510
CCB			-0.003195							11/11/1999	1511
CCV		V199270G	0.199045		0.2000		99.5	%	85-115	11/11/1999	1514
CCB			-0.003235							11/11/1999	1514

Test Method.....: EPA 160.1
 Method Description.: Solids, Total Dissolved (TDS)
 Parameter.....: Solids, Total Dissolved (TDS)
 Batch.....: 49210
 Units.....: mg/L
 Analyst...: lam
 Test Code.: TDS

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
MB			0.0							11/10/1999	1410
LCS		V199269D	9503.0		10000		95.0	%	80-120	11/10/1999	1420
MD	912804-1		1782.0			1774.0	0.4	R 20		11/10/1999	1450
MS	912804-1	V199269D	2326.0		500.000000	1774.0	110.4	%	75-125	11/10/1999	1500

Test Method.....: EPA 300.0
 Method Description.: Ion Chromatography Analysis
 Parameter.....: Sulfate (SO4)
 Batch.....: 49213
 Units.....: mg/L
 Analyst...: kso
 Test Code.: SO4

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
ICV		V199269C	20.217		20		101.1	%	85-115	11/10/1999	1149
ICB			0.506							11/10/1999	1202
		V199269C	20.660		20		103.3	%	85-115	11/10/1999	1253
			0.506							11/10/1999	1306



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Test Method.....: EPA 300.0
 Method Description.: Ion Chromatography Analysis
 Parameter.....: Sulfate (SO4)

Batch.....: 49213
 Units.....: mg/L

Analyst...: kso
 Test Code.: SO4

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
MD	912816-1		14.51647			14.61164	0.7	R	20	11/10/1999	1332
MS	912816-1	V199269B	35.568		20.000000	14.61164	104.8	%	75-125	11/10/1999	1345
CCV		V199269C	21.063		20		105.3	%	85-115	11/10/1999	1358
CCB			0.485							11/10/1999	1411
CCV		V199269C	21.054		20		105.3	%	85-115	11/10/1999	1502
CCB			0.503							11/10/1999	1515

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Aluminum (Al)

Batch.....: 49281
 Units.....: mg/L

Analyst...: pal
 Test Code.: AL

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	0.00630		0.00					11/11/1999	1003
CAL		ICPCALSTD	2.17210		10.0					11/11/1999	1008
ICV		V211204A	2.03914		2.00		102.0	%	90-110	11/11/1999	1026
			-0.01382							11/11/1999	1030
		V211206A	488.59609		500.0		97.7	%	80-120	11/11/1999	1035
PB	1110-2		0.01572							11/11/1999	1046
LCS	1110-2	ICPSPK99B	1.02274		1.000		102.3	%	80-120	11/11/1999	1051
MD	912804-1		0.01623			0.04165	0.02542	A	0.10000	11/11/1999	1100
MS	912804-1	ICPSPK99B	1.16268		1.000	0.04165	112.1	%	75-125	11/11/1999	1104
ISB		V211206A	473.41082		500.0		94.7	%	80-120	11/11/1999	1132
CCV		V211204A	1.97128		2.00		98.6	%	90-110	11/11/1999	1143
CCB			-0.01565							11/11/1999	1148

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Arsenic (As)

Batch.....: 49229
 Units.....: mg/L

Analyst...: amw
 Test Code.: AS

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
ICV		V211205B	4.11327		4.00		102.8	%	90-110	11/10/1999	2109
ICB			0.00220							11/10/1999	2115
PB	1103-3		0.00598							11/10/1999	2144
LCS	1103-3	ICPSPK99B	0.53014		0.5000		106.0	%	80-120	11/10/1999	2150
MD	912510-1		0.02004			0.03000	0.00996	A	0.02000	11/10/1999	2202
MS	912510-1	ICPSPK99B	0.58903		0.5000	0.03000	111.8	%	75-125	11/10/1999	2207
PB	1110-2		0.00174							11/10/1999	2228
LCS	1110-2	ICPSPK99B	0.51947		0.5000		103.9	%	80-120	11/10/1999	2234
CCV		V211205B	4.09142		4.00		102.3	%	90-110	11/10/1999	2240
CCB			0.00120							11/10/1999	2246
MD	912804-1		0.02857			0.03230	0.00373	A	0.02000	11/10/1999	2257
MS	912804-1	ICPSPK99B	0.51995		0.5000	0.03230	97.5	%	75-125	11/10/1999	2303
PB	1108-1		0.00689							11/10/1999	2315
LCS	1108-1	V16008711	0.50299		0.516906		97.3	%	80-120	11/10/1999	2323
MS	912685-1	V16008208	1.72295		2.000000	0.00515	85.9	%	75-125	11/10/1999	2336
MSD	912685-1	V16008208	1.78756	1.72295	2.000000	0.00515	89.1	%	75-125	11/10/1999	2342
							3.7	R	20		
		V211205B	3.61105		4.00		90.3	%	90-110	11/11/1999	0006
			-0.00010							11/11/1999	0012



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Test Method.....: EPA 6010B

Batch.....: 49224

Analyst...: chh

Method Description.: Metals Analysis (ICAP)

Units.....: mg/L

Test Code.: BA

Parameter.....: Barium (Ba)

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	-0.00120		0.00					11/10/1999	1432
CAL		ICPCALSTD	0.99510		1.00					11/10/1999	1439
ICV		V211204A	2.07557		2.00		103.8	%	95-105	11/10/1999	1501
ICB			0.00050							11/10/1999	1506
ISB		V211204E	0.50175		0.50		100.3	%	80-120	11/10/1999	1510
CCV		V211204A	2.02930		2.00		101.5	%	95-105	11/10/1999	1602
CCB			0.00100							11/10/1999	1607
PB	1110-2		0.00100							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.50697		0.5000		101.4	%	80-120	11/10/1999	1634
MD	912804-1		0.45277			0.45106	0.4	R 20		11/10/1999	1642
MS	912804-1	ICPSPK99B	0.97761		0.5000	0.45106	105.3	%	75-125	11/10/1999	1646
CCV		V211204A	2.09976		2.00		105.0	%	95-105	11/10/1999	1713
CCB			0.00130							11/10/1999	1717
PB	1108-5		0.00010							11/10/1999	1750
LCS	1108-5	ICPSPK99B	0.52072		0.5000		104.1	%	80-120	11/10/1999	1755
CCV		V211204A	2.07467		2.00		103.7	%	95-105	11/10/1999	1803
CCB			0.00010							11/10/1999	1807
		V211204A	1.97571		2.00		98.8	%	95-105	11/10/1999	1947
			0.00115							11/10/1999	1953
ISB		V211204E	0.48981		0.50		98.0	%	80-120	11/10/1999	1956
MD	912691-2		0.06832			0.06634	2.9	R 20		11/10/1999	2005
MS	912691-2	ICPSPK99B	0.54399		0.5000	0.06634	95.5	%	75-125	11/10/1999	2009
ISB		V211204E	0.48180		0.50		96.4	%	80-120	11/10/1999	2022
CCV		V211204A	1.96174		2.00		98.1	%	95-105	11/10/1999	2032
CCB			0.00097							11/10/1999	2036

Test Method.....: EPA 6010B

Batch.....: 49281

Analyst...: pal

Method Description.: Metals Analysis (ICAP)

Units.....: mg/L

Test Code.: B

Parameter.....: Boron (B)

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	0.01799							11/11/1999	1003
CAL		ICPCALSTD	1.17519		2.00					11/11/1999	1020
ICV		V211204A	1.90770		2.00		95.4	%	90-110	11/11/1999	1026
ICB			0.00034							11/11/1999	1030
PB	1110-2		0.00674							11/11/1999	1046
LCS	1110-2	ICPSPK99B	0.48306		0.5000		96.6	%	80-120	11/11/1999	1051
MD	912804-1		0.34013			0.31991	6.1	R 20		11/11/1999	1100
MS	912804-1	ICPSPK99B	0.88627		0.5000	0.31991	113.3	%	75-125	11/11/1999	1104
CCV		V211204A	1.82682		2.00		91.3	%	90-110	11/11/1999	1143
CCB			-0.00276							11/11/1999	1148



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Cadmium (Cd)

Batch.....: 49224
 Units.....: mg/L

Analyst....: chh
 Test Code.: CD

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	0.00179		0.00					11/10/1999	1432
CAL		ICPCALSTD	3.98740		3.00					11/10/1999	1443
ICV		V211204A	2.04204		2.00		102.1	%	95-105	11/10/1999	1501
ICB			-0.00090							11/10/1999	1506
ISB		V211204E	0.89071		1.00		89.1	%	80-120	11/10/1999	1510
CCV		V211204A	1.99431		2.00		99.7	%	95-105	11/10/1999	1602
CCB			0.00067							11/10/1999	1607
PB	1110-2		-0.00173							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.04821		0.05000		96.4	%	80-120	11/10/1999	1634
MD	912804-1		0.00075			-0.00233	0.00308	A	0.00500	11/10/1999	1642
MS	912804-1	ICPSPK99B	0.04670		0.05000	-0.00233	98.1	%	75-125	11/10/1999	1646
CCV		V211204A	2.02239		2.00		101.1	%	95-105	11/10/1999	1713
CCB			0.00037							11/10/1999	1717
PB	1108-5		-0.00331							11/10/1999	1750
LCS	1108-5	ICPSPK99B	0.05024		0.05000		100.5	%	80-120	11/10/1999	1755
CCV		V211204A	2.00440		2.00		100.2	%	95-105	11/10/1999	1803
CCB			-0.00007							11/10/1999	1807
		V211204A	2.02085		2.00		101.0	%	95-105	11/10/1999	1947
			0.00349							11/10/1999	1953
ISB		V211204E	0.90071		1.00		90.1	%	80-120	11/10/1999	1956
MD	912691-2		-0.00065			-0.00092	0.00027	A	0.00500	11/10/1999	2005
MS	912691-2	ICPSPK99B	0.05126		0.05000	-0.00092	104.4	%	75-125	11/10/1999	2009
ISB		V211204E	0.91419		1.00		91.4	%	80-120	11/10/1999	2022
CCV		V211204A	2.07255		2.00		103.6	%	95-105	11/10/1999	2032
CCB			0.00026							11/10/1999	2036

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Chromium (Cr)

Batch.....: 49224
 Units.....: mg/L

Analyst....: chh
 Test Code.: CR

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	0.00069		0.00					11/10/1999	1432
CAL		ICPCALSTD	0.48109		1.0					11/10/1999	1436
ICV		V211204A	1.98753		2.00		99.4	%	95-105	11/10/1999	1501
ICB			0.00228							11/10/1999	1506
ISB		V211204E	0.44476		0.50		89.0	%	80-120	11/10/1999	1510
CCV		V211204A	1.94411		2.00		97.2	%	95-105	11/10/1999	1602
CCB			0.00061							11/10/1999	1607
PB	1110-2		-0.00291							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.19136		0.2000		95.7	%	80-120	11/10/1999	1634
MD	912804-1		-0.00145			-0.00104	0.00041	A	0.01000	11/10/1999	1642
MS	912804-1	ICPSPK99B	0.18719		0.2000	-0.00104	94.1	%	75-125	11/10/1999	1646
CCV		V211204A	1.97649		2.00		98.8	%	95-105	11/10/1999	1713
CCB			0.00353							11/10/1999	1717
PB	1108-5		-0.00187							11/10/1999	1750
LCS	1108-5	ICPSPK99B	0.19530		0.2000		97.7	%	80-120	11/10/1999	1755
CCV		V211204A	1.94762		2.00		97.4	%	95-105	11/10/1999	1803
CCB			0.00291							11/10/1999	1807
CCV		V211204A	1.97503		2.00		98.8	%	95-105	11/10/1999	1947
			0.00570							11/10/1999	1953
		V211204E	0.45111		0.50		90.2	%	80-120	11/10/1999	1956



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Test Method.....: EPA 6010B

Batch.....: 49224

Analyst....: chh

Method Description.: Metals Analysis (ICAP)

Units.....: mg/L

Test Code.: CR

Parameter.....: Chromium (Cr)

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
MD	912691-2		0.09901			0.09012	9.4	R	20	11/10/1999	2005
MS	912691-2	ICPSPK99B	0.28722		0.2000	0.09012	98.5	%	75-125	11/10/1999	2009
ISB		V211204E	0.44951		0.50		89.9	%	80-120	11/10/1999	2022
CCV		V211204A	1.99441		2.00		99.7	%	95-105	11/10/1999	2032
CCB			0.00889							11/10/1999	2036

Test Method.....: EPA 6010B

Batch.....: 49224

Analyst....: chh

Method Description.: Metals Analysis (ICAP)

Units.....: mg/L

Test Code.: CO

Parameter.....: Cobalt (Co)

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	0.00009		0.00					11/10/1999	1432
CAL		ICPCALSTD	0.66299		1.00					11/10/1999	1439
ICV		V211204A	2.07074		2.00		103.5	%	95-105	11/10/1999	1501
ICB			-0.00150							11/10/1999	1506
		V211204E	0.43837		0.50		87.7	%	80-120	11/10/1999	1510
		V211204A	2.02262		2.00		101.1	%	95-105	11/10/1999	1602
CCB			0.00015							11/10/1999	1607
PB	1110-2		-0.00030							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.50339		0.5000		100.7	%	80-120	11/10/1999	1634
MD	912804-1		-0.00090			0.00045	0.00135	A	0.02000	11/10/1999	1642
MS	912804-1	ICPSPK99B	0.49766		0.5000	0.00045	99.4	%	75-125	11/10/1999	1646
CCV		V211204A	2.05672		2.00		102.8	%	95-105	11/10/1999	1713
CCB			0.00075							11/10/1999	1717
PB	1108-5		-0.00316							11/10/1999	1750
LCS	1108-5	ICPSPK99B	0.51802		0.5000		103.6	%	80-120	11/10/1999	1755
CCV		V211204A	2.03333		2.00		101.7	%	95-105	11/10/1999	1803
CCB			-0.00075							11/10/1999	1807
CCV		V211204A	1.97970		2.00		99.0	%	95-105	11/10/1999	1947
CCB			-0.00080							11/10/1999	1953
ISB		V211204E	0.43766		0.50		87.5	%	80-120	11/10/1999	1956
MD	912691-2		0.00531			0.00211	0.00320	A	0.02000	11/10/1999	2005
MS	912691-2	ICPSPK99B	0.50418		0.5000	0.00211	100.4	%	75-125	11/10/1999	2009
ISB		V211204E	0.43685		0.50		87.4	%	80-120	11/10/1999	2022
CCV		V211204A	2.01401		2.00		100.7	%	95-105	11/10/1999	2032
CCB			-0.00241							11/10/1999	2036

Test Method.....: EPA 6010B

Batch.....: 49224

Analyst....: chh

Method Description.: Metals Analysis (ICAP)

Units.....: mg/L

Test Code.: CU

Parameter.....: Copper (Cu)

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	-0.00010		0.00					11/10/1999	1432
CAL		ICPCALSTD	0.23160		1.00					11/10/1999	1439
ICV		V211204A	2.05607		2.00		102.8	%	95-105	11/10/1999	1501
ICB			0.00646							11/10/1999	1506
ISB		V211204E	0.44436		0.50		88.9	%	80-120	11/10/1999	1510
	912648-4		0.01120			0.00861	0.00259	A	0.01000	11/10/1999	1554
	912648-4	V16008208	0.27411		0.250000	0.00861	106.2	%	75-125	11/10/1999	1558



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, TX

ATTN: Mr. Paul Peacock

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Copper (Cu)

Batch.....: 49224
 Units.....: mg/L

Analyst....: chh
 Test Code.: CU

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CCV		V211204A	2.01206		2.00		100.6	%	95-105	11/10/1999	1602
CCB			0.00388							11/10/1999	1607
PB	1110-2		0.00129							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.24774		0.2500		99.1	%	80-120	11/10/1999	1634
MD	912804-1		0.00086			0.00129	0.00043	A	0.01000	11/10/1999	1642
MS	912804-1	ICPSPK99B	0.24558		0.2500	0.00129	97.7	%	75-125	11/10/1999	1646
CCV		V211204A	2.05779		2.00		102.9	%	95-105	11/10/1999	1713
CCB			0.00474							11/10/1999	1717
PB	1108-5		-0.00172							11/10/1999	1750
LCS	1108-5	ICPSPK99B	0.25292		0.2500		101.2	%	80-120	11/10/1999	1755
CCV		V211204A	2.03578		2.00		101.8	%	95-105	11/10/1999	1803
CCB			-0.00000							11/10/1999	1807
CCV		V211204A	1.98334		2.00		99.2	%	95-105	11/10/1999	1947
CCB			0.00040							11/10/1999	1953
ISB		V211204E	0.45043		0.50		90.1	%	80-120	11/10/1999	1956
MD	912691-2		0.06876			0.05000	0.01876	A	0.01000	11/10/1999	2005
MS	912691-2	ICPSPK99B	0.29549		0.2500	0.05000	98.2	%	75-125	11/10/1999	2009
		V211204E	0.44395		0.50		88.8	%	80-120	11/10/1999	2022
		V211204A	1.97769		2.00		98.9	%	95-105	11/10/1999	2032
CCB			-0.00000							11/10/1999	2036

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Iron (Fe)

Batch.....: 49224
 Units.....: mg/L

Analyst....: chh
 Test Code.: FE

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	0.00960		0.00					11/10/1999	1432
CAL		ICPCALSTD	83.38069		100.00					11/10/1999	1439
ICV		V211204A	2.06757		2.00		103.4	%	95-105	11/10/1999	1501
ICB			-0.00263							11/10/1999	1506
ISB		V211204E	184.46746		200.0		92.2	%	80-120	11/10/1999	1510
CCV		V211204A	2.03659		2.00		101.8	%	95-105	11/10/1999	1602
CCB			0.00647							11/10/1999	1607
PB	1110-2		0.01391							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.50448		0.5000		100.9	%	80-120	11/10/1999	1634
MD	912804-1		0.03982			0.01907	0.02075	A	0.05000	11/10/1999	1642
MS	912804-1	ICPSPK99B	0.52440		0.5000	0.01907	101.1	%	75-125	11/10/1999	1646
CCV		V211204A	2.07416		2.00		103.7	%	95-105	11/10/1999	1713
CCB			0.00035							11/10/1999	1717
PB	1108-5		0.00000							11/10/1999	1750
LCS	1108-5	ICPSPK99B	0.53003		0.5000		106.0	%	80-120	11/10/1999	1755
CCV		V211204A	2.05836		2.00		102.9	%	95-105	11/10/1999	1803
CCB			-0.00120							11/10/1999	1807
CCV		V211204A	1.98853		2.00		99.4	%	95-105	11/10/1999	1947
CCB			0.01584							11/10/1999	1953
ISB		V211204E	180.25849		200.0		90.1	%	80-120	11/10/1999	1956
MD	912691-2		0.41103			0.35765	13.9	R	20	11/10/1999	2005
MS	912691-2	ICPSPK99B	0.85928		0.5000	0.35765	100.3	%	75-125	11/10/1999	2009
ISB		V211204E	179.55508		200.0		89.8	%	80-120	11/10/1999	2022
		V211204A	2.01156		2.00		100.6	%	95-105	11/10/1999	2032
			0.01956							11/10/1999	2036



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Test Method.....: EPA 6010B

Batch.....: 49224

Analyst....: chh

Method Description.: Metals Analysis (ICAP)

Units.....: mg/L

Test Code.: PB

Parameter.....: Lead (Pb)

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	-0.02160		0.00					11/10/1999	1432
CAL		ICPCALSTD	5.03679		10.0					11/10/1999	1443
ICV		V211204A	2.08801		2.00		104.4	%	95-105	11/10/1999	1501
ICB			0.04962							11/10/1999	1506
ISB		V211204E	1.06901		1.00		106.9	%	80-120	11/10/1999	1510
CCV		V211204A	2.01665		2.00		100.8	%	95-105	11/10/1999	1602
CCB			0.02570							11/10/1999	1607
PB	1110-2		0.04796							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.51828		0.5000		103.7	%	80-120	11/10/1999	1634
MD	912804-1		0.02968			0.00260	0.02708	A	0.05000	11/10/1999	1642
MS	912804-1	ICPSPK99B	0.49773		0.5000	0.00260	99.0	%	75-125	11/10/1999	1646
CCV		V211204A	1.98915		2.00		99.5	%	95-105	11/10/1999	1713
CCB			0.05239							11/10/1999	1717
PB	1108-5		0.03366							11/10/1999	1750
LCS	1108-5	ICPSPK99B	0.53097		0.5000		106.2	%	80-120	11/10/1999	1755
CCV		V211204A	2.01825		2.00		100.9	%	95-105	11/10/1999	1803
CCB			0.06504							11/10/1999	1807
		V211204A	2.02497		2.00		101.2	%	95-105	11/10/1999	1947
			0.01537							11/10/1999	1953
ISB		V211204E	0.95396		1.00		95.4	%	80-120	11/10/1999	1956
MD	912691-2		-0.00452			0.04172	0.04624	A	0.05000	11/10/1999	2005
MS	912691-2	ICPSPK99B	0.50937		0.5000	0.04172	93.5	%	75-125	11/10/1999	2009
ISB		V211204E	0.94240		1.00		94.2	%	80-120	11/10/1999	2022
CCV		V211204A	2.03451		2.00		101.7	%	95-105	11/10/1999	2032
CCB			-0.01311							11/10/1999	2036

Test Method.....: EPA 6010B

Batch.....: 49224

Analyst....: chh

Method Description.: Metals Analysis (ICAP)

Units.....: mg/L

Test Code.: MN

Parameter.....: Manganese (Mn)

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	0.01740		0.00					11/10/1999	1432
CAL		ICPCALSTD	0.92269		2.00					11/10/1999	1443
ICV		V211204A	2.03519		2.00		101.8	%	95-105	11/10/1999	1501
ICB			-0.00132							11/10/1999	1506
ISB		V211204E	0.44561		0.50		89.1	%	80-120	11/10/1999	1510
CCV		V211204A	1.99253		2.00		99.6	%	95-105	11/10/1999	1602
CCB			0.00044							11/10/1999	1607
PB	1110-2		-0.00088							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.48168		0.5000		96.3	%	80-120	11/10/1999	1634
MD	912804-1		-0.00131			-0.00153	0.00022	A	0.01000	11/10/1999	1642
MS	912804-1	ICPSPK99B	0.47856		0.5000	-0.00153	96.0	%	75-125	11/10/1999	1646
CCV		V211204A	2.04535		2.00		102.3	%	95-105	11/10/1999	1713
CCB			-0.00220							11/10/1999	1717
PB	1108-5		-0.00287							11/10/1999	1750
LCS	1108-5	ICPSPK99B	0.49507		0.5000		99.0	%	80-120	11/10/1999	1755
CCV		V211204A	2.03253		2.00		101.6	%	95-105	11/10/1999	1803
CCB			-0.00309							11/10/1999	1807
CCV		V211204A	2.01995		2.00		101.0	%	95-105	11/10/1999	1947
			0.00137							11/10/1999	1953
		V211204E	0.45609		0.50		91.2	%	80-120	11/10/1999	1956



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Manganese (Mn)

Batch.....: 49224
 Units.....: mg/L

Analyst....: chh
 Test Code.: MN

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
MD	912691-2		0.00869			0.00598	0.00271	A	0.01000	11/10/1999	2005
MS	912691-2	ICPSPK99B	0.50038		0.5000	0.00598	98.9	%	75-125	11/10/1999	2009
ISB		V211204E	0.45571		0.50		91.1	%	80-120	11/10/1999	2022
CCV		V211204A	2.04127		2.00		102.1	%	95-105	11/10/1999	2032
CCB			0.00206							11/10/1999	2036

Test Method.....: EPA 7470
 Method Description.: Mercury, Total
 Parameter.....: Mercury (Hg)

Batch.....: 49327
 Units.....: mg/L

Analyst....: pal
 Test Code.: HG

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		HGCALBLK	26277		0.000					11/11/1999	1520
CAL		V211205C	33050		0.000050					11/11/1999	1523
CAL		V211205C	48244		0.000200					11/11/1999	1526
CAL		V211205C	131319		0.001000					11/11/1999	1529
		V211205C	602098		0.005000					11/11/1999	1532
		V211205C	1094966		0.010000					11/11/1999	1535
ICV		V211205D	0.00547		0.005000		109.4	%	90-110	11/11/1999	1538
ICB			-0.000003							11/11/1999	1541
PB			-0.000131							11/11/1999	1544
LCS		V211205D	0.00543		0.005000		108.6	%	80-120	11/11/1999	1547
MD	912809-2		-0.000142			-0.000167	0.000025	A	0.001000	11/11/1999	1552
MS	912809-2	V211205D	0.00501		0.005000	-0.000167	103.5	%	75-125	11/11/1999	1555
CCV		V211205C	0.00471		0.005000		94.2	%	90-110	11/11/1999	1613
CCB			-0.000008							11/11/1999	1616
CCV		V211205C	0.00490		0.005000		98.0	%	90-110	11/11/1999	1649
CCB			-0.000013							11/11/1999	1652
CCV		V211205C	0.00467		0.005000		93.4	%	90-110	11/11/1999	1724
CCB			-0.000032							11/11/1999	1727

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Molybdenum (Mo)

Batch.....: 49224
 Units.....: mg/L

Analyst....: chh
 Test Code.: MO

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	0.00130							11/10/1999	1432
CAL		ICPCALSTD	0.20409		2.00					11/10/1999	1453
ICV		V211204A	2.10563		2.00		105.3	%	95-105	11/10/1999	1501
ICB			0.04635							11/10/1999	1506
CCV		V211204A	1.96660		2.00		98.3	%	95-105	11/10/1999	1602
CCB			0.07593							11/10/1999	1607
PB	1110-2		0.00098							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.48404		0.5000		96.8	%	80-120	11/10/1999	1634
MD	912804-1		0.02957			0.05818	0.02861	A	0.10000	11/10/1999	1642
MS	912804-1	ICPSPK99B	0.53729		0.5000	0.05818	95.8	%	75-125	11/10/1999	1646
CCV		V211204A	2.01293		2.00		100.6	%	95-105	11/10/1999	1713
CCB			0.06804							11/10/1999	1717
		V211204A	2.02379		2.00		101.2	%	95-105	11/10/1999	1803
			0.04832							11/10/1999	1807



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Nickel (Ni)

Batch.....: 49224
 Units.....: mg/L

Analyst....: chh
 Test Code.: NI

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	-0.00160		0.00					11/10/1999	1432
CAL		ICPCALSTD	0.64550		1.0					11/10/1999	1436
ICV		V211204A	2.03516		2.00					11/10/1999	1501
ICB			-0.00030				101.8	%	95-105	11/10/1999	1506
ISB		V211204E	0.83814		1.00		83.8	%	80-120	11/10/1999	1510
CCV		V211204A	1.97738		2.00		98.9	%	95-105	11/10/1999	1602
CCB			0.00139							11/10/1999	1607
PB	1110-2		-0.00448							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.47202		0.500		94.4	%	80-120	11/10/1999	1634
MD	912804-1		-0.00139			-0.00680	0.00541	A	0.01000	11/10/1999	1642
MS	912804-1	ICPSPK99B	0.45625		0.500	-0.00680	92.6	%	75-125	11/10/1999	1646
CCV		V211204A	2.01105		2.00		100.6	%	95-105	11/10/1999	1713
CCB			0.00324							11/10/1999	1717
PB	1108-5		-0.00231							11/10/1999	1750
LCS	1108-5	ICPSPK99B	0.47619		0.500		95.2	%	80-120	11/10/1999	1755
CCV		V211204A	1.99174		2.00		99.6	%	95-105	11/10/1999	1803
CCB			0.00834							11/10/1999	1807
		V211204A	1.98981		2.00		99.5	%	95-105	11/10/1999	1947
			0.00189							11/10/1999	1953
ISB		V211204E	0.86134		1.00		86.1	%	80-120	11/10/1999	1956
MD	912691-2		0.05968			0.05142	14.9	R	20	11/10/1999	2005
MS	912691-2	ICPSPK99B	0.53017		0.500	0.05142	95.8	%	75-125	11/10/1999	2009
ISB		V211204E	0.86280		1.00		86.3	%	80-120	11/10/1999	2022
CCV		V211204A	2.02778		2.00		101.4	%	95-105	11/10/1999	2032
CCB			0.00206							11/10/1999	2036

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Selenium (Se)

Batch.....: 49229
 Units.....: mg/L

Analyst....: amw
 Test Code.: SE

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
ICV		V211205B	4.13607		4.00					11/10/1999	2109
ICB			0.00716				103.4	%	90-110	11/10/1999	2115
PB	1103-3		-0.00774							11/10/1999	2144
LCS	1103-3	ICPSPK99B	0.52583		0.5000		105.2	%	80-120	11/10/1999	2150
MD	912510-1		0.04239			0.05221	0.00982	A	0.02000	11/10/1999	2202
MS	912510-1	ICPSPK99B	0.60952		0.5000	0.05221	111.5	%	75-125	11/10/1999	2207
PB	1110-2		0.00754							11/10/1999	2228
LCS	1110-2	ICPSPK99B	0.51176		0.5000		102.4	%	80-120	11/10/1999	2234
CCV		V211205B	4.11920		4.00		103.0	%	90-110	11/10/1999	2240
CCB			-0.00049							11/10/1999	2246
MD	912804-1		0.06091			0.06711	0.00620	A	0.02000	11/10/1999	2257
MS	912804-1	ICPSPK99B	0.53834		0.5000	0.06711	94.2	%	75-125	11/10/1999	2303
PB	1108-1		-0.00048							11/10/1999	2315
LCS	1108-1	V16008711	1.26703		1.389429		91.2	%	80-120	11/10/1999	2323
MS	912685-1	V16008208	1.66516		2.000000	-0.00141	83.3	%	75-125	11/10/1999	2336
MSD	912685-1	V16008208	1.73536	1.66516	2.000000	-0.00141	86.8	%	75-125	11/10/1999	2342
							4.1	R	20		
CCV		V211205B	3.61532		4.00		90.4	%	90-110	11/11/1999	0006
			0.00502							11/11/1999	0012



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Silver (Ag)

Batch.....: 49229
 Units.....: mg/L

Analyst....: nmw
 Test Code.: AG

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
ISB		V21122A	1.01911		1.00		101.9	%	80-120	11/10/1999	2059
ICV		V211205B	0.82532		0.80		103.2	%	90-110	11/10/1999	2109
ICB			0.00639							11/10/1999	2115
PB	1103-3		0.00602							11/10/1999	2144
LCS	1103-3	ICPSPK99B	0.21922		0.2000		109.6	%	80-120	11/10/1999	2150
MD	912510-1		-0.00134			0.00301	0.00435	A	0.01000	11/10/1999	2202
MS	912510-1	ICPSPK99B	0.23286		0.2000	0.00301	114.9	%	75-125	11/10/1999	2207
PB	1110-2		0.00387							11/10/1999	2228
LCS	1110-2	ICPSPK99B	0.20008		0.2000		100.0	%	80-120	11/10/1999	2234
CCV		V211205B	0.81442		0.80		101.8	%	90-110	11/10/1999	2240
CCB			0.00538							11/10/1999	2246
MD	912804-1		-0.00299			0.00267	0.00566	A	0.01000	11/10/1999	2257
MS	912804-1	ICPSPK99B	0.18444		0.2000	0.00267	90.9	%	75-125	11/10/1999	2303
PB	1108-1		0.00394							11/10/1999	2315
LCS	1108-1	V16008711	0.98418		1.039642		94.7	%	80-120	11/10/1999	2323
MS	912685-1	V16008208	0.42520		0.400000	0.09302	83.0	%	75-125	11/10/1999	2336
MSD	912685-1	V16008208	0.44731	0.42520	0.400000	0.09302	88.6	%	75-125	11/10/1999	2342
							5.1	R	20		
CCV		V21122A	0.92430		1.00		92.4	%	80-120	11/10/1999	2356
CCB		V211205B	0.72690		0.80		90.9	%	90-110	11/11/1999	0006
CCB			0.00329							11/11/1999	0012

Test Method.....: EPA 6010B
 Method Description.: Metals Analysis (ICAP)
 Parameter.....: Zinc (Zn)

Batch.....: 49224
 Units.....: mg/L

Analyst....: chh
 Test Code.: ZN

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CAL		ICPCALBLK	0.00100		0.00					11/10/1999	1432
CAL		ICPCALSTD	0.74320		3.00					11/10/1999	1443
ICV		V211204A	2.05861		2.00		102.9	%	95-105	11/10/1999	1501
ICB			0.00000							11/10/1999	1506
ISB		V211204E	0.94520		1.00		94.5	%	80-120	11/10/1999	1510
CCV		V211204A	2.01376		2.00		100.7	%	95-105	11/10/1999	1602
CCB			-0.00241							11/10/1999	1607
PB	1110-2		-0.00399							11/10/1999	1629
LCS	1110-2	ICPSPK99B	0.49158		0.5000		98.3	%	80-120	11/10/1999	1634
MD	912804-1		0.02308			0.01626	0.00682	A	0.01000	11/10/1999	1642
MS	912804-1	ICPSPK99B	0.51147		0.5000	0.01626	99.0	%	75-125	11/10/1999	1646
CCV		V211204A	2.06765		2.00		103.4	%	95-105	11/10/1999	1713
CCB			-0.00283							11/10/1999	1717
PB	1108-5		-0.00442							11/10/1999	1750
LCS	1108-5	ICPSPK99B	0.49473		0.5000		98.9	%	80-120	11/10/1999	1755
CCV		V211204A	2.04205		2.00		102.1	%	95-105	11/10/1999	1803
CCB			-0.00407							11/10/1999	1807
CCV		V211204A	2.04812		2.00		102.4	%	95-105	11/10/1999	1947
CCB			-0.00179							11/10/1999	1953
ISB		V211204E	0.95902		1.00		95.9	%	80-120	11/10/1999	1956
MD	912691-2		0.42511			0.40387	5.1	R	20	11/10/1999	2005
MS	912691-2	ICPSPK99B	0.92205		0.5000	0.40387	103.6	%	75-125	11/10/1999	2009
		V211204E	0.96117		1.00		96.1	%	80-120	11/10/1999	2022
		V211204A	2.06797		2.00		103.4	%	95-105	11/10/1999	2032



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, TX

ATTN: Mr. Paul Peacock

Test Method.....: EPA 6010B

Batch.....: 49224

Analyst...: chh

Method Description.: Metals Analysis (ICAP)

Units.....: mg/L

Test Code.: ZN

Parameter.....: Zinc (Zn)

QC	Lab ID	Reagent	QC Result	QC Result	True Value	Orig. Value	Calc. Result	*	Limits	Date	Time
CCB			-0.00401							11/10/1999	2036



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, TX

ATTN: Mr. Paul Peacock

QC Type	Description	Reag. Code	Lab ID	Dilution Factor	Date	Time
---------	-------------	------------	--------	-----------------	------	------

Test Method.....: EPA 8310

Batch.....: 49504

Analyst....: rm

Method Description.: Polynuclear Aromatic Hydrocarbons-HPLC

Units.....: ug/L

MB	Method Blank				11/16/1999	0111
----	--------------	--	--	--	------------	------

Parameter/Test Description	QC Result	QC Result	True Value	Orig. Value	Calc. Result	* Limits
Acenaphthene	ND					
Acenaphthylene	ND					
Anthracene	ND					
Benzo(b)fluoranthene	ND					
Benzo(k)fluoranthene	ND					
Benzo(a)anthracene	ND					
Benzo(a)pyrene	ND					
Benzo(ghi)perylene	ND					
Chrysene	ND					
Dibenzo(a,h)anthracene	ND					
Fluoranthene	ND					
Fluorene	ND					
Indeno(1,2,3-cd)pyrene	ND					
Naphthalene	ND					
Phenanthrene	ND					
Pyrene	ND					

LCS	Laboratory Control Sample	V173725B			11/16/1999	0154
-----	---------------------------	----------	--	--	------------	------

Parameter/Test Description	QC Result	QC Result	True Value	Orig. Value	Calc. Result	* Limits
Acenaphthene	651.7		1000.000000		65.2	% 10-92
Acenaphthylene	735.6		1000.000000		73.6	% 11-127
Anthracene	632.7		1002.000000		63.1	% 13-110
Benzo(b)fluoranthene	348.2		500.000000		69.6	% 57-102
Benzo(k)fluoranthene	360.5		500.000000		72.1	% 59-107
Benzo(a)anthracene	346.8		500.000000		69.4	% 61-109
Benzo(a)pyrene	328.3		500.000000		65.7	% 42-131
Benzo(ghi)perylene	427.2		500.000000		85.4	% 55-119
Chrysene	364.7		500.000000		72.9	% 59-103
Dibenzo(a,h)anthracene	323.0		500.000000		64.6	% 63-108
Fluoranthene	350.5		500.000000		70.1	% 40-122
Fluorene	735.3		1000.000000		73.5	% 20-95
Indeno(1,2,3-cd)pyrene	358.8		500.000000		71.8	% 57-104
Naphthalene	483.3		1000.000000		48.3	% 10-82
Phenanthrene	380.7		502.500000		75.8	% 37-102
Pyrene	382.8		500.000000		76.6	% 59-111



QUALITY CONTROL RESULTS

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

QC Type	Description	Reag. Code	Lab ID	Dilution Factor	Date	Time
---------	-------------	------------	--------	-----------------	------	------

Test Method.....: EPA 8260B

Batch.....: 49489

Analyst....: weh

Method Description.: Volatile Organic Compounds

Units.....: ug/L

MB	Method Blank				11/15/1999	1439
----	--------------	--	--	--	------------	------

Parameter/Test Description	QC Result	QC Result	True Value	Orig. Value	Calc. Result	* Limits
Vinyl chloride	ND					
1,1-Dichloroethene	ND					
Methylene chloride	ND					
Benzene	ND					
Carbon tetrachloride	ND					
Chloroform	ND					
1,2-Dibromoethane (EDB)	ND					
1,1-Dichloroethane	ND					
1,2-Dichloroethane	ND					
Ethylbenzene	ND					
1,1,2,2-Tetrachloroethane	ND					
Tetrachloroethene	ND					
Toluene	ND					
1,1,1-Trichloroethane	ND					
1,1,2-Trichloroethane	ND					
1,1,1-Trichloroethane	ND					
Xylenes (total)	ND					

LCS	Laboratory Control Sample	CLPVOAMS2			11/15/1999	1510
-----	---------------------------	-----------	--	--	------------	------

Parameter/Test Description	QC Result	QC Result	True Value	Orig. Value	Calc. Result	* Limits
1,1-Dichloroethene	50.90		50		101.8	% 51-141
Benzene	50.28		50		100.6	% 67-130
Toluene	50.26		50		100.5	% 75-114
Trichloroethene	49.80		50		99.6	% 72-114

MS	Matrix Spike	CLPVOAMS2	913032-1		11/15/1999	1611
----	--------------	-----------	----------	--	------------	------

Parameter/Test Description	QC Result	QC Result	True Value	Orig. Value	Calc. Result	* Limits
1,1-Dichloroethene	50.80		50	ND	101.6	% 51-141
Benzene	50.91		50	1.12	99.6	% 67-130
Toluene	50.52		50	ND	101.0	% 75-114
Trichloroethene	49.66		50	ND	99.3	% 72-114

MSD	Matrix Spike Duplicate	CLPVOAMS2	913032-1		11/15/1999	1642
-----	------------------------	-----------	----------	--	------------	------

Parameter/Test Description	QC Result	QC Result	True Value	Orig. Value	Calc. Result	* Limits
1,1-Dichloroethene	51.40	50.80	50	ND	102.8	% 51-141
					1.2	R 30
Benzene	50.41	50.91	50	1.12	98.6	% 67-130
					1.0	R 30
Toluene	50.59	50.52	50	ND	101.2	% 75-114
					0.1	R 30
1,1,1-Trichloroethene	48.32	49.66	50	ND	96.6	% 72-114
					2.7	R 30



SURROGATE RECOVERIES REPORT

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Method.....: Volatile Organic Compounds
Method Code.....: 826TCL

Batch.....: 49489
Analyst.....: weh

Surrogate	Units
1,2-Dichloroethane-d4 (surrogate)	ug/L

Lab ID	Matrix	QC Type	Dilution	Result	True Value	Percent Recovery	Limits	Flag	Date	Time
		MB		51.26	50.00	102.5	76-120		11/15/1999	1439
		LCS		50.76	50.00	101.5	76-120		11/15/1999	1510
913032-1				51.66	50.00	103.3	76-120		11/15/1999	1540
913032-1		MS		50.97	50.00	101.9	76-120		11/15/1999	1611
913032-1		MSD		50.92	50.00	101.8	76-120		11/15/1999	1642
913032-3				50.89	50.00	101.8	76-120		11/15/1999	1712
913032-2				51.00	50.00	102.0	76-120		11/15/1999	1743
912816-1			50	47.02	50.00	94.0	76-120		11/15/1999	2036
912767-15				52.17	50.00	104.3	76-120		11/15/1999	2107
912767-16				51.00	50.00	102.0	76-120		11/15/1999	2137

Surrogate	Units
BFB (Surrogate)	ug/L

Lab ID	Matrix	QC Type	Dilution	Result	True Value	Percent Recovery	Limits	Flag	Date	Time
		MB		51.80	50.00	103.6	85-115		11/15/1999	1439
		LCS		51.23	50.00	102.5	85-115		11/15/1999	1510
913032-1				52.45	50.00	104.9	85-115		11/15/1999	1540
913032-1		MS		53.36	50.00	106.7	85-115		11/15/1999	1611
913032-1		MSD		52.32	50.00	104.6	85-115		11/15/1999	1642
913032-3				52.36	50.00	104.7	85-115		11/15/1999	1712
913032-2				52.46	50.00	104.9	85-115		11/15/1999	1743
912816-1			50	48.12	50.00	96.2	85-115		11/15/1999	2036
912767-15				50.96	50.00	101.9	85-115		11/15/1999	2107
912767-16				50.19	50.00	100.4	85-115		11/15/1999	2137

Surrogate	Units
Toluene-d8	ug/L

Lab ID	Matrix	QC Type	Dilution	Result	True Value	Percent Recovery	Limits	Flag	Date	Time
		MB		50.11	50.00	100.2	85-112		11/15/1999	1439
		LCS		49.94	50.00	99.9	85-112		11/15/1999	1510
913032-1				49.91	50.00	99.8	85-112		11/15/1999	1540
913032-1		MS		50.52	50.00	101.0	85-112		11/15/1999	1611
913032-1		MSD		51.24	50.00	102.5	85-112		11/15/1999	1642
913032-3				51.57	50.00	103.1	85-112		11/15/1999	1712
913032-2				50.89	50.00	101.8	85-112		11/15/1999	1743
912816-1			50	50.44	50.00	100.9	85-112		11/15/1999	2036
912767-15				51.31	50.00	102.6	85-112		11/15/1999	2107
912767-16				54.32	50.00	108.6	85-112		11/15/1999	2137



SURROGATE RECOVERIES REPORT

Job Number.: 912816

Report Date.: 11/16/99

CUSTOMER: Marathon Oil Company

PROJECT: Marathon Oil Co., Midland, Tx

ATTN: Mr. Paul Peacock

Method.....: Polynuclear Aromatic Hydrocarbons-HPLC
 Method Code.....: 8310

Batch.....: 49504
 Analyst.....: rm

Surrogate	Units
1-Fluoronaphthalene	ug/L

Lab ID	Matrix	QC Type	Dilution	Result	True Value	Percent Recovery	Limits	Flag	Date	Time
912816-1		MB		371.7	1000	37.2	10-74		11/16/1999	0111
		LCS		555.3	1000	55.5	10-74		11/16/1999	0154
				720.4	1000	72.0	10-74		11/16/1999	0236

Surrogate	Units
Terphenyl-d14	ug/L

Lab ID	Matrix	QC Type	Dilution	Result	True Value	Percent Recovery	Limits	Flag	Date	Time
912816-1		MB		749.9	1000	75.0	56-122		11/16/1999	0111
		LCS		936.4	1000	93.6	56-122		11/16/1999	0154
				776.2	1000	77.6	56-122		11/16/1999	0236

QUALITY ASSURANCE FOOTER

METHOD REFERENCES

1. EPA SW-846, Test Methods for Evaluating Solid Waste Update I, IIA, IIB, III
2. Standard Methods for the Examination of Water and Wastewater, 18th Edition
3. EPA 600/4-79-020, Methods of Chemical Analysis for Waters and Wastes, March 1983
4. Federal Register, Friday, October 26, 1984 (40 CFR Part 136)
5. American Society for Testing and Materials, Volumes 5.01, 5.02, 5.03, 11.01, 11.02, 11.03, 11.04
6. EPA Methods for Environmental Samples

COMMENTS

All methods of chemical analysis have a statistical uncertainty associated with the results. Unless otherwise indicated, the data in this report are within the limits of uncertainty as specified in the referenced method. Quality Control acceptance criteria are based either on actual laboratory performance or on limits specified in the referenced method. The date and time of analysis indicated on the QA report may not reflect the actual time of analysis for QC samples. All data are reported on an "as received" basis unless otherwise indicated. Data reported in the QA report may be lower than sample data due to dilution of samples into the calibration range of the analysis. Sample concentration for solid samples are calculated on an as received (wet) basis. Unless otherwise indicated, volatiles by gas chromatography (GC) are reported from a single column. Volatile analysis by GC on low level soil extractions are conducted at room temperature.

FLAGS, FOOTNOTES AND ABBREVIATIONS (as needed)

NA	=	Not Analyzed	ND	=	Not detected at a value greater than the reporting limit
N/A	=	Not applicable	NC	=	Not calculable due to values lower than the reporting limit
ug/L	=	Micrograms per liter	mg/L	=	Milligrams per liter
ug/Kg	=	Micrograms per kilogram	mg/kg	=	Milligrams per kilogram
U	=	Undetected			
J	=	Indicates value is > MDL, but < Reporting Limit			
B	=	Analyte was detected in the method blank analyzed with this sample.			
D	=	Surrogate recoveries are not calculated due to sample dilution.			
X	=	Surrogate recovery is outside quality control limits.			
Y	=	Spike or spike duplicate recovery is outside quality control limits.			
Z	=	Relative percent difference for a spike and spike duplicate is outside quality control limits. The precision of the method was impacted by matrix.			
^	=	Indicates value is above QC acceptance criteria.			

QC SAMPLE IDENTIFICATIONS

MB	=	Method Blank	SB	=	Storage Blank
RB	=	Reagent Blank	EB	=	Extraction Blank
PB	=	Preparation Blank	CALB	=	Calibration Blank
MD	=	Method Duplicate	RS	=	Reference Standard
LCS	=	Laboratory Control Sample	LCSD	=	Laboratory Control Sample Duplicate
MS	=	Matrix Spike	MSD	=	Matrix Spike Duplicate
ICB	=	Initial Calibration Blank	CCB	=	Continuing Calibration Blank
ICV	=	Initial Calibration Verification	ICB	=	Initial Calibration Blank
PDS	=	Post Digestion Spike	SS	=	Surrogate Spike
ISA	=	Interference Check standard "A"	ISB	=	Interference Check Standard "B"
ISCAB	=	Interference Check Sample AB	MSA	=	Method of Standard Additions
CAL	=	Calibration standard	SD	=	Serial Dilution
MST	=	TCLP Matrix Spike	MSQ	=	TCLP Matrix Spike Duplicate
PST	=	TCLP Post Digestion Spike	LCT	=	TCLP Laboratory Control Sample

Job Number.....: 912816	Location.: 57211	Customer Job ID.....:	Job Check List Date.: 11/09/99
Project Number.: 96000746	Project Description.: INDIAN BASIN REMEDIATION STRIPPER	Contact.: Mr. Paul Peacock	Project Manager.....: lpa
Customer.....: Marathon Oil Company			

Questions ?	(Y/N) Comments
-------------	----------------

Chain-of-Custody Present?..... Y

Custody seal on shipping container?..... Y

...If "yes", custody seal intact?..... Y

Custody seals on sample containers?.....

...If "yes", custody seal intact?.....

Samples chilled?..... Y

Temperature of cooler acceptable? (4 deg C +/- 2). RECEIVED ON ICE

Samples received intact (good condition)?..... Y

Volatile samples acceptable? (no headspace)..... Y

Correct containers used?..... Y

Adequate sample volume provided?..... Y

Samples preserved correctly?..... Y

Samples received within holding-time?..... Y

Agreement between COC and sample labels?..... Y

Additional.....

Comments.....

Sample Custodian Signature... 



Severn Trent Laboratories

CHAIN OF CUSTODY RECORD

Customer Information			Project Information			Analysis/Method																				
PO			PROJECT NAME	INDIAN BASIN GAS PLT		A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S		
NO			LAB NUMBER	912816	BOTTLE ORDER	96000813																				
COMPANY	Marathon Oil Company		BILL TO	Marathon Oil Company																						
SEND REPORT TO	Mr. Paul Peacock		INVOICE ATTN	Mr. Paul Peacock																						
ADDRESS	Midland, TX		ADDRESS	125 West Missouri Street																						
	Bottles to: Mr. Jack Brown			P.O. Box 552																						
CITY/STATE/ZIP	Lakewood, New Mexico		CITY/STATE/ZIP	Midland, TX 79702-0552																						
PHONE			PHONE	915-687-8312																						
FAX			FAX	915-687-8305																						
SAMP NO.	SAMPLE DESCRIPTION	PRESERV.	F	SAMPLE MATRIX	SAMPLE DATE	SAMPLE TIME	#CONTAINERS	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
1	DOMESTIC COMBINED GAS PLY WISE EFF	HNO3	N	AQ	11/8/99	1000	2	1-12 Pias	X																	
		NaOH					2	1-12 Pias	X																	
		H2SO4					2	1-12 GASS		X																
		NONE					2	1-12 Pias			X															
		NONE					6	3-12 GASS				X														
		HCl					8	4-40ml WA					X													

Sampler:	Shipment Method:		Airbill No.:		Required TurnAround:	
1. Relinquished By: <i>J. Brown</i>	Date: 11/8/99	2. Relinquished By:	Date:	3. Relinquished By:	Date:	
Company Name: MARATHON	Time: 11:30	Company Name:	Time:	Company Name:	Time:	
1. Received By: <i>J. Bil</i>	Date: 11/9/99	2. Received By:	Date:	3. Received By:	Date:	
Company Name: STL	Time: 1000	Company Name:	Time:	Company Name:	Time:	

**SPILL PREVENTION,
CONTROL AND COUNTERMEASURE
PLAN**

For

**MARATHON OIL COMPANY
INDIAN BASIN GAS PLANT**

August 2001

Name of facility	Indian Basin Gas Plant
Operator	Marathon Oil Company

**INDIAN BASIN GAS PLANT
SPILL PREVENTION CONTROL AND COUNTERMEASURE
PLAN CONTENTS**

Page 1	Cover page
Page 2	Index
Page 3	Part I, Items 1 thru 6 General Information
Page 4	Part I, Item 7 General Information
Page 5	Part I, Items 8 thru 10 General Information
Page 6	Part II, Alt. A, Design and Operating Information, Section A
Page 7	Part II, Alt. A, Design and Operating Information, Section B
Page 8	Section B (continued)
Page 9	Part II, Alt. A, Design and Operating Information, Section C
Page 10	Part II, Alt. A, Design and Operating Information, Section D
Page 11	Part II, Alt. A, Design and Operating Information, Section E
Page 12	Attachments Index

Name of facility Indian Basin Gas Plant
Operator Marathon Oil Company

SPILL PREVENTION CONTROL & COUNTERMEASURE PLAN
PART I - GENERAL INFORMATION

1. Name of Facility Indian Basin Gas Plant
2. Type of Facility Onshore Production Facility
3. Location of Facility Eddy Count, New Mexico
Approximately 20 miles W/NW of Carlsbad, New Mexico
Unit Letter G, Section 23, Township 21S, Range 23E
4. Name and address of owner or operator:
Name: Marathon Oil Company
Address: P O Box 1324
Artesia, New Mexico 88210
5. Designated person accountable for oil spill prevention at facility:
Name and title: Mike Schweser, Gas Plant Superintendent
6. Facility experienced a reportable oil spill event during the twelve months prior to the issuance date of this Plan below. (If YES, complete attachment #1) No

MANAGEMENT APPROVAL

This SPCC Plan will be implemented as herein described.

Signature _____
Name C.M. Schweser
Title Plant Superintendent

CERTIFICATION

I hereby certify that I have examined the facility, and being familiar with the provisions of 40 CFR, Part 112, attest that the SPCC Plan has been prepared in accordance with good engineering practices.

Roger D. Edelbrock
Printed Name of Registered Professional Engineer

Signature of Registered Professional Engineer

Date 8/16/01 Registration No. 20128 State LA

Name of facility Indian Basin Gas Plant
Operator Marathon Oil Company

PART I
GENERAL INFORMATION

7. Potential Spills -- Prediction and Control

ITEM	SOURCE	MAJOR TYPE OF FAILURE	QUANTITY LARGEST TANK	RATE Bbls/Hr	DIRECTION OF FLOW	SECONDARY CONTAINMENT
1	Generator Turbine Oil	Leaks, Tank Rupture	7 bbl	N/A*	SE	Yes
2	Open Top Transfer Tank	Leaks, Tank Rupture	500 bbl	N/A*	SE	Yes
3	Outlet Compressor Lube Oil	Leaks, Tank Rupture	24 bbl	N/A*	SE	Yes
4	Field Storage Area	Leaks, Tank Rupture	12 bbl	N/A*	SE	Yes
5	Stabilizer Compressor Lube Oil	Leaks, Tank Rupture	5 bbl	N/A*	SE	Yes
6	IBLEAP Stripper Tank Area	Leaks, Tank Rupture	500 bbl	.001 BO 112 BW	SE	Yes
7	Skimmer Basin	Leaks, Tank Rupture	500 bbl	8 BO 833 BW	SE	Yes
8	Recompressor Lube Oil	Leaks, Tank Rupture	210 bbl	N/A*	SE	Yes
9	SWD Pump Lube Oil	Leaks, Tank Rupture	7 bbl	N/A*	SE	Yes
10	Condensate Storage Tank 5B	Leaks, Tank Rupture	3000 bbl	12.5 BO	SE	Yes
11	1 Bullet - Flare Drum PV-34.2B	Leaks, Tank Rupture	1571 bbl	Approx .125 BO	SE	Yes
12	1 Bullet - Sales Condensate Knockout	Leaks, Tank Rupture	1571 bbl	12.5 BO	SE	Yes
13	3 Bullets - Sour NGL Surge Tanks	Leaks, Tank Rupture	1605 bbl	Note 2	SE	Yes
14	LACT Unit Loading Rack	Leaks, Truck Rupture, Premature Departure	180 bbl	12.5 BO Note 3	SE	Yes

* Not connected to an inflowing process.

Note 2 NGL stored during upset situations only. Tanks kept empty as is practicable during normal operations. NGL is 100% volatile at atmospheric conditions.

Note 3 Condensate sold at same rate its produced. Hauled by truck.

Name of facility Indian Basin Gas Plant
Operator Marathon Oil Company

**PART I
GENERAL INFORMATION**

(Response to statements should be: Yes, No, or NA)

8. Containment or diversionary structures or equipment to prevent oil from reaching navigable waters are practicable. (If No, complete Attachment #2) No

9. Inspections and Records

A. The required inspections follow written procedures. Yes

B. The written procedures and a record of inspections, signed by the appropriate supervisor or inspector, are attached Yes

Discussion: : Daily visual inspections are made and readings taken and recorded by operational personnel during normal rounds on both twelve hour shifts. During these rounds, operating personnel search for atypical situations. If these situations are encountered, they are documented and promptly reported to supervisory personnel via the plant work order system. Spills are reported as soon as practical to the supervisor on a Marathon Spill Reporting form. Semi-Annual inspections are conducted by plant supervision or their designee. Records of these inspections are on file at the Indian Basin Gas Plant.

10. Personnel Training and Spill Prevention Procedures

A. Personnel are properly instructed in the following:

1. Operation and Maintenance of equipment to prevent oil discharge Yes

2. Applicable pollution control laws, rules, and regulations. Yes

Describe procedures employed for instruction: All employees have received 8 hours of HAZWOPER training, and many are 24 hour HAZWOPER trained. Annual instruction is provided on SPCC and other environmental topics by the Southern Business Units HES department. Other instructions are narrative. Environmental Control and Site Security are discussed at safety meetings, which are held on a monthly basis. Potential spill situations are reported to the superintendent via the plant work order system and also reported by the safety committee on a monthly basis. Such situations are corrected

B. Scheduled prevention briefings for the operating personnel are conducted frequently enough to assure adequate understanding of the SPCC Plan Yes

Describe Briefing program: Operation Management frequently reviews environmental standards at safety meetings. Such reviews assure an adequate understanding of SPCC. Operation superintendents are periodically requested to update Contingency Plans. Superintendents thereby assess and revise procedures when necessary.

Name of facility Indian Basin Gas Plant
Operator Marathon Oil Company

PART II, ALTERNATE A
DESIGN AND OPERATING INFORMATION
ONSHORE FACILITY (EXCLUDING PRODUCTION)

(Prior to completing Part II Alternate A, Refer to regulations and instructions, pages 6-7)

A. Facility Drainage

1. Drainage from diked storage areas is controlled as follows (include operating description of valves, pumps, ejectors, etc. (Note: Flapper type valves should not be used):

None of the earthen diked areas have installed drains. Any spill that might occur would be removed with a vacuum truck, or transferred, via a portable pump, to the plant open drain system. Concrete pollution catchments are connected directly to the plant open drain system which processes the fluid for removal of free hydrocarbon. The waste is then commingled and injected with Indian Basin Field produced water. Rain water captured in containments is also removed in this manner.

2. Drainage from undiked areas is controlled as follows (include description of ponds, lagoons, or catchment basins and methods of retaining and returning oil to facility):

The plant operates under a Storm Water Pollution Prevention Plan and a Groundwater Discharge Plan created for the New Mexico Oil Conservation Division. The plant is in compliance with all phases of these plans. The Groundwater Discharge Plan and the Storm Water Pollution Prevention Plan is available for review on site at the Indian Basin Gas Plant office and in the Southern Business Unit office, Midland, Texas.

3. The procedure for supervising the drainage of rain water from secondary containment in to a storm drain or an open watercourse is as follows (include description of (a) inspection for pollutants, and (b) method valving security). (A record of inspection and drainage events is to be maintained on a form similar to Attachment #3):

No secondary containment is drained into a storm drain or open watercourse.

Name of facility Indian Basin Gas Plant
Operator Marathon Oil Company

PART II, ALTERNATE A
DESIGN AND OPERATING INFORMATION
ONSHORE FACILITY (EXCLUDING PRODUCTION)

(Response to statements should be: Yes, No, or NA)

B. Bulk Storage Tanks

1. Describe tank design, materials of construction, fail-safe engineering features, and if needed, corrosion protection:

Generator Turbine Oil - A vented, 7 barrel, welded, carbon steel, above ground lube oil storage tank. This tank is filled by vendor from a truck and is attended at all times during filling operations.

Open top transfer tank - A 500 barrel fiberglass open top tank used to transfer produced fluids hauled in by truck into the skimmer system. The tank is continuously monitored during loading operations to prevent overflowing.

Outlet compressor lube oil tank - A vented, 24 barrel, welded, carbon steel, above ground, lube oil storage tank. This tank is filled by vendor from a truck and is attended at all times during filling operations.

Field storage area - .

- One, vented, 12 barrel, welded, carbon steel, above ground, storage tank containing gasoline.
- One, vented, 7 barrel, welded, carbon steel, above ground, lube oil storage tank.

These tanks are filled by vendor from a truck and are attended at all times during filling operations

Stabilizer compressor lube oil - A vented, 5 barrel, welded, carbon steel, above ground, lube oil storage tank. This tank is filled by vendor from a truck and is attended at all times during filling operations.

IBLEAP stripper tanks:

- One, 500 barrel, fiberglass, gun barrel (separator) tank. Tank has a high level switch which shuts the inlet valve.
- Two, 210 barrel, welded, carbon steel, untreated, water tanks. These tanks have high level switches that shut the inlet valve.
- One, 34 barrel, horizontal, welded, carbon steel, condensate storage tank.

Skimmer Basin:

All tanks are equipped with thief hatches for vacuum/vent protection.

- One, 210 barrel, welded, carbon steel, oil tank. This tank has a level transmitter and high level alarm
- One, 500 barrel, fiber glass, gun barrel (separator) tank.
- Four, 500 barrel, fiber glass, produced water, storage tanks. These tanks are equipped with level transmitters and high level alarms. Signals from these instruments are transmitted to the plant control room which is manned 24 hours a day.

Name of facility Indian Basin Gas Plant
Operator Marathon Oil Company

PART II, ALTERNATE A
DESIGN AND OPERATING INFORMATION
ONSHORE FACILITY (EXCLUDING PRODUCTION)

(Response to statements should be: Yes, No, or NA)

C. Facility Transfer Operations, Pumping, and In-plant Process.

1. Corrosion protection for buried pipelines:

(a) Pipelines are wrapped and coated to reduce corrosion
Cathodic protection is provided for pipelines if determined
necessary by electrolytic testing. Yes

(b) Electrolytic testing is not performed. No

When a pipeline section is exposed, it is examined and corrective
(c) action taken as necessary. Yes

2. Pipeline terminal connections are capped or blank-flanged and marked
if the pipeline is not in service or on standby service for extended
periods NA

Describe criteria for determining when to cap or blank-flange:

The plant is in continuous operation. Procedures for abandonment of
pipelines will be developed when necessary.

3. Pipe supports are designed to minimize abrasion and corrosion and
allow for expansion and contraction. Yes

Describe pipe support design:

Pipe supports are steel stanchion with wear plated protection at
points of wear and contact. Where large temperature swings are
anticipated, expansion loops are installed.

4. Describe procedures for regularly examining all above-ground valves
and pipelines (including flange joints, valve glands and bodies, catch
pans, pipeline supports, locking of valves, and metal surfaces):

All equipment is observed in operation daily by plant operating
personnel for signs of leakage or other deterioration. Such signs are
reported and corrected via the plant work order system.

Where deemed appropriate, more rigorous inspection methods, such as
ultra-sonic thickness testing or X-ray inspection, are conducted.
(Records of these tests are on file at the Indian Basin Gas Plant.)

5. Describe procedures for warning vehicles entering the facility to
avoid damaging above ground piping:

Signs and traffic barrier guards are installed where needed.

Name of facility Indian Basin Gas Plant
Operator Marathon Oil Company

PART II, ALTERNATE A
DESIGN AND OPERATING INFORMATION
ONSHORE FACILITY (EXCLUDING PRODUCTION)

(Response to statements should be: Yes, No, or NA)

- D. Facility Tank Car & Tank Truck Loading/Unloading Rack Tank car and tank truck loading/unloading occurs at the facility.

(If yes complete 1 through 5 below).

Yes

1. Loading/unloading procedures meet the minimum requirements and regulations of the Department of Transportation. Yes
2. The unloading area has a quick drainage system. No
3. The containment system will hold the maximum capacity of any single compartment of a tank truck loaded/unloaded in the plant. Yes

Describe containment system design, construction materials, and volume:

The truck loading facility is enclosed by an earthen dike designed to contain 110% of the volume of one transport truck. See attached drawing and calculation sheets for more detail.

4. An interlocked warning light, a physical barrier system, or warning signs are provided in loading/unloading areas to prevent vehicular departure before disconnect of transfer lines. No

Describe methods, procedures, and/or equipment used to prevent premature vehicular departure:

A ground wire system is in use, which will not allow the transfer pump to operate unless the truck is attached to both the ground wire and to the loading rack via the transfer line. If this circuit is broken, the transfer pump will shut down. In addition, the loading rack is equipped with an automatic shutoff, which activates when a pre-set volume passes through the LACT meter. This will limit the volume of condensate that could be leaked if premature truck departure would occur.

5. Drains and outlets on tank trucks and tank cars are checked for leakage before loading/unloading or departure. Yes

Name of facility Indian Basin Gas Plant
Operator Marathon Oil Company

PART II, ALTERNATE A
DESIGN AND OPERATING INFORMATION
ONSHORE FACILITY (EXCLUDING PRODUCTION)

(Response to statements should be: Yes, No, or NA)

E. Security

1. Plants handling, processing or storing oil are fenced. No*
2. Entrance gates are locked and/or guarded when the plant is unattended or not in production. NA*
3. Any valves which permit direct outward flow of a tanks contents are locked closed when in non-operating or standby status. Yes
4. Starter controls on all oil pumps in non-operating or standby status are:
 - (a) Locked in the off position, No**
 - (b) located at sites accessible only to authorized personnel. Yes
5. Discussion of items 1 through 4 as appropriate:
 - * The gas plant is attended 24 hours per day, each day of the year. The gas plant is fenced, the condensate storage tanks are outside the fenced area.
 - ** The LACT unit addressed in Item D. 4, has a key lock security system which requires an assigned key to allow loading trucks.
6. Discussion of lighting around the facility:
Flood lighting and localized area lighting provided by Marathon Oil Company.

Name of facility Indian Basin Gas Plant
Operator Marathon Oil Company

IGBP SPCC Plan Attachments Index

Section 1

Attachment 1	_____	Plan re-certification / modification record
Attachment 2	_____	API SPCC Plan Attachment #2
Attachment 3	_____	Commitment of Manpower, Equipment, and Materials
Attachment 4	_____	SBU Oil Spill Contingency Plan (5 pages)
Attachment 5	_____	SPCC Inspection procedure
Attachment 6	_____	SPCC Plan annual review form
Attachment 7A	_____	SPCC semi-annual facility inspection form, page 1
Attachment 7B	_____	SPCC semi-annual facility inspection form, page 2
Attachment 8	_____	Example of daily SPCC inspection documentation
Attachment 9	_____	Plant plot plan
Attachment 10	_____	Contact information. Marathon and contract
Attachment 11	_____	Marathon spill report form

Section 2

Worksheets	_____	Secondary containment volume worksheets & drawings
------------	-------	--

Section 3

Maps	_____	Topographic Map
	_____	Road map to plant
	_____	Gathering system

Section 4

Documentation	_____	Inspection records
---------------	-------	--------------------

SPCC Plan Review Record.

This SPCC plan will be periodically reviewed for accuracy in a timely manner as specified by current SPCC regulations. Any amendment to the SPCC plan shall be certified by a PE (Professional Engineer) within six months after a change in the facility design, construction, operation, or maintenance occurs which materially affects the facility's potential for the discharge of oil into or upon the navigable water of the United States or adjoining shorelines. Amendments and PE certifications can be added to the plan as an Attachment, as long as it is consistent with the spill prevention goals of the rest of the plan. The PE is not required to re-certify the entire plan again under these circumstances.

Review Dates	Title	Signature

SPCC PLAN, ATTACHMENT #2
OIL SPILL CONTINGENCY PLANS AND
WRITTEN COMMITMENT OF MANPOWER, EQUIPMENT, AND MATERIALS

Secondary containment or diversionary structures are not practical for this facility for the following reasons (attach additional pages if necessary):

Secondary containment is not provided around the bases of selected storage tanks and process vessels since trapped volatile liquid will vaporize at atmospheric conditions and/or trapped hydrocarbons would create an extreme fire hazard in the plant area. All secondary containments in existence are capable of containing at least 110% the volume of the largest tank within.

A strong oil spill contingency plan is attached.

Yes

A written commitment of manpower, equipment, and materials is Yes attached.

Attachment 2

SPPC PLAN
COMMITMENT OF MANPOWER, EQUIPMENT AND MATERIALS

To: OPERATIONS SUPERVISORS

This is your authority to expeditiously commit manpower, equipment and materials necessary to arrest and contain and initiate cleanup of any harmful quantity of oil or hazardous material discharged from this facility. This authority may be delegated by yourselves to the person in charge of the facility to ensure that necessary activities are implemented as quickly as possible after a spill is noted.



R. V. Coleman

Operations Superintendent

Southern Business Unit

Attachment 3

MCR EMERGENCY RESPONSE PLAN

OIL SPILL

Page 1 of 5

ON LAND

All oil spills, regardless of the quantity shall be reported to the respective area Production Supervisor. The Production Supervisor and/or their designee shall in turn, use the flowcharts contained in the Reporting Section(s) of this manual to determine if the spill is reportable.

If the spill is determined to be reportable the Production Supervisor will be responsible for notifying the proper federal/state and local authorities of the oil spill. They will also be responsible for notifying the area's Production Superintendent and HES Department of the spill. If additional Marathon Oil Company (MOC) resources are needed to respond to the spill the Production Supervisor shall inform the Production Superintendent of this need. The Production Superintendent will be responsible for obtaining the additional MOC resources that are needed to respond to the spill (i.e. activating the Regions Incident Command System).

Gas leaks and gas line breaks shall be reported in the same manner as oil spills. All gas leaks (whether it is natural gas or casinghead gas) need to be reported to the appropriate state oil and gas regulatory agency. Venting of gas from tanks, pressure relief valves, etc. is not reportable under this section. However, these types of releases may be reportable under Federal regulations (CERCLA/SARA) or under the State Air Control Agency regulations. If the escaping gas or oil contains H₂S consult the applicable H₂S Contingency Plan for that facility for additional guidance.

In the case of an oil spill/gas leak from a producing well, a testing vessel, a tank, flow line or any other related oil field equipment, action should be designed to protect human life and control the spill as rapidly as possible. All steps should be considered carefully; however, timing of these steps should be altered to fit the individual circumstances.

1. Shut off source feeding the spill, analyze the type of spill and determine the best immediate action to be taken to contain the spill.
2. Obtain labor and equipment from the nearest source to construct a containment barrier as rapidly as possible.
3. If Item 2 is only a temporary measure and earth moving equipment is required, call out the necessary equipment from the source from which it is most readily available.
4. Employ the use of the most readily available absorbent material (straw, dirt, lost circulation material, etc.). When the location is a heavy clay soil, dirt will be ineffectual.

MCR EMERGENCY RESPONSE PLAN

OIL SPILL

Page 2 of 5

5. If practical, call for vacuum truck to pick up hydrocarbons.
6. Collect lighters and matches from personnel working in the area to assure an explosion or fire does not occur.
7. Restrict entrance to affected area by persons not involved in containment and cleanup operations.
8. Notify Production Superintendent of spill and action being taken. The Production Superintendent will notify the Region's upper management (Operations Superintendent, Region Production Manager, etc) of the spill.
9. Keep livestock from affected area and if practical, notify the farmer or rancher of the situation.
10. The Production Supervisor will notify the required regulatory agencies (National Response Center, TRRC, NMED, etc) of the spill.
11. Be aware of the presence of H₂S gas. Personal Protective Equipment (SCBA's) should be readily available if H₂S gas is known or suspected.
12. In the event the spill results in curtailing deliveries, the Production Superintendent will notify the crude oil purchaser.
13. The Duty Officer at the National Response Center must be notified immediately when a spill reaches "waters of the U.S.", or it appears a certainty that the spill will reach "waters of the U.S."

ON INLAND WATER

All action should be designed to protect human life and control the spill as rapidly as possible. All steps listed should be considered; however, timing of these steps should be altered to the individual circumstances to best accomplish these objectives.

MCR EMERGENCY RESPONSE PLAN

OIL SPILL

Page 3 of 5

1. Any employee sighting a spill will immediately attempt to shut off the source feeding it.
2. The employee will notify his supervisor or the Production Supervisor who will in turn advise the Production Superintendent of the spill.
3. The Production Supervisor shall notify immediately the appropriate state and federal agencies (National Response Center, TRRC, NMED, etc).
4. The employee and/or Production Supervisor will furnish their best estimate of the following information concerning the spill.
 - A. Location of the spill.
 - B. Source and type of oil spilled.
 - C. Is the source still feeding the spill?
 - D. Area covered and volume.
 - E. Direction of movement
 - F. Speed of movement.
 - G. Currents (if applicable).
 - H. Estimate of the area likely to be affected.
 - I. Other action taken.
5. The Incident Commander or his/her designated representative shall keep a daily log of response activities. The log book shall be bound, not loose leaf. Entries shall be dated, time and signed.

A. MINOR SPILLS

1. If the spill is minor (5 to 25 bbls) and a boom is not immediately available, sorbent material should be spread on the spill and collected afterwards.
2. Attempts should be made to cleanup the shoreline and recover as much oil as possible

MCR EMERGENCY RESPONSE PLAN

OIL SPILL

Page 4 of 5

B. MAJOR SPILLS

In all probability, a major spill (greater than 25 bbls) will initially require two basic efforts: 1) stop the leak, and 2) contain the spill. Stopping the leak may require other outside services such as well control specialists, a drilling or workover rig, pipeline repair crew, etc. Requirements should be determined and action initiated as soon as possible.

1. To contain the spill, if a containment boom is readily available, order it out immediately and commence skimming operations as soon as possible.
2. If a contract or coop-containment service is to be employed, it should be mobilized without delay.
3. If weather and water conditions are such that the time required to implement containment will permit the spill to spread beyond possible containment; sorbent material should be spread on the spill.
4. Shoreline work sites for each facility shall be pre-selected, marked as such and made known to the employees who will be involved in spill control activities for the facility.
5. In shallow water, containment should be attempted by boom and the material hand-harvested.
6. If sorbent material has been employed, the local air control agency should be contacted for permission to burn the collected material.
8. When applicable, aircraft should be employed to discourage waterfowl from staying in the spill area.
9. A photographic record of the spill movement, containment and cleanup operations, damage to property, fish kills, efforts to disperse waterfowl, waterfowl kills, and other relevant actions should be kept.

Attachment 4

MCR EMERGENCY RESPONSE PLAN

OIL SPILL Page 5 of 5

CERT REPORTING REQUIREMENTS

In certain cases a spill or release may trigger reporting requirements under Marathon's Corporate Emergency Response Plan. Refer to the section on CERT to make this determination.

REGULATORY AGENCIES TO BE NOTIFIED

The flowcharts contained in the State and Federal Reporting sections provide guidance for determining when a spill is reportable and which regulatory agencies need to be notified. Phone numbers for all of these agencies are listed in the section entitled, "Agency Information."

DEFINITION OF WATERCOURSE OR WATERS OF THE U.S.

The term watercourse is defined as any lakebed (playa), gully, draw, streambed, wash, arroyo, or natural or man-made channel through which water flows or has flowed. An arroyo, which is dry most of the time but flows after a heavy rainstorm is, considered a watercourse. A spill into the arroyo when it is dry is a reportable spill to the National Response Center. Two examples of a watercourse in this Region are Rocky Arroyo behind the Indian Basin Gas Plant and the arroyo's located in Discovery Canyon in the Yates Field. Both happen to drain into the Pecos River. If there is any doubt concerning whether or not a spill has entered a watercourse contact should be made with the Environmental and Safety Department for a final determination.

CERCLA/SARA REPORTING REQUIREMENTS

In some cases a spill may trigger reporting requirements under EPA's CERCLA/SARA regulations. Reference the Federal section of this manual to determine when a spill is covered by these reporting requirements.

IBGP SPCC PLAN INSPECTION PROCEDURES

Eddy County, New Mexico

1. As part of his normal routine, the plant operator(s) will visually inspect the plants production facilities for accumulations, leaks of oil or other hazardous substances. The operator must perform the inspection at least once per shift.
2. The production facilities to be inspected will include but are not limited to lines, vessels, valves, pumps, sumps, ditches, containments, and miscellaneous fittings.
3. In the event that an accumulation or leak is discovered, the operator shall initiate the actions detailed in the current SPCC Plan.
4. The operator shall record his daily inspection on the plant daily reading sheets.
5. Annual SPCC plan and semi-annual SPCC facility inspections will be performed by the plant superintendent, or their designee, using the attached inspection forms. Completed inspections forms will be filed with this plan.

C.M. Schweser

C.M. Schweser

Indian Basin Gas Plant
Superintendent

8/16/01
Date

R.V. Coleman

R.V. Coleman

Indian Basin Operations
Superintendent

8/16/01
Date

Indian Basin Gas Plant Annual SPCC Plan Review Record

Instructions:

Each inspection item listed below should be checked with the most appropriate answer (Y)es or (N)o. If the inspection item requires additional work to complete, note it in the comment section.

Note, the IBGP semiannual facility inspection should also be performed.

Work order(s) should be written for all corrective actions noted during review or inspections. Work orders should be written to show requested by SPCC. Include work order numbers or copies of work orders in this report. The Inspector must initial each item inspected and print their name on each form. The Marathon Supervisor responsible for the facilities being inspected must sign all forms and ensure all necessary corrections are completed.

Plan Review	Y	N	Comments
*Has there been a change in any facility covered by the plan which materially affects its discharge potential to navigable waters?			(See note below)
Has the plan been PE certified within the last 3 years or documentation attached affirming that re-certification is not required?			Note: If the plan is still in effect a originally prepared, this may be documented on a signature page and attached.
Are there three years of inspection records on file?			
Are facility plot plans attached with drainage directions?			
Has the spill history been reviewed for NRC reportable spill trends?			Note: all spills are investigated and actions to correct are tracked to completion.
Has any facility had 2 NRC reportable spill within 12 calendar months or an NRC spill greater than 1000 gallons of oil?			Note: If Yes, was the SPCC plan submitted to the EPA Regional Administrator?
Is an Emergency Contingency Plan available?			
Is a written commitment to manpower, equipment and material attached? Current?			
Is Substantial Harm self determination attached?			
Is drainage direction shown on plot plans?			
Is a topographic map of the area attached or on file?			
Does PART I, #7 of plan accurately describe spill potential and direction?			
Are all oil storage tanks compatible with material stored?			
Have there been any facility modifications which affect the dike size requirements?			
Are daily visual inspections being performed and documented by operators?			
Are oil tanks of adequate capacity to prevent overfilling?			
Is there adequate vacuum/pressure relief protection on oil tanks?			
Have all previously written SPCC related work orders been closed?			

Printed Name
Inspector

Signature

Date Inspected

Printed Name
Plant Superintendent

Signature

Date Accepted

Attachment 6


Comments Code:			
Tanks	Tank foundations	Dikes	Piping / Valves
T1 Drip Marks	TF 1 Cracks	D1 Dike damaged.	P1 Droplets of stored material
T2 Discoloration	TF2 Discoloration	D2 Dike material not impervious	P2 Discoloration
T3 Puddles containing spilled or leaked material	TF3 Settling	D3 Dike not large enough to contain current potential oil volume.	P3 Corrosion
T4 Corrosion	TF4 Gaps between tank and foundation	D4 Vegetation growing in dike.	P4 Pipe supports OK?
T5 Cracks	TF5 Damage caused by vegetation roots	NOTE: There should be NO drainage valves from dikes.	P5 Bowing of pipe between supports
			P5 Evidence of stored material seepage from valves or seals
			P6 Valve glands and bodies OK?

General inspection items to look for:


G1. Drip pans empty ?	G5. Drainage ditches empty?
G2. Lube oil tanks/drums in secondary containment?	G6. Netting in place & in good condition (if applicable)
G3. Chemical Tanks/Pumps in secondary containment?	G7. Sumps empty?
G4. Drain valves plugged?	G8. Localized dead vegetation

Tank inspection guide. For vertical tanks, wall inspections should be described by quadrant. Start quadrant #1 on the North side of tank. For horizontal tanks start description at the top, include direction of view (i.e. looking west). Number quadrants in a clockwise rotation.

Top view
Vertical tank



End view
Horizontal tank



Does Facility Drawing Represent Current Facility Layout & Direction of Drainage? Yes/No _____

Inspector Name Printed

Signature

Date Complete

Tank Description	Comments
Generator Turbine Oil	
Transfer Tank	

Attachment 7A

IBGP SPCC Facility Inspection

Page 2 of 2

Outlet Compressor Lube Oil	
Field Storage Area	
Stabilizer Compressor Lube Oil	
IBLEAP Stripper Tank Area	
Skimmer Basin	
Recompressor Lube Oil	
SWD Pump Lube Oil	
Condensate tank 5B	
Flare Drum Bullet	
Sales Condensate Knockout Bullet	
Sour NGL Surge Bullets (3 ea)	
LACT: Grounding and Auto-shutoff	
General Area Piping and Equipment	

Superintendent Name
Printed

Signature

Date Accepted

Work orders shall be written for any item requiring correction. Work orders will be requested by SPCC. The IBGP work order system will serve to track action items to completion. Attach a copy of SPCC work orders generated by this inspection to this report. File with the SPCC plan.

Attachment 7B

**INDIAN BASIN GAS PLANT
DAILY LOG SHEET #5**

Cryo Plant Readings

Date On: _____

Off: _____

	Normal Operating Range	3 AM	6 AM	9 AM	12 - N	3 PM	6 PM	9 PM	12 - M
Cryo Temperatures									
Warm G/G Inlet Gas In	80 - 115 F								
Warm G/G Inlet Gas Out	65 - 80 F								
Warm G/G Residue Gas Out	80 - 100 F								
Cool G/G Inlet Gas In	65 - 80 F								
Cool G/G Residue Gas In	-50 - -5 F								
Cool G/G Residue Gas Out	50 - 80 F								
Side Reboiler Inlet Gas In	5 - 25 F								
Side Reboiler Inlet Gas Out	-10 - 15 F								
Side Reboiler Draw	-65 - -40 F								
Side Reboiler Return	0 - 25 F								
Cold G/G Inlet Gas In	-10 - 15 F								
Cold G/G Inlet Gas Out	-110 - -90 F								
Cold G/G Residue Gas In	-145 - -120 F								
Cold G/G Residue Gas Out	-35 - -20 F								
Ratio Control Valve Out	-150 - -135 F								
Exp Compressor Discharge	125 - 140 F								
Expander Outlet	-105 - -75 F								
Bottom Reboiler Draw	40 - 55 F								
Bottom Reboiler Out	65 - 90 F								
Trim Reboiler Return	70 - 105 F								
Product to MAPCO	70 - 105 F								

Dehydration/Regeneration System Readings


	Normal Operating Range	3 AM	6 AM	9 AM	12 - N	3 PM	6 PM	9 PM	12 - M
Filter Separator delta P	55 - 85 "H2O								
Dehydrated Gas Dewpoint	-120 - -80 F								
Dust Filter delta P	55 - 85 "H2O								
Dehydrated Gas Flowrate	120 - 180 mmscfd								
Regeneration Gas System:									
Regen Gas Flow	15 - 18 mmscfd								
Regen Bed	A, B or C								
Heating or Cooling	LH, HH or C								
Regen Gas Temperature	80 - 580 F								
Regen Cooler Outlet Temp	80 - 120 F								
Regen Scrubber Pressure	850 - 875 psig								
Regen Compressor	Circle One	E or W							
Oil Pressure	18 - 25 psig								
Oil Temperature	120 - 150 F								
Suction Pressure	850 - 875 psig								
Discharge Pressure	925 - 950 psig								

COMMENTS DAYS _____

I have inspected the equipment and find no leaks or other hazardous conditions
 Operator Signature _____

COMMENTS NIGHTS _____

I have inspected the equipment and find no leaks or other hazardous conditions
 Operator Signature _____



SPCC ITEM KEY

- 1 = Generator Turbine Oil
- 2 = Open top transfer tank
- 3 = Outlet compressor lube oil
- 4 = Field Storage Area
- 5 = Stabilizer Compressor lube oil
- 6 = IBLEAP
- 7 = Skimmer Basin
- 8 = Recompressor lube oil
- 9 = SWD pump lube oil
- 10 = Condensate tank 5B
- 11 = Flare Drum
- 12 = Knockout
- 13 = Sour NGL surge
- 14 = LACT loading area

LACT UNIT
14

11
12

13

INDIAN BASIN
PRODUCTION AREA
ICS STRUCTURE

Incident Commander									
Bob Coleman	(505) 457-2621 (Ext 103)	866-499-7600	(505) 420-2028	(505) 628-0049	40	1			
Operations Section									
Dwight Brodbeck * Field ♦	(505) 457-2621 (Ext 131)	866-499-7602	(505) 420-3509	(505) 887-9097	24	36			
Mike Schweser * IGBP ♦	(505) 457-2621 (Ext 104)	866-499-7601	(505) 420-2337	(505) 885-0716	24	2			
Jerry Harrison	(505) 457-2621 (Ext 121)	866-499-7603	(505) 420-2200	(505) 746-6754	24	3			
Timmy Klein	(505) 457-2621 (Ext 108)	866-499-7640	(505) 365-5518	(505) 484-3675	24	13			
Tim Winters	(505) 457-2621 (Ext 120)	866-499-7604	(505) 365-7589	(505) 746-4662	24	4			
Planning Section									
Rick Gaddis*	(505) 457-2621 (Ext 119)	866-499-7626	(505) 365-7791	(505) 885-7786	24	8			
David Ellwood	(505) 457-2621 (Ext 130)	866-499-7613	(505) 365-5405	N/A	24	22			
Logistics Section									
James Faught*	(505) 457-2162	866-499-7636	(505) 365-8259	(505) 392-6575	24	32			
Sharky Morgan	(505) 457-2621 (Ext 111)	866-499-7618	(505) 365-7618	(505) 745-3327	24	16			
Bruce Waldrip*	(505) 457-2621 (Ext 107)	866-499-7641	(505) 365-5518	(505) 457-2252	24	13			
Safety									
Pat Reynolds*	(505) 457-2621 (Ext 139)	866-499-7628	(505) 420-2463	(505) 748-1472	40	Handheld			
Jim Wilson	(505) 457-2621 (Ext 106)	866-499-7638	(505) 365-5518	(505) 746-6481	40	Handheld			
Jack Ivy	(505) 457-2621 (Ext 128)	866-499-7611	(505) 365-8442	(505) 748-2763	24	17			
Public Affairs									
Pat Bowen	(505) 457-2621 (Ext 133)	866-499-7627	(505) 365-5517	(505) 748-2885	24	26			
Jamey Standard	None	866-499-7615	(505) 365-4976	(505) 887-1645	24	7			

* Denotes Command Staff/Section Chief "Lead" if applicable.

♦ Denotes Alternate Incident Commanders

IB MARATHON EMPLOYEES

First	Last	Employee No.	Extension	Cell Phone 1	Cell Phone 2	Pager Number	Radio #	Home Number	Home Address 1	City	Zip
Becky	Altemus		151					(814)883-8980	505 W. Mermod Apt.1	Carlsbad	88220
Keith	Anderson	65755	156	(505) 365-7592		(888) 621-2938		(505) 628-1494	1218 MIEHLS	Carlsbad	88220
Winston	Ballard	102194	128	(505) 420-2398		(888) 226-4697	18	(505) 885-5325	413 CORINNE PLACE	Carlsbad	88220
Jimmy	Barnett	71868	110			(888)621-2940	hand held	(505) 746-2818	P.O BOX 1173	Artesia	88210
Pat	Bowen	95085	133	(505) 748-5022		(888) 386-5241	26	(505) 748-2885	#3 NORTHGATE PLACE	Artesia	88210
Gerald	Brasfield	101886	110		746-7593	(888) 621-2941	hand held	(505) 365-2116	#16 SHEILA RD.	Artesia	88210
Dwight	Brodbeck	67903	131	(505) 420-3509		(888) 251-8204	36	(505) 887-9097	305 FARRELL	Carlsbad	88220
Robert (Bob)	Coleman	71684	103			(888) 226-4691	1	(505) 628-0049	612 RIDGECREST DR.	Carlsbad	88220
Rick	Crawford		154	(915)2587726		(915) 488-3062					
Archie	Crossland	99707		(915) 528-1099		(915) 560-8804	5	(915) 337-2573	341 E. HARRISBURGH		
Larry	Davis	76675	110			(888) 621-2942	hand held	(505) 748-9747	1404 HERMOSA DRIVE	Artesia	88210
Dan	Dowhower	63809		(505) 365-8214			38	(505) 885-6834	2014 E. PEPPER TREE	Carlsbad	88220
David	Ellwood	62918	130	(505) 420-2359		(888) 226-5089	22		308 E. ORCHARD LN #2	Carlsbad	88220
James	Faught	70496	457-2162	(505) 365-8259			32	(505) 392-6575	308 E. ORCHARD LN #3	Carlsbad	88220
Rick	Gaddis	67708	119	(505) 420-2391		(888) 386-5240	8	(505) 885-7786	1002 N. SHORE	Carlsbad	88220
Kenny	Garrett	72212	114	(505) 365-5518		(888) 226-4699	15	(505) 748-2932	2104 W. BRISCOE	Artesia	88210
Jared	Hall	109031	140	(505) 365-7607		(888) 251-8205	34	(505) 628-8759	1009 N. PATE	Carlsbad	88220
Brady	Hamilton			(505) 365-7614		(505) 364-1921	40	(505) 361-0991	1921 N. GUADALUPE	Carlsbad	88220
Jerry (Bubba)	Harrison	76325	121	(505) 420-2200			3	(505) 746-6754	34 W. BLEVINS ROAD	Artesia	88210
Jack	Ivy	95080	138	(505) 365-8442		(888) 227-4277	17	(505) 748-2763	2007 W. RUNYAN	Artesia	88210
Morris	Jones	75255		(505) 365-4350			33	(505) 746-0852	611 S. ROSELAWN	Artesia	88210
Clint	Kirkos	101910	110			(888) 627-7711	hand held	(505) 885-2883	14 TOBYN ROAD	Carlsbad	88220
Timmy	Klein	75647	108	(505) 365-5518		(888) 226-4699	13	(505) 484-3675	P.O BOX1463	Hope	88250
Steve (Sharky)	Morgan	99715	111	(505) 365-7618		(888) 251-8195	16	(505) 745-3327	P.O BOX 283	Carlsbad	88220
John	Norris	102979	127	(505) 365-6776		(888) 251-8201	10	(505) 887-3836	1814 SOLANA	Carlsbad	88220
Jack	Rauch	95090	110			(888) 627-7886	hand held	(505) 885-8440	2129 Haston RD.	Carlsbad	88220
Pat	Reynolds	74936	139	(505) 420-2463		(888) 627-8299	hand held	(505) 748-4172	1002 W. Clayton Ave.	Artesia	88210
David	Rouse	74162	110			(888) 627-7896	hand held	(505) 746-2619	2108 Center	Artesia	88210
Margie	Ruiz	114065	101				hand held	(505) 887-2025	2315 Washington	Carlsbad	88220
Mike	Schweser	71606	104			(888) 266-4693	2	(505) 885-0716	1535 ARBOR COURT	Carlsbad	88220
Jamey	Standard	113234		(505) 365-4976	361-1645	(888) 251-8207	7	(505) 887-1645	1608 W. URAL DR.	Carlsbad	88220
Darlin	Stanfield	114064	102					(505) 628-0469	502 S. WALNUT	Carlsbad	88220
Jim	Tomlinson		126	(505)420-2393			35			Carlsbad	88220
Mark	Treesh	102607	115	(505) 420-2353		(888) 226-4695	12	(505) 887-8116	1413 DESERT WILLOW	Carlsbad	88220
Joe	Trevino	101468	127	(505) 365-5899		(888) 251-8203	9	(505) 887-6225	P.O BOX 1372	Carlsbad	88220
Shaun	Troublefield	100134	110			(888) 627-7897	hand held	(505) 748-1326	1813 Briscoe	Artesia	88210
Bruce	Turpin	74114	110				hand held	(505) 887-1961	1901 Boyd DR. #37	Carlsbad	88220
Dario	Velasquez	101303	110			(888) 627-8189	hand held	(505) 628-8782	4214 Harmon LN.		
Bruce	Waldrip	73482	107	(505) 365-5518		(888) 226-4699	13	(505) 457-2252	506 LAKE ROAD	Artesia	88210
Charlie	Williams	113111		(505) 365-8441		(888) 577-2755	6	(505) 457-2393	5857 S. 7 RIVERS	Artesia	88210
Don	Williams	74998	117	(505) 365-5585		(888) 226-5089	11	(505) 628-8038	1615 DESERT WILLOW	Artesia	
Jim	Wilson	76453	106	(505) 365-7598				(505) 746-6481	P.O BOX 351	Artesia	88210
Tim	Winters	74561	120	(505) 748-4979		(888) 251-4808	4	(505) 746-4662	2301 BULLOCK	Artesia	88210

IB CONTRACTORS

Company	First	Last	Service Description	Main Phone Number	Ext.	Cell Phone 1	Pager Number	Radio #	Home Number
Aranda's Welding	Joe	Aranda		(505) 887-9755		(505) 365-8079		19	
B&H Construction	Mike	Wright	Construction equipment, manpower	(505) 887-9755		(505) 369-5963			
B&H Construction	Alan	Walker	Construction equipment, manpower	(505) 887-9755		(505) 420-8950	(800) 647-4350		
Centrilift	Steve	Fulwider				(915) 425-3737	(800) 888-7756		(505)234-1658
Centrilift	Ray	Holcomb		(505)457-2621	134	(915) 425-3975	(888) 848-2485	30	(505)885-7683
Centrilift	Joe	Lisenbe		(505) 457-2309	134	(505) 425-3620	(888) 848-2491		
Dean's Elect	JD	Atkins		(505) 748-5861		(505) 748-5861	(500) 364-1237		(505)746-8797
ESP	Danny	Denson		(505) 457-2621	148	(505) 748-5198	(505) 364-1353	37	(505)746-1228
Hanover	Denny (Bones)	Reams				(505) 631-7861		24	
Indian Fire & Safety	Don	Tidwell	Air, fire, monitors	(505) 746-4660		(505) 369-8629			
Key Energy	Marcos	Hernandez	Marathon main contact for Key Energy	(505) 457-2309	136	(505) 390-9442	(505) 370-7679	31	
Key Energy	Jimmy		HOT OILER					109	
Key Energy	Tony		VAC.					108	
Loudon Elect	Ray	Methola	Electrician			(505) 365-6164			(505)885-7257
Loudon Elect	Tim	Methola	Electrician			(505) 365-5903	364-1227	20	(505)887-8515
Mesquite Services	Arturo	Moreno		(505) 885-3996		(505) 910-5056	1-800-560-9557	107	
Mesquite Services	Ricky	Buendia						105	
Nalco/Exxon	Randy	Fulwider		(505) 457-2621	145	(505) 631-7812	(888) 727-3872	39	
Nalco/Exxon	Ismael	Porras		(505)457-2621	155	(505) 631-2731	(800) 701-9763		
Nalco/Exxon	Bill	Vickers		(505)623-8423		(505) 631-2728	(505) 364-1959		
NGM	Larry	Lejune				(505) 420-7752		29	(505)623-8423
NGM	David	Ortega				(505) 420-7750			
RedMan	David	Anaya	Warehouse	457-2163		(505) 365-5172	1-364-1148		
TESSCO	Reid	Harris				(505) 390-3542	(800) 595-0703		(505)887-3092
Truck & Tractor	David	Wilson		(505) 457-2309		(505) 365-6758	800-232-3073		
WSI / Pumper	Mike	Briseno	Cleanup Service. Roustabouts.	(505) 887-7475		(505) 365-5040	(888) 887-6818	21	
WSI / Unit101	Richard	Gomez	Cleanup Service. Roustabouts.	(505) 887-7475		(505) 365-4375	(505)364-1872	101	(505)746-1856
WSI / Unit102	Joe	Gomez		(505) 887-7475		(505)365-4403		102	
WSI / Unit102	Wendell	Malone		(505) 887-7475		(505)365-7464		102	(505)748-2575
WSI Unit 103	Thomas	Martinez	Cleanup Service. Roustabouts.	(505) 887-7475		(505) 365-6854	(505)234-2419	103	(505)887-0225
WSI Unit 103	James	Perez		(505) 887-7475				103	(505)746-6629
WSI Unit 103	Mark	Velasquez		(505) 887-7475				103	(505)748-6417
WSI / Unit106	Tito	Salmon	Cleanup Service. Roustabouts.	(505) 887-7475		(505) 361-2003	(505) 364-1874	106	
WSI / Unit106	Arland	Cox		(505) 887-7475				106	(505)457-2360
WSI Unit 100	Tony	Trujillo	Cleanup Service. Roustabouts.	(505) 887-7475		(505) 369-2002	(505) 234-2418	100	
WSI Unit 100	Tony	Castillo		(505) 887-7475				100	(505)628-1042
WSI Unit 100	Kevin	Glissen		(505) 887-7475				100	(505)887-9889
WSI / Pumper	Delbert	Yandell	Pumper	(505) 887-7475					(505)885-6442
Natco	Bigo	Aguilera	Lab Tech.						(505) 885-5474
WSI / Janitor	Charlis	Tosillos	Janitor						(505) 746-0214
Garrison	Buddy	Lanehart				(915) 940-4017			

Emergency Services

<i>Service Provider</i>	<i>Description</i>	<i>Main Phone</i>
General Emergency	Police, Fire, Ambulance	911
Carlsbad Police, Fire & Ambulance Service		(505) 885-2111
Artesia General Hospital	Medical Services	(505) 748-3333
Carlsbad Fire Dept.	Fire Control	(500) 885-3124
Artesia Fire Dept.	Fire Control	(505) 746-2701
Happy Valley Fire Dept.	Fire Control	(505) 885-1982
NM State Police	Sub-District 3, Carlsbad	(505) 885-3138
NM State Police	District 3, Roswell	(505) 827-9312
Eddy County Sheriff	Law enforcement	(505) 887-7551

REGULATORY CONTACTS

Agency	Contact Name		Division/Area	Main Phone Number	Cell Phone 1	Home Phone Number
	First	Last				
NMOCD	Emergency Number		Distict 2	(505) 746-4302		
NMOCD	Field Rep On-Call		Distict 2	(505) 939-8622		
NMOCD	Tim	Gum	Distict 2	(505) 748-1283	(505) 365-7566	(505) 324-1387
NMOCD	Mike	Stubblefield	Distict 2	(505) 748-1283	(505) 365-8211	(505) 746-6422
NMOCD	Gary	Williams	Distict 2	(505) 748-1283	(505) 365-7562	(505) 748-2259
NMOCD	Gerry	Guye	Distict 2	(505) 748-1283	(505) 365-7563	(505) 887-3254
NMOCD	Phil	Hawkins	Distict 2	(505) 748-1283	(505) 365-7564	(505) 746-9272
NMOCD	Bryan	Arrant	Distict 2	(505) 748-1283	(505) 365-7565	(505) 748-2092
NMOCD	Lori	Wortenberhy	Santa Fe Division Offices	(505) 827-7131	(505) 476-3460	(505) 466-0134
NMOCD	Ed	Martin	Santa Fe Division Offices	(505) 827-7131	(505) 476-3492	(505) 685-4056
NMOCD	Roger	Anderson	Santa Fe Division Offices	(505) 827-7131	(505) 476-3490	(505) 471-2017
NM State Police			District 3, Roswell	(505) 827-9312		
NM State Police			Sub-District 3, Carlsbad	(505) 885-3138		
BLM			Carlsbad	(505) 887-6544		
US Coast Guard			National Response Center	(800) 424-8802		
NMED			Air Quality Bureau	(505) 827-1494		
	State Emergency Response Center			(505) 827-9126		
LEPC	Local Emerg Planning Commission		Eddy County	(505) 885-2111		
NM OSHA	New Mexico OSHA Office			(505) 827-2850		

Other Services

<i>Facility Name</i>	<i>Address</i>	<i>City</i>	<i>Phone Number</i>	<i>Services</i>
Stevens Motel	1829 S. Canal	Carlsbad	(505) 887-2851	Lodging, Food, Laundry, Meeting Rooms
Comfort Inn & Suites	2429 W. Pierce	Carlsbad	(505) 887-1994	Lodging
Holiday Inn Express	2210 W. Main	Artesia	(505) 748-3904	Lodging
Best Western Pecos Inn	2209 W. Main	Artesia	(800) 676-7481	Lodging, Food, Meeting Rooms
Denny's Restaurant	810 W. Pierce	Carlsbad	(505) 885-5600	Food
Furr's Family Dinning	901 S Canal St	Carlsbad	(505) 885-0430	Food
K-Bob's Steakhouse	601 S 1st St	Artesia	(505) 748-2208	Food
LaFonda Restaurant	206 W. Main S	Artesia	(505) 746-9377	Food, Meeting Room
Catering- Granny's Chuckwagon	3204 W. Main	Artesia	(505) 746-3209	Food Catering
Domino's Pizza	302 S. 1st	Artesia	(505) 746-0030	
Carlsbad Civic Center	4012 Nationals Prk Hw	Carlsbad	(505) 887-9004	Meeting Rooms
Carlsbad Country Club	1700 Orchard Ln.	Carlsbad	(505)885-3926	Meeting Rooms
Artesia Country Club	2701 W. Richey	Artesia	(505)746-6732	Meeting Rooms

MARATHON OIL COMPANY NEW MEXICO SPILL AND RELEASE REPORT

This form to be completed for any spill or release

Release/Spill Date Mo Day Yr	Estimated Time of Release/Spill	Fluid Type	Amount Released	Volume Recovered
/ /	am/pm	Oil	Bbls	Bbls
Was Spill Contained?		Water	Bbls	Bbls
<input type="checkbox"/> Yes <input type="checkbox"/> No Other (please list) →			Bbls	Bbls
<input type="checkbox"/> Dike <input type="checkbox"/> Pit <input type="checkbox"/> Basin		Total	0 Bbls	0 Bbls
GAS RELEASE		MSCF		

* Use unit letter or footages, both are not required.

LOCATION OF RELEASE

Unit Letter	Section	Township	Range	Feet from the	North/South Line	Feet from the	East/West Line	County

Field _____ Lease No. _____ Well: _____

Facility Name: _____ Facility Type: _____

CAUSE OF RELEASE

Equipment Which Leaked	Type of Failure Causing Leak	Location of Leak	Cause of Failure/Leak	Probable Method of Repair
<input type="checkbox"/> Tank <input type="checkbox"/> Heater Treater <input type="checkbox"/> Separator <input type="checkbox"/> FWKO <input type="checkbox"/> Valve <input type="checkbox"/> Stuffing Box <input type="checkbox"/> Process Piping <input type="checkbox"/> Other (specify) _____	<input type="checkbox"/> Break <input type="checkbox"/> Cracked <input type="checkbox"/> Hole <input type="checkbox"/> Plugged <input type="checkbox"/> Split <input type="checkbox"/> Striker Plate Missing <input type="checkbox"/> Overfill <input type="checkbox"/> Other (specify) _____	<input type="checkbox"/> Shell <input type="checkbox"/> Bottom <input type="checkbox"/> Connection <input type="checkbox"/> Associated Piping <input type="checkbox"/> Line <input type="checkbox"/> Fire tube <input type="checkbox"/> Gasket <input type="checkbox"/> Manway <input type="checkbox"/> Nozzle (specify) _____ <input type="checkbox"/> Seam <input type="checkbox"/> Weld <input type="checkbox"/> Other _____	<input type="checkbox"/> Joint Failure <input type="checkbox"/> Internal Corrosion <input type="checkbox"/> External Corrosion <input type="checkbox"/> Improper Application <input type="checkbox"/> Freezing <input type="checkbox"/> High Temperature <input type="checkbox"/> Over Pressure <input type="checkbox"/> Electrical Failure <input type="checkbox"/> High Gas Line Pressure <input type="checkbox"/> Excessive Volume <input type="checkbox"/> Process Shut Down <input type="checkbox"/> Maintenance <input type="checkbox"/> Instrumentation Failure <input type="checkbox"/> Vibration/Impact <input type="checkbox"/> Human Error (specify) _____ <input type="checkbox"/> Other (specify) _____	<input type="checkbox"/> Replaced <input type="checkbox"/> Clamped <input type="checkbox"/> Repaired <input type="checkbox"/> Coated <input type="checkbox"/> Other (specify) _____ <input type="checkbox"/> Return to Service

Flowline _____ **If Flowline**

Buried Steel
 Surface Int. Coating
 Size: _____ Wrapped
 Poly/PVC
 Fiberglass

Cause of Spill or Release (Detailed Description)

Description of Spill Area (proximity to water course, surface water, penetration depth, direction of flow, dimensions, etc.)

(include diagram)

Action taken to contain & begin cleanup spill:

Action taken to prevent recurrence:

Was recommendation to prevent recurrence entered in to a Tracking System? Yes No

Surface Conditions			Weather Conditions				Land Use		
<input type="checkbox"/> Sandy	<input type="checkbox"/> Sandy Loam	<input type="checkbox"/> Clay	<input checked="" type="checkbox"/> Raining	<input type="checkbox"/> Dry	<input type="checkbox"/> Snow	<input type="checkbox"/> Wind	<input type="checkbox"/> Cultivated	<input type="checkbox"/> Rural	<input type="checkbox"/> Residential
<input type="checkbox"/> Rocky	<input type="checkbox"/> Caliche		<input type="checkbox"/> Other				<input type="checkbox"/> Grazing	<input type="checkbox"/> Vacant	

HOW & WHEN WAS SPILL/RELEASE DISCOVERED: _____ : _____ am/pm DATE: _____

Person Initiating Report / Date _____ Supervisor Review / Date _____ Supervisor Review / Date _____

Distribution - Original : Environmental and Safety Department (in Midland)
 Copy: Indian Basin Asset Team Manager
Field Office Spill Report File
HES Technician

NOTIFICATION OF REGULATORY AGENCIES OR OTHER PERTINENT PARTIES

<input type="checkbox"/>	OCD (Hobbs 393-6161) (Artesia 748-1283) (Aztec 334-6178)	Date: _____	Time: _____	am/pm	Person Contacted: _____	Report Number: _____	Comments: _____
<input type="checkbox"/>	OCD Environmental Bureau (505) 476 - 3490	Date: _____	Time: _____	am/pm	Person Contacted: _____	Report Number: _____	Comments: _____
<input type="checkbox"/>	BLM (Hobbs 393-3612) (Carlsbad 887-6544) (Farmington 599-8900)	Date: _____	Time: _____	am/pm	Person Contacted: _____	Report Number: _____	Comments: _____
<input type="checkbox"/>	National Response Center (800) 424-8802	Date: _____	Time: _____	am/pm	Person Contacted: _____	Report Number: _____	Comments: _____
<input type="checkbox"/>	Corporate Emergency Response Team (713) 629-7118	Date: _____	Time: _____	am/pm	Person Contacted: _____	Report Number: _____	Comments: _____
<input type="checkbox"/>	Environmental and Safety Dept (915) 687-8305	Date: _____	Time: _____	am/pm	Fax report	Person Contacted: _____	
<input type="checkbox"/>	Other: _____	Date: _____	Time: _____	am/pm	Fax report	Person Contacted: _____	

Immediate Verbal Notice Required When:

	Not in Water course		In Water course		Vent H2S	Flare SO2	Natural Gas	Blowout	Chemical ¹	Results in Fire
	Oil	Water	Oil	Water						
OCD (district office)	>25 Bbls		Any Amount				>500 mcf	All	> RQ	YES
OCD (Env. Bureau)			Any Amount							
BLM	>100 Bbls & ³		Any Amount				>500 mcf	Yes		Note 2
NRC	Note 4		Any Amount		Note 4	Note 4	N/A	Note 4	> RQ	Note 4
LEPC					> 100 Lbs	N/A	N/A	N/A	> RQ	
CERT	> 500 Bbl	N/A	> 50 Bbl	N/A	> 300 Lbs	N/A	N/A	All	> 3 x RQ	

Note 1 - RQ = SARA Title III or CERCLA Reportable Quantities.
 Note 2 - YES if in a sensitive area or >100 Bbls or >500 mcf
 Note 3 - YES if not entirely contained in secondary containment.
 Note 4 - YES for any spill, release, or fire in a sensitive area.
 Revised 1/11/01

DIKE CALCULATIONS

	Height	X	Length	X	Width	=	Fit
	1.4		6		6		50


Tank Capacity	Volume (bbl)	X	Gal/bbl	X	Fit/Gal	=	Fit
	7.13		42		0.1337		40

dimensions: Diameter = 38", Length = 61"

Available Space	Dike Capacity	X	Bbl/fit	=	Bbls
	50		0.1781		8.98

Freeboard	Available Space	Tank Capacity	Freeboard		
21%	50	40	10	0.1781	2

Diagram: IBGP
Generator Turbine Oil Storage Tank



Located approximately one-half mile north west of Rocky Arroyo.

Drainage to SE

Transfer Tank

DIKE CALCULATIONS Height from lowest point on dike

	Radius	PI	Height	FT ³
	20.25	3.14159	2.5	3220.621


ACTUAL VOLUME AVAILABLE (Tank Capacity)

	Volume(bbl)	X Gal/bbl	X Ft ³ /Gal	FT ³
(Largest Tank)	498.00	42	0.1337	2796

Available Space	Dike Capacity	Occupied Area	FT ² X BB/FT ²	BB/bbl
	3220.62	0	3221	0.1781
				574

Freeboard	Available Space	Tank Capacity	Freeboard (FT)	BB/FT ²	BB/bbl
13%	3221	2796	424	0.1781	76

Diagram: IBGP
 Open Top Fiber Glass Transfer Tank
 Tank Height 5'-4"



Located approximately one-half mile north west of Rocky Arroyo.

Drainage to SE

DIKE CALCULATIONS

	Height	X	Length	X	Width	=	FT ³
	1		14.67		12.67		186


Tank Capacity	Volume(Bbl)	X	Gal/Bbl	X	FT ³ /Gal	=	FT ³
	24		42		0.1337		135

dimensions: Diameter = 45", Length = 146"

Available Space	Dike Capacity	X	BB/FT ³	=	BBls
	186		0.1781		33.10

Freeboard	Available Space	-	Tank Capacity	=	(FT ³)	X	BB/FT ³	=	BBls
27%	186		135		51		0.1781		9

Diagram: IBGP
24 Barrel Outlet Compressor Lube Oil Storage Tank



Located approximately one-half mile north west of Rocky Arroyo.

Drainage to SE

Field storage area

DIKE CALCULATIONS

Height	X	Length	X	Width	=	Ft
0.416		57		32.5		770.64


ACTUAL VOLUME AVAILABLE (Tank Capacity)

Volume (bbl)	X	Gal/bbl	X	Ft/Gal	=	Ft
(Largest Tank) 4.95		42		0.1337		28

Available Space	Dike Capacity	Occupied Area	=	Ft	X	Bbl/Ft	=	Bbl's
770.64		0		771		0.1781		137

Freeboard	Available Space	Tank Capacity	=	Ft	Bbl/Ft	=	Bbl's
96%	771	28		743	0.1781		132

Diagram: IBGP
FIELD STORAGE AREA



Located approximately one-half mile north west of Rocky Arroyo.

Drainage to SE



DIKE CALCULATIONS

	Height	X	Length	X	Width	=	Fl ³
	1.5		6.25		5		47


Tank Capacity	Volume (bbl)	X	Gal/bbl	X	Fl ³ /Gal	=	Fl ³
	5		42		0.1337		29

dimensions: Diameter = 32", Length = 62"

Available Space	Dike Capacity	X	Bbl/Fl ³	=	BBLs
	47		0.1781		8.35

Freeboard	Available Space	-	Tank Capacity	=	Freeboard (Fl ³)	Bbl/Fl ³	=	BBLs
38%	47		29		18	0.1781		3

Diagram: IBGP
Stabilizer Compressor Lube Oil Storage Tank



Located approximately one-half mile north west of Rocky Arroyo.

Drainage to SE



DIKE CALCULATIONS

	Height	Length	Width	Fr
	1.08	80	36	3110.4

OCCUPIED AREA

Tanks	Number of Tanks	Fr	Radius	Height	Fr
Untreated water East	1	3.14	5	1.08	85
Untreated water West	1	3.14	5	1.08	85
					<u>170</u> total

*Do not count single tank of largest capacity.

Air Strippers	Length	Width	Height	Fr
East	6	3	1.08	19.44
West	6	3	1.08	19.44
				<u>38.88</u> total


ACTUAL VOLUME AVAILABLE (Tank Capacity)

	Volume(bbl)	Gal/bbl	Fr/Gal	Fr
(Largest Tank)	500	42	0.1337	2808

Available Space	Dike Capacity	Occupied Area	Fr	Bbl/Fr	Bbls
	3110.4	209	2902	0.1781	517

Freeboard	Available Space	Tank Capacity	Fr	Bbl/Fr	Bbls
3%	2902	2808	94	0.1781	17

Diagram: IBLEAP Remediation Project Treatment Area



Located approximately one-half mile north west of Rocky Arroyo.

Drainage to SE

IBGP Skimmer Basin

DIKE CALCULATIONS - Sloped cement containment

Rectangular section	Height	Length	Width	Ft ³
	0.5	100	74	3700
Prism section	Area	Length	Ft ³	
	18.5	100	1850	

Total Dike Volume = 5550 Ft³

OCCUPIED AREA (Concrete Hexagonal Tank Foundations)

Tank Foundations	Side Length	Constant	Height	Ft ³	
Oil Storage tank	4.58	2.5981	0.8	43.6	Height is actual base height.
Gunbarrel	5.42	2.5981	0.9	68.7	
Water Tanks	6.83	2.5981	0.6	72.7	No tank left out of calculations due to tanks being on elevated foundations.
	4D 6.83	2.5981	0.6	72.7	
	4E 6.83	2.5981	0.8	97.0	
Salt Water tank	4 6.58	2.5981	0.75	84.4	
TEG Tank	4.08	2.5981	0.63	27.2	
Total =				466.3	Ft ³

Pump Bases	Length	Width	Height	Ft ³	
SWD Pump	36.67	5.33	0.5	98	Height equal to approx. dike height
each	4.75	1.75	0.5	4	
each	11	1.42	0.5	8	
Total =				109.7	Ft ³

ACTUAL VOLUME AVAILABLE

Tank Capacity	Volume (bbl)	Gal/bbl	Ft ³ /Gal	Ft ³
	500	42	0.1337	2808


Available Space	Dike Capacity	Occupied Area (Ft ²)	Ft ³ (Ft ² X BB/Ft)	BB/Ft	BB/ft ³
	5550	576	4974	0.1781	386

886


Freeboard	Available Space	Tank Capacity	Freeboard (Ft ³ X BB/Ft)	BB/ft ³	BB/ft ³
100%	4974	2808	2166	0.1781	386

84

Diagram: IBGP SKIMMER BASIN



End View of Dike from east side.



Prism Area = .5 ft X 74 ft / 2
Prism Volume = Area X Width

Re-Comp Lube Oil Storage tank

DIKE CALCULATIONS

	Height	X	Length	X	Width	=	FT
	2.66		26		26		1798.16


ACTUAL VOLUME AVAILABLE (Tank Capacity)

	Volume (bbl)	X	Gal/bbl	X	FT ³ /Gal	=	FT
(Largest Tank)	210		42		0.1337		1179

Available Space	Dike Capacity	Occupied Area	FT	X	GBL/FT	=	GBL
	1798.16	0	1798		0.1781		320

Freeboard	Available Space	Tank Capacity	Freeboard (FT)	GBL/FT	=	GBL
	34%	1798	1179	619	0.1781	110

Diagram: IBGP
 210 Barrel Recompressor Lube Oil Storage Tank
 ST-15.21.2102



Located approximately one-half mile north west of Rocky Arroyo.



Drainage to SE

DIKE CALCULATIONS

	Height	X	Length	X	Width	=	Ft
	1.5		6.08		5		46


Tank Capacity	Volume (bbl)	X	Gal/bbl	X	Ft ³ /Gal	=	Ft
	7.13		42		0.1337		40

dimensions: Diameter = 38", Length = 61"

Available Space	Dike Capacity	X	BBL/Ft	=	BBUs
	46		0.1781		8.12

Freeboard	Available Space	Tank Capacity	Freeboard	(ft ³)	BBL/Ft	BBUs
12%	46	40	6	0.1781	1	

Diagram: IBGP
SWD Tri-plex Pump Oil Storage Tank



Located approximately one-half mile north west of Rocky Arroyo.

Drainage to SE

5B condensate tank

DIKE CALCULATIONS

Area	Height	X	Length	X	Width	=	Fl ³
	2.67		110		114		33481.8

OCCUPIED AREA

Area	Number of Tanks	X	π × Radius ²	X	Height	=	Fl ³	
	1		3.14		12		2.67	1208

*Do not count single tank of largest capacity.


ACTUAL VOLUME AVAILABLE (Tank Capacity)

Area	Volume (bbl)	X	Gal/bbl	X	Fl ³ /Gal	=	Fl ³
(Largest Tank)	3000		42		0.1337		16846

Available Space	Dike Capacity	-	Occupied Area	=	Fl ³	X	BB/Fl ³	=	BBUs
	33481.8		1208		32274		0.1781		5748

Freeboard	Available Space	-	Tank Capacity	=	Fl ³	X	BB/Fl ³	=	BBUs
48%	32274		16846		15428		0.1781		2748

Diagram: IBGP condensate storage tank 5B



Located approximately one-half mile north west of Rocky Arroyo.

DIKE CALCULATIONS

Bullet tanks	Height	Length	Width	Ft
	1	221	55	12155

OCCUPIED AREA (Concrete Tank supports)

Tank supports	Length	Width	Height	Ft ³
each	11	1.42	1	16
number of	14			
Total Area =	218			Ft ³


ACTUAL VOLUME AVAILABLE

Tank Capacity	Volume (bbl)	Gal/bbl	Ft ³ /Gal	Ft ³
	1605	42	0.1337	9013

Available Space	Dike Capacity	Occupied Area	Ft ³	BB/Ft ³	BBLs
	12155	218	11937	0.1781	2128

Freeboard	Available Space	Tank Capacity	Freeboard	Ft ³	BB/Ft ³	BBLs
24%	11937	9013	2924	0.1781	521	

Diagram: IBGP Bullet Storage Tanks



Located approximately one-half mile north west of Rocky Arroyo.

Drainage to SE

DIKE CALCULATIONS

	Height	X	Length	X	Width	=	Fi ³
	1.83		57		29		3025

OCCUPIED AREA (Concrete Slab)

Drive Thru	Total Area of A, B, C, D						=	Fi ²
								743

LACT Base	Length	X	Width	X	Height	=	Fi ³
	20		11.5		0.83		192

Side Walk	Length	X	Width	X	Height	=	Fi ³
	54		3.5		0.33		63

Combined Total Area 998

ACTUAL VOLUME AVAILABLE




Truck Capacity	Volume (bbl)	X	Gal/bbl	X	Fi ³ /Gal	=	Fi ³
	180		42		0.1337		1011

Available Space	Dike Capacity	-	Occupied Area	=	Fi ²	X	BBL/Fi ³	=	BBLs
	3025		998		2027		0.1781		361

Freeboard	Available Space	-	Tank Capacity	=	Freeboard (Fi ³)	BBL/Fi ³	=	BBLs
50%	2027		1011		1016		0.1781	181

IBGP LACT UNIT

Diagram: IBGP LACT Unit




IBGP LACT UNIT

A Length	552	Area	1192320 cu/in
Width	144		
Height	15		
B Height	7	Area	23184 cu/in
Width	144		
Length	46		
C Length	60	Area	60480 cu/in
Width	144		
Height	7		
D Length	8	Area	8064 cu/in
Width	144		
Height	7		
Total displacement by drive thru			1284048 cu/in


LACT Pad Length	240	Area	331200 cu/in
Width	138		
Height	10		

Side Walk Length	648	Area	108864 cu/in
Width	42		
Height	4		

Total cement structure displacement =			1724112 cu/in
---------------------------------------	--	--	---------------




Copyright (c) 1997 Horizons Technology, Inc.



MILE

**Marathon Oil Company
Southern Business Unit**

**Indian Basin
Eddy County, New Mexico**





FLUOR DANIEL GTI

**MARATHON OIL COMPANY
STORM WATER POLLUTION PREVENTION PLAN (SWPPP)
INDIAN BASIN GAS PLANT**

March 12, 1998
Revised June 1, 1998

**MARATHON OIL COMPANY
P.O. BOX 1324
ARTESIA, NEW MEXICO 88211**

Prepared by:
Fluor Daniel GTI, Inc.
2501 Yale Boulevard, SE, Suite 204
Albuquerque, New Mexico 87106



Contents

1.0	INTRODUCTION AND REGULATORY INFORMATION	1-1
2.0	FACILITY DESCRIPTION AND GENERAL COMPLIANCE INFORMATION	2-1
2.1	Facility Description	2-1
2.2	Summary of Mapping Requirements	2-1
2.3	Summary of Spills and Leaks	2-1
2.4	Non-Storm Water Discharges and Certification	2-2
2.5	Description of Existing Storm Water Measures	2-2
2.6	Coordination with Existing Environmental Management Plans	2-3
2.7	Existing Sampling Data	2-4
2.8	EPCRA Section 313 Requirements	2-4
3.0	STORM WATER POLLUTION SOURCE INFORMATION	3-1
3.1	Drainage Patterns	3-1
3.2	Inventory of Exposed Materials	3-1
3.3	SWPPP Risk Identification	3-1
4.0	BEST MANAGEMENT PRACTICES (BMP)	4-1
4.1	Non-Structural BMP's	4-1
4.2	Structural BMPs	4-4
5.0	COMPLIANCE EVALUATION AND MONITORING	5-1
5.1	Compliance Evaluation	5-1
5.2	Storm Water Monitoring	5-1
6.0	SWPPP IMPLEMENTATION	6-1
6.1	Pollution Prevention Team	6-1
6.2	Implementation Activities, Priorities, and Schedule	6-1
6.3	Employee Training	6-1
6.4	Erosion and Sediment Control for Well Drilling	6-2
6.5	SWPPP Certification	6-3
7.0	SWPPP RECORDKEEPING AND AMENDMENTS	7-1
7.1	SWPPP Recordkeeping	7-1
7.2	SWPPP Revisions	7-1

List of Tables

Table 2-1	Reportable Spill Summary	2-5
Table 2-2	Non-Storm Water Discharge Certification	2-2
Table 5-1	Storm Water Pollution Prevention Plan Compliance Evaluation Inspection Form	5-3
Table 5-2	Storm Water Pollution Prevention Plan Visual Monitoring Form	5-4

ATTACHMENT 1

Notice of Intent for Multi Sector General Permit

ATTACHMENT 2

Figure 1
Figure 2

ATTACHMENT 3

Table A. Potential Source Identification and Risk Assessment
Table B. Storm Water Control Measures

ATTACHMENT 4

Storm Water Pollution Prevention Team
Training Dates/Minutes of Employee Training Sessions

ATTACHMENT 5

Blank Forms

1.0 INTRODUCTION AND REGULATORY INFORMATION

This Storm Water Pollution Prevention Plan (SWPPP) has been prepared to transfer the Indian Basin Gas Plant from prior coverage under EPA's Baseline General Permit to the modified Multi-Sector General Permit. This action was taken pursuant to EPA's Proposed Modification of National Pollutant Discharge Elimination System (NPDES) Storm Water Multi-Sector General Permit (MSGP) for Industrial Activities (Notice; Federal Register, Vol. 62, No. 133, Friday, July 11, 1997). The Indian Basin Gas Plant (SIC code 1311) had previously completed, a SWPPP prepared pursuant to EPA's Baseline General Permit for the Storm Water NPDES program. This prior SWPPP was prepared following the submittal of a Notice of Intent (NOI) to EPA prior to October 1, 1992. The facility has been assigned Permit No. NMR05A228.

This new SWPPP is based on the implementation experiences and information for the prior SWPPP that was prepared pursuant to the Baseline General Permit. A new Notice of Intent has been completed pursuant to the permit coverage transfer instruction in the EPA July 11, 1997 Federal Register Notice. A copy of this new NOI is attached to this plan (Attachment 1). The information contained in this SWPPP satisfies the content requirements of the 1995 MSGP, as described in Section I of the MSGP Notice (Federal Register Vol. 60, No. 189, Friday, September 29, 1995).

The primary objectives of this SWPPP are to:

1. Evaluate plant operating procedures as they relate to storm water pollution;
2. Identify potential sources of storm water pollution;
3. Suggest specific techniques for minimizing pollution of storm water,
4. Provide instructions, procedures, guidance, and sample forms for SWPPP implementation;
5. Serve as a focal point and training tool for plant personnel; and,
6. Establish an overall framework for the continuing effort of storm water pollution prevention at the plant.

2.0 FACILITY DESCRIPTION AND GENERAL COMPLIANCE INFORMATION

2.1 Facility Description

The Indian Basin Gas Plant is approximately 26 acres in area. It processes gas gathered from a much larger producing gas field. The plant produces natural gas, demethanized hydrocarbon mix, stabilized condensate, and sulfur on a continuous 24 hour per day schedule. The location of the Indian Basin Gas Plant is indicated in Figure 1 (Attachment 2). Approximately one percent of the plant is paved. The gas plant is located on Eddy County Road 401. There is a truck loading area on the east side of the plant. Offices, a warehouse, and parking areas are located near the eastern part of the plant (Figure 2, Attachment 2).

The plant is located in a relatively flat area surrounded by mountainous terrain. The soil is rock and sand with scrub brush and grassy vegetation. The mean annual total precipitation is approximately 14 inches. Average annual Class A pan evaporation is approximately 100 inches, and average annual lake evaporation is approximately 65 inches in this area.

2.2 Summary of Mapping Requirements

The following site-specific information is included in Figure 2:

- Storm water drainage patterns/outfalls (on-site);
- Surface water bodies to which site drainage is directed;
- Footprints of buildings, structures, paved areas, parking lots;
- Storm water pollution source areas (See Table A in Attachment 3); and
- Existing and currently planned storm water structural controls.

2.3 Summary of Spills and Leaks

Spills or leaks of a reportable quantity since 1994 are identified in Table 2-1. Table 2-1 indicates the nature of the release, the amount released and recovered, date, and cause of the release (where possible).

This facility implements a SPCC plan pursuant to EPA regulations and guidelines. Provisions have been developed and are implemented through the SPCC program, to address future spills and releases at this facility. The SPCC plan for this facility is referenced in this SWPPP as being a part of this facility's storm water pollution prevention program as well. This facility also has a Groundwater Discharge Plan (GDP) that defines policies and procedures that affect spill/release planning and response. A current list of spills and/or leaks is maintained in the SPCC/SWPPP file.

2.4 Non-Storm Water Discharges and Certification

Storm water outfalls at this facility were inspected to determine the presence or absence of non-storm water discharges. The procedure used is described below:

Visual Inspection - involves inspection of the storm water discharge points on several different dry-weather occasions in order to visually look for any flow in the storm drain. In the absence of precipitation, no water flow should be observed. If there is water flowing through the outfalls during dry weather, tests should be conducted to determine the source of the flow. An inspection should take place concurrently with an activity that is likely to cause such discharges.

No discharge of water was found on the days that this inspection was conducted. The following table includes this facility's certification regarding non-storm water discharges. Because of the nature of this facility's drainage system this visual inspection for non-storm water discharges can be conducted on a recurring basis.

Table 2-2. Non-Storm Water Discharge Certification

I certify that storm drain systems at the Indian Basin Gas Plant have been tested for non-storm discharges, and that the non-storm water testing described above was conducted and the results presented above are true and accurate.		
_____	_____	_____
Storm Water Coordinator	Signature	Date

2.5 Description of Existing Storm Water Measures

Since October 30, 1989, Indian Basin Gas Plant has been operated under the conditions of a Groundwater Discharge Plan (GDP). That GDP was approved by the State of New Mexico and includes the following aspects that affect storm water runoff:

1. A large uphill diversion berm has been constructed around the north and west sides of the plant. It diverts surface runoff away from the plant and reduces the volume of water that can potentially contact polluting materials at the plant.
2. Containment devices have been constructed around most of the chemical storage areas. In most cases, the containment device is an earth berm. In other cases (such as the sulfuric acid tank at the water treatment unit), a steel pan with manual valve is used for secondary containment. Marathon Oil Company is attempting to reduce the use of drums at the Indian Basin Gas Plant and rely more on bulk chemical storage.

3. Product effluent from most plant equipment is drained through a closed system. In addition, an open collection system has been constructed around much of the plant process equipment. The system consists of concrete pads with curbs, concrete troughs covered with steel grates, drainage collection pipes, sumps, and sump pumps. The purpose of this system is to capture material that originates from a leak or spill, convey it to the sump, and pump it into the skimmer basin. Material collected in this manner is ultimately reprocessed, or disposed in the injection well. (Refer to the "Plant Processes" section of the GDP, pages 5 and 6, for descriptions of an integrity test on the open collection system and closed drain system disposal procedures.)
4. Material handling practices include employee education as to proper procedures and spill/leak response, storing chemical containers in containment berms, and routine inspections.
5. Domestic sewage is treated with a septic system on the plant site. It does not contribute any flow to storm water runoff. There are three septic treatment systems, and a warning to avoid non-domestic sewage is posted on each one.
6. Plant equipment is periodically cleaned with detergents, solvents, or steam. Consistent with the GDP, cleaning effluent is captured by the open drain collection system and disposed of in the injection well (see part 3 above).
7. The SPCC for the Indian Basin Gas Plant has recently been revised (October 15, 1997) and plant spill response capabilities have been improved.
8. Underground storage tanks are not used at the Indian Basin Gas Plant.
9. Spent process catalyst is not exposed to storm water.

In addition to the measures listed above, storm water from approximately four acres of site drains to the southeast corner and passes through a vegetated strip. Storm water from the remainder of the site drains as sheet flow to the southeast where it passes through approximately 800 feet of vegetation before it reaches Rocky Arroyo.

2.6 Coordination with Existing Environmental Management Plans

Marathon has a number of existing regulatory compliance programs and/or plans in effect at the Indian Basin Gas Plant. These plans and/or programs were evaluated during the preparation of this SWPPP and appropriate information for these existing environmental management plans was used as necessary. In addition, existing Marathon standard operating procedures have been incorporated into the development of this SWPPP. The Indian Basin Gas Plant has the following spill prevention and response procedures that relate to, and/or are considered a part of this SWPPP:

- Daily Inspection Checklist
- SPCC Plan
- Hazardous Waste Contingency Plan
- Emergency Response Plan
- Groundwater Discharge Plan

2.7 Existing Sampling Data

There are no storm water quality data available for the Indian Basin Gas Plant.

2.8 EPCRA Section 313 Requirements

Based on current information, the Indian Basin Gas Plant is not a plant subject to EPCRA Section 313 water priority chemical regulations.

Table 2-1. Reportable Spill Summary

Record #	Date	Spill Type	Spill Quantity	Quantity Recovered	Cause
1706	02-07-94	Condensate	0.48	0	Oil dump failed. Spilled out of vent of BP valve.
1714	02-15-94	30 percent DEA sol'n.	59	1.5	Amine pump plunger broke. Solution leaked around the seal.
1741	03-09-94	Condensate	1	1	Tank overflowed (High level switch failed).
1792	05-09-94	Condensate	5.5	5	Skimmer basin overflowed.
1794	05-12-94	Lube Oil	0.25	0.2	Heavy rain run-off caused sump to overflow.
1797	05-23-94	Lube Oil	0.4	0.3	Open drain sump did not start automatically.
1828	06-22-94	Lube Oil	0	0	Pin hole leak in piping.
1841	07-13-94	Condensate	125	1	Pinhole leak on dresser coupling (line 1)
1842	07-16-94	Condensate	3	2.5	SWD Tank ran over.
1858	08-01-94	Amine	1.2	0	Two-inch opened by mistake.

Table 2-1. Reportable Spill Summary

Record #	Date	Spill Type	Spill Quantity	Quantity Recovered	Cause
1878	08-27-94	Condensate	2	0	Leak in line due to corrosion.
1880	09-13-94	Condensate	0.1	0	Unplugging sample line.
1936	12-29-94	Condensate	0.2	0	Tank 3A overfilled.
1963	01-23-95	Condensate	1	0.5	Spillover weir set to high.
1948	03-01-95	Lube oil	0.12	0.08	Pulled plug during maintenance.
2000	03-13-95	Triethylene glycol	0.11	0.04	Unit 25 tank overfilled.
2036	05-15-95	Condensate	2	0	West skimmer tank discharge pump line leaked.
2021	06-01-95	Condensate	10	5	LACT failed to shut down.
2043	06-19-95	Condensate	0.5	0	Separator overflow.
2118	09-14-95	Amine	1.5	1	Pump failure.
2107	10-09-95	Condensate	2.3	0	Separator overfilled.

Table 2-1. Reportable Spill Summary

Record #	Date	Spill Type	Spill Quantity	Quantity Recovered	Cause
2200	02-01-96	Basic sediment	0.75	0	Tank overflow
2201	02-05-96	Basic sediment	3.5	2.5	Tank overflow. Bypass was not shut on SWD pump.
2151	02-07-96	Condensate	2	2	Tank overflow. Electrical or instrument failure.
2135	03-01-96	Gasoline	0.24	0	Valve came off of hose. Loose clamp.
2191	03-09-96	Condensate	8	5	Tank overflow out top of tank. Freezing.
2214	04-27-96	Condensate	4	2	6-inch PVC gathering line west of valve pit leaked.
2239	05-30-96	Condensate	2	2	Separator relief valve not completely opened.
2238	05-30-96	Condensate	5	0	Loading condensate into truck. Driver let overflow, spill.
2279	08-01-96	Condensate	8	7	Top of tank at hatch. Overflow exceeded process capacity.
2343	11-14-96	Condensate	3	2	Tank overflow at vent on tank. Human error.
2395	12-29-96	Condensate	3	0	Tank. Plugged drain. Bottom. Human error.

3.0 STORM WATER POLLUTION SOURCE INFORMATION

3.1 Drainage Patterns

The property is quite flat, but generally drains to the southeast. The only distinct outfall is from a small channel which begins near the west side of the old office, flows south past the residue gas compressors, turns east, and continues between the loading docks and the out-of-service condensate tanks. This channel mainly conveys storm water from the office and workshop areas. Runoff from the remainder of the plant drains to the southeast as sheet flow. All of the runoff eventually drains to the receiving watercourse, Rocky Arroyo. The arroyo is an intermittent stream that contains flowing water only after a significant rainfall.

3.2 Inventory of Exposed Materials

This section contains a description of the Indian Basin Gas Plant's potential storm water pollution sources. Pursuant to EPA guidelines for preparing SWPPPs, this section identifies potential sources which could reasonably be expected to add "significant" amounts of pollutants to storm water discharges. The source areas were also limited to those identified in EPA regulations and guidance as source areas associated with industrial activity that needs to be addressed in an SWPPP.

In addition to identifying and mapping the source areas, this section also describes an inventory of the materials (e.g., chemicals) that are associated with each source area. A narrative description is provided (see Table A, Attachment 3) that lists the materials that are handled at the indicated source area which could be exposed to precipitation. Table A in Attachment 3 presents the necessary SWPPP source area information in a way that:

- is easily understood (i.e., each regulatory source area is listed in Table A and shown on the facility map (Figure 2, Attachment 2)).
- meets multiple SWPPP needs in a single table.

3.3 SWPPP Risk Identification

Determining potential storm water runoff pollution "risks" associated with "industrial activity" involves the following steps:

1. Define the chemical use characteristics of the source area(s), by facility activity, using site inspection and an available data review. Evaluate the nature of each source area to determine:
 - a. The level, or extent, of chemical use or storage in each area.
 - b. The potential for the discharge of this chemical as storm water pollution from the area.

2. Review and evaluate the existing water quality standards for the receiving water bodies.
3. Based on a review of the factors in items 1 and 2 above, specify a relative "risk" ranking for each storm water pollution source area, identifying the potential for storm water runoff to cause a water quality impact.

The simple three-step approach described above results in the identification of not only the potential storm water runoff pollution "risk" from the identified source area(s), but also helps in prioritizing the sources area(s) by their relative "risk." This process then leads to the development of a responsive set of best management practice plans (BMPs) that are related to the priority of pollution risk for the source area, which helps in developing a prioritized schedule for their implementation. In order to implement the three-step risk identification approach described above for the Indian Basin Gas Plant source areas, the following specific procedure was used:

1. Evaluate each facility source area for the materials stored or used in the area and the nature of any existing storm water pollution management measures, or systems, currently in place for that activity.
2. Evaluate the nature of the existing storm water management systems, that do (or could) control storm water pollution from the source area and rank them as "adequate" versus "inadequate" using a common sense judgement approach. This ranking is based on the ability of the existing management system to protect the potential storm water pollution source area during rainfall events.
3. Evaluate readily available water quality information for the receiving water(s) for storm water discharges from the facility, including any existing water quality standards. In addition, identify any specific chemical compounds, or categories of compounds that are of concern to appropriate regulatory agencies for the receiving water(s) to which storm water discharge from this facility is directed.
4. Based on the types of chemicals used or stored in/at the source area, the existing level of runoff management for the source area, and the sensitivity of the receiving water(s) to those chemicals, identify a relative "risk" (i.e., high, medium, low) for potential storm water pollution to the receiving water(s).

The following list shows how the four factors outlined above determine the relative risk factors for storm water pollution source areas at the Indian Basin Gas Plant:

Chemical Use and Control Characteristics	No Specific Standards
Heavy Chemical Use, Adequate Controls	MEDIUM
Heavy Chemical Use, Inadequate Controls	HIGH
Moderate Chemical Use, Adequate Controls	LOW
Moderate Chemical Use, Inadequate Controls	MEDIUM
Light Chemical Use, Adequate Controls	LOW
Light Chemical Use, Inadequate Controls	MEDIUM

The High, Medium, and Low designations in the above listing are defined as follows:

1. **HIGH** - source area has likely impact on receiving water quality, due to significant chemical use, or currently inadequate management controls, or because of identified receiving water sensitivities to a particular chemical being used at the source area. Management controls for this area should be given a high priority for implementation.
2. **MEDIUM** - source area may have an impact on receiving waters, but specific water quality limits for the chemical(s) being used at the source area may not exist. In addition, a **MEDIUM** storm water pollution risk would exist for areas with current management controls that are deemed to be "adequate," but the extent of chemical use is high, such that management attention should continue to be focused on maintaining these management controls. Storm water pollution problems are difficult to reliably quantify for this risk category. Therefore, more information may be necessary concerning storm water pollution amounts, and receiving water conditions, before a more extensive (and/or costly) management control can or should be selected.
3. **LOW** - source area is currently fully contained and controlled, or chemical use is low. Impacts on receiving water quality is not likely. Areas should be included in other management control programs, if applicable, but no prioritized storm water pollution management control is necessary for this source area.

Table A, in Attachment 3, contains the results of a risk evaluation for the Indian Basin Gas Plant storm water pollution source areas, conducted using the procedure outlined above.

4.0 BEST MANAGEMENT PRACTICES (BMP)

This section provides general descriptive information for the BMPs that have been identified (see Table B, Attachment 3) for the storm water pollution source areas at this facility (see Table A, Attachment 3). Table B lists the specific type of BMP, from those described in this section, that can be used to control storm water pollution from each of the specifically identified source areas listed in Table A. This section (4.0) provides background and descriptive information for how the particular BMP can be implemented for a source area.

BMP is a term which refers to measures for preventing or controlling storm water pollution from regulated "industrial activities". BMP's can include processes, procedures, schedules of activities, prohibitions on practices and other management practices to prevent or reduce storm water pollution. Despite the broad nature of BMP's, they can be characterized into two types: structural and non-structural. These two types of BMP's are described in greater detail below.

4.1 Non-Structural BMP's

Non-structural BMP's are primarily (simple and inexpensive) management program(s) that are applicable to a wide variety of regulated "industrial activities". The following six non-structural BMP's are identified in this SWPPP.

- Good Housekeeping
- Preventive Maintenance
- Visual Inspections
- Spill Prevention and Response
- Employee Training
- Recordkeeping and Reporting

Good Housekeeping

Good housekeeping involves developing and maintaining a clean and orderly work environment. Good housekeeping is already practiced at the Indian Basin Gas Plant as part of existing environmental management plans. A slight tailoring of existing good housekeeping practices will help prevent storm water pollution as a part of this SWPPP.

Examples of good housekeeping actions to be conducted pursuant to this SWPPP include:

- Implementing a routine clean-up program using hand shovels, hand brooms, vacuum machines, sweeping machines or other types of cleaning machines.
- Storing containers away from direct traffic paths and stack containers in accordance with manufacturer's instructions to avoid damage and spills.
- Labeling all containers showing contents.

- Covering receptacles and drums when possible or protecting them from storm water exposure (e.g., using indoor storage).
- Prevent potential overflow of harmful chemicals by ensuring regular pick up and disposal of waste material.
- Using temporary covers and pallets for outside parts storage (e.g., tarps) whenever practical or store indoors.

Maintaining employee interest in good housekeeping is an important part of the overall storm water pollution control program at Marathon. Methods for maintaining good housekeeping goals include regular housekeeping inspections by supervisors, discussions of housekeeping at meetings and publicity through posters, suggestion boxes, bulletin boards, and employee publications are other tools that will be used to implement good housekeeping activities.

Preventive Maintenance

An effective Preventive Maintenance Program is a key to a successful pollution management effort. This includes a regular visual inspections of systems, equipment, or devices such as valves, dikes and oil/water separator.

The following are the basic elements of Marathon's SWPPP preventive maintenance program:

- Inventory and identify systems, equipment and areas that should be inspected/maintained.
- Conduct routine inspections and/or tests of the systems, equipment and areas.
- Assure that timely repair, adjustment, replacement, cleaning or other needed maintenance is performed. Use equipment manufacturers' recommended procedures as a guide.
- Maintain documentation on inspections, repairs, maintenance, and corrective actions taken.

Many aspects of this SWPPP preventive maintenance program are currently being implemented at the Indian Basin Gas Plant through existing operating procedures and environmental management plans.

Visual Inspections

A routine visual inspection program is a key element in preventing storm water pollution and is an intricate part of the compliance evaluation component of this SWPPP (see Section 5.0). The Indian Basin Gas Plant Storm Water Coordinator is responsible for performing, or specifically delegating, the necessary visual inspections. The inspections will be integrated with the existing Marathon Inspection Check List. The Compliance Evaluation Inspection Form (Table 5-1) will be used to document the annual compliance evaluations.

Spill Prevention and Response

Spill prevention and control, as well as spill response, is an extremely important component of existing Marathon environmental management plans. Vacuum trucks are called to the site, when needed, to remove free liquid resulting from a spill. Other equipment required for spill response (e.g., shovels) is readily available at the facility.

Employee Training

Employee training programs serve to instill in personnel, at all levels of responsibility, an understanding of the storm water regulatory requirements, potential storm water pollution source areas and this SWPPP's BMP program. In addition, training may be used to instruct employees on proper practices for preventing storm water pollution and establishing proper procedures for responding to a release or spill. To the extent possible, SWPPP training will be coordinated with other existing environmental management plan training programs, as well as other Marathon training programs.

Open communications shall be used for matters relating to storm water pollution. The following principles are guidelines for communications, but may be modified when direct action is needed to reduce storm water pollution:

1. Each employee is empowered to take immediate action to prevent or reduce storm water pollution. Such actions shall be reported at the first available opportunity to the Storm Water Coordinator.
2. Any employee may ask questions, discuss ideas, make suggestions regarding storm water.

Record Keeping and Internal Reporting

Relevant documents are maintained at the Indian Basin Gas Plant as part of Marathon's overall regulatory compliance program. These documents include:

- SWPPP(s);
- Inspection and Spill Records;
- Training Records; and
- Certifications;
- SPCC Plan;
- Groundwater Discharge Plan (GDP)

4.2 Structural BMPs

Structural BMP's serve three basic functions:

1. Reduce or eliminate the volume and pollution from storm water runoff or run-on;
2. Divert or direct storm water runoff/run-on; and
3. Reduce the velocity of the storm water runoff/run-on.

The objective in diverting storm water runoff (or run-on) falls into one of two categories:

1. Divert storm water away from, or around (instead of across or through) regulated "industrial activities".
2. Direct storm water runoff that may have come in contact with chemicals from regulated "industrial activities" to a storm water BMP.

Structural BMP's are considered an "advanced" approach for the reduction or elimination of storm water pollution. Several structural BMPs are in place at the Indian Basin Gas Plant. These structural BMPs are described in Parts 1, 2, and 3 of Section 2.5 of this SWPPP. Storm water runoff from regulated "industrial activities" that is not controlled through the existing and proposed structural BMPs for the facility will be controlled using non-structural BMPs presented in Section 4.1. The following is a general list of structural BMPs that may be applied to a facility.

- Sediment and Erosion Control
- Ballast Ground Cover
- Grassed Swales
- Curbs/Berms
- Grading and Paving
- Storm water Conveyances
- Roofing
- Dikes

Each of these structural BMP's is described in greater detail below with details applying to the Indian Basin Gas Plant added as appropriate.

Sediment and Erosion Control

Erosion prevention may be achieved by using one or more of the following techniques:

- Maintaining beneficial vegetation;
- Reducing runoff velocity;
- Minimizing the exposure of bare soil;
- Immediately stabilizing disturbed soil areas;
- Providing appropriate drainage path ways for runoff;

- Preventing runoff from flowing across exposed (bare earth) areas; or
- Filtering, settling, or removing sediment from runoff.

Preserving as much ground cover as possible will decrease the impact rainfall has on ground surfaces, which in turn prevents erosion. For example, a buffer zone is a naturally vegetated strip that is adjacent to a stream, ditch, or steep, unstable slope. The buffer zone decreases the velocity of storm water runoff and helps prevent erosion. The outfall from approximately four acres of the Indian Basin Gas Plant passes through a vegetated strip. Storm water from the remainder of the facility drains as sheet flow to the southeast where it passes through about 800 feet of vegetation before reaching Rocky Arroyo.

The following structural practices can be used to implement the techniques listed above:

- Straw Bale Dikes, Silt Fences, Earth Dikes
- Subsurface Drain, Pipe Slope Drain
- Storm Drain Inlet Protection, Rock Outlet Protection
- Sediment Traps, Temporary Sediment Basins
- Retention/Detention Basins

Ballast Ground Cover

Infiltration is a structural BMP that causes storm water to enter the ground surface into subsurface soils rather than runoff into surface water bodies. Ballast cover used for storm water infiltration should be installed with a depth and gradation that will promote infiltration and prevent erosion. Soil type and ground slope should also be considered. Potential ground water impacts must also be considered for this (and in fact any) infiltration type of BMP. When storm runoff from areas with known storm water pollution risk is directed to infiltration type systems an evaluation of groundwater pollution impacts must be performed.

Ballast sometimes requires cleaning and/or replacement due to sediment build up that can prevent proper drainage. Cleaning procedures should be conducted in a manner that avoids or minimizes the potential for storm water contamination.

Grassed Swales

Grassed swales are gentle sloping vegetated depressions constructed to promote infiltration, control runoff pollution by filtering sediments, and to channel runoff to a desirable location.

Curbs/Berms

Diversions structures prevent the flow of storm water onto regulated "industrial activities". Often a diversion structure and a storm water conveyance are used together to achieve this goal. Conveyances carry the water away and prevent it from pooling at the curb or berm. For example, an employee parking lot is not a regulated area. If a parking lot drains across a regulated "industrial activity", curbing the perimeter of the lot may be an appropriate BMP. Such action would reduce the amount of storm water that would flow across the "industrial activity", and therefore reduce the potential for generating storm water pollution. Curbing, berms, and associated conveyances need regular inspection, repair, and cleaning to keep them functioning properly.

A large uphill diversion berm has been constructed around the north and west sides of the Indian Basin Gas Plant. It diverts surface runoff away from the plant and reduces the volume of water that can potentially contact polluting materials at the plant.

Grading and Paving

Finished grades at the Indian Basin Gas Plant are designed to facilitate the prevention of runoff onto regulated "industrial activities". Therefore, this surface grading is a BMP, and is a part of this SWPPP that can reduce the exposure of storm water to potential pollutants. However, due to the constraints imposed by normal operations grading and paving may have to be combined with other BMP's (such as curbs or conveyances) to be effective.

Storm Water Conveyances

Storm water conveyances are channels, gutters, drains, and sewers which are used to collect storm water and direct its flow. They are part of a site's storm water collection system. A primary purpose of a storm water conveyance is to prevent storm water from being exposed to a storm water pollution source area.

Gutter systems, down spouts and storm sewers can be retrofitted to discharge runoff away from regulated "industrial activities". This will help minimize the volume of potentially polluted storm water generated at the site. Subsurface conveyance systems are already in place at the Indian Basin Gas Plant. Product effluent from most plant equipment is drained through a closed system. In addition, an open collection system has been constructed around much of the plant process equipment. The system consists of concrete pads with curbs, concrete troughs covered with steel grates, drainage collection pipes, sumps, sump pumps. The purpose of this system is to capture material that originates from a leak or spill, convey it to the sump, and pump it into the skimmer basin. Material collected in this manner is ultimately reprocessed or disposed in the injection well.

Roofing

The construction of a roof over a potential storm water pollution source area (e.g., drum storage) will eliminate the direct exposure of chemicals in that area to rainfall. However, simply covering potential storm water pollution source areas may not be sufficient to prevent contact with "run-on" and "run-through". Simply stated, these terms refer to storm water that does not fall onto potential source materials, but rather flows through a potential source area. Therefore, for roofing to be effective, combination with curbs/berms may be required.

Dikes

Earthen and concrete dikes are used around storage and break-out tankage as a means of collecting storm water and any potential spills. The storm water can then be inspected prior to being discharged into the surface water body. Earthen and concrete dikes are used extensively at the Indian Basin Gas Plant as part of the SPCC. A summary of the storage tanks and the volumes of the dikes are presented in the SPCC.

