1R-

# REPORTS

DATE:



October 28, 1993

Mr. John Hite Shell Pipe Line Company Two Shell Plaza P.O. Box 2099 Houston, Texas 77252-2099

RECEIVED

NOV 1 7 1995

PHASE III SUBSURFACE INVESTIGATION LEA STATION LEA COUNTY, NEW MEXICO

**CURA PROJECT NO. 15-93677.3** 

OIL CONSERVATION DIV. SANTA FE

#### Mr. Hite:

RE:

CURA, Inc. has completed the Phase III Subsurface Investigation at the above-referenced facility. As outlined in Shell Pipe Line Corporation's Scope of Work dated August 10, 1993, the field investigation included the drilling and sampling of four soil borings (B-13, B-14, B-15, and B-16) to an approximate depth of 30 feet. Four additional borings were drilled to an approximate depth of 40 feet and converted to monitor wells (MW-8, MW-9, MW-10, and MW-11). The borings were completed to delineate the hydrocarbon-impacted soils and groundwater previously identified at the site in borings B-1 through B-12 and monitor wells MW-1 through MW-7.

Two general areas, one in the east and the other in the western half of the site, were previously identified as hydrocarbon-impacted areas by elevated total petroleum hydrocarbon (TPH) concentrations in the soils (>100 ppm TPH). Hydrocarbon-impacted soils in the western portion of the site ranged in depth from approximately 3 feet in boring B-3 to 27 feet (depth to groundwater) in B-8, B-11, and MW-5. Hydrocarbon-impacted soils in the eastern portion of the site ranged from a depth of 3 feet in a majority of the borings to 12 feet in monitor well MW-4. Hydrocarbon-impacted groundwater was previously identified in MW-1, MW-2, and MW-3 which are located in the northeast portion of the site.

#### SOIL BORING OPERATIONS AND ANALYTICAL RESULTS

On September 22 and 23, 1993, four soil borings (B-13, B-14, B-15, and B-16) and four monitor wells (MW-8, MW-9, MW-10, and MW-11) were drilled to depths ranging from 27 feet to 40 feet using an air rotary drilling rig. Borings B-13, B-14, and monitor well MW-8 were placed north (upgradient) of the previously identified hydrocarbon-impacted soils in the western portion of the site. Borings B-15, B-16, MW-9, and MW-10 were located south and east of the hydrocarbon-impacted soils and groundwater in the eastern portion of the site to delineate the downgradient extent of hydrocarbon impact. Boring MW-11 was placed upgradient to monitor well MW-3 to further delineate the extent of hydrocarbon-impacted groundwater in the northeastern portion of the site (Appendix A, Figure 1).

The soils encountered during the boring operations consisted of 1 foot to 5 feet of brown to gray silty sands (SM) underlain by multicolored calcareous to slightly calcareous sands to a depth of approximately 41 feet (maximum boring depth).

Based on the data obtained, the extent of hydrocarbon-impacted soils in the western portion of the site is limited to an area approximately 250 feet by 400 feet with the greatest hydrocarbon concentration adjacent to boring B-11, MW-5, and MW-8. The extent of hydrocarbon-impacted soils identified in the eastern portion of the site consists of a 3 foot deep area covering approximately 400 feet by 200 feet. However, hydrocarbon-impacted soils extend to a depth of 12 feet near boring MW-4. Monitor well MW-11 identified hydrocarbon-impacted soils in the northcentral portion of the site from a depth of approximately 10 feet to top of groundwater at 31 feet. However, no phase separated hydrocarbons (PSH) was observed in MW-11 during drilling operations. An area containing hydrocarbon-impacted soils in the two foot interval above groundwater was identified in borings B-15 and MW-2. The area is approximately 50 feet wide and extends approximately 200 feet downgradient (southeast) of the sump and pumps in the eastern portion of the site.

Groundwater was encountered at depths ranging from 26 feet to 31 feet during drilling operations. The boring logs are included in Appendix B and provide a more detailed description of the subsurface conditions encountered at the site. Soil samples were collected intermittently using a split spoon sampling device. The samples were field screened with a Century 128 organic vapor analyzer (OVA). The soil samples which registered the highest OVA reading, had the greatest hydrocarbon odors or staining, and the samples from the greatest depth above groundwater were submitted to the laboratory to be analyzed for TPH and BTEX.

A complete listing of the OVA readings and the soil sample analytical results is provided in Table 1 (Appendix C). Hydrocarbon concentrations of the subsurface soils are illustrated on the site map (Appendix A, Figure 1). The laboratory reports and chains-of-custody are included in Appendix D.

#### MONITOR WELL OPERATIONS AND ANALYTICAL RESULTS

Borings MW-8 was drilled to a depth of 38 feet and converted to a monitor well to delineate groundwater conditions south of Tank No. 1843. Hydrocarbon-impacted soils from near surface to groundwater were identified in this vicinity during the Phase II investigation. Monitor wells MW-9 and MW-10 were placed south of previously identified hydrocarbon-impacted soils and in a downgradient position from the hydrocarbon-impacted groundwater previously identified in monitor wells MW-1 and MW-2 along the southeastern portion of the site. Monitor well MW-11 was located upgradient to MW-3 to delineate previously identified hydrocarbon-impacted groundwater in that monitor well.

The monitor wells were constructed of 4 inch diameter schedule 40 PVC well casing and screen. The screened portion of the monitor wells were surrounded by a sandpack which was capped with a bentonite seal (minimum thickness of 4 feet). The annular space above the bentonite seal was then grouted to surface. A 3-foot by 3-foot concrete pad and an above grade steel monument pipe well cover were then installed at the surface. The boring logs in Appendix B provide a more detailed description of the screened intervals and well construction materials used.

The monitor wells were gauged on September 28, 1993 to determine the presence of PSH, groundwater elevation and gradient. Depth to groundwater on site ranged from 26 feet to 31 feet below ground surface with the apparent groundwater gradient toward the southeast. No PSH was observed in the monitor wells with the exception of 0.04-inch recorded in monitor well MW-8. Monitor well MW-8 is located approximately 200 feet downgradient (southeast) from Tank No. 1843. The western and southern extent of the PSH identified in MW-8 is limited to a radius of less than 300 feet from Tank No. 1843 based on field observations and analytical data from borings B-14, MW-6, and MW-7.

On September 30, 1993, groundwater samples obtained from monitor wells MW-9, MW-10, and MW-11 recorded benzene and total dissolved BTEX levels ranging from less than the method detection limit of 0.001 ppm in monitor well MW-9 to 0.24 and 0.63 ppm, respectively, in MW-11. Monitor well MW-8 was not sampled due to the presence of PSH. Based on the southeasterly groundwater gradient and water analytical results, offsite impact to groundwater downgradient from the site is not probable. Possible source areas for the elevated hydrocarbon levels in MW-8 include Tank 1843 and the associated piping. Possible source areas for the elevated hydrocarbon levels in monitor wells MW-11 and MW-3 include subsurface crude pipelines and the off-site tank batteries north of the site.

A dissolved hydrocarbon concentration map is presented in Appendix A (Figure 3) and depicts the distribution of groundwater BTEX and TPH concentrations. The water analytical results are summarized in Appendix C (Table 3). Laboratory reports and chains-of-custody are included in Appendix D.

#### **CONCLUSIONS**

• Field observations, OVA readings and soil sample analytical results indicate three hydrocarbon-impacted areas are present on site, one in the eastern portion, one in the northcentral portion, and one in the western portion of the site.

- The extent of hydrocarbon-impact in the eastern portion of the site appears to extend from the abandoned water well in the northeast portion of the site to just south of monitor wells MW-4 and MW-2. Depth of soil impact extends from approximately 3 feet below ground surface in the vicinity of borings B-5, B-6, and B-7 to a depth of 15 feet near monitor well MW-4.
- The extent of hydrocarbon-impacted soils and groundwater in the western portion of the site appears to be limited to the area south and southeast of Tank No. 1843 and is confined to within 300 feet of the tank. Depth of soil impact extends from approximately 30 feet below ground surface along the berm of Tank No. 1843 to less than 1 foot just north of monitor wells MW-6 and MW-7. Groundwater impact appears to extend from the PSH observed in monitor well MW-8 southward to the sump area just north of monitor wells MW-6 and MW-7. Probable source area is Tank No. 1843 and/or the associated subsurface piping.
- Hydrocarbon-impacted soils extending from near surface to groundwater at 31 feet
  were identified in the northcentral portion of the site in the vicinity of monitor well
  MW-11. The horizontal extent of this impacted area is unknown. Possible sources
  include subsurface crude lines and the offsite tank batteries located immediately
  north and upgradient to monitor well MW-11.
- The extent of hydrocarbon-impacted groundwater in the northcentral and eastern portions of the site appears limited to the vicinity of monitor well MW-11 and extends to the north and west of monitor wells MW-4, MW-9, and MW-10. The relative concentrations of hydrocarbons in monitor wells MW-3 and MW-11 indicate probable source area to the north (upgradient) which includes subsurface crude pipelines and the off-site tank batteries.

#### **RECOMMENDATIONS**

Feasibility testing is needed to evaluate soil and groundwater remedial methods for implementation on the site. Testing should evaluate potential soil vapor extraction/sparging, groundwater recovery and in situ/exsitu enhanced bioremediation.

CURA will present a workplan for additional activities as requested. CURA appreciates the opportunity to provide you with our professional consulting services. If you have any questions, please do not hesitate to contact us.

Walterscheid, R.E.M., C.P.G.

Branch Manager - Midland

Respectively, CURA, Inc.


F. Wesley Root


**Environmental Geologist** 


FWR/chs

Attachments

# APPENDIX A FIGURES







# APPENDIX B SOIL BORING LOGS



2735 VILLA CREEK DRIVE - TWO METRO SOUARE BLDQ C - SUITE 250 - DALLAS, TX 75234 620-7117 FAX - 620-8219

# RECORD OF SUBSURFACE EXPLORATION

<u> </u>	20-717 FAX - 620-8219							
Project	No.: 15-93677	Well/Bor	ing‡: в	-13		Date Drilled: 09/22/93		
Project:	LEA STATION LEA COUNTY, NEW MEXICO	Depth o	f Boring:	32 FEET		Diameter of Boring: 5 1/8 INCHE		
110,000	-	Depth of	f Well: -		Diameter of Screen: -			
Drilling (	CO: HI PLAINS DRILLING	Length (	of Screer	ኑ -	Diameter of Casing: -			
Driller: B	S.	Length o	of Casing:			Slot Size: -		
Drilling I	Method: AIR ROTARY	Logged	By: r.w.r	₹.		Well Material: GROUT		
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS		
o	Brown medium-grained SAND (SM)					o— = = =		
2.5 - - - -	White calcareous SAND (caliche)					2.5— - - - - - -		
5.0   	White fine—grained SAND (SW)	1	ss	<1		5.0— Benzene <0.001 mg/kg — BTEX <0.001 mg/kg — TPH=20 mg/kg —		
7.5    10.0						7.5— - - - 10.0—		
-	Gray CLAY (CH)	2	SS	<1		10.0		
12.5   	Brown & white mottled fine grained slightly calcareous SAND (SM)					12.5		
15.0 _ _ _ _		3	SS	<1		15.0		
17.5  			1			17.5— - - - -		
20.0 - - -	Red-brown calcareous CLAY (caliche)	4	SS	<1		20.0		
22.5 						22.5		
25.0   	Gray-white calcareous SAND (caliche)	5	ss	1	•	25.0 — Benzene <0.001 mg/kg — BTEX <0.001 mg/kg — TPH=20 mg/kg —		
27.5 - - - - -						27.5 —		
30.0   	Bottom of boring @ 32.0 feet	6	ss	<1		30.0 — ∇Water @ 30.5' — —		
SS-Driven		CAND	CVVDOL			Sample submitted to lab		

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND SYMBOLS

HSA-Hollow Stem Augers CFA-Continuous Flight Augers DC-Driving Casing MD-Mud Drilling

 Sample submitted to lab
Bottom Cap Factory—Slotted
Well Screen

Sand Pack Well Casing
Bentonite Seal Volclay Grout Seal



2735 VILLA CREEK DRIVE - TWO METRO SQUARE BLDQ C - SUITE 250 - DALLAS, TX 75234 620-717 FAX - 620-8219

## RECORD OF SUBSURFACE EXPLORATION

6	20-717 FAX - 620-8219						
Project	No.: 15-93677	Well/Bot	ing‡⊧ в	-14	-	Date Drilled: 09/22/93	
Project:	LEA STATION . LEA COUNTY, NEW MEXICO	Depth o	f Boring:	27 FEET		Diameter of Boring:5 1/8 INCHES	
1 TOJECT	- mexico	Depth of	f Well: -			Diameter of Screen: -	
Drilling C	CO: HI PLAINS DRILLING	Length (	of Screer	ኑ –		Diameter of Casing: -	
Driller: B.	s.	Length	of Casing	-		Slot Size: -	
Drilling N	Method: AIR ROTARY	Logged	By: F.W.F	₹.		Well Material: GROUT	
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS	
— o	Brown fine-grained SAND (SM)					o — - -	
2.5   5.0	Buff-white calcareous SAND (caliche)					2.5— - - - 5.0—	
- - - - - 7.5		1	SS	10		Benzene <0.001 mg/kg — BTEX=0.007 mg/kg — TPH=10 mg/kg — 7.5—	
_ _ _ _ _ 10.0	White fine—grained slightly calcareous SAND (SM)					- - - 10.0—	
- - - - 12.5	<b>,</b> ,	2	SS	<1		- - - 12.5 —	
  15.0						15.0	
- - - -	Light-green fine-grained SAND (SM)	3	SS	4		3	
17.5   -						17.5 - - - -	
20.0 _ _ _ _ _		4	SS	5		20.0	
22.5   			<u> </u>	1		22.5	
25.0 _ _ _ _		5	SS	21		25.0 — Benzene <0.001 mg/kg — BTEX=0.003 mg/kg — TPH=20 mg/kg —	
27.5  _ _ _	Bottom of boring @ 27.0 feet					∇Water @ 26' 27.5 —	
- 30.0 - -				·	:	30.0	
<u> </u>	<u> </u>		<u> </u>	<u> </u>			

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND
HSA-Hollow Stem Augers
CFA-Continuous Flight Augers
DC-Driving Casing
MD-Mud Drilling

ABBREVIATIONS AND SYMBOLS

Sample submitted to lab
Bottom Cap Factory—Slotted
Well Screen Sand Pack Well Casing Bentonite Seal Volclay Grout Seal



2735 VILLA CREEK DRIVE - TWO METRO SQUARE BLDQ C - SUITE 250 - DALLAS, TX 75234 620-717 FAX - 620-8219

## RECORD OF SUBSURFACE EXPLORATION

6	20-7117 FAX - 620-8219						
Project	No.: 15-93677	Well/Bor	ing #⊧ в	-15		Date Drilled: 09/23/93	
Project:	LEA STATION LEA COUNTY, NEW MEXICO	Depth of	f Boring:	32 FEET		Diameter of Boring:5 1/8 INCHES	
110,000	_	Depth of	Well: -		Diameter of Screen: -		
Drilling C	O: HI PLAINS DRILLING	Length o	of Screen	ኑ –	Diameter of Casing: -		
Driller: B.		Length of	of Casing	-		Slot Size: -	
Drilling N	Method: AIR ROTARY	Logged	By: F.W.F	₹.		Well Material GROUT	
DEPTH	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS	
o  	Light—brown fine to medium—grained slightly calcareous SAND (SM)					o— = =	
2.5 						2.5	
- 5.0 - -		1	SS	<1		5.0	
_ _ 7.5 _ _						7.5	
_ _ 10.0 _ -		2	ss	<1		10.0	
- - 12.5 - -					Ī	12.5	
- - 15.0 - -		3	ss	1	: -	15.0— Benzene <0.001 mg/kg	
- - 17.5					-	BTEX=0.004 mg/kg TPH=50 mg/kg 17.5—	
			<u></u>			20.0	
- - - 22.5		4	SS	1			
- - - - 25.0						25.0 —	
<u> </u>		5	ss	<1			
27.5 - - -						27.5 — - - -	
30.0 	Slight hydrocarbon staining & odor	6	ss	700		→ Water @ 31' 30.0 Benzene <0.001 mg/kg BTEX=0.033 mg/kg TPH=1,200 mg/kg	
	Bottom of boring @ 32.0 feet	<u></u>		<u> </u>	<u> </u>	TPH=1,200 mg/kg	

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND SYMBOLS

HSA-Hollow Stem Augers
CFA-Continuous Flight Augers
DC-Driving Casing
MD-Mud Drilling

 Sample submitted to lab
Bottom Cap Factory—Slotted
Well Screen

Sand Pack Well Casing

Bentonite Seal Volclay Grout Seal



2735 VILLA CREEK DRIVE - TWO METRO SQUARE BLDQ C - SUITE 250 - DALLAS, TX 75234 620-7117 FAX - 620-8219

# RECORD OF SUBSURFACE EXPLORATION

Project	No.: 15-93677	Well/Bor	ing #: в	-16		Date Drilled: 09/23/93
Project:	LEA STATION LEA COUNTY, NEW MEXICO	Depth o	f Boring:	27 FEET		Diameter of Boring:5 1/8 INCHES
1 TOJECT		Depth of	f Wel⊧ –			Diameter of Screen: -
Drilling C	O: HI PLAINS DRILLING	Length (	of Screer	ኑ –		Diameter of Casing: -
Driller: B.	s.	Length (	of Casing			Slot Size: -
Drilling N	Method: AIR ROTARY	Logged	By: F.W.F	₹.		Well Material: grout
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS
o	Brown fine-grained SAND (SM)					o- <u>-</u> -
- - 2.5	Buff-white silty SAND (SM)					2.5
- -						5.0
5.0 - - -	Buff-white fine-grained calcareous	1	SS	<1		5.0
7.5 	SAND (caliche)					7.5
10.0 10.0 		2	SS	<1		10.0 — Benzene <0.001 mg/kg — BTEX=0.001 mg/kg — TPH <10 mg/kg —
- 12.5 -						12.5 —
_ 15.0 _	Buff-green silty slightly calcareous SAND (SM)	3	SS	<1		15.0
_ _ 17.5			33			17.5
-						
20.0 _ _ _		4	SS	<1		20.0
- 22.5 - - -		]				22.5
_ —-25.0 - -		5	SS	<1		25.0 — Benzene <0.001 mg/kg — BTEX=0.001 mg/kg
- - 27.5 -	Bottom of boring @ 27.0 feet				_	TPH=30 mg/kg
- - - 30.0						30.0
SS-Driven						=

SS-Driven Spilt Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND SYMBOLS
HSA-Hollow Stem Augers WATER LEV

HSA-Hollow Stem Augers
CFA-Continuous Flight Augers
DC-Driving Casing
MD-Mud Drilling

 Sample submitted to lab
Bottom Cap Factory—Slotted
Well Screen

Sand Pack Well Casing

Bentonite Seal Volclay Grout Seal



2735 VILLA CREEK DRIVE - TWO METRO SQUARE BLDQ C - SUITE 250 - DALLAS, TX 75234 620-7117 FAX - 620-8219

## RECORD OF SUBSURFACE EXPLORATION

6	20-7117 FAX - 620-8219							
Project	No.: 15-93677	Well/Bor	ing #: м	w-8		Date Drilled: 09/22/93		
Project:	LEA STATION LEA COUNTY, NEW MEXICO	Depth o	f Boring:	40 FEET		Diameter of Boring: 8 INCHES		
1 TOJECT	-	Depth of	<b>Wel</b> l: 38	FEET		Diameter of Screen: 4 INCHES		
Drilling C	CO: HI PLAINS DRILLING	Length (	of Screer	F 15 FEET	Diameter of Casing: 4 INCHES			
Driller: B.	S.	Length o	of Casing	23 FEET		Slot Size: 0.02 INCH		
Drilling N	Method: AIR ROTARY	Logged By: F.W.R.				Well Material: sch 40 pvc		
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS		
o - - -	Brown fine-grained SAND (SM)					o — - -		
- 2.5 - - -	Light-gray calcareous SAND (caliche)					2.5		
5.0 - - - -	Brown medium-grained slightly	1	SS	4		5.0 — —		
7.5 - - -	calcareous SAND (SM)					7.5- <u> </u>		
10.0 		2	ss	200		10.0 — Benzene <0.001 mg/kg — BTEX=0.090 mg/kg — TPH=3,300 mg/kg —		
12.5 - - - - - 15.0		) :				12.5		
		3	SS	90	ATATAKAN TARIHAN KATAKAN TARIHAN TARIH	15.0		
17.5   						17.5		
20.0 - - - -	Gray calcareous SAND (caliche)	4	SS	11		20.0		
22.5 - - - -	Dark gray staining hydrocarbon odor					22.5 —		
25.0 _ _ _ _ _		5	ss	>1000		25.0 — Benzene=0.036 mg/kg — BTEX=1.326 mg/kg — TPH=1,400 mg/kg —		
27.5    30.0						∇ Water @ 27' 27.5 —		
						30.5		

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS ANI
HSA-Hollow Stem Augers
CFA-Continuous Flight Augers
DC-Driving Casing
MD-Mud Drilling

ABBREVIATIONS AND SYMBOLS

Sand Pack Bentonite Seal Volclay Grout Seal

Sample submitted to lab
Factory—Slotted
Well Screen Well Casing



2735 VILLA CREEK DRIVE - TWO METRO SQUARE BLDQ. C - SUITE 250 - DALLAS, TX 75234 620-7117 FAX - 620-8219

### RECORD OF SUBSURFACE EXPLORATION

6	20-7117 . FAX - 620-8219					
Project	No.: 15-93677	Well/Bor	ing#: м	w-8		Date Drilled: 09/22/93
Project:	LEA STATION LEA COUNTY, NEW MEXICO	Depth o	f Boring:	40 FEET		Diameter of Boring: 8 INCHES
TTOJECT	-	Depth of	f Well: 38	FEET		Diameter of Screen: 4 INCHES
Drilling C	CO: HI PLAINS DRILLING	Length	of Screen	F 15 FEET	Diameter of Casing: 4 INCHES	
Driller: B.	S.	Length (	of Casing:	23 FEET		Slot Size: 0.02 INCH
Drilling N	Method: AIR ROTARY	Logged	l B <b>y</b> : f.w.f	١.		Well Material: sch 40 pvc
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS
— 30.0 - - -	Gray & red-brown mottled calcareous SAND (caliche)					30.0—
_ 32.5 _ _ -						32.5—
35.0 						35.0— -
37.5 _ _ _ _	Bottom of boring @ 38.0 feet					37.5—
						40.0 <del>-</del>  
- 						42.5
45.0 -						45.0—
- - - 47.5		] ]				47.5—
- - 50.0 - -			i		<u> </u>	50.0—
- - - 52.5 -						- 52.5 -
- - 55.0 -						55.0 —
- - 57.5 -						57.5 —
60.0				· 		60.0
	Salit Sacra					=

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND SYMBOLS

HSA-Hollow Stem Augers
CFA-Continuous Flight Augers
DC-Driving Casing
MD-Mud Drilling

Water on Rods

Sand Pack Bentonite Seal Volclay Grout Seal

Sample submitted to lab
Bottom Cap Factory—Slotted
Well Screen Well Casing



2735 VILLA CREEK DRIVE - TWO METRO SQUARE BLDQ C - SUTTE 250 - DALLAS, TX 75234 620-7117 FAX - 620-8219

### RECORD OF SUBSURFACE EXPLORATION

6	620-7117 . FAX - 620-8219				···········			
Project	No.: 15-93677	Well/Bor	ing‡∺ м	W-9		Date Drilled: 09/22/93		
Project:	LEA STATION LEA COUNTY, NEW MEXICO	Depth o	f Boring:	38 FEET		Diameter of Boring: 8 INCHES		
1 TOJECE		Depth of	f <b>Wel</b> l: 38	FEET		Diameter of Screen: 4 INCHES		
Drilling (	CO: HI PLAINS DRILLING	Length (	of Screer	F 15 FEET		Diameter of Casing: 4 INCHES		
Driller: B.	.S.	Length	of Casing	23 FEET		Slot Size: 0.02 INCH		
Drilling I	Method: AIR ROTARY	Logged By: F.W.R.				Well Material: sch 40 pvc		
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS		
— o - - -	Light—brown fine to medium—grained slightly calcareous SAND (SM)	}   				o —		
2.5   			į			2.5—		
5.0  		1	ss	<1		5.0— 		
7.5 - - -						7.5— - - - -		
10.0		2	SS	<1		10.0—		
12.5						12.5		
15.0  -  -  -  -		3	SS	1		15.0— Benzene <0.001 mg/kg BTEX=0.005 mg/kg TPH=60 mg/kg		
17.5 						17.5		
20.0 		4	SS	<1		20.0		
- 						22.5		
- 25.0  	Gray-green sandy CLAY (CL)	5	SS	20		25.0 — Benzene=<0.001 mg/kg BTEX=0.001 mg/kg TPH=30 mg/kg		
_ 27.5  	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \					Vwater @ 26' 27.5 —		
- 30.0 -				·		30.0		
-		<u> </u>	<u> </u>	<u> </u>				

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND SYMBOLS HSA-Hollow Stem Augers
CFA-Continuous Flight Augers
DC-Driving Casing
MD-Mud Drilling

Sample submitted to lab
Bottom Cap Factory—Slotted
Well Screen Well Casing Sand Pack Bentonite Seal Wolclay Grout Seal



2735 VILLA CREEK DRIVE - TWO METRO SQUARE BLDG. C - SUITE 250 - DALLAS, TX 75234 620-7117 FAX - 620-8219

### RECORD OF SUBSURFACE EXPLORATION

6	20-7117 FAX - 620-8219					
Project	No.: 15-93677	Well/Bot	ing #: м	W-9		Date Drilled: 09/22/93
Project	LEA STATION LEA COUNTY, NEW MEXICO	Depth o	f Boring:	38 FEET		Diameter of Boring: 8 INCHES
Project	- MEN MENTO	Depth o	f Well: 38	FEET	Diameter of Screen: 4 INCHES	
Drilling C	O: HI PLAINS DRILLING	Length	of Screen	F 15 FEET	Diameter of Casing: 4 INCHES	
Driller: B.	s.	Length	of Casing:	23 FEET		Slot Size: 0.02 INCH
Drilling N	Method: AIR ROTARY	Logged	By: F.W.F	ł.		Well Material: sch 40 pvc
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS
— 30.0 –	Gray-green sandy CLAY (CL)	-				30.0—
_ _ _ 32.5						32.5—
- - -						52.3 - -
- 35.0 -						35.0
_ _ _ _ 37.5						37.5—
	Bottom of boring @ 38.0 feet					37.5 - -
40.0						40.0 —
- - - - 42.5					!	42.5
- 42.5						42.5
_ 45.0 _						45.0 <del>-</del>
_ _ 47.5						47.5—
- 47.3 -				,		47.5
- 50.0						50.0 -
_ _ _ 52.5						52.5 —
<b>E 1</b>						=
_ 55.0 _						55.0 —
_ _ 57.5						57.5 —
£ ,,,,					 	37.3
- 60.0				·		60.0
<u> </u>		<u> </u>				

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND SYMBOLS HSA-Hollow Stern Augers
CFA-Continuous Flight Augers
DC-Driving Casing
MD-Mud Drilling

• Water on Rods Bentonite Seal Wolclay Grout Seal

Sample submitted to lab
Bottom Cap Factory—Slotted
Well Screen Sand Pack Well Casing



2735 VILLA CREEK DRIVE - TWO METRO SQUARE BLDQ. C - SUITE 250 - DALLAS, TX 75234 620-7117 FAX - 620-8219

## RECORD OF SUBSURFACE EXPLORATION

6	20-7117 FAX - 620-8219							
Project	No.: 15-93677	Well/Bor	ing #: м	W-10		Date Drilled: 09/23/93		
Project	LEA STATION LEA COUNTY, NEW MEXICO	Depth o	f Boring:	38 FEET		Diameter of Boring: 8 INCHES		
Troject	-	Depth of	f <b>Wel</b> l: 38 ≀	FEET	Diameter of Screen: 4 INCHES			
Drilling C	CO: HI PLAINS DRILLING	Length	of Screen	15 FEET		Diameter of Casing: 4 INCHES		
Driller: B.	S.	Length (	of Casing:	23 FEET		Slot Size: 0.02 INCH		
Drilling N	Method: AIR ROTARY	Logged	l By: f.w.r	l.		Well Material sch 40 pvc		
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS		
o	Brown fine—grained SAND (SM)					0		
_					<u>ĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦĦ</u>	3		
2.5						2.5		
E						]		
- 5.0						5.0		
_	Light—brown fine to medium—grained slightly calcareous SAND (SM)	1	ss	1		Benzene <0.001 mg/kg = BTEX=0.008 mg/kg		
F	slightly calcareous SAND (SM)		<b>.</b>			TPH <10 mg/kg		
7.5 -			į	ı		7.5		
F		ŀ				=		
10.0						10.0		
E		2	ss	<1		3		
- 12.5						 12.5		
						12.3		
-						1		
15.0 _					KICKKITCKKICKKICKKICKKICKKICKKICKKICKKIC	15.0 —		
F		3	SS	<1		] ]		
17.5						17.5—		
E						] ]		
20.0						]		
£ 20.0		4	ss	<1		20.0—		
E				` '		E		
22.5 						22.5		
E		[				-		
25.0			<b></b>			25.0 —		
F		5	ss	<1				
_ 27.5			<del> </del>			=		
E 27.3			1			27.5 — —		
E			1			\ \ \ \ \ \		
30.0		1		·		30.0		
E		1	Ì					
SS-Driven	Split Spoon ADDDEVIATION	1	<u> </u>	<u> </u>		Sample submitted to lab		

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND SYMBOLS

HSA-Hollow Stem Augers
CFA-Continuous Flight Augers
DC-Driving Casing
MD-Mud Drilling

Water on Rods Sample submitted to lab
Bottom Cap Factory—Slotted
Well Screen Well Casing Bentonite Seal Wolclay Grout Seal



2735 VILLA CREEK DRIVE - TWO METRO SQUARE BLDG. C - SUITE 250 - DALLAS, TX 75234 620-7117 FAX - 620-8219

### RECORD OF SUBSURFACE EXPLORATION

6	520-7117 FAX - 620-8219					
Project	No.: 15-93677	Well/Bo	ring #: м	W-10		Date Drilled: 09/23/93
Project	LEA STATION LEA COUNTY, NEW MEXICO	Depth o	f Boring:	38 FEET		Diameter of Boring: 8 INCHES
TTOJECE	-	Depth o	f Well: 38	FEET		Diameter of Screen: 4 INCHES
Drilling (	Co: HI PLAINS DRILLING	Length	of Screer	F 15 FEET	Diameter of Casing: 4 INCHES	
Driller: 8.	.s.	Length	of Casing	23 FEET		Slot Size: 0.02 INCH
Drilling N	Method: AIR ROTARY	Logged By: F.W.R.				Well Material: sch 40 PVC
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS
	Brown—green fine—grained slightly calcareous SAND (SM)	1			DESIGN	REMARKS  30.0— Benzene <0.001 mg/kg
52.5 						52.5   55.0
- - 57.5 - -						57.5 —
- 60.0 - - -						60.0

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND SYMBOLS HSA-Hollow Stem Augers
CFA-Continuous Flight Augers
DC-Driving Casing
MD-Mud Drilling

• Water on Rods Sample submitted to lab
Factory—Slotted
Well Screen Sand Pack Well Casing

Bentonite Seal Volclay Grout Seal



2735 VILLA CREEK DRIVE - TWO METRO SQUARE BLDG. C - SUITE 250 - DALLAS, TX 75234 620-7117 FAX - 620-8219

## RECORD OF SUBSURFACE EXPLORATION

0	20-7117 FAX - 620-8219							
Project	No.: 15-93677	Well/Bor	ing #: M	W-11		Date Drilled: 09/23/93		
Project:	LEA STATION LEA COUNTY, NEW MEXICO	Depth o	f Boring:	38 FEET		Diameter of Boring: 8 INCHES		
1 TOJECT	-	Depth of	f Well: 38	FEET		Diameter of Screen: 4 INCHES		
Drilling C	O: HI PLAINS DRILLING	Length o	of Screer	F 15 FEET	Diameter of Casing: 4	INCHES		
Driller: в.	S.	Length o	of Casing:	23 FEET		Slot Size: 0.02 INCH		
Drilling N	Method: AIR ROTARY	Logged	By: F.W.F	₹.		Well Material sch 40 pv	С	
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS		
0    	Brown fine-grained SAND (SM)						0-	
2.5    5.0	Buff-white calcareous SAND (caliche)						2.5	
- - - - - 7.5		1	SS	4			7.5	
- - - 10.0	Block-gray medium-grained SAND (SM) heavy hydrocarbon staining and	2	SS	600		Benzene <0.001 mg/k BTEX=6.66 mg/kg	10.0 - g -	
 12.5 	odor to total depth		33			TPH=5,900 mg/kg	12.5	
15.0 15.0		3	SS	>1000			15.0	
- 17.5 - -	Green medium-grained slightly calcareous SAND (SM)				ARIORALICHORALICHURIANIANIANIANIANIANIANIANIANIANIANIANIANI		17.5— - - -	
— 20.0 - -		4	SS	>1000		Benzene=970 mg/kg BTEX=130.27 mg/kg TPH=1,100 mg/kg	20.0	
22.5 - - - -	Blue-gray calcareous fine-grain SAND						22.5 — - - -	
25.0   	(caliche)	5	ss	>1000			25.0 — - - -	
27.5 _ _ _ _ _						χ.	27.5 —	
30.0  							30.0	
SS-Driven	Split Spoon ARREVIATION	6 4116	014.400			Sample submitted to lo		

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND SYMBOLS
HSA-Hollow Stem Augers
CFA-Continuous Flight Augers

At Comp

HSA-Hollow Stem Augers
CFA-Continuous Flight Augers
DC-Driving Casing
MD-Mud Drilling

 Sample submitted to lab
Factory—Slotted
Well Screen
Sand Pack Well Casing
Bentonite Seal



2735 VILLA CREEK DRIVE - TWO METRO SOUARE BLDQ. C - SUITE 250 - DALLAS, TX 75234 620-7117 FAX - 620-8219

# RECORD OF SUBSURFACE EXPLORATION

6	20-7117 FAX - 620-8219						
Project	No.: 15-93677	Well/Bor	ing#: M	W-11		Date Drilled: 09/23/93	
Project:	LEA STATION LEA COUNTY, NEW MEXICO	Depth o	f Boring:	38 FEET		Diameter of Boring: 8 INCHES	
TTOJECE		Depth o	f Well: 38	FEET	Diameter of Screen:	INCHES	
Drilling C	CO: HI PLAINS DRILLING	Length	of Scree	ን 15 FEET	Diameter of Casing: 4	INCHES	
Driller: B	.S.	Length	of Casing	23 FEET		Slot Size: 0.02 INCH	
Drilling I	Method: AIR ROTARY	Logged	By: F.W.	R.		Well Material: sch 40 pv	С
DEPTH FEET	SOIL DESCRIPTION	SAMPLE NUMBER	SAMPLE TYPE	OVA (PPM)	WELL DESIGN	REMARKS	
30.0  	Blue—gray calcareous fine—grained SAND (caliche)	6	SS	>1000		Benzene=0.01 mg/kg BTEX=0.142 mg/kg TPH=370 mg/kg	30.0
32.5 - - - -						TPH=370 mg/kg ∨Water @ 31'	32.5
35.0 - - - -							35.0— - - -
37.5  	Bottom of boring @ 38.0 feet						37.5— - - -
- 40.0  -							40.0
- 42.5 - -							42.5
- 45.0 - -							45.0 — - -
- 47.5 - -							47.5—
- 50.0 - -							50.0 <del>-</del>
_ 52.5 _ _ _							52.5
55.0 5							55.0
57.5 57.5 							57.5 — -
- 60.0 -	·						60.0 — -

SS-Driven Split Spoon
ST-Pressed Shelby Tube
CA-Continuous Flight Auger
RC-Rock Core
THD-Texas Highway Department Cone
CT-5' Continuous Sampler

ABBREVIATIONS AND SYMBOLS
HSA-Hollow Stem Augers WATER LEV

HSA-Hollow Stern Augers CFA-Continuous Flight Augers DC-Driving Casing MD-Mud Drilling

 Sample submitted to lab
Bottom Cap Factory—Slotted
Well Screen

Sand Pack Well Casing

Bentonite Seal Volctoy Grout Seal

# APPENDIX C TABLES

TABLE 1 SOIL SAMPLE ANALYTICAL RESULTS													
Boring	Date Sampled	Sample Interval (feet)	OVA	Benzene	Toluene	Ethyl- benzene	Xylenes	Total BTEX	ТРН				
B-1	12-08-92	1 - 3	2	<u>-</u>									
	i	5 - 7	5	0.001	0.002	0.002	0.005	0.010	15				
		9 - 11	<1										
		15 - 17	<1	< 0.001	0.012	0.017	0.050	0.079	24				
B-2	12-08-92	1 - 3	>1000										
	i	5 - 7	>1000	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	9,400				
		10 - 12	>1000	·									
		15 - 17	11	< 0.001	0.004	< 0.001	0.002	0.006	19				
		20 - 22	7										
		25 - 27	<1	< 0.001	0.002	< 0.001	0.003	0.005	13				
B-3	12-08-92	1 - 3	8										
		5 - 7	12	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	31				
		10 - 12	1		<u> </u>								
		15 - 17	<1	< 0.001	0.003	0.001	0.006	0.010	20				
B-4	12-08-92	1 - 3	300		]								
		3 - 5	800	<0.001	< 0.001	< 0.001	< 0.001	< 0.001	14,000				
		10 - 12	>1000	< 0.001	< 0.001	< 0.001	0.940	0.940	9,200				
		15 - 17	>1000										
		20 - 22	200										
		25 - 27	>1000	< 0.001	< 0.001	< 0.001	0.460	0.460	2,700				
B-5	12-09-92	3 - 5	5	0.001	0.002	0.011	0.021	0.035	1,700				
		5 - 7	<1				 						
		8 - 10	<1	< 0.001	< 0.001	< 0.001	< 0.001	<0.001	15				
B-6	12-09-92	1 - 3	8										
		3 - 5	<1	<0.001	0.003	< 0.001	0.004	0.007	47				
B-7	12-09-92	1 - 3	8										
		5 - 7	<1										
		10 - 12	<1	<0.001	0.003	< 0.001	0.004	0.007	14				

			SOIL SAM	TABL PLE ANAL		ESULTS			
Boring	Date Sampled	Sample Interval (feet)	OVA	Benzene	Toluene	Ethyl- benzene	Xylenes	Total BTEX	TPH
B-8	02-01-93	1 - 3	6	< 0.001	< 0.001	0.053	0.031	0.084	9,100
		5 - 7	50						
		10 - 12	900						
		15 - 17	>1,000	< 0.001	< 0.001	14.000	6.300	20.300	7,300
		20 - 22	600						
		25 - 27	>1,000	< 0.001	<0.001	13.000	17.000	30.000	10,000
		30 - 32	12						
<b>B</b> -9	02-01-93	1 - 3							
		5 - 7	<1	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	110
	}	10 - 12	<1		<u></u>				
		15 - 17	<1						
		20 - 22	<1	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	20
B-10	02-01-93	1 - 3	<1						
		5 - 7	11	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	20
		10 - 12	<1						
		15 - 17	<1					 	
		20 - 22	<1	< 0.001	<0.001	< 0.001	< 0.001	< 0.001	10
B-11	02-03-93	1 - 3	<1						
		5 - 7	30	< 0.001	0.100	1.500	4.100	5.700	4,900
		10 - 12	900						
		15 - 17	>1,000	< 0.001	< 0.001	25.000	16.000	41.000	13,000
		20 - 22	>1,000						
		25 - 27	>1,000	< 0.001	< 0.001	12.000	8.700	20.700	11,000
B-12	02-04-93	1 - 3	<1						
		5 - 7	<1	< 0.001	< 0.001	< 0.001	0.001	0.001	20
į.		10 - 12	<1						
		15 - 17	<1						
		20 - 22	<1	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	10
B-13	09-22-93	5 - 7	<1	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	20
		10 - 12	<1						
		15 - 17	<1					\	
		20 - 22	<1						
		25 - 27	21	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	20

TABLE 1 SOIL SAMPLE ANALYTICAL RESULTS												
	Date	Sample Interval				Ethyl-	•	Total				
Boring B-14	Sampled 09-22-93	(feet) 5 - 7	OVA 10	<b>Benzene</b> < 0.001	Toluene 0.001	benzene 0.001	Xylenes 0.005	8TEX 0.007	<b>TPH</b> 10			
D-14	09-22-93	10 - 12	<1	<b>\0.001</b>	0.001	0.001	0.003	0.007	10			
		15 - 17	4		!							
		20 - 22	5									
		25 - 27	21	< 0.001	0.002	< 0.001	0.001	0.003	20			
B-15	09-23-93	5 - 7	<1	70,002		10.002	0.002	0,000				
· -		10 - 12	<1									
		15 - 17	1	< 0.001	< 0.001	0.001	0.003	0.004	50			
		20 - 22	1									
		25 - 27	<1									
		30 - 32	700	< 0.001	< 0.001	0.012	0.021	0.033	1,200			
B-16	09-23-93	5 - 7	<1									
		10 - 12	<1	< 0.001	< 0.001	< 0.001	0.001	0.001	<10			
		15 - 17	<1									
		20 - 22	<1									
		25 - 37	<1	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	<10			
MW-1	12-08-92	1 - 3	700	< 0.001	< 0.001	7.100	8.500	15.600	8,600			
		5 - 7	110									
		10 - 12	21	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	19			
		15 - 17	20									
		20 - 22	25									
	,	25 - 27	70	< 0.001	0.002	0.048	0.004	0.054	58			
	ĺ	30 - 32	5									
		35 - 37	1									
MW-2	02-01-93	1 - 3	<1	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	150			
		5 - 7	<1									
		10 - 12	<1	<0.001	< 0.001	< 0.001	_<0.001	< 0.001	30			
i		15 - 17	<1	_								
		20 - 22	<1									
		25 - 27	>1,000	< 0.001	< 0.001	6.200	2.800	9.000	6,300			

	TABLE 1 SOIL SAMPLE ANALYTICAL RESULTS												
Boring	Date Sampled	Sample Interval (feet)	OVA	Велгеле	Toluene	Ethyl- benzene	Xylenes	Total BTEX	ТРН				
MW-3	02-02-93	1 - 3	<1	< 0.001	< 0.001	< 0.001	0.001	0.001	20				
		5 - 7	<1				1						
		10 - 12	<1	<0.001	< 0.001	< 0.001	0.001	0.001	10				
		15 - 17	<1										
		20 - 22	1	< 0.001	0.001	0.002	0.006	0.009	20				
		25 - 27	No Recov	ery									
		27 - 30	60										
MW-4	02-02-93	1 - 3	<1	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	700				
i i		5 - 7	200										
		10 - 12	400	< 0.001	0.140	0.085	0.420	0.645	1,600				
		15 - 17	4										
		20 - 22	<1										
		25 - 27	<1	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	20				
MW-5	02-01-93	1 - 3	2	< 0.001	0.014	0.140	0.340	0.494	8,900				
		5 - 7	80										
		10 - 12	100										
		15 - 17	500										
		20 - 22	600	< 0.001	< 0.001	6.200	0.710	6.910	15,000				
		25 - 27	400	< 0.001	< 0.001	5.900	3.500	9.400	10,000				
MW-6	02-02-93	1 - 3	2	< 0.001	< 0.001	< 0.001	0.001	0.001	20				
		5 - 7	<1										
		10 - 12	<1										
		15 - 17	<1	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	20				
		20 - 22	<1										
		25 - 26	200										
		26 - 27	20	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	10				
MW-7	02-03-93	1 - 3	1										
		5 - 7	<1	< 0.001	< 0.001	< 0.001	0.002	0.002	40				
	i	10 - 12	<1										
		15 - 17	<1										
		20 - 22	1	< 0.001	< 0.001	< 0.001	0.001	0.001	20				

	TABLE 1 SOIL SAMPLE ANALYTICAL RESULTS												
Boring	Date Sampled	Sample Interval (feet)	OVA	Benzene	Toluene	Ethyl- benzene	Xylenes	Total BTEX	TPH				
MW-8	09-22-93	5 - 7	4										
		10 - 12	200	< 0.001				0.090	3,300				
		15 - 17	90										
		20 - 22	11										
		25 - 27	<1,000	0.036				1.326	1,400				
MW-9	09-22-93	5 - 7	<1										
		10 - 12	<1					_					
		15 - 17	1	< 0.001	< 0.001	0.001	0.004	0.005	60				
		20 - 22	<1										
		25 - 27	20	< 0.001	< 0.001	< 0.001	0.001	0.001	30				
MW-10	09-23-93	5 - 7	1	< 0.001	0.001	0.001	0.006	0.008	<10				
		10 - 12	<1										
		15 - 17	<1										
		20 - 22	<1										
		25 - 27	<1										
		30 - 32	2	< 0.001	< 0.001	< 0.001	0.001	0.001	20				
MW-11	09-23-93	5 - 7	4										
		10 - 12	600	< 0.001	0.160	4.700	1.800	6.660	5,900				
		15 - 17	<1,000										
		20 - 22	<1,000	0.970	2.300	45.000	82.000	130.270	1,100				
		25 - 27	<1,000						<u>, ,</u>				
		30 - 32	<1,000	0.010	0.023	0.045	0.064	0.142	370				

OVA results listed in parts per million (ppm) equivalent methane.
BTEX results in mg/kg (parts per million; ppm) method detection limit listed in appendix D.
TPH results in mg/kg (parts per million; ppm) method detection limit listed in appendix D.
Analyses were conducted using EPA Method 8020 (BTEX) and EPA Method 418.1 (TPH) by SPL Environmental Laboratories.

#### TABLE 2 SUMMARY OF RELATIVE GROUNDWATER LEVEL ELEVATIONS AND PHASE-SEPARATED HYDROCARBON THICKNESSES

Groundwater Elevations Obtained September 28, 1993

Monitor Well	Relative Ground Surface Elevation (feet)	Relative Top of Casing Elevation (feet)*	Depth to Water Below Top of Casing (feet)	Corrected Relative Groundwater Elevation (feet)**	Phase- Separated Hydrocarbon Thickness (feet)
MW-1	98.88	100.73	29.18	71.55	0.00
MW-2	100.78	102.37	30.23	72.14	0.00
MW-3	101.79	103.61	30.04	73.57	0.00
MW-4	93.80	96.08	26.12	69.96	0.00
MW-5	107.08	109.21	30.42	78.79	0.00
MW-6	103.66	106.26	29.96	76.30	0.00
MW-7	104.34	106.27	30.65	75.62	0.00
MW-8	105.52	107.44	32.81	76.63	0.04
MW-9	93.76	97.21	28.60	68.61	0.00
MW-10	99.63	102.51	34.11	68.40	0.00
MW-11	104.48	105.62	31.38	74.24	0.00

<sup>\*</sup> Measured from a relative datum (benchmark = 100.00 feet). The monitor well casings were marked to provide consistent reference points for future gauging operations.

<sup>\*\*</sup> Correction Equation for Phase-Separated Hydrocarbons: Corrected Groundwater Elevation = Top of Casing Elevation - (Depth to Water Below Top of Casing - [SG] [PSH Thickness]) Specific Gravity (SG) = 0.73 for gasoline, 0.85 for diesel, 0.9 for crude oil.

## TABLE 3 WATER SAMPLE ANALYTICAL RESULTS

Monitor Well	Date	Benzene	Toluene	Ethyl- benzene	Xylenes	Total BTEX	TPH	TDS
WW-1	12-08-92	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	5	1,800
MW-1	12-21-92	0.440	0.005	0.120	0.063	0.628	3	2,380
MW-1	02-16-93	0.350	0.010	0.095	0.070	0.525	5	
MW-2	02-16-93	0.370	0.040	0.210	0.510	1.130	1	
MW-3	02-16-93	2.500	0.010	0.370	0.640	3.520	2	
MW-4	02-16-93	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	<1	
MW-5	02-16-93	< 0.001	< 0.001	0.002	0.004	0.006	<1	
MW-6	02-16-93	0.002	0.001	< 0.001	0.091	0.094	<1	2,500
MW-7	02-16-93	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	<1	
MW-8	09-30-93	PSH		,				
MW-9	09-30-93	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	<1	2,130
MW-10	09-30-93	< 0.001	< 0.001	< 0.009	0.001	0.01	7	
MW-11	09-30-93	0.24	0.14	0.11	0.14	0.63	3	

BTEX results listed in m/l (parts per million; ppm) with a method detection limit of 0.001 ppm. TPH and TDS results listed in mg/l (parts per million; ppm) with a method detection limit of 1 ppm. Analyses were conducted using EPA Method 8020 (BTEX), EPA Method 418.1 (TPH), and EPA Method 160.1 (TDS) by SPL Environmental Laboratories.

# APPENDIX D ANALYTICAL RESULTS



SPL, INC.

### REPORT APPROVAL SHEET

WORK ORDER NUMBER: 93-09-960

Approved for release by:

M. Most Muncle Date: 40/6/9: S. Sample, Laboratory Director

Ed Fry, Project Manager

Date: 6/6/93



\*\*\*\*SUMMARY REPORT\*\*\*\*

10/06/93

Company:

Shell Pipe Line Corporation

Site:

Lea County, New Mexico

Project No:

15-93677.3

Project:

Lea Station

ANALYTICAL DATA NOTE: ND - Not Detected

SPL ID MATRIX	CLIENT ID DATE SAMPLED	BENZENE PQL	TOLUENE PQL	ETHYLBENZ. PQL	XYLENE PQL	TPH-IR	TPH-GC	LEAD	MTBE
9309960-01 SOIL	B-13 (5-7) 09/22/93 09:25:00	ND 0.0050mg//≤	ND 0.0050mg	ND 0.0050mg	ND 0.0050mg/ <sub>2</sub>	20 10mg/Kg			,
9309960-02 SOIL	B-13 (25-27) 09/22/93 10:00:00	ND 0.0010mg/s	ND 0.0010mg/kg	ND 0.0010mg/kg	ND 0.0010mg/kg	20 10mg/Kg			
9309960-03 SOIL	MW-8 (10-12) 09/22/93 10:45:00	ND 0.0010mg/kg	ND 0.0010mg√s	ND 0.0010mg	0.012 0.0010mg	3000 20mg/Kg			
9309960-04 SOIL	MW-8 (25-27) 09/22/93 11:15:00	0.036 0.010mg/k <sub>y</sub>	0.20 0.010mg/kg	0.54 0.010mg/k	0.55 0.010mg/kg	1400 10mg/Kg			
9309960-05 SOIL	B-14 (5-7) 09/22/93 14:05:00	ND 0.0010mg/	0.0010 0.0010mg// <sub>5</sub>	0.0010 0.0010mg/4	0.0050 0.0010mg/s	10 10mg/Kg			
9309960-06 SOIL	B-14 (25-27) 09/22/93 14:40:00	ND 0.0010mg/ <sub>2</sub>	0.0020 0.0010mg/s	ND 0.0010mg/ <sub>S</sub>	0.0010 0.0010mg/	20 10mg/Kg			
9309960-07 SOIL	MW-9 (15-17) 09/22/93 16:00:00	ND 0.0010mg/s	ND 0.0010mg	0.0010 0.0010mg/K	0.0040 0.0010mg/s	60 10mg/Kg			
9309960-08 SOIL	MW-9 (25-27) 09/22/93 16:20:00	ND 0.0010mg/s	ND 0.0010mg&	ND 0.0010mg/	ND 0.0010mg/y	10 10mg/Kg			
9309960-09 SOIL	MW-10 (5-7) 09/23/93 09:55:00	ND 0.0010mg俟	0.0010 0.0010mg/ <b>/</b>	0.0010	0.0060	ND 10mg/Kg			
9309960-10 SOIL	MW-10 (31-32) 09/23/93 10:30:00	ND 0.0010mg/s	ND 0.0010mg/≰	ND 0.0010mg/g	0.0010 0.0010mg	20 10mg/Kg			,

METHOD 5030/8020 \*\*\* TPH-IR - METHOD Mod. 418.1\*



#### \*\*\*\*SUMMARY REPORT\*\*\*\*

10/06/93

Company:

Shell Pipe Line Corporation Lea County, New Mexico 15-93677.3

Site:

Project No: Project: Lea Station

> ANALYTICAL DATA NOTE: ND - Not Detected

SPL ID MATRIX	CLIENT ID DATE SAMPLED	BENZENE PQL	TOLUENE PQL	ETHYLBENZ. PQL	XYLENE PQL	TPH-IR	TPH-GC	LEAD	MTBE
9309960-11 \$01L	8-15 (15-17) 09/23/93 13:00:00	ND 0.0010mg	ND 0.0010mg/	0.0010 0.0010mg/	0.0030 0.0010mg/s	50 10mg/Kg			,
9309960-12 SOIL	B-15 (30-32) 09/23/93 13:20:00	ND 0.010mg/kg	ND 0.010mg/	0.012 0.010mg/kg	0.021 0.010mg/k	1200 10mg/Kg			,
9309960-13 SOIL	MW-11 (10-12) 09/23/93 14:20:00	NO 0.050mg/kg	0.16 0.050mg/\$	4.7 0.050mg/kg	1.8 0.050mg/kg	5900 50mg/Kg			
9309960-14 SOIL	MW-11 (20-22) 09/23/93 14:40:00	0.97 0.25mg/kg	2.3 0.25mg/kg	45 0.25mg/kg	82 0.25mg/kg	1100 10mg/Kg			
9309960-15 SOIL	MW-11 (30-32) 09/23/93 15:00:00	0.010 0.010mg/k	0.023 0.010mg/kg	0.045 0.010mg/kg	0.064 0.010mg/kg	370 10mg/Kg			
9309960-16 SOIL	B-16 (10-12) 09/23/93 17:20:00	ND 0.0010mg/ <sub>s</sub>	ND 0.0010mg/	ND 0.0010mg俟	0.0010 0.0010mg <b>/</b>	ND 10mg/Kg			
9309960-17 SOIL	B-16 (25-27) 09/23/93 17:48:00	ND 0.0010mg/	ND 0.0010mg/kg	ND 0.0010mg/	ND 0.0010mg/ <sub>S</sub>	ND 10mg/Kg			
9309960-18 SOIL	MW-8 (10-12) << DUP 09/22/93 10:45:00	NO 0.010mg/kg	0.018 0.010mg/k	NO 0.010mg/kg	0.072 0.010mg/kg	3300 20mg/Kg			
9309960-19 \$01L	MW-9 (25-27) << DUP 09/22/93 16:20:00	ND 0.0010mg/ <sub>s</sub>	ND 0.0010mg//⊊	ND 0.0010mg/上	0.0010 0.0010mg/	30 10mg/Kg			

BTEX - METHOD 5030/8020 \*\*\*
TPH-IR - METHOD Mod. 418.1\*

SPL, Inc., - Shari L.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.# CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc.

**SAMPLE ID:** B-13 (5-7)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/22/93 09:25:00

DATE RECEIVED: 09/29/93

						<del></del>
	ANALYTICAL	DATA				
PARAMETER			RESULTS	DET	ECTION	UNITS
				LIM	IT	
BENZENE			ND	0.0050	P	mg/kg
TOLUENE			ND	0.0050	P	mg/kg
ETHYLBENZENE			ND	0.0050	P	mg/kg
TOTAL XYLENE			ИD	0.0050	P	mg/kg
TOTAL BTEX			ND			mg/kg
METHOD 5030/8020 ***						
Analyzed by: KA						
Date: 10/02/93						
V						
Petroleum Extractables			20		10	mg/Kg
METHOD Mod. 418.1*	•					
Analyzed by: AR						
Date: 09/30/93						

ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA

\*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.# CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc.

**SAMPLE ID:** B-13 (25-27)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/22/93 10:00:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA				
PARAMETER			RESULTS	DET	ECTION	UNITS
				LIM	ΓT	
BENZENE			ND	0.0010	P	mg/kg
TOLUENE			ND	0.0010	P	mg/kg
ETHYLBENZENE			ND	0.0010	P	mg/kg
TOTAL XYLENE			ND	0.0010	P	mg/kg
TOTAL BTEX			ND			mg/kg
METHOD 5030/8020 ***						
Analyzed by: KA						
Date: 09/30/93						
Petroleum Extractables			20		10	mg/Kg
METHOD Mod. 418.1*						J. J
Analyzed by: AR						
Date: 09/30/93						

#### ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA

\*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.

\*\*\*Ref: Test Methods for Evaluating Solid Waste, EPA SW846, 3rd Ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: MW-8 (10-12)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/22/93 10:45:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA				
PARAMETER			RESULTS	DET:	ECTION IT	UNITS
BENZENE			ND	0.0010	P	mg/kg
TOLUENE			ND	0.0010	P	mg/kg
ETHYLBENZENE			ND	0.0010	P	mg/kg
TOTAL XYLENE			0.012	0.0010	P	mg/kg
TOTAL BTEX			0.012			mg/kg
METHOD 5030/8020 ***						
Analyzed by: KA						
Date: 10/01/93						
Petroleum Extractables			3000		20	mg/Kg
METHOD Mod. 418.1*						
Analyzed by: AR						
Date: 09/30/93						

ND - Not detected.

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA

\*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.

\*\*\*Ref: Test Methods for Evaluating Solid Waste, EPA SW846, 3rd Ed.

<sup>(</sup>P) - Practical Quantitation Limit



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. **SAMPLE ID:** MW-8 (25-27) PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/22/93 11:15:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA		
PARAMETER		RESULTS	DETECTION	UNITS
			LIMIT	
BENZENE		0.036	0.010 P	mg/kg
TOLUENE		0.20	0.010 P	mg/kg
ETHYLBENZENE		0.54	0.010 P	mg/kg
TOTAL XYLENE		0.55	0.010 P	mg/kg
TOTAL BTEX		1.326		mg/kg
METHOD 5030/8020 ***				
Analyzed by: KA				
Date: 10/02/93				
Petroleum Extractables		1400	10	mg/Kg
METHOD Mod. 418.1*				37 3
Analyzed by: AR				
Date: 09/30/93				

#### (P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA

\*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.

\*\*\*Ref: Test Methods for Evaluating Solid Waste, EPA SW846, 3rd Ed.

QUALITY ASSURANCE: These analyses are performed in accordance with EPA guidelines for quality assurance.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: B-14 (5-7)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/22/93 14:05:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA		
PARAMETER		RESULTS	DETECTION	UNITS
			LIMIT	
BENZENE		ND	0.0010 P	mg/kg
TOLUENE		0.0010	0.0010 P	mg/kg
ETHYLBENZENE		0.0010	0.0010 P	mg/kg
TOTAL XYLENE		0.0050	0.0010 P	mg/kg
TOTAL BTEX		0.007		mg/kg
METHOD 5030/8020 ***				
Analyzed by: KA				
Date: 10/01/93				
,				
Petroleum Extractables		10	10	mg/Kg
METHOD Mod. 418.1*	•			3. 3
Analyzed by: AR				
Date: 09/30/93				

#### ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: B-14 (25-27)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/22/93 14:40:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA			
PARAMETER		RESULTS	DETI	ECTION	UNITS
			LIM	[T	
BENZENE		ND	0.0010	P	mg/kg
TOLUENE		0.0020	0.0010	P	mg/kg
ETHYLBENZENE		ND	0.0010	P	mg/kg
TOTAL XYLENE		0.0010	0.0010	P	mg/kg
TOTAL BTEX		0.003			mg/kg
METHOD 5030/8020 ***					
Analyzed by: KA					
Date: 10/02/93					
Petroleum Extractables		20	:	10	mg/Ko
METHOD Mod. 418.1*					
Analyzed by: AR					
Date: 09/30/93					

ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA

\*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.

\*\*\*Ref: Test Methods for Evaluating Solid Waste, EPA SW846, 3rd Ed.

QUALITY ASSURANCE: These analyses are performed in accordance with EPA guidelines for quality assurance.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: MW-9 (15-17)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/22/93 16:00:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA		
PARAMETER		RESULTS	DETECTION	UNITS
			LIMIT	
BENZENE		ND	0.0010 P	mg/kg
TOLUENE		ND	0.0010 P	mg/kg
ETHYLBENZENE		0.0010	0.0010 P	mg/kg
TOTAL XYLENE		0.0040	0.0010 P	mg/kg
TOTAL BTEX		0.005		mg/kg
METHOD 5030/8020 ***				
Analyzed by: KA				
Date: 09/30/93				
Petroleum Extractables		60	10	mg/Ko
METHOD Mod. 418.1*				
Analyzed by: AR				
Date: 09/30/93				

ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.

\*\*\*Ref: Test Methods for Evaluating Solid Waste, EPA SW846, 3rd Ed.

QUALITY ASSURANCE: These analyses are performed in accordance with EPA guidelines for quality assurance.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: MW-9 (25-27)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/22/93 16:20:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA			
PARAMETER		RESULTS	DETE	ECTION	UNITS
			LIMI	[T	
BENZENE		ND	0.0010	P	mg/kg
TOLUENE		ND	0.0010	P	mg/kg
ETHYLBENZENE		ND	0.0010	P	mg/kg
TOTAL XYLENE		ND	0.0010	P	mg/kg
TOTAL BTEX		ND			mg/kg
METHOD 5030/8020 ***					
Analyzed by: KA					
Date: 09/30/93					
· · · · · · · · · · · · · · · · · · ·					
Petroleum Extractables		10		10	mg/Kg
METHOD Mod. 418.1*					
Analyzed by: AR					
Date: 09/30/93					

ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: MW-10 (5-7)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/23/93 09:55:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA		
PARAMETER		RESULTS	DETECTION	UNITS
			LIMIT	
BENZENE		ND	0.0010 P	mg/kg
TOLUENE		0.0010	0.0010 P	mg/kg
ETHYLBENZENE		0.0010	0.0010 P	mg/kg
TOTAL XYLENE	•	0.0060	0.0010 P	mg/kg
TOTAL BTEX		0.008		mg/kg
METHOD 5030/8020 ***				
Analyzed by: KA				
Date: 10/01/93				
Petroleum Extractables		MD	1.0	ma /Va
METHOD Mod. 418.1*		ND	10	mg/Kg
Analyzed by: AR				
Date: 09/30/93				

ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: MW-10 (31-32)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/23/93 10:30:00

DATE RECEIVED: 09/29/93

<del></del>	<del></del>		
ANALYTICAL	DATA		
	RESULTS	DETECTIO	N UNITS
		LIMIT	
	ND	0.0010 P	mg/kg
	ND	0.0010 P	mg/kg
•	ND	0.0010 P	mg/kg
	0.0010	0.0010 P	mg/kg
	0.001		mg/kg
	20	10	mg/Kg
			3. 3
	ANALYTICAL	ND ND ND 0.0010 0.001	RESULTS DETECTIO LIMIT ND 0.0010 P ND 0.0010 P ND 0.0010 P 0.0010 0.0010 P 0.001

ND - Not detected.

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.

<sup>(</sup>P) - Practical Quantitation Limit



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: B-15 (15-17)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/23/93 13:00:00

DATE RECEIVED: 09/29/93

	ANALYTICAL DATA		
PARAMETER	RESULTS	DETECTION	UNITS
•		LIMIT	
BENZENE	ND	0.0010 P	mg/kg
TOLUENE	ND	0.0010 P	mg/kg
ETHYLBENZENE	0.0010	0.0010 P	mg/kg
TOTAL XYLENE	0.0030	0.0010 P	mg/kg
TOTAL BTEX	0.004		mg/kg
METHOD 5030/8020 ***			
Analyzed by: KA			
Date: 10/01/93			
Petroleum Extractables	50	10	mg/Ko
METHOD Mod. 418.1*			
Analyzed by: AR			
Date: 09/30/93			

ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: B-15 (30-32)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/23/93 13:20:00

DATE RECEIVED: 09/29/93

	ANALYTICAL DATA		
PARAMETER	RESULTS		UNITS
		LIMIT	
BENZENE	ND	0.010 P	mg/kg
TOLUENE	ND	0.010 P	mg/kg
ETHYLBENZENE	0.012	0.010 P	mg/kg
TOTAL XYLENE	0.021	0.010 P	mg/kg
TOTAL BTEX	0.033		mg/kg
METHOD 5030/8020 ***			
Analyzed by: KA			
Date: 10/02/93			
V.			
Petroleum Extractables	1200	10	mg/Kg
METHOD Mod. 418.1*			
Analyzed by: AR			
Date: 09/30/93			

ND - Not detected.

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.

<sup>(</sup>P) - Practical Quantitation Limit



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: MW-11 (10-12)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/23/93 14:20:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA		
PARAMETER		RESULTS	DETECTION LIMIT	UNITS
BENZENE		ND	0.050 P	mg/kg
TOLUENE		0.16	0.050 P	mg/kg
ETHYLBENZENE		4.7	0.050 P	mg/kg
TOTAL XYLENE		1.8	0.050 P	mg/kg
TOTAL BTEX METHOD 5030/8020 *** Analyzed by: KA Date: 10/04/93		6.66		mg/kg
Petroleum Extractables METHOD Mod. 418.1* Analyzed by: AR Date: 09/30/93		5900	50	mg/Kg

ND - Not detected.

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.

<sup>(</sup>P) - Practical Quantitation Limit



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc.

**SAMPLE ID:** MW-11 (20-22)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/23/93 14:40:00

DATE RECEIVED: 09/29/93

	ANALYTICAL DATA		
PARAMETER	RESULTS	DETECTION	UNITS
		LIMIT	
BENZENE	0.97	0.25 P	mg/kg
TOLUENE	2.3	0.25 P	mg/kg
ETHYLBENZENE	45	0.25 P	mg/kg
TOTAL XYLENE	82	0.25 P	mg/kg
TOTAL BTEX	130.27		mg/kg
METHOD 5030/8020 ***		1	
Analyzed by: KA			
Date: 10/04/93			
Petroleum Extractables	1100	10	mg/Kg
METHOD Mod. 418.1*			97 -1.9
Analyzed by: AR			
Date: 09/30/93			

#### (P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA

\*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: MW-11 (30-32)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/23/93 15:00:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA		
PARAMETER		RESULTS	DETECTION	UNITS
			LIMIT	
BENZENE		0.010	0.010 P	mg/kg
TOLUENE		0.023	0.010 P	mg/kg
ETHYLBENZENE		0.045	0.010 P	mg/kg
TOTAL XYLENE		0.064	0.010 P	mg/kg
TOTAL BTEX		0.142		mg/kg
METHOD 5030/8020 ***			•	
Analyzed by: KA				
Date: 10/02/93				
1				
Petroleum Extractables		370	10	mg/Kg
METHOD Mod. 418.1*				
Analyzed by: AR				
Date: 09/30/93				

#### (P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: B-16 (10-12)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/23/93 17:20:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA		
PARAMETER		RESULTS	DETECTION	UNITS
			LIMIT	
BENZENE		ND	0.0010 P	mg/kg
TOLUENE		ND	0.0010 P	mg/kg
ETHYLBENZENE		ND	0.0010 P	mg/kg
TOTAL XYLENE		0.0010	0.0010 P	mg/kg
TOTAL BTEX		0.001		mg/kg
METHOD 5030/8020 ***				<i>3. 3</i>
Analyzed by: KA				
Date: 09/30/93				
Petroleum Extractables		ND	10	mg/Kg
METHOD Mod. 418.1*				5 / 5
Analyzed by: AR				
Date: 09/30/93				

ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA

\*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc. SAMPLE ID: B-16 (25-27)

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/23/93 17:48:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA		
PARAMETER		RESULTS	DETECTION LIMIT	UNITS
BENZENE		ND	0.0010 P	mg/kg
TOLUENE		ND	0.0010 P	mg/kg
ETHYLBENZENE		ND	0.0010 P	mg/kg
TOTAL XYLENE		ND	0.0010 P	mg/kg
TOTAL BTEX		ND		mg/kg
METHOD 5030/8020 ***				
Analyzed by: KA				
Date: 09/30/93		•		
Petroleum Extractables		ND	10	mg/Kg
METHOD Mod. 418.1*				
Analyzed by: AR				
Date: 09/30/93				

ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc.

**SAMPLE ID:** MW-8 (10-12) << DUP >>

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/22/93 10:45:00

DATE RECEIVED: 09/29/93

PARAMETER	ANALYTICAL	 RESULTS	DETECTION LIMIT	UNITS
BENZENE		ND	0.010 P	mg/kg
TOLUENE		0.018	0.010 P	mg/kg
ETHYLBENZENE		ND	0.010 P	mg/kg
TOTAL XYLENE		0.072	0.010 P	mg/kg
TOTAL BTEX METHOD 5030/8020 *** Analyzed by: KA Date: 10/02/93		0.090		mg/kg
Petroleum Extractables METHOD Mod. 418.1* Analyzed by: AR Date: 09/30/93		3300	20	mg/Kg

ND - Not detected.

(P) - Practical Quantitation Limit

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA

\*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.



Shell Pipe Line Corporation

P.O. Box 2099

Houston, TX 77252-2099

ATTN: John Hite

P.O.#

CAO-B-131201-GK

DATE: 10/06/93

PROJECT: Lea Station

SITE: Lea County, New Mexico

SAMPLED BY: CURA, Inc.

**SAMPLE ID:** MW-9 (25-27) << DUP >>

PROJECT NO: 15-93677.3

MATRIX: SOIL

DATE SAMPLED: 09/22/93 16:20:00

DATE RECEIVED: 09/29/93

	ANALYTICAL	DATA		
PARAMETER		RESULTS	DETECTION	UNITS
			LIMIT	
BENZENE		ND	0.0010 P	mg/kg
TOLUENE		ND	0.0010 P	mg/kg
ETHYLBENZENE		ND	0.0010 P	mg/kg
TOTAL XYLENE		0.0010	0.0010 P	mg/kg
TOTAL BTEX		0.001		mg/kg
METHOD 5030/8020 ***				
Analyzed by: KA				
Date: 09/30/93				
Petroleum Extractables		30	10	mg/Kg
METHOD Mod. 418.1*		•		
Analyzed by: AR				
Date: 09/30/93				

ND - Not detected.

Notes: \*Ref: Methods for Chemical Analysis of Water and Wastes, 1983, EPA \*\*Ref: Standard Methods for Examination of Water & Wastewater, 17th ed.

<sup>(</sup>P) - Practical Quantitation Limit



## \*\* SPL Quality Control Report \*\* BTEX MATRIX SPIKE/MATRIX SPIKE DUPLICATE Method 8020

SPL Sample ID: 9309513-03A

Soil

Reported on:

10/05/93

Matrix:

Analyzed on:

09/30/93

This sample was randomly selected for use in the SPL quality control program. One in twenty samples is fortified, in duplicate, with a known concentration of the substance being analyzed.

The results are as follows:

---- SPIKE ANALYSIS -----

Compound	Blank Value	Spike Added μg/Kg	Original Sample Concentration µg/Kg	MS Concentration μg/Kg	MS % Rec#	QC Limits Range
BENZENE	ND	20	N D	21	105	39 - 150 %
TOLUENE	ND	20	N D	22	110	46 - 148 %
ETHYL_BENZENE	ND	20	N D	21	105	32 - 160 %
O XYLENE	ND .	20	N D	21	105	32 - 160 %
M AND P XYLENE	ND	40	1	44	107	32 - 160 %

#### ---- SPIKE DUPLICATE ANALYSIS -----

Compound	Spike Added #g/Kg	MSD Concentration µg/Kg	MSD % Rec#	% RPD	RPD Limit	QC Rec Range
BENZENE	20	23	115	9	20	39 - 150 %
TOLUENE	20	24	120	9	20	46 - 148 %
ETHYL_BENZENE	20	22	110	5	20	32 - 160 %
O XYLENE	20	22	110	5	20	32 - 160 %
M AND P XYLENE	40	47	115	7	20	32 - 160 %

VARJ930930133200

Idelis Williams QC Officer



#### \*\* SPL Quality Control Report \*\* BTEX MATRIX SPIKE/MATRIX SPIKE DUPLICATE Method: 8020

SPL Sample ID: 9309731-06A

Reported on:

10/05/93

Matrix:

Soil

Analyzed on:

10/01/93

This sample was randomly selected for use in the SPL quality control program. One in twenty samples is fortified, in duplicate, with a known concentration of the substance being analyzed.

The results are as follows:

---- SPIKE ANALYSIS -----

Compound	Blank Value	Spike Added µg/Kg	Original Sample Concentration µg/Kg	MS Concentration μg/Kg	MS % Rec#	QC Limits Range
BENZENE	ND	20	ND	. 19	95	39 - 150 %
TOLUENE	ND	20	ND	18	90	46 - 148 %
ETHYL_BENZENE	ND	20	ND	16	80	32 - 160 %
O XYLENE	ND	20	1	17	80	32 - 160 %
M AND P XYLENE	ND	40	2	32	75	32 - 160 %

#### DUPLICATE

Compound	Spike Added µg/Kg	MSD Concentration µg/Kg	MSD % Rec#	% RPD	RPD Limit	QC Rec Range
BENZENE	20	19	95	0	20	39 - 150 %
TOLUENE	20	17	85	6	20	46 - 148 %
ETHYL_BENZENE	20	14	70	13	20	32 - 160 %
O XYLENE	20	15	70	13	20	32 - 160 %
M AND P XYLENE	40	28	65	14	20	32 - 160 %

VARJ931001072800



#### \*\* SPL Quality Control Report \*\* BTEX MATRIX SPIKE/MATRIX SPIKE DUPLICATE Method 8020

SPL Sample ID: 9309513-01A

Reported on:

10/05/93

Matrix:

Soil

Analyzed on:

10/02/93

This sample was randomly selected for use in the SPL quality control program. One in twenty samples is fortified, in duplicate, with a known concentration of the substance being analyzed.

The results are as follows:

---- SPIKE ANALYSIS -----

Compound	Blank Value	Spike Added µg/Kg	Original Sample Concentration µg/Kg	MS Concentration μg/Kg	MS % Rec#	QC Limits Range
BENZENE	ND	20	ND	17	85	39 - 150 %
TOLUENE	ND	20	ND	17	85	46 - 148 %
ETHYL_BENZENE	ND	20	ND	16	80	32 - 160 %
O XYLENE	ND	20	ND	16	80	32 - 160 %
M AND P XYLENE	ND	40	. 1	32	77	32 - 160 %

#### ---- SPIKE DUPLICATE ANALYSIS -----

Compound	Spike Added µg/Kg	MSD Concentration µg/Kg	MSD % Rec#	% RPD	RPD Limit	QC Rec Range
BENZENE	20	19	95	11	20	39 - 150 %
TOLUENE	20	18	90	6	20	46 - 148 %
ETHYL_BENZENE	20	16	80	0	20	32 - 160 %
O XYLENE	20	17	85	6	20	32 - 160 %
M AND P XYLENE	40	32	77	0	20	32 - 160 %

VARJ931002050600



#### \*\* SPL Quality Control Report \*\* BTEX MATRIX SPIKE/MATRIX SPIKE DUPLICATE Method 8020

SPL Sample ID: 9309513-01A

Reported on:

10/05/93

Soil

Analyzed on:

10/04/93

This sample was randomly selected for use in the SPL quality control program. One in twenty samples is fortified, in duplicate, with a known concentration of the substance being analyzed.

The results are as follows:

---- SPIKE ANALYSIS -----

Compound	Blank Value	Spike Added µg/Kg	Original Sample Concentration µg/Kg	MS Concentration µg/Kg	MS % Rec#	QC Limits Range
BENZENE	ND	20	ND	20	100	39 - 150 %
TOLUENE	ND	20	N D	22	110	46 - 148 %
ETHYL_BENZENE	ND	20	ND	22	110	32 - 160 %
O XYLENE	ND	20	ND	24	120	32 - 160 %
M AND P XYLENE	ND	40	1	48	117	32 - 160 %

#### ---- SPIKE DUPLICATE ANALYSIS ----

Compound	Spike Added µg/Kg	MSD Concentration μg/Kg	MSD % Rec#	% RPD	RPD Limit	QC Rec Range
BENZENE	20	19	95	5	20	39 - 150 %
TOLUENE	20	21	105	5	20	46 - 148 %
ETHYL_BENZENE	20	20	100	10	20	32 - 160 %
O XYLENE	20	21	105	13	20	32 - 160 %
M AND P XYLENE	40	41	100	16	20	32 - 160 %

VARJ931004124800

Idelis Williams, QC Officer



#### \*\* SPL QUALITY CONTROL REPORT \*\* TOTAL PETROLEUM HYDROCARBONS [TPH]

SPL sample Id: 9309968-1B

**Reported on: 10/05/93** 

Matrix:

Analyzed on: 09/30/93

This sample was randomly selected for use in the SPL quality control program. One in ten samples is fortified with a known concentration of the substance being analyzed and one in ten samples is analyzed in duplicate. The result are as follows:

#### SPIKE ANALYSIS --

Sample Id	Blank Value	Spike Added mg/L	Original Sample Concentration mg/Kg	MS Concentration mg/Kg	MS % Rec
9309968-1B	ND	384	7	329	84

#### SPIKE DUPLICATE ANALYSIS --

Sample Id	Spike Added mg/L	MSD Concentration mg/Kg	MSD % Rec	% RPD
9309968-1B	384	351	90	6

SPL, Incorporated

Lynthia Schreiner, QC Officer

9209960

11st 8/30/93

SHELL OIL COMPANY RETAIL ENVIRONMENTAL ENGINEERING	CHAIN OF CUSTODY RECORD NO.	RECOR	D NO. H	10278		Date: Page.	e: 9-27-93
13	CHECK ONE BOX ONLY CT/DT		AN	ANALYSIS REQUEST: (CHECK APPROPRIATE BOX)		ОТНЕВ	REMARKS
STEADORESS: Le4 Station		-4	-				
Lea Count, New Mexico	QUARTERLY MONITORING   5461		381				
5-93672,3	SITE INVESTIGATION DE 5441		M HTTV (21+) S		ABICIDI MBICIDI	:	
. & ADDRESS:	SOIL FOR DISPOSAL   5442		NBS	Wed Did			
3001 N. B.y Spaing, Ste 101, Midland, TX 27735	MATER FOR DISPOSAL   5443		ער ם	D 14T			
CONSULTANT CONTACT: F. Wesley Root	AIR SAMPLER - SYS O+M	SA	BONS SS40/T				
PHONE: 915-570-8408 FAX: 715-570-8409	WATER SAMPLE - SYS O+N   5453		0	MAN C			
SAMPLED BY: 7. (Wasking Root	OTHER	F CONT	SOLUTION COS CO	41810 41812 41812 41812	atəm X Oytuv		
IME COMP. GRAS	OTHER METHOD PRESERVED OTHER		BTEXC	SEMI -			
7 32/8 82-6-6 (6		12		┼			
(25-27) 9-22-931	301	1 402	2	7			
(10-12)	301	2 402	1	7		_	Field to te
MW-8 (25-27) 9-22-931115 1	32/	1 402	7	7			
	40/	1 403	3	3			
B-14 (25-27) 9-22-93 14:40 V	37/	**************************************	2	7	-	1	
MW-9 (15-17) 9-22-93 16:000 V V	30/	1 900	2	7			
MW-9 (25-27) 8-22-2/6,20 1	105	2 403	2	2			おくしょ ひゅんしゅお
NW-10 (5-7) 9-23-73 9:55 V V	30/	1 1/32	2	1			
MW-10 (31-32) 9-23-93 10:30 U U	30/	1 903	2	2			
8-15 (15-17) 9-23-9313500 1 1	301	1 403	7	2			
B-15(30-32) 9-23-9313720 V V	30/	1 403	1	7			
RELINQUISHED BY: (SIGNATURE) DATE TIME RECEIVED BY: (SIGNAT	SIGNATURE) DATE TIME	E BILL NO.:	<u>Ş</u>				
7. Wesley Root 8-27-93/10:30		<b>Z</b>	LABORATORY:		1		
RECEIVED BY:	SIGNATURE) DATE TIME		SHELL CONTACT: John	H.tc	PHONE: 2/ 3	7, 3-241-100/xx	Ü
	/INTRET3% 1	S S	TURN AROUND TIME (CHECK ONE)				
RELINQUISHED BY: (SIGNATURE) DATE TIME RECEIVED BY	(SGNATURE) GATE TIME		7 DAYS (INORMAL) 48 HOURS (I	41 TO	14 DAYS (1)	DER CON	contract
THE LABORATORY MUSTIP	THE LABORATORY MUSTIPROVIDE A COPY OF THIS CHAIN OF CUSTODY WITH INVOICE AND RESULTS	AIN OF CU	STODY WITH IN	VOICE AND RESULT	မှ		

÷ ..

۲,

THE LABORATORY MUSTYPROVIDE A COPY OF THIS CHAIN OF CUSTODY WITH INVOICE AND RESULTS
DISTRIBUTION: PINK Sempting Coordinator - WHITE & YELLOW Accompanies Shipment - WHITE Returned with Report

096666

SHELL OIL COMPANY  SHELL OIL COMPANY  She LL Proa Line Corp  May 15 - 93677.3  CONSULTANT NAME a ADDRESS: CURA Inc.  3001 N. B.g. Spainty, Ste 181, Midland, TX  CONSULTANT CONTACT: F. Wedley Root  SAMPLED: DATE TIME COMPONING TO 10 N  MW-11 (10-72) 9-23-73 17:20 U U  MW-11 (20-22) 9-23-73 17:20 U U  MW-11 (30-32) 9-23-73 17:20 U U  B-16 (10 - 12) 7-23-73 17:48 U U  B-17 (10 - 12) 7-23-73 17:48 U U  B-18 (10 - 12) 7-23-73 17:48 U U  B-19 (10 - 12) 7-23-73 17:48 U U  B-10 (10 - 12) 7-23-73	7-23 9-23-93 H120 V V V	RELINQUISHED BY: (SIGNATURE) DATE TIME RECEIVED BY: (SIGNATURE) DATE TIME BILL NO:
LENVIRONME  Le (L P, pa  Le (L P, pa  Le (L P, pa  LE -93677  LE -93677  LE -93673  LE LLAGLA  LE LLAGLA  LE -93-73   P-23-73   P-23-73		

5 40 E

THE LABORATORY/MUST FROVIDE A COPT OF THIS CHAIN OF CUSTOUT WITH INVOICE AND DESCRISS DISTRIBUTION: PINK Sampling Coordinator . WHITE & YELLOW Accompanies Shipment . WHITE Returned with Report

### SPL HOUSTON ENVIRONMENTAL LABORATORY

### SAMPLE LOGIN CHECKLIST

LOT	: TIME: CLIENT NO NO TOME: CONTRACT NO NT SAMPLE NOS	
SPL	sample nos.: 9309960	
		YES NO
1.	Is a Chain-of-Custody form present? Is the COC properly completed? If no, describe what is incomplete:	<u> </u>
3.	If no, has the client been contacted about it? (Attach subsequent documentation from client about the Is airbill/packing list/bill of lading with shipment? If yes, ID#:	
4. 5. 6.	If yes, ID#: // > // > // > // > IS a USEPA Traffic Report present?  Is a USEPA SAS Packing List present?  Are custody seals present on the package?  If yes, were they intact upon receipt?	
7.	Are all samples tagged or labeled?  Do the sample tags/labels match the COC?  If no, has the client been contacted about it?  (Attach subsequent documentation from client about the	situation)
8.	Do all shipping documents agree?  If no, describe what is in nonconformity:	<u> </u>
9. 10. 11.	Condition/temperature of shipping container: NTACT Condition/temperature of sample bottles: Solv Sample Disposal?: SPL disposal Return	3°C to client
NOTE	S (reference item number if applicable):	
	ST: DATE: DA	9/29/93

# APPENDIX E PHOTO-DOCUMENTATION



Photograph 1: View of well installation operations on monitor well MW-11 at Lea Station. Note offset tank battery on right in background.



Photograph 2: View looking southeast towards Monument Draw and the locations of monitor wells MW-4, MW-9, and MW-10 (from right to left).

