

3R -

377

REPORTS

DATE:

JAN 2001

BLAGG ENGINEERING, INC.


P.O. Box 87, Bloomfield, New Mexico 87413

Phone: (505)632-1199 Fax: (505)632-3903

3R-377

January 19, 2001

Mr. William C. Olson, Hydrologist
New Mexico Oil Conservation Division-NMOCD
Environmental Bureau
2040 S. Pacheco
Santa Fe, New Mexico 87505



**Re: BP Amoco (formerly Amoco Production Company)
Groundwater Monitoring Report
Cooper GC # 1E, Unit J, Sec. 15, T29N, R11W, NMPM
San Juan County, New Mexico**

Dear Mr. Olson:

BP Amoco has retained Blagg Engineering, Inc. to conduct environmental monitoring and reclamation of groundwater at the Cooper GC # 1E currently operated by Cross Timbers Oil Company (CTOC). CTOC acquired the well site in January, 1998, however, BP Amoco has and is currently accepting the environmental obligation associated with the soil and groundwater contamination.

After the initial pit closure cleanup effort in October/November, 1993, an air sparge system was utilized in aggressively remediating on-site hydrocarbon contamination in groundwater. The system was designed to treat soils and groundwater that could not be accessed or reclaimed by other practical methods. An extension of the air sparge system was conducted in September, 2000 to address a rise in the local water table.

If you have any questions concerning this document, please contact either myself or Jeffrey C. Blagg at the address or phone number listed above. Thank you for your cooperation and assistance.

Respectfully submitted:
Blagg Engineering, Inc.

Nelson J. Velez
Staff Geologist

cc: Mr. Denny Foust, Environmental Geologist, NMOCD District III Office, Aztec, NM
Mr. Buddy Shaw, Environmental Coordinator, BP Amoco, Farmington, NM (without document)
Ms. Nina Hutton, Environmental & Safety Manager, CTOC, Ft. Worth, TX
Mr. Terry Matthews, Regional Manager, CTOC, Farmington, NM

**BP AMOCO
Cooper GC #1E
Nw/4 Se/4 Sec. 15, T29N, R11W**

<u>Pit Closure Dates:</u>	Oct.-Nov., 1993 & Aug.-Sept., 1997
<u>Monitor Well Installation Dates:</u>	Apr. 26-29, 1996, Sept. 19, 1996, Mar. 30-Apr. 1, 1998
<u>Air Sparge Installation Dates:</u>	Mar. 31-Apr. 3, 1998 & Sept. 12, 2000

Pit Closures & Background:

Pit closure was conducted by BP Amoco's (BP) contractor Paul & Sons, Inc. (P&S) in **October, 1993** (refer to pit closure information section). The excavated area encompassed approximately 30 feet by 70 feet in dimension within the fenced portion of the well pad at its southern perimeter. The soil excavated was removed and transported to BP's Cooper GC # 1 well site located at Unit B, Section 15, T29N, R11W, NMPM, San Juan County, NM. Groundwater was encountered during the soil excavation at approximately twenty (20) feet below grade. The exposed groundwater within the pit area was sampled and tested by Envirotech, Inc. on **November 1, 1993** for benzene, toluene, ethylbenzene, and total xylenes (BTEX) per US EPA method 8020. It was documented that the exposed groundwater in the pit excavation was pumped on **November 2, 1993** and upon review of the groundwater lab results, a resampling of the pit water was conducted on **November 5, 1993**. The BTEX results of the two (2) groundwater sampling events are as follows;

Date	11/1/93	11/5/93	NMWQCC standards
Sample ID	12B @ 20 ft.	13B @ 20 ft.	
benzene (ppb)	12,900	8,200	10
toluene (ppb)	6,200	16,400	750
ethylbenzene (ppb)	720	373	750
xylenes (ppb)	5,430	6,580	620

Note: ppb = parts per billion, NMWQCC = New Mexico Water Quality Control Commission.

Afterwards, the excavation was backfilled and a monitor well (MW #1) was installed by P&S on an **undisclosed date in 1994** (Figure 1). After six (6) sampling events from MW #1 dating between **October, 1994 & December, 1995** (refer to summary table for results), an apparent air sparge system was installed by P&S between **December, 1995 & March, 1996**. Specifications of the system are unknown. All that can be disclosed of the system is that three (3) air sparge points were installed; one near the south end of the dehydrator tank pit, one adjacent to the production tank on its north side, and MW #1 converted as the last point. As a result of the modification to MW #1, it was apparent that it was unusable for groundwater sampling.

In **April, 1996**, Blagg Engineering, Inc. (BEI) installed four (4) groundwater monitor wells (MW #'s 2, 3, 4, & 5) using a truck mounted drill rig (see Figure 1 for locations). MW #4 was positioned as to replace MW #1. Boring logs and monitor well completion schematics can be reviewed under the Boring Logs & MW Details tab headings respectively. The initial sampling event for these monitor wells conducted in **June, 1996**. Upon review of the lab results, BP's groundwater plan called for down gradient delineation and placing MW #'s 3, 4, & 5 on an annual sampling schedule. Sampling of MW #2 was terminated as all BTEX constituents tested at non detectable levels.

In **September, 1996**, BEI conducted down gradient test holes and installed monitor wells (MW's 6, 7, 8, & 9) off-site (Figure 2). BTEX results from these test holes and monitor wells can be reviewed in the table below as well as on Figure 3.

Sample ID	Date	benzene (ppb)	toluene (ppb)	ethyl- benzene (ppb)	total xylenes (ppb)
TH #1	9/19/96	1,200	1.03	4.52	49.0
TH #2	9/19/96	0.99	0.24	ND	0.45
TH #3 / MW #6	9/19/96	0.92	0.91	0.49	2.15
TH #4 / MW #7	9/23/96	3,550	2,100	319	2,126
TH #5 / MW #8	9/23/96	0.56	1.71	4.79	11.95
TH #6 / MW #9	9/23/96	14.0	1.05	ND	ND
NMWQCC standards		10.0	750	750	620

Note: ppb = parts per billion, TH = test hole, MW = monitor well, NMWQCC = New Mexico Water Quality Control Commission.

Boring logs for test holes 1 through 3 (designated TH-1 to TH-3) are included within the Boring Logs tab heading. The other test holes or installed monitor wells were not documented; however, based on their proximities to other test holes or monitor wells that were logged, it can be postulated that the lithology are somewhat similar in comparison.

Commencing at the end of **July, 1997**, BP selected to conduct further on-site soil and groundwater remediation by means of excavation (Figure 5). Upon completion of the excavated areas, grab soil samples were collected from the excavation sidewalls at various intervals from the relative ground surface on **August 6, 1997**. Recovered soil samples were field screened for volatile hydrocarbon vapors with an organic vapor meter (OVM) applying the Headspace Field Method (New Mexico Oil Conservation Division (NMOCD) Surface Impoundment Closure Guidelines, February, 1993). The soil sample with the highest OVM reading was collected in laboratory supplied four (4) ounce glass jar with teflon seal and submitted to a qualified laboratory for total petroleum hydrocarbons (TPH) analysis per US EPA method 8015.

The sample was stored in a cooler with blue ice pack(s) and hand delivered on the same day as sampled. The OVM results and TPH analysis can be reviewed on Figure 5. The laboratory report, quality assurance/quality control (QA/QC), and Chain-of-Custody Record are presented within the Soil Lab Reports tab heading.

The excavated areas were measured at approximately 135 feet in width by 162 feet in length by 25 in depth and 47 feet in width by 66 feet in length by 25 feet in depth. The total cubic yardage excavated is estimated between 15,000 to 20,000. Approximately two thirds (2/3) of the excavated soil was considered clean overburden (no apparent discoloration observed or hydrocarbon odor detected physically) which was eventually placed back into the bottom portion of the excavations (10,000 to 13,333 cubic yards). The contaminated soil portion (5,000 to 6,667 cubic yards) was temporarily stockpiled north of the well head during the remediation effort. A rock crusher, utilizing its conveyor belt as an aerator was transported on location. The contaminated soil was handled several times applying the aeration process prior to sampling. OVM (grab) and/or lab TPH (grab and composite) samples were collected from the stockpile prior to and after the aeration remediation was completed (see Figure 5 for summary results). After receiving the laboratory analyses, the remediated soil was placed back into the excavated areas above the apparent clean overburden soil previously mentioned.

In addition to the soil remediation, P&S personnel installed four (4) each two (2) inch diameter PVC groundwater monitor wells off-site and south/down gradient of the remediation effort (Figure 3). These wells, labels TH A through TH D, were sampled on **August 22, 1997** by BEI. BTEX results can be reviewed in the table below as well as on Figure 3.

Sample ID	Date	benzene (ppb)	toluene (ppb)	ethyl- benzene (ppb)	total xylenes (ppb)
TH A	8/22/97	ND	0.4	1.1	13.4
TH B	8/22/97	ND	11.3	11.1	18.6
TH C	8/22/97	92.8	ND	ND	79.1
TH D	8/22/97	10.3	2.4	ND	11.5
NMWQCC standards		10.0	750	750	620

Note: ppb = parts per billion, TH = test hole, MW = monitor well, NMWQCC = New Mexico Water Quality Control Commission.

It is important to note that during the sampling of these wells, physical detection of apparent PVC primer and glue was evident. Afterwards, it was later confirmed by the personnel who installed the wells that primer and glue were indeed used at the PVC screen and casing connections. Based on this fact, BEI does not view the samples as viable and the data may not be valid.

In **September, 1997**, the well site's surface equipment was relocated and presently appears as in Figure 4.

As evident in Figure 5, a buried concrete ditch split the excavation areas previously mentioned. Contaminated soil below the ditch could not practically be removed or remediation by excavation, therefore as an alternative, an air sparge system was developed and installed by BEI to address the remaining contamination in soil and groundwater.

Reclamation System:

The present air sparge reclamation system (Figure 6 & 7) was installed in two separate events. The initial event was installed by BEI using a CME drill rig in **March-April, 1998** to address the groundwater at the measured depths during that period. As time progressed, the groundwater surface rose dramatically, creating a situation that rendered the air sparge system unproductive due to insufficient air pressure from the air injection blowers to overcome the total head within each air sparge point. This lead to a sparge system revision, which was conducted in **September, 2000** using BEI's truck mount drill rig. Two (2) additional air sparge points, designated AS-12 & AS-13, were installed at shallower depths (refer to Air Sparge Schematic tab heading) to address the higher groundwater surface. BEI installed gate valves (Figure 8) to direct the air flow to either the shallower or deeper seated air sparge points to address changes in groundwater level. Periodic inspection of the groundwater level would dictate which air sparge points to utilize.

It should be noted that during the July/August, 1997 remedial effort, P&S installed an air sparge/vacuum extraction system in the southwest portion of the southern most excavation perimeter. Although no specifications of the system are present, the following outline highlights the intent.

1. Horizontal borings were advanced using a water pump to drive four (4) inch piping into the southwest sidewall of the southern excavation. Penetration lengths ranged from twenty five (25) to forty (40) feet.
2. The borings, total number unknown, were advanced within the water table [estimated at twenty five (25) feet below grade] and above [estimated at twenty (20) feet].
3. Perforated four (4) inch pipe (similar to sewer/leach line piping) was utilized for both the air sparge and vacuum extraction systems.

Between April, 1998 and May, 1999, the compressor used for the reclamation was alternated every three (3) months between P&S and BEI installed systems due to incompatible air flow movement in the vertical (BEI) and horizontal (P&S) piping. BEI's air sparge system below the concrete ditch has been exclusively used since May, 1999.

Groundwater Monitor Well Sampling Procedures:

Groundwater samples were collected from site monitor wells following US EPA: SW-846 protocol. The samples were collected using new disposable bailers and placed in new laboratory supplied forty (40) milliliter glass vials with teflon septa caps. Samples were analyzed BTEX per US EPA Method 8021. Additional groundwater was collected and placed in laboratory supplied 500 ml plastic containers and analyzed for general water quality per US EPA Method 600/4-79-020.

The samples were preserved cool (BTEX samples also preserved with mercuric chloride or hydrochloric acid) and hand delivered to a qualified laboratory for testing. Waste generated during monitor well sampling and development was disposed of utilizing the separator tank pit located on the well site.

Groundwater Quality & Flow Direction Information:

Sampling of the groundwater monitor wells at the site has been ongoing since October, 1994. A summary of laboratory analytical results is included within the tables on the following pages and laboratory data reports are included in MW Data with Lab Reports tab heading. Analytical data indicates that groundwater impact in excess of NMWQCC standards has been identified in three (3) monitor wells (MW #3R, MW #7 & MW #9). Of the three (3) monitor wells, MW #3R (which replaced MW #3) is the only well being sampled on a continuous basis. Water quality in MW #3R has shown variable values of BTEX over time. These trends will be further evaluated from periodic monitoring after the addition/modification to the air sparge system in September, 2000. MW #'s 7 & 9 have only been sampled on one occasion in September, 1996. All other monitor wells listed within the proceeding tables have either established sampling termination based on BP's NMOCD approved groundwater plan or removed during the July/August, 1997 soil excavation activity.

Groundwater contour maps of relative water table elevations for sample events with sufficient data is included within the GW Contour Maps tab heading. The general flow direction tends to be either due south or in the southwest direction with the latter being predominant.

Summary

Contaminated soil and groundwater at the site that could not be accessed by excavation below the buried concrete ditch is presently being remediated with BEI's active air sparge system. Operation of the air sparge system is on-going as is groundwater monitoring from MW #3R.

AMOCO GROUNDWATER MONITOR WELL LABORATORY RESULTS

SUBMITTED BY BLAGG ENGINEERING, INC.

COOPER GC #1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

REVISED DATE: JANUARY 3, 2001

FILENAME: (CO-4Q-00.WK4) NJV

SAMPLE DATE	MONITOR WELL #	D.T.W. (ft)	T.D. (ft)	TDS mg/L	COND. (umhos/cm)	pH	PRODUCT (ft)	BTEX EPA METHOD 8021 (ppb)			
								Benzene	Toluene	Ethyl Benzene	Total Xylene
03-Oct-94	MW #1	22.04	27.30		2,400	7.3		2032	940	282	2595
15-Dec-94		23.45			2,400	7.0		2010	268	337	1749
10-Mar-95		27.21			2,600	6.9		1860	32	147	326
12-Jun-95		26.74			2,600	6.8		1082	1300	156	1678
08-Sep-95		22.07			1,700	7.0		661	786	606	1748
05-Dec-95		24.46			2,100	6.7		8130	1250	638	4035
March 96	Remediation System Installed - Well Not Usable										
07-Jun-96	MW #2	21.16	30.00	1110	900	7.3		ND	ND	ND	ND
09-Apr-98	MW #2R	22.67	26.00	586		6.6		2.4	9.9	2.7	16.2
07-Jun-96	MW #3	22.22	30.00	2090	200	6.9		2290	5410	1460	16010
27-Jun-97		26.19	30.00		2,100	7.4		14.3	29.6	97.9	498
09-Apr-98	MW #3R	25.59	34.03	7780		7.1		43.3	222	8.3	134.6
30-May-98		25.48			5,900	7.2		110	81.3	1.5	24.2
29-Sep-98		21.16			2,900	7.2		895	587	165	919
18-Dec-98		22.04			6,000	7.6		301	44.2	49.9	169.6
18-Feb-99		23.62			4,300	7.3		329	125	94.8	258.5
26-May-99		21.37			1,200	6.9		628	733	106	393
23-Aug-99		18.33			1,100	7.0		270	33.7	85.4	289
06-Dec-99		17.82			1,200	7.1		103	410	98.5	1005
24-Feb-00		21.62			2,500	7.6		290	790	130	1420
15-May-00		20.49			6,600	7.2		140	110	8.3	640
28-Nov-00		15.56			900	7.6		220	880	74	1010
07-Jun-96	MW #4	24.15	30.00	323	800	6.8		2900	18220	937	13920
27-Jun-97		27.73	30.00		1,200	7.3		1215	71.7	1620.0	5726.0
07-Jun-96	MW #5	19.81	23.77	595	1,100	6.8		9940	24260	962	10250
27-Jun-97		22.70	23.68	595	1,300	7.5		1720	635	72.8	965
30-May-98	MW #5R	30.03	31.00		2,500	7.3		1.1	1.1	1.0	2.0
29-Sep-98		22.04			3,200	7.0		4.7	2.3	ND	29.2
18-Dec-98		22.34			4,250	7.1		9.1	1.4	0.8	4.5
18-Feb-99		23.92			2,400	6.9		3.0	1.8	0.5	4.7
26-May-99		20.37			1,200	7.4		20.3	22.7	2.1	30.8
23-Aug-99		17.93			1,600	7.0		1.0	2.4	0.2	11.3
06-Dec-99		17.05			1,800	7.0		5.4	ND	ND	50.9
24-Feb-00		21.66			1,000	7.6		ND	ND	ND	ND
15-May-00		20.30			1,200	7.2		ND	ND	ND	ND

GENERAL WATER QUALITY
AMOCO PRODUCTION COMPANY
COOPER GC # 1E
SAMPLE DATE : JUNE 7, 1996

PARAMETERS		MW # 2	MW # 3	MW # 4	MW # 5	Units
GENERAL	LAB pH	7.6	7.3	7.4	7.4	s. u.
	LAB CONDUCTIVITY (25 DEG. CELCIUS)	1,660	2,760	829	986	umhos cm
	TOTAL DISSOLVED SOLIDS (180 DEG. CELCIUS)	1,110	2,090	323	595	mg / L
	TOTAL DISSOLVED SOLIDS (CALCULATED)	1,010	1,920	319	588	mg / L
ANIONS	TOTAL ALKALINITY AS CaCO3	191	334	263	501	mg / L
	BICARBONATE ALKALINITY (AS CaCO3)	191	334	263	501	mg / L
	CARBONATE ALKALINITY (AS CaCO3)	NA	NA	NA	NA	mg / L
	HYDROXIDE ALKALINITY (AS CaCO3)	NA	NA	NA	NA	mg / L
	CHLORIDE	1.67	1.67	4.17	35.8	mg / L
	SULFATE	581	1,140	37.0	11.5	mg / L
	NITRATE + NITRITE - N	NA	NA	NA	NA	
	NITRATE - N	NA	NA	NA	NA	
	NITRITE - N	NA	NA	NA	NA	
CATIONS	TOTAL HARDNESS AS CaCO3	556	859	222	465	mg / L
	CALCIUM	202	308	72.9	158	mg / L
	MAGNESIUM	12.3	22.1	9.82	17.2	mg / L
	POTASSIUM	<5.0	<5.0	<5.0	<5.0	mg / L
	SODIUM	100	240	37.0	65.0	mg / L
DATA VALIDATION						ACCEPTANCE LEVEL
	CATION/ANION DIFFERENCE	1.46	4.94	0.51	3.60	+/- 5 %
	TDS (180):TDS (CALCULATED)	1.1	1.1	1.0	1.0	1.0 - 1.2


GENERAL WATER QUALITY
AMOCO PRODUCTION COMPANY
COOPER GC # 1E

SAMPLE DATE : APRIL 9, 1998

PARAMETERS	MW # 2R	MW # 3R	Units
LAB pH	6.58	7.13	s. u.
LAB CONDUCTIVITY @ 25 C	1,200	15,600	umhos / cm
TOTAL DISSOLVED SOLIDS @ 180 C	590	7,800	mg / L
TOTAL DISSOLVED SOLIDS (Calc)	586	7,780	mg / L
SODIUM ABSORPTION RATIO	0.0	26.0	ratio
TOTAL ALKALINITY AS CaCO ₃	235	346	mg / L
TOTAL HARDNESS AS CaCO ₃	464	1,156	mg / L
BICARBONATE as HCO ₃	235	346	mg / L
CARBONATE AS CO ₃	< 1	< 1	mg / L
HYDROXIDE AS OH	< 1	< 1	mg / L
NITRATE NITROGEN	0.1	21.1	mg / L
NITRITE NITROGEN	< 0.001	0.064	mg / L
CHLORIDE	46.9	23.1	mg / L
FLUORIDE	0.85	1.87	mg / L
PHOSPHATE	0.9	0.5	mg / L
SULFATE	202	5,035	mg / L
IRON	NA	NA	mg / L
CALCIUM	185	425	mg / L
MAGNESIUM	< 0.1	22.9	mg / L
POTASSIUM	5.03	10.1	mg / L
SODIUM	2.2	2,030	mg / L
CATION / ANION DIFFERENCE	0.01	0.04	%



FIGURE 1
(prior to Aug. '97)



0 25 50 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

AMOCO PRODUCTION COMPANY

COOPER GC 1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: MW INSTALL.

DRAWN BY: NJV

FILENAME: 06-07-SM


REVISED: 2/10/97 NJV

SITE
MAP

6/96



FIGURE 2
(prior to Aug. '97)



TH #6
MW #9

STREET

TH #3
MW #6

TH #2
⊕

0 25 50 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

AMOCO PRODUCTION COMPANY

COOPER GC 1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: DELINEATION

DRAWN BY: NJV


FILENAME: SOUTH-SM

REVISED: 1/10/98 NJV

SITE
MAP

9/96

FIGURE 3
(prior to Sept. '97)



AMOCO PRODUCTION COMPANY
COOPER GC 1E
NW/4 SE/4 SEC. 15, T29N, R11W
SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.
CONSULTING PETROLEUM / RECLAMATION SERVICES
P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413
PHONE: (505) 632-1199


PROJECT: DELINEATION
DRAWN BY: NJV
FILENAME: SOUT-BTEX
REVISED: 1/2/01 NJV

**SITE
MAP**
8/97

FIGURE 4
(after Sept. '97)



OPEN FIELD



MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

1 INCH = 30 FT.

0 30 60 FT.

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 832-1199

PROJECT: REMED. PLAN

DRAWN BY: NJV

FILENAME: COOP-SM4

REVISED: 3/23/00 NJV

SITE
MAP

4/98

FIGURE 5




OPEN FIELD

SAMPLE DATE 8/6/97.

SAMPLE ID	OVM (ppm)	TPH (ppm)
1 @ 26'	0.0	-
2 @ 23'	1,382	1,520 *
4 @ 19'	454	-
4A @ 25'	0.0	-
5 @ 14'	0.0	-
6 @ 15'	0.0	-

* - SEE LAB REPORT
SAMPLE DATE 8/6/97.

SOIL REMEDIATED
ON-SITE REFER
TO SUMMARY TABLE
BELOW.



1 INCH = 30 FT.
0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

NOTES : STOCKPILE OVM READINGS TAKEN @ INDIVIDUAL SAMPLE POINTS. TPH ANALYSIS PER US EPA METHOD 8015.

OVM = ORGANIC VAPOR METER.
TPH = TOTAL PETROLEUM HYDROCARBONS.
ppm = PARTS PER MILLION.

EXCAVATED ON-SITE
SOIL REMEDIATION

SAMPLE ID & DATE	OVM (ppm)	TPH (ppm)
SPG-1 STOCKPILE GRAB SAMPLE 10/2/97	-	15.1
SPC-1 STOCKPILE 5 PT. COMPOSITE SAMPLE 10/2/97	1-10.4	13.8
	2-6.9	
	3-11.9	
	4-53.8	
SPG-2 STOCKPILE GRAB SAMPLES 10/7/97	1-70.4	78.1
	2-18.4	
	3-11.9	
	4-53.8	
STOCKPILE GRAB SAMPLES BEFORE REMED. EFFORT 9/15/97	1-691	-
	2-1,015	
	3-1,078	
	4-1,046	

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: REMED. PLAN

DRAWN BY: NJV

FILENAME: COOP-EX1

REVISED: 4/07/98 NJV

SEPT. '97
EXCAVATION
MAP

4/98


BLAGG ENGINEERING, Inc.

P.O. BOX 87
BLOOMFIELD, NM 87413
(505) 632-1199

AIR SPARGE SYSTEM BORE HOLE SCHEMATIC

PAGE #..... 1
DATE STARTED 3/31/98
DATE FINISHED 4/01/98
OPERATOR..... MC
PREPARED BY NJV

LOCATION NAME: COOPER GC # 1E
CLIENT: CROSS TIMBERS OIL COMPANY
CONTRACTOR: BLAGG ENGINEERING, INC. / ENVIROTECH, INC.
EQUIPMENT USED: MOBILE DRILL RIG
BORING LOCATION: SEE AIR SPARGING SITE SCHEMATIC.



GROUND SURFACE

LEGEND

- AS-1 = AIR SPARGE POINT DESIGNATION.
S = NON COHESIVE SAND.
C = SLIGHTLY TO HIGHLY PLASTIC CLAY.
SC = COHESIVE TO SLIGHTLY PLASTIC SILTY CLAY.
SS = NON COHESIVE TO SLIGHTLY COHESIVE SILTY SAND.
▼ - INDICATES APPROX. WATER TABLE DEPTH.


BLAGG ENGINEERING, Inc.

P.O. BOX 87
BLOOMFIELD, NM 87413
(505) 632-1199

AIR SPARGE SYSTEM BORE HOLE SCHEMATIC

PAGE #..... 1
DATE STARTED 3/31/98
DATE FINISHED 4/01/98
OPERATOR..... MC
PREPARED BY NJV

LOCATION NAME: COOPER GC # 1E
CLIENT: CROSS TIMBERS OIL COMPANY
CONTRACTOR: BLAGG ENGINEERING, INC. / ENVIROTECH, INC.
EQUIPMENT USED: MOBILE DRILL RIG
BORING LOCATION: SEE AIR SPARGING SITE SCHEMATIC.




← GROUND SURFACE

COLLECTED TPH & BTEX SAMPLES AT
AS-8 (20') - OVM = 222 parts per
million (ppm) TIME: 0810.

LEGEND

- AS-1 = AIR SPARGE POINT DESIGNATION.
- S = NON COHESIVE SAND.
- C = SLIGHTLY TO HIGHLY PLASTIC CLAY.
- SC = COHESIVE TO SLIGHTLY PLASTIC SILTY CLAY.
- SS = NON COHESIVE TO SLIGHTLY COHESIVE SILTY SAND.
- PC = HIGHLY PLASTIC CLAY.
- (ds) (19) = DISCOLORED SOIL WITH TOP INTERVAL STATED.
- ▼ = INDICATES APPROX. WATER TABLE DEPTH.

SIMPLISTIC AIR SPARGE POINT CONSTRUCTION



AMOCO PRODUCTION COMPANY

COOPER GC # 1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: RECLAM. SYS.

DRAWN BY: NJV


FILENAME: ASP-TEMP

DRAFTED: 3/22/00 NJV

AIR
SPARGE
POINT

3/00

FIGURE 6



ALL AIR SPARGE POINTS
ADJACENT TO BURIED CONCRETE
IRRIGATION DITCH MEASURED
AT APPROX. 3.5 FT. ALONG
EASTERN SIDE EXCEPT AS-8
(MEASURED AT 4.4 FT).

AIR SPARGE POINT'S PERPENDICULAR DISTANCES FROM FENCE LINE				
AS-5	AS-4	AS-3	AS-2	AS-1
5.75'	6.70'	5.25'	4.00'	2.15'

MW #5	TO AS-5	=	6.20 FT.
MW #5	TO MW #5R	=	6.50 FT.
MW #5R	TO AS-5	=	12.00 FT.
MW #5R	TO AS-4	=	8.70 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE
AS THE INSTRUMENTS USED IN OBTAINING THE
FOOTAGE AND BEARING FROM THE WELL HEAD
(BRUNTON COMPASS AND LASER RANGE FINDER).
ALL OTHER STRUCTURES DISPLAYED ON THE SITE
MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO
SCALE.

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: REMED. PLAN

DRAWN BY: NJV


FILENAME: COOP-AS

REVISED: 4/07/98 NJV

AIR SPARGE
SYSTEM AS
BUILT

4/98

FIGURE 7



MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: REMED. PLAN

DRAWN BY: NJV

FILENAME: COOP-AS2

REVISED: 8/30/00 NJV

AIR SPARGE
SYSTEM AS
BUILT


8/00

FIGURE 8

WELL HEAD

AS-8 @ 20 FT.
SOIL ANALYSIS
SAMPLED 4/3/98

OVM	=	222	ppm
BENZENE	=	1.420	ppm
TOTAL BTEX	=	259.4	ppm



NOTES: MW = MONITOR WELL.
OVM = ORGANIC VAPOR METER.
TPH = TOTAL PETROLEUM HYDROCARBONS.
BTEX = BENZENE, TOLUENE, ETHYLBENZENE, & XYLENES.
ppm = PARTS PER MILLION.

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: REMED. PLAN

DRAWN BY: NJV


FILENAME: COOP-AS3

REVISED: 8/30/00 NJV

AIR SPARGE
SYSTEM
CLOSE UP

8/00

FIGURE 9
(2nd 1/4, 1996)



MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

0 25 50 FT.

Top of Well Elevation	
MW #2	(101.88)
MW #3	(101.28)
MW #4	(101.32)
MW #5	(95.22)
MW #2 (80.72)	Groundwater Elevation as of 6/7/96.

AMOCO PRODUCTION COMPANY

COOPER GC 1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: MW SAMP.


DRAWN BY: NJV

FILENAME: 06-07-GW

REVISED: 2/10/97 NJV

GROUNDWATER
GRADIENT
MAP
6/96

FIGURE 10
(2nd 1/4, 1997)



MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

0 25 50 FT.

Top of Well Elevation	
MW #2	(101.88)
MW #3	(101.28)
MW #4	(101.32)
MW #5	(95.22)
MW #2	Groundwater Elevation as of 6/27/97.

FENCE

AMOCO PRODUCTION COMPANY

COOPER GC 1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: MW SAMP.

DRAWN BY: NJV

FILENAME: 06-27-GW

REVISED: 1/10/98 NJV

GROUNDWATER

GRADIENT


MAP

6/97

FIGURE 11
(2nd 1/4, '98)



OPEN FIELD



1 INCH = 30 FT.

0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

Top of Well Elevation	
MW #2R	(94.29)
MW #3R	(97.03)
MW #5	(94.00)
MW #5R	(94.12)
● MW #2R	Groundwater Elevation as of 4/01/98
(71.75)	

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: 1/4ly SAMP.

DRAWN BY: NJV

FILENAME: 04-09-GW

REVISED: 4/09/98 NJV


GROUNDWATER
CONTOUR
MAP

4/98

FIGURE 12 (3rd 1/4, 1998)



OPEN FIELD



1 INCH = 30 FT.

0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

Top of Well Elevation	
MW #2R	(94.29)
MW #3R	(97.03)
MW #5	(94.00)
MW #5R	(94.12)
● MW #2R	Groundwater Elevation as of 9/29/98.
(74.29)	

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: MW SAMPLING

DRAWN BY: NJV

FILENAME: 09-29-GW

REVISED: 9/29/98 NJV


GROUNDWATER
CONTOUR
MAP

9/98

FIGURE 13
(4th 1/4, 1998)



OPEN FIELD



1 INCH = 30 FT.

0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

Top of Well Elevation	
MW #2R	(94.29)
MW #3R	(97.03)
MW #5	(94.00)
MW #5R	(94.12)
● MW #2R	Groundwater Elevation as of 12/18/98.
(74.37)	

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: MW SAMPLING

DRAWN BY: NJV

FILENAME: 12-18-GW


REVISED: 12/18/98 NJV

GROUNDWATER
CONTOUR
MAP
12/98

FIGURE 14 (1st 1/4, 1999)



OPEN FIELD



1 INCH = 30 FT.

0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

Top of Well Elevation	
MW #2R	(94.29)
MW #3R	(97.03)
MW #5	(94.00)
MW #5R	(94.12)
● MW #2R	Groundwater Elevation as of 2/18/99.
(73.33)	

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: MW SAMPLING

DRAWN BY: NJV

FILENAME: 02-18-GW

REVISED: 7/23/99 NJV


GROUNDWATER
CONTOUR
MAP

02/99

FIGURE 15
(2nd 1/4, 1999)



OPEN FIELD



1 INCH = 30 FT.

0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

Top of Well Elevation	
MW #2R	(94.29)
MW #3R	(97.03)
MW #5	(94.00)
MW #5R	(94.12)
● MW #2R	Groundwater Elevation (78.22) as of 5/27/99.

AMOCO PRODUCTION COMPANY
COOPER GC #1E
NW/4 SE/4 SEC. 15, T29N, R11W
SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.
CONSULTING PETROLEUM / RECLAMATION SERVICES
P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413
PHONE: (505) 632-1199


PROJECT: MW SAMPLING
DRAWN BY: NJV
FILENAME: 05-27-GW
REVISED: 7/23/99 NJV

GROUNDWATER
CONTOUR
MAP
05/99

FIGURE 16 (3rd 1/4, 1999)



OPEN FIELD



1 INCH = 30 FT.

0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

Top of Well Elevation	
MW #2R	(94.29)
MW #3R	(97.03)
MW #5	(94.00)
MW #5R	(94.12)
• MW #2R	Groundwater Elevation as of 8/23/99.
(79.68)	

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: MW SAMPLING

DRAWN BY: NJV

FILENAME: 08-23-GW


REVISED: 8/31/99 NJV

GROUNDWATER
CONTOUR
MAP
8/99

FIGURE 17 (4th 1/4, 1999)



OPEN FIELD



1 INCH = 30 FT.

0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

Top of Well Elevation	
MW #2R	(94.29)
MW #3R	(97.03)
MW #5	(94.00)
MW #5R	(94.12)
● MW #2R	Groundwater Elevation (80.64) as of 12/6/99.

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: MW SAMPLING

DRAWN BY: NJV

FILENAME: 12-06-GW


REVISED: 12/6/99 NJV

GROUNDWATER
CONTOUR
MAP
12/99

FIGURE 18 (1st 1/4, 2000)



OPEN FIELD



1 INCH = 30 FT.

0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

Top of Well Elevation	
MW #2R	(94.29)
MW #3R	(97.03)
MW #5	(94.00)
MW #5R	(94.12)
● MW #2R	Groundwater Elevation as of 2/24/00.
(75.64)	

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 832-1199

PROJECT: MW SAMPLING

DRAWN BY: NJV

FILENAME: 02-24-GW


REVISED: 01/3/01 NJV

GROUNDWATER
CONTOUR
MAP
02/00

FIGURE 19 (2nd 1/4, 2000)



OPEN FIELD



1 INCH = 30 FT.

0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

Top of Well Elevation	
MW #2R	(94.29)
MW #3R	(97.03)
MW #5R	(94.12)
● MW #2R Groundwater Elevation as of 5/15/00.	
(78.17)	

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.
CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: MW SAMPLING

DRAWN BY: NJV

FILENAME: 05-15-GW


REVISED: 01/3/01 NJV

GROUNDWATER
CONTOUR
MAP
05/00

FIGURE 20 (4th 1/4, 2000)



OPEN FIELD



1 INCH = 30 FT.

0 30 60 FT.

MONITOR WELL LOCATIONS ARE ONLY AS ACCURATE AS THE INSTRUMENTS USED IN OBTAINING THE FOOTAGE AND BEARING FROM THE WELL HEAD (BRUNTON COMPASS AND LASER RANGE FINDER). ALL OTHER STRUCTURES DISPLAYED ON THE SITE MAP ARE SOLELY FOR REFERENCE AND ARE NOT TO SCALE.

Top of Well Elevation	
MW #2R	(94.29)
MW #3R	(97.03)
MW #5R	(94.12)
● MW #2R	Groundwater Elevation as of 11/28/00.
(81.62)	

AMOCO PRODUCTION COMPANY

COOPER GC #1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: MW SAMPLING

DRAWN BY: NJV

FILENAME: 11-28-GW

REVISED: 01/3/01 NJV

GROUNDWATER
CONTOUR
MAP
11/00

MONITOR WELL #2

AMOCO PRODUCTION COMPANY
COOPER GC # 1E
MONITOR WELL CONSTRUCTION & COMPLETION
INSTALLED WITH MOBILE RIG

BLAGG ENGINEERING, INC.
CONSULTING PETROLEUM / RECLAMATION SERVICES
P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413
PHONE: (505) 632-1199

MONITOR WELL SCHEMATIC
DRAFTED BY: NJV
DATE: FEB. '97
FILENAME: MW-2

2" DIA. SCH. 40 PVC
WELL CASING WITH SLIP CAP
(approx. 1.83 ft. above
ground surface)

TOTAL CASING
LENGTH = 23.17 ft.
FROM GROUND SURFACE
TO TOP OF SCREEN

WATER TABLE
APPROX. 19.33 ft. FROM
GROUND SURFACE
(measured 6/7/96)


0.02 INCH SLOTTED
SCREEN SCH 40 WITH
POINTED ENC CAP
(5 ft. total length)

TOTAL DEPTH = 28.17 ft.
FROM GROUND SURFACE

BACK FILLED WITH
CLEAN NATIVE SOIL
TO SURFACE

8 TO 12 MESH COLORADO
SILICA SAND
(approx. 2 ft. above
top of screen)

SCREEN INTERVAL SET
INTO EXISTING SOIL &
GROUNDWATER CONDITIONS



MONITOR WELL #2R

AMOCO PRODUCTION COMPANY

COOPER GC #1E

MONITOR WELL CONSTRUCTION & COMPLETION

INSTALLED WITH MOBILE RIG

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87

BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

MONITOR WELL SCHEMATIC

DRAFTED BY: NJV

INSTALL. DATE: MAR. '98

FILENAME: MW-2R

2" DIA. SCH. 40 PVC
WELL CASING WITH SLIP
CAP (approx. 1.10 ft.
above ground surface)

GROUND
SURFACE

TOTAL CASING
LENGTH = 14.90 ft.
FROM GROUND SURFACE
TO TOP OF SCREEN

0.02 INCH SLOTTED
SCREEN SCH 40
(top of screen
approx. 6.54 ft.
above water table)


0.02 INCH SLOTTED
SCREEN SCH 40 WITH
POINTED END CAP
(10 ft. total length;
approx. 3.46 ft. below
water table)

TOTAL DEPTH = 24.90 ft.
FROM GROUND SURFACE

21.44 ft. ANNULAR ABOVE
WATER TABLE COMPLETED
WITH COLORADO SILICA SAND

WATER TABLE
APPROX. 21.44 ft. FROM
GROUND SURFACE
(measured 3/31/98)

3.56 ft. ANNULAR BELOW
WATER TABLE COMPLETED
WITH EXISTING SOIL



MONITOR WELL #3

AMOCO PRODUCTION COMPANY
COOPER GC # 1E
MONITOR WELL CONSTRUCTION & COMPLETION
INSTALLED WITH MOBILE RIG

BLAGG ENGINEERING, INC.
CONSULTING PETROLEUM / RECLAMATION SERVICES
P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413
PHONE: (505) 632-1199

MONITOR WELL SCHEMATIC
DRAFTED BY: NJV
DATE: FEB. '97
FILENAME: MW-3

2" DIA. SCH. 40 PVC
WELL CASING WITH SLIP CAP
(approx. 1.57 ft. above
ground surface)

TOTAL CASING
LENGTH = 23.43 ft.
FROM GROUND SURFACE
TO TOP OF SCREEN

WATER TABLE
APPROX. 20.65 ft. FROM
GROUND SURFACE
(measured 6/7/96)


0.02 INCH SLOTTED
SCREEN SCH 40 WITH
POINTED ENC CAP
(5 ft. total length)

TOTAL DEPTH = 28.43 ft.
FROM GROUND SURFACE

BACK FILLED WITH
CLEAN NATIVE SOIL
TO SURFACE

8 TO 12 MESH COLORADO
SILICA SAND
(approx. 2 ft. above
top of screen)

SCREEN INTERVAL SET
INTO EXISTING SOIL &
GROUNDWATER CONDITIONS



MONITOR WELL #3R

2" DIA. SCH. 40 PVC
WELL CASING WITH LOCKING
CAP ENCASED WITH 8 X 12"
MANHOLE COVER

(top of casing approx. 0.40 ft.
below ground surface)

GROUND
SURFACE

PORTLAND CEMENT
(approx. 1 ft. interval)

15.43 ft. ANNULAR
COMPLETED WITH EXISTING
CLEAN NATIVE SOIL

1.00 ft. ANNULAR COMPLETED
WITH BENTONITE CHIPS
(16.43-17.43 ft. INTERVAL)

8.49 ft. ANNULAR ABOVE
WATER TABLE COMPLETED
WITH COLORADO SILICA SAND

WATER TABLE
APPROX. 25.92 ft. FROM
GROUND SURFACE
(measured 3/31/98)

9.08 ft. ANNULAR BELOW
WATER TABLE COMPLETED
WITH COLORADO SILICA SAND

TOTAL CASING
LENGTH = 19.43 ft.
FROM GROUND SURFACE
TO TOP OF SCREEN

0.02 INCH SLOTTED
SCREEN SCH 40
(top of screen
approx. 6.49 ft.
above water table)

0.02 INCH SLOTTED
SCREEN SCH 40 WITH
POINTED END CAP
(15 ft. total length;
approx. 8.51 ft. below
water table)

TOTAL DEPTH = 34.43 ft.
FROM GROUND SURFACE

AMOCO PRODUCTION COMPANY

COOPER GC #1E

MONITOR WELL CONSTRUCTION & COMPLETION

INSTALLED WITH MOBILE RIG

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87

BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

MONITOR WELL SCHEMATIC

DRAFTED BY: NJV

INSTALL. DATE: MAR. '98

FILENAME: MW-3R

MONITOR WELL #4

AMOCO PRODUCTION COMPANY
COOPER GC # 1E
MONITOR WELL CONSTRUCTION & COMPLETION
INSTALLED WITH MOBILE RIG

BLAGG ENGINEERING, INC.
CONSULTING PETROLEUM / RECLAMATION SERVICES
P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413
PHONE: (505) 632-1199

MONITOR WELL SCHEMATIC
DRAFTED BY: NJV
DATE: FEB. '97
FILENAME: MW-4

2" DIA. SCH. 40 PVC
WELL CASING WITH SLIP CAP
(approx. 1.35 ft. above
ground surface)

TOTAL CASING
LENGTH = 23.65 ft.
FROM GROUND SURFACE
TO TOP OF SCREEN

WATER TABLE
APPROX. 22.80 ft. FROM
GROUND SURFACE
(measured 6/7/96)


0.02 INCH SLOTTED
SCREEN SCH 40 WITH
POINTED ENC CAP
(5 ft. total length)

TOTAL DEPTH = 28.65 ft.
FROM GROUND SURFACE

BACK FILLED WITH
CLEAN NATIVE SOIL
TO SURFACE

8 TO 12 MESH COLORADO
SILICA SAND
(approx. 2 ft. above
top of screen)

SCREEN INTERVAL SET
INTO EXISTING SOIL &
GROUNDWATER CONDITIONS



MONITOR WELL #5

AMOCO PRODUCTION COMPANY

COOPER GC # 1E

MONITOR WELL CONSTRUCTION & COMPLETION

INSTALLED WITH MOBILE RIG

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87

BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

MONITOR WELL SCHEMATIC

DRAFTED BY: NJV

DATE: FEB. '97

FILENAME: MW-5

2" DIA. SCH. 40 PVC
WELL CASING WITH SLIP CAP
(approx. 2.05 ft. above
ground surface)

TOTAL CASING
LENGTH = 16.45 ft.
FROM GROUND SURFACE
TO TOP OF SCREEN

0.02 INCH SLOTTED
SCREEN SCH 40 WITH
POINTED ENC CAP
(5 ft. total length;
top of screen 1.31 ft.
above groundwater)


TOTAL DEPTH = 21.45 ft.
FROM GROUND SURFACE

BACK FILLED WITH
CLEAN NATIVE SOIL
TO SURFACE

8 TO 12 MESH COLORADO
SILICA SAND
(approx. 2 ft. above
top of screen)

WATER TABLE
APPROX. 17.76 ft. FROM
GROUND SURFACE
(measured 6/7/96)

3.69 ft. SCREEN INTERVAL
SET INTO EXISTING SOIL &
GROUNDWATER CONDITIONS



MONITOR WELL #5R

INSTALLED WITH MOBILE RIG

MONITOR WELL CONSTRUCTION & COMPLETION

COOPER GC #1E

AMOCO PRODUCTION COMPANY

PHONE: (505) 632-1199

BLOOMFIELD, NEW MEXICO 87413

P.O. BOX 87

CONSULTING PETROLEUM / RECLAMATION SERVICES

BLAGG ENGINEERING, INC.

FILENAME:

MW-5R

INSTALL. DATE: MAR. '98

DRAFTED BY: NJV

MONITOR WELL SCHEMATIC

2" DIA. SCH. 40 PVC
WELL CASING WITH SLIP
CAP (approx. 1.40 ft.
above ground surface)

TOTAL CASING
LENGTH = 14.60 ft.
FROM GROUND SURFACE
TO TOP OF SCREEN

0.02 INCH SLOTTED
SCREEN SCH 40
(top of screen
approx. 6.04 ft.
above water table)

0.02 INCH SLOTTED
SCREEN SCH 40 WITH
POINTED END CAP
(15 ft. total length;
approx. 8.96 ft. below
water table)

TOTAL DEPTH = 29.60 ft.
FROM GROUND SURFACE

GROUND
SURFACE


11.60 ft. ANNULAR
COMPLETED WITH EXISTING
CLEAN NATIVE SOIL

1.00 ft. ANNULAR COMPLETED
WITH BENTONITE CHIPS
(11.60-12.60 ft. INTERVAL)

8.04 ft. ANNULAR ABOVE
WATER TABLE COMPLETED
WITH COLORADO SILICA SAND

WATER TABLE
APPROX. 20.64 ft. FROM
GROUND SURFACE
(measured 9/29/98)

9.36 ft. ANNULAR BELOW
WATER TABLE COMPLETED
WITH COLORADO SILICA SAND



P.O. BOX 87
BLOOMFIELD, NM 87413
(505) 632-1199

BORING #.....	BH - 1
MW #.....	2
PAGE #.....	1
DATE STARTED	4/26/96
DATE FINISHED	4/26/96
OPERATOR.....	JCB
PREPARED BY	NJV

LOCATION NAME:	COOPER GC # 1E
CLIENT:	AMOCO PRODUCTION COMPANY
CONTRACTOR:	BLAGG ENGINEERING, INC.
EQUIPMENT USED:	MOBILE DRILL RIG (EARTHPROBE)
BORING LOCATION:	S49E, 30 FEET FROM WELL HEAD.

DEPTH FEET	INTERVAL	LITHOLOGY INTERVAL	MW SCHEMATIC	FIELD CLASSIFICATION AND REMARKS
				GROUND SURFACE
1				TOP OF CASING APPROX. 1.83 FT. ABOVE GROUND SURFACE.
2				
3				
4				
5				
6				
7				
8				
9				
10				DARK YELLOWISH BROWN SAND TO SILTY SAND CONTINUOUS THROUGHOUT ENTIRE BORING, NON COHESIVE, SLIGHTLY MOIST TO SATURATED (AT GROUNDWATER), FIRM, NO APPARENT HYDROCARBON ODOR OBSERVED (0 - 28.17 FT. INTERVAL).
11				
12				
13				
14				
15				
16				
17				
18				
19				▼ GW DEPTH ON 6/7/96 = 19.33 FT. (APPROX.) FROM GROUND SURFACE.
20				
21				
22				
23				
24				
25				
26				
27				
28				
29				
30				
31				

TOS 23.17
 TD 28.17

NOTES: - SAND TO SILTY SAND.
 TOS - TOP OF SCREEN FROM GROUND SURFACE.
 TD - TOTAL DEPTH OF MONITOR WELL FROM GROUND SURFACE.
 GW - GROUND WATER.

DRAWING: COOP1E-2
DATE: 2/07/97
DWN BY: NJV


BLAGG ENGINEERING, Inc.

P.O. BOX 87
BLOOMFIELD, NM 87413
(505) 632-1199

BORE / TEST HOLE REPORT

BORING #..... BH - 2
MW #..... 3
PAGE #..... 2
DATE STARTED 4/26/96
DATE FINISHED 4/26/96
OPERATOR..... JCB
PREPARED BY NJV

LOCATION NAME: COOPER GC # 1E
CLIENT: AMOCO PRODUCTION COMPANY
CONTRACTOR: BLAGG ENGINEERING, INC.
EQUIPMENT USED: MOBILE DRILL RIG (EARTHPROBE)
BORING LOCATION: S40W, 87 FEET FROM WELL HEAD.




BLAGG ENGINEERING, Inc.

P.O. BOX 87
BLOOMFIELD, NM 87413
(505) 632-1199

BORE / TEST HOLE REPORT

LOCATION NAME: COOPER GC # 1E
CLIENT: AMOCO PRODUCTION COMPANY
CONTRACTOR: BLAGG ENGINEERING, INC.
EQUIPMENT USED: MOBILE DRILL RIG (EARTHPROBE)
BORING LOCATION: S15W, 126 FEET FROM WELL HEAD.

BORING #..... BH - 3
MW #..... 4
PAGE #..... 3
DATE STARTED 4/28/96
DATE FINISHED 4/28/96
OPERATOR..... JCB
PREPARED BY NJV




BLAGG ENGINEERING, Inc.

P.O. BOX 87
BLOOMFIELD, NM 87413
(505) 632-1199

BORE / TEST HOLE REPORT

LOCATION NAME: COOPER GC # 1E
CLIENT: AMOCO PRODUCTION COMPANY
CONTRACTOR: BLAGG ENGINEERING, INC.
EQUIPMENT USED: MOBILE DRILL RIG (EARTHPROBE)
BORING LOCATION: S22W, 189 FEET FROM WELL HEAD.

BORING #..... BH - 4
MW #..... 5
PAGE #..... 4
DATE STARTED 4/29/96
DATE FINISHED 4/29/96
OPERATOR..... JCB
PREPARED BY NJV



DRAWING: COOP1E-5

DATE: 2/07/97

DWN BY: NJV

BLAGG ENGINEERING, Inc.

P.O. BOX 87
BLOOMFIELD, NM 87413
(505) 632-1199

BORE / TEST HOLE REPORT

BORING #..... BH - 5
MW #..... 2R
PAGE #..... 5
DATE STARTED 3/30/98
DATE FINISHED 3/30/98
OPERATOR..... JCB
PREPARED BY NJV

LOCATION NAME: COOPER GC # 1E
CLIENT: AMOCO PRODUCTION COMPANY
CONTRACTOR: BLAGG ENGINEERING, INC.
EQUIPMENT USED: MOBILE DRILL RIG (EARTHPROBE)
BORING LOCATION: S18E, 108 FEET FROM WELL HEAD.

DEPTH FEET	INTERVAL	LITHOLOGY INTERVAL	MW SCHEMATIC	FIELD CLASSIFICATION AND REMARKS
				GROUND SURFACE
1				TOP OF CASING APPROX. 1.10 FT. ABOVE GROUND SURFACE.
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15			TOS 14.90	
16				
17				
18				
19				
20				
21				
22				
23				
24				
25			TD 24.90	
26				
27				
28				
29				
30				
31				

DARK YELLOWISH BROWN SAND TO SILTY SAND CONTINUOUS THROUGHOUT ENTIRE BORING. NON COHESIVE TO COHESIVE. SLIGHTLY MOIST TO SATURATED (IN GROUNDWATER). FIRM TO LOOSE. NO APPARENT DISCOLORATION OBSERVED OR HYDROCARBON ODOR DETECTED (0.0 - 25.00 FT. INTERVAL).

▼ GW DEPTH ON 3/31/98 = 21.44 FT. (APPROX.) FROM GROUND SURFACE.

NOTES:  - SAND TO SILTY SAND.
TOS - TOP OF SCREEN FROM GROUND SURFACE.
TD - TOTAL DEPTH OF MONITOR WELL FROM GROUND SURFACE.
GW - GROUND WATER.

BLAGG ENGINEERING, Inc.

P.O. BOX 87
BLOOMFIELD, NM 87413
(505) 632-1199

BORE / TEST HOLE REPORT

BORING #..... BH - 6

MW #..... 3R

LOCATION NAME: COOPER GC # 1E

CLIENT: AMOCO PRODUCTION COMPANY

CONTRACTOR: BLAGG ENGINEERING, INC.

EQUIPMENT USED: MOBILE DRILL RIG (EARTHPROBE)

BORING LOCATION: S43.5W, 110.5 FEET FROM WELL HEAD.

PAGE #..... 6

DATE STARTED 3/31/98

DATE FINISHED 3/31/98

OPERATOR..... MC

PREPARED BY NJV

DEPTH FEET	INTERVAL	LITHOLOGY INTERVAL	MW SCHEMATIC	FIELD CLASSIFICATION AND REMARKS
				GROUND SURFACE
1				TOP OF CASING APPROX. 0.40 FT. BELOW GROUND SURFACE.
2				
3				DARK YELLOWISH BROWN SAND TO SILTY SAND, NON COHESIVE TO COHESIVE, SLIGHTLY MOIST, FIRM, NO APPARENT DISCOLORATION OBSERVED OR HYDROCARBON ODOR DETECTED (0.0 - 7.00 FT. INTERVAL).
4				
5				
6				
7				
8				DARK YELLOWISH BROWN CLAY, PLASTIC TO HIGHLY PLASTIC (9.0 - 11.0 FT. INTERVAL), SLIGHTLY MOIST, FIRM TO STIFF, NO APPARENT DISCOLORATION OBSERVED OR HYDROCARBON ODOR DETECTED (7.0 - 11.00 FT. INTERVAL).
9				
10				
11				
12				DARK YELLOWISH BROWN SAND TO SILTY SAND, NON COHESIVE TO COHESIVE, SLIGHTLY MOIST, FIRM, NO APPARENT DISCOLORATION OBSERVED OR HYDROCARBON ODOR DETECTED (11.0 - 15.00 FT. INTERVAL).
13				
14				
15				
16				DARK YELLOWISH BROWN SILTY SAND PHASING INTO CLAY, NON COHESIVE TO PLASTIC, SLIGHTLY MOIST TO SATURATED, FIRM TO STIFF, DISCOLORATION OBSERVED WITH STRONG HYDROCARBON ODOR DETECTED BETWEEN (18.0 - 26.00 FT. INTERVAL), TOTAL INTERVAL (15.0 - 26.0 FT.).
17				
18				
19				
20				
21				
22				
23				
24				OLIVE GRAY CLAY, HIGHLY PLASTIC, SATURATED, STIFF, NO APPARENT DISCOLORATION OBSERVED OR HYDROCARBON ODOR DETECTED, (26.0 - 35.0 FT. INTERVAL).
25				
26				
27				
28				
29				
30				
31				

▼ GW DEPTH ON 3/31/98 = 25.92 FT. (APPROX.) FROM GROUND SURFACE.

NOTES:

- SAND TO SILTY SAND.
- SILTY SAND TO CLAY.
- CLAY.
- TOS - TOP OF SCREEN FROM GROUND SURFACE.
- TD - TOTAL DEPTH OF MONITOR WELL FROM GROUND SURFACE.
- GW - GROUND WATER.

DRAWING: COOP-3R

DATE: 4/20/98

DWN BY: NJV


BLAGG ENGINEERING, Inc.

P.O. BOX 87
BLOOMFIELD, NM 87413
(505) 632-1199

BORE / TEST HOLE REPORT

LOCATION NAME: COOPER GC # 1E
CLIENT: AMOCO PRODUCTION COMPANY
CONTRACTOR: BLAGG ENGINEERING, INC.
EQUIPMENT USED: MOBILE DRILL RIG (EARTHPROBE)
BORING LOCATION: S20W, 185.5 FEET FROM WELL HEAD.

BORING #..... BH - 7
MW #..... 5R
PAGE #..... 6
DATE STARTED 3/31/98
DATE FINISHED 4/1/98
OPERATOR..... MC
PREPARED BY NJV



BLAGG ENGINEERING, INC.

FIELD BORING LOG

TEST BORING No. TH1	MONITOR WELL No. —	PROJECT No.	PROJECT NAME: Amoco	SHEET: 1 OF 1
MFG DESIGNATION OF DRILL: BLAGG DRILL RIG			PROJECT LOCATION: COOPER GC IE	
TYPE OF BIT: 3" AUGER			SURFACE ELEVATION OF TB OR MW:	TOTAL DEPTH OF HOLE: 25'
DATE: 9-19-96	TIME STARTED:	TIME COMPLETED:	DRILLING Co.: BLAGG	
COMPLETION TYPE: BACKFILLED		ENGINEER: RED	CREW: JCB	GROUNDWATER DEPTH: _____ TIME: _____

SURFACE CONDITIONS:

DIST FROM SURF.	SAMPLE TYPE	SAMPLE No.	OVM READ IN PPM	BLOWS PER 6 IN.	USCS	LOG OF MATERIAL/COMMENTS
2					SW	MOLT, BROWN, WELL GRADED SAND - NO STAIN, NO ODSR
4						
6						
8						
10						
12						
14						
16						APPROX. WATER SAMPLE COLLECTED
18						
20						
22						
24						TD = 23'
26						
28						
30						

FIELD BORING LOG

TEST BORING No. TH2	MONITOR WELL No.	PROJECT No.	PROJECT NAME: AMOCO	SHEET: 1 OF 1		
MFG. DESIGNATION OF DRILL: BLAGG DRILL RIG			PROJECT LOCATION: COOPER GC IE			
TYPE OF BIT: 3" AUGER			SURFACE ELEVATION OF TB OR MW:	TOTAL DEPTH OF HOLE: 20'		
DATE: 9-19-96	TIME STARTED:	TIME COMPLETED:	DRILLING Co.: BLAGG			
COMPLETION TYPE: BACKFILLED		ENGINEER: REO	CREW: JCB	GROUNDWATER DEPTH: _____ TIME: _____		
SURFACE CONDITIONS:						
DIST FROM SURF.	SAMPLE TYPE	SAMPLE No.	OVM READ IN PPM	BLOWS PER 6 IN.	USCS	LOG OF MATERIAL/COMMENTS
2					SW	MOIST BROWN, WELL GRADED SAND - NO STAIN, NO GISP
4						
6						
8						
10						
12						
14					▽	~APPROX. WATER SAMPLE COLLECTED
16						
18						
20						TD = 20'
22						
24						
26						
28						
30						

FIELD BORING LOG

TEST BORING No. TA3	MONITOR WELL No. 6	PROJECT No.	PROJECT NAME: AMOCO	SHEET: 1 OF 1		
MFG. DESIGNATION OF DRILL: BLAGG DRILL RIG			PROJECT LOCATION: COOPER GC IE			
TYPE OF BIT: 3" AUGER			SURFACE ELEVATION OF TB OR MW:	TOTAL DEPTH OF HOLE: 20'		
DATE: 9-19-86	TIME STARTED:	TIME COMPLETED:	DRILLING Co.: BLAGG			
COMPLETION TYPE: MONITOR WELL		ENGINEER: REO	CREW: JCB	GROUNDWATER DEPTH: _____ TIME: _____		
SURFACE CONDITIONS:						
DIST FROM SURF.	SAMPLE TYPE	SAMPLE NO.	OVM READ IN PPM	BLOWS PER 6 IN.	USCS	LOG OF MATERIAL/COMMENTS
2					SW	MOLT. BROWN, WELL GRADED SAND - NO COB, NO GRAV
4						
6						
8						
10						
12						
14						
16						APPROX WATER SAMPLE COLLECTED
18						
20						T.D. = 20'
22						
24						
26						
28						
30						

(505) 632-1199

PAGE #..... 1


LOCATION NAME:	COOPER GC # 1E
CLIENT:	CROSS TIMBERS OIL COMPANY
CONTRACTOR:	BLAGG ENGINEERING, INC. / ENVIROTECH, INC.
EQUIPMENT USED:	MOBILE DRILL RIG
BORING LOCATION:	SEE AIR SPARGING SITE SCHEMATIC.

DATE STARTED 3/31/98

DATE FINISHED 4/01/98

OPERATOR..... MC

PREPARED BY..... NJV



AS-1 = AIR SPARGE POINT DESIGNATION.

S = NON COHESIVE SAND.

C = SLIGHTLY TO HIGHLY PLASTIC CLAY.

SC = COHESIVE TO SLIGHTLY PLASTIC SILTY CLAY.

SS = NON COHESIVE TO SLIGHTLY COHESIVE SILTY SAND.

▼ - INDICATES APPROX. WATER TABLE DEPTH.

BLAGG ENGINEERING, Inc.

P.O. BOX 87
BLOOMFIELD, NM 87413
(505) 632-1199

AIR SPARGE SYSTEM BORE HOLE SCHEMATIC

PAGE #..... 2


LOCATION NAME: COOPER GC # 1E
CLIENT: CROSS TIMBERS OIL COMPANY
CONTRACTOR: BLAGG ENGINEERING, INC. / ENVIROTECH, INC.
EQUIPMENT USED: MOBILE DRILL RIG
BORING LOCATION: SEE AIR SPARGING SITE SCHEMATIC.

DATE STARTED 3/31/98

DATE FINISHED 4/01/98

OPERATOR..... MC

PREPARED BY..... NJV



LEGEND

AS-1 = AIR SPARGE POINT DESIGNATION.
S = NON COHESIVE SAND.
C = SLIGHTLY TO HIGHLY PLASTIC CLAY.
SC = COHESIVE TO SLIGHTLY PLASTIC SILTY CLAY.
SS = NON COHESIVE TO SLIGHTLY COHESIVE SILTY SAND.
PC = HIGHLY PLASTIC CLAY.
(ds 19') = DISCOLORED SOIL WITH TOP INTERVAL STATED.
▽ = INDICATES APPROX. WATER TABLE DEPTH.

DRAWING: 1E-AS-2

DATE: 3/22/00

DWN BY: NJV

BLAGG ENGINEERING, Inc.

P.O. BOX 87

BLOOMFIELD, NM 87413

(505) 632-1199

AIR SPARGE SYSTEM BORE HOLE SCHEMATIC

PAGE #..... 3


LOCATION NAME: COOPER GC # 1E
CLIENT: CROSS TIMBERS OIL COMPANY
CONTRACTOR: BLAGG ENGINEERING, INC.
EQUIPMENT USED: MOBILE DRILL RIG
BORING LOCATION: SEE AIR SPARGING SITE SCHEMATIC.

DATE STARTED 9/12/00

DATE FINISHED 9/12/00

OPERATOR..... JCB

PREPARED BY..... NJV



LEGEND

AS-12 = AIR SPARGE POINT DESIGNATION.

S = NON COHESIVE SAND.


SS = NON COHESIVE TO SLIGHTLY COHESIVE SILTY SAND.

C = SLIGHTLY TO HIGHLY PLASTIC CLAY.

PC = HIGHLY PLASTIC CLAY.

▼ - INDICATES APPROX. WATER TABLE DEPTH.

SIMPLISTIC AIR SPARGE POINT CONSTRUCTION



AMOCO PRODUCTION COMPANY

COOPER GC # 1E

NW/4 SE/4 SEC. 15, T29N, R11W

SAN JUAN COUNTY, NEW MEXICO

BLAGG ENGINEERING, INC.

CONSULTING PETROLEUM / RECLAMATION SERVICES

P.O. BOX 87
BLOOMFIELD, NEW MEXICO 87413

PHONE: (505) 632-1199

PROJECT: RECLAM. SYS.

DRAWN BY: NJV

FILENAME: ASP-TEMP

DRAFTED: 3/22/00 NJV

AIR
SPARGE
POINT

3/00

BLAGG ENGINEERING, INC.
MONITOR WELL SAMPLING DATA

CLIENT : AMOCO PRODUCTION CO.

CHAIN-OF-CUSTODY # : 2481

COOPER GC #1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ANAITAS

Date : June 7, 1996

SAMPLER : RE O

Filename : 06-07-96.WK4

PROJECT MANAGER : RE O

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING	pH TIME	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
2	101.88	80.72	21.16	30.00	1010	7.3	900	2.00	-
3	101.28	79.06	22.22	30.00	1040	6.9	2,000	1.50	-
4	101.32	77.17	24.15	30.00	1110	6.8	800	3.00	-
5	95.22	75.41	19.81	23.50	1140	6.8	1,100	1.50	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$
(i.e. 2" MW $r = (1/12) \text{ ft.}$ $h = 1 \text{ ft.}$) (i.e. 4" MW $r = (2/12) \text{ ft.}$ $h = 1 \text{ ft.}$)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 "

PURGEABLE AROMATICSBlagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: MW - 2
Lab ID: 3810
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 06/24/96
Date Sampled: 06/07/96
Date Received: 06/07/96
Date Analyzed: 06/20/96

Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	ND	0.50
Toluene	ND	0.50
Ethylbenzene	ND	0.50
m,p-Xylenes	ND	1.00
o-Xylene	ND	0.50


Total BTEX	ND
------------	----

ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	94	88 - 110%
	Bromofluorobenzene	96	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209,
Oct. 1984.

Comments:


Analyst


Review

PURGEABLE AROMATICSBlagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: MW - 3
Lab ID: 3811
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 06/24/96
Date Sampled: 06/07/96
Date Received: 06/07/96
Date Analyzed: 06/20/96

Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	2,290	125
Toluene	5,410	125
Ethylbenzene	1,460	125
m,p-Xylenes	13,420	500
o-Xylene	2,590	125


Total BTEX	25,200
------------	--------


ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	93	88 - 110%
	Bromofluorobenzene	96	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209,
Oct. 1984.

Comments:


Analyst


Review

PURGEABLE AROMATICSBlagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: MW - 4
Lab ID: 3812
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 06/24/96
Date Sampled: 06/07/96
Date Received: 06/07/96
Date Analyzed: 06/20/96


Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	2,900	125
Toluene	18,220	500
Ethylbenzene	937	125
m,p-Xylenes	11,180	250
o-Xylene	2,740	125
Total BTEX		36,000

ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	93	88 - 110%
	Bromofluorobenzene	95	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209,
Oct. 1984.

Comments:


Analyst


Review

PURGEABLE AROMATICSBlagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: MW - 5
Lab ID: 3813
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 06/25/96
Date Sampled: 06/07/96
Date Received: 06/07/96
Date Analyzed: 06/21/96


Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	9,940	500
Toluene	24,260	500
Ethylbenzene	962	500
m,p-Xylenes	8,070	1,000
o-Xylene	2,180	500

Total BTEX	45,400
------------	--------

ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	97	88 - 110%
	Bromofluorobenzene	98	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209,
Oct. 1984.

Comments:
Analyst
Review

General Water Quality Blagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: MW - 2
Laboratory ID: 3810
Sample Matrix: Water

Date Reported: 06/24/96
Date Sampled: 06/07/96
Time Sampled: 10:10
Date Received: 06/07/96

Parameter	Analytical Result	Units
General		
Lab pH.....	7.6	s.u.
Lab Conductivity @ 25° C.....	1,660	µmhos/cm
Total Dissolved Solids @ 180°C.....	1,110	mg/L
Total Dissolved Solids (Calc).....	1,010	mg/L
Anions		
Total Alkalinity as CaCO ₃	191	mg/L
Bicarbonate Alkalinity as CaCO ₃	191	mg/L
Carbonate Alkalinity as CaCO ₃	NA	mg/L
Hydroxide Alkalinity as CaCO ₃	NA	mg/L
Chloride.....	1.67	mg/L
Sulfate.....	581	mg/L
Nitrate + Nitrite - N.....	NA	
Nitrate - N.....	NA	
Nitrite - N.....	NA	
Cations		
Total Hardness as CaCO ₃	556	mg/L
Calcium.....	202	mg/L
Magnesium.....	12.3	mg/L
Potassium.....	< 5.0	mg/L
Sodium.....	100	mg/L
Data Validation		<u>Acceptance Level</u>
Cation/Anion Difference.....	1.46	+/- 5 %
TDS (180):TDS (calculated).....	1.1	1.0 - 1.2

Reference U.S.E.P.A. 600/4-79-020, Methods for Chemical Analysis of Water and Wastes, 1983.
Standard Methods For The Examination Of Water And Wastewater, 18th ed., 1992.


Review

General Water Quality

Blagg Engineering, Inc.

Project ID: Cooper GC 1E
 Sample ID: MW - 3
 Laboratory ID: 3811
 Sample Matrix: Water

Date Reported: 06/24/96
 Date Sampled: 06/07/96
 Time Sampled: 10:40
 Date Received: 06/07/96

Parameter	Analytical Result	Units
General		
Lab pH.....	7.3	s.u.
Lab Conductivity @ 25° C.....	2,760	µmhos/cm
Total Dissolved Solids @ 180°C.....	2,090	mg/L
Total Dissolved Solids (Calc).....	1,920	mg/L
Anions		
Total Alkalinity as CaCO ₃	334	mg/L
Bicarbonate Alkalinity as CaCO ₃	334	mg/L
Carbonate Alkalinity as CaCO ₃	NA	mg/L
Hydroxide Alkalinity as CaCO ₃	NA	mg/L
Chloride.....	1.67	mg/L
Sulfate.....	1,140	mg/L
Nitrate + Nitrite - N.....	NA	
Nitrate - N.....	NA	
Nitrite - N.....	NA	
Cations		
Total Hardness as CaCO ₃	859	mg/L
Calcium.....	308	mg/L
Magnesium.....	22.1	mg/L
Potassium.....	< 5.0	mg/L
Sodium.....	240	mg/L
Data Validation		<u>Acceptance Level</u>
Cation/Anion Difference.....	4.94	+/- 5 %
TDS (180):TDS (calculated).....	1.1	1.0 - 1.2

Reference U.S.E.P.A. 600/4-79-020, Methods for Chemical Analysis of Water and Wastes, 1983.
Standard Methods For The Examination Of Water And Wastewater, 18th ed., 1992.


 Review

General Water Quality


Blagg Engineering, Inc.

Project ID: Cooper GC 1E
 Sample ID: MW - 4
 Laboratory ID: 3812
 Sample Matrix: Water

Date Reported: 06/24/96
 Date Sampled: 06/07/96
 Time Sampled: 11:10
 Date Received: 06/07/96

Parameter	Analytical Result	Units
General		
Lab pH.....	7.4	s.u.
Lab Conductivity @ 25° C.....	829	µmhos/cm
Total Dissolved Solids @ 180°C.....	323	mg/L
Total Dissolved Solids (Calc).....	319	mg/L
Anions		
Total Alkalinity as CaCO ₃	263	mg/L
Bicarbonate Alkalinity as CaCO ₃	263	mg/L
Carbonate Alkalinity as CaCO ₃	NA	mg/L
Hydroxide Alkalinity as CaCO ₃	NA	mg/L
Chloride.....	4.17	mg/L
Sulfate.....	37.0	mg/L
Nitrate + Nitrite - N.....	NA	
Nitrate - N.....	NA	
Nitrite - N.....	NA	
Cations		
Total Hardness as CaCO ₃	222	mg/L
Calcium.....	72.9	mg/L
Magnesium.....	9.82	mg/L
Potassium.....	< 5.0	mg/L
Sodium.....	37.0	mg/L
Data Validation		<u>Acceptance Level</u>
Cation/Anion Difference.....	0.51	+/- 2 %
TDS (180):TDS (calculated).....	1.0	1.0 - 1.2

Reference U.S.E.P.A. 600/4-79-020, Methods for Chemical Analysis of Water and Wastes, 1983.
Standard Methods For The Examination Of Water And Wastewater, 18th ed., 1992.


 Review

General Water Quality


Blagg Engineering, Inc.

Project ID: Cooper GC 1E
 Sample ID: MW - 5
 Laboratory ID: 3813
 Sample Matrix: Water

Date Reported: 06/24/96
 Date Sampled: 06/07/96
 Time Sampled: 11:40
 Date Received: 06/07/96

Parameter		Analytical Result	Units
General	Lab pH.....	7.4	s.u.
	Lab Conductivity @ 25° C.....	986	µmhos/cm
	Total Dissolved Solids @ 180°C.....	595	mg/L
	Total Dissolved Solids (Calc).....	588	mg/L
Anions	Total Alkalinity as CaCO ₃	501	mg/L
	Bicarbonate Alkalinity as CaCO ₃	501	mg/L
	Carbonate Alkalinity as CaCO ₃	NA	mg/L
	Hydroxide Alkalinity as CaCO ₃	NA	mg/L
	Chloride.....	35.8	mg/L
	Sulfate.....	11.5	mg/L
	Nitrate + Nitrite - N.....	NA	
	Nitrate - N.....	NA	
Cations	Nitrite - N.....	NA	
	Total Hardness as CaCO ₃	465	mg/L
	Calcium.....	158	mg/L
	Magnesium.....	17.2	mg/L
	Potassium.....	< 5.0	mg/L
Data Validation	Sodium.....	65.0	mg/L
			<u>Acceptance Level</u>
	Cation/Anion Difference.....	3.60	+/- 5 %
	TDS (180):TDS (calculated).....	1.0	1.0 - 1.2

Reference U.S.E.P.A. 600/4-79-020, Methods for Chemical Analysis of Water and Wastes, 1983.
Standard Methods For The Examination Of Water And Wastewater, 18th ed., 1992.



Review



June 25, 1996

Bob O'Neill
Blagg Engineering, Inc.
PO Box 87
Bloomfield, NM 87413

Dear Mr. O'Neill:

Enclosed are the results for the analysis of the samples received June 7, 1996. The samples were from the Cooper GC 1E site. Analyses for Benzene, Toluene, Ethylbenzene, and Xylenes (BTEX) and general water quality parameters were performed on the samples, as per the accompanying chain of custody form.

Analysis was performed on the samples according to EPA Method 602, using a Hewlett-Packard 5890 gas chromatograph equipped with an OI Analytical purge and trap (model 4560) and a photoionization detector. Detectable levels of btex analytes were found in the samples, as reported.

Water parameters were determined for the samples according to the appropriate methodologies as outlined in Standard Methods for the Examination of Water and Wastewater, 18th edition, 1992.

Quality control reports appear at the end of the analytical package and can be identified by title. Should you have any questions regarding the analysis, feel free to call.

Sincerely,

A handwritten signature in black ink, appearing to read "Denise A. Bohemier".

Denise A. Bohemier
Lab Director

PURGEABLE AROMATICS

Quality Control Report

Method Blank Analysis

Sample Matrix: Water
Lab ID: MB35236

Report Date: 06/24/96
Date Analyzed: 06/20/96


Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	ND	0.50
Toluene	ND	0.50
Ethylbenzene	ND	0.50
m,p-Xylenes	ND	1.00
o-Xylene	ND	0.50


ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	98	88 - 110%
	Bromofluorobenzene	100	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

PURGEABLE AROMATICS

Quality Control Report

Method Blank Analysis

Sample Matrix: Water
Lab ID: MB35237

Report Date: 06/24/96
Date Analyzed: 06/21/96

Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	ND	0.50
Toluene	ND	0.50
Ethylbenzene	ND	0.50
m,p-Xylenes	ND	1.00
o-Xylene	ND	0.50


ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	99	88 - 110%
	Bromofluorobenzene	99	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

Purgeable Aromatics

Duplicate Analysis

Lab ID: 3808Dup
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 06/24/96
Date Sampled: 06/07/96
Date Received: 06/07/96
Date Analyzed: 06/20/96

Target Analyte	Original Conc. (ug/L)	Duplicate Conc. (ug/L)	Acceptance Range (ug/L)
Benzene	347	339	280 - 406
Toluene	28.5	26.2	21.5 - 33.2
Ethylbenzene	156	148	99.4 - 205
m,p-Xylenes	1,580	1,550	NE
o-Xylene	ND	ND	NE

ND - Analyte not detected at the stated detection limit.


NA - Not applicable or not calculated.

NE - Duplicate acceptance range not established by the EPA.

	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
Quality Control:	Trifluorotoluene	99	88 - 110%
	Bromofluorobenzene	97	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

Purgeable Aromatics

Matrix Spike Analysis

Lab ID: 3807Spk
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 06/24/96
Date Sampled: 06/07/96
Date Received: 06/07/96
Date Analyzed: 06/20/96

Target Analyte	Spike Added (ug/L)	Original Conc. (ug/L)	Spiked Sample Conc. (ug/L)	% Recovery	Acceptance Limits (%)
Benzene	10	ND	10.5	101%	39 - 150
Toluene	10	1.84	11.5	97%	46 - 148
Ethylbenzene	10	ND	10.5	103%	32 - 160
m,p-Xylenes	20	ND	20.9	102%	NE
o-Xylene	10	ND	10.2	98%	NE

ND - Analyte not detected at the stated detection limit.


NA - Not applicable or not calculated.

NE - Spike acceptance range not established by the EPA.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	103	88 - 110%
	Bromofluorobenzene	104	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

Purgeable Aromatics

Duplicate Analysis

Lab ID: 3813Dup
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 06/24/96
Date Sampled: 06/07/96
Date Received: 06/07/96
Date Analyzed: 06/21/96

Target Analyte	Original Conc. (ug/L)	Duplicate Conc. (ug/L)	Acceptance Range (ug/L)
Benzene	9,940	9,930	8,150 - 11,700
Toluene	24,260	24,350	19,930 - 28,700
Ethylbenzene	962	957	632 - 1,290
m,p-Xylenes	8,070	8,110	NE
o-Xylene	2,180	2,140	NE

ND - Analyte not detected at the stated detection limit.


NA - Not applicable or not calculated.


NE - Duplicate acceptance range not established by the EPA.

	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
Quality Control:	Trifluorotoluene	96	88 - 110%
	Bromofluorobenzene	99	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

Purgeable Aromatics

Matrix Spike Analysis

Lab ID: 3883Spk
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 06/24/96
Date Sampled: 06/10/96
Date Received: 06/10/96
Date Analyzed: 06/21/96

Target Analyte	Spike Added (ug/L)	Original Conc. (ug/L)	Spiked Sample Conc. (ug/L)	% Recovery	Acceptance Limits (%)
Benzene	10	ND	10.1	101%	39 - 150
Toluene	10	0.58	10.4	98%	46 - 148
Ethylbenzene	10	ND	10.7	104%	32 - 160
m,p-Xylenes	20	ND	20.4	100%	NE
o-Xylene	10	ND	10.2	99%	NE

ND - Analyte not detected at the stated detection limit.


NA - Not applicable or not calculated.

NE - Spike acceptance range not established by the EPA.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	96	88 - 110%
	Bromofluorobenzene	99	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

General Water Quality Quality Control Report


Blagg Engineering, Inc.

Report Date: 6/24/96

Parameter	Analytical Result	Certified Value	Acceptance Range	Units
Laboratory pH	8.96	9.05	8.85 - 9.25	s.u.
Conductivity	1323	1210	1030 - 1400	µmhos/cm
Total Dissolved Solids	900	905	787 - 1020	mg/L
Total Alkalinity	167	174	155 - 193	mg/L
Chloride	152	155	144 - 166	mg/L
Sulfate	107	116	99.8 - 132	mg/L
Total Hardness	232	254	218 - 290	mg/L
Calcium	60.7	54.6	47.0 - 62.2	mg/L
Magnesium	NA	NA	NA	mg/L
Potassium	110	112	95.2 - 129	mg/L
Sodium	180	180	153 - 207	mg/L

Reference: U.S.E.P.A. 600/4-79-020, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination Of Water And Wastewater, 18th ed., 1992.

Comments:



Review

PURGEABLE AROMATICSBlagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: TH - 1
Lab ID: 5125
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 09/20/96
Date Sampled: 09/19/96
Date Received: 09/19/96
Date Analyzed: 09/19/96

Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	1,200	20.0
Toluene	1.03	0.20
Ethylbenzene	4.52	0.20
m,p-Xylenes	19.9	0.40
o-Xylene	29.1	2.00

Total BTEX	1,250
-------------------	--------------


ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	111	88 - 110%
	Bromofluorobenzene	103	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments: High toluene-d8 recovery is due to hydrocarbon interference at the d8 retention time.


Analyst


Review

PURGEABLE AROMATICSBlagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: TH - 2
Lab ID: 5126
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 09/20/96
Date Sampled: 09/19/96
Date Received: 09/19/96
Date Analyzed: 09/19/96


Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	0.99	0.20
Toluene	0.24	0.20
Ethylbenzene	ND	0.20
m,p-Xylenes	0.45	0.40
o-Xylene	ND	0.20

Total BTEX	1.68
-------------------	-------------

ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	105	88 - 110%
	Bromofluorobenzene	105	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209,
Oct. 1984.

Comments:
Analyst
Review

PURGEABLE AROMATICSBlagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: TH - 3 - MW #6
Lab ID: 5127
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 09/20/96
Date Sampled: 09/19/96
Date Received: 09/19/96
Date Analyzed: 09/19/96

Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	0.92	0.20
Toluene	0.91	0.20
Ethylbenzene	0.49	0.20
m,p-Xylenes	1.64	0.40
o-Xylene	0.51	0.20
Total BTEX		4.46

ND - Analyte not detected at the stated detection limit.

Quality Control:	Surrogate	Percent Recovery	Acceptance Limits
	Trifluorotoluene	105	88 - 110%
	Bromofluorobenzene	105	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209,
Oct. 1984.

Comments:


Analyst


Review

PURGEABLE AROMATICSBlagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: MW - 5
Lab ID: 5128
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 09/20/96
Date Sampled: 09/19/96
Date Received: 09/19/96
Date Analyzed: 09/19/96

Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	7,860	200
Toluene	7,160	200
Ethylbenzene	364	20.0
m,p-Xylenes	2,850	40.0
o-Xylene	742	20.0

Total BTEX	19,000
-------------------	---------------


ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	99	88 - 110%
	Bromofluorobenzene	100	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209,
Oct. 1984.

Comments:

Analyst



Review

PURGEABLE AROMATICSBlagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: TH - 4 - mw #7
Lab ID: 5131
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 09/25/96
Date Sampled: 09/23/96
Date Received: 09/23/96
Date Analyzed: 09/24/96


Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	3,550	100
Toluene	2,100	100
Ethylbenzene	319	100
m,p-Xylenes	1,730	200
o-Xylene	396	100

Total BTEX	8,100
-------------------	--------------


ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	105	88 - 110%
	Bromofluorobenzene	102	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209,
Oct. 1984.

Comments:

Analyst



Review

PURGEABLE AROMATICS

Blagg Engineering, Inc.

Project ID: Cooper GC 1E
 Sample ID: TH - 5 *mw # 8*
 Lab ID: 5132
 Sample Matrix: Water
 Preservative: Cool, HgCl₂
 Condition: Intact

Report Date: 09/25/96
 Date Sampled: 09/23/96
 Date Received: 09/23/96
 Date Analyzed: 09/24/96


Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	0.56	0.50
Toluene	1.71	0.50
Ethylbenzene	4.79	0.50
m,p-Xylenes	8.39	1.00
o-Xylene	3.56	0.50
Total BTEX		19.0

ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	103	88 - 110%
	Bromofluorobenzene	101	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


 Analyst


 Review

PURGEABLE AROMATICS

Blagg Engineering, Inc.

Project ID: Cooper GC 1E
Sample ID: TH - 6 *mw # 9*
Lab ID: 5133
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 09/25/96
Date Sampled: 09/23/96
Date Received: 09/23/96
Date Analyzed: 09/24/96

Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	14.0	0.50
Toluene	1.05	0.50
Ethylbenzene	ND	0.50
m,p-Xylenes	ND	1.00
o-Xylene	ND	0.50


Total BTEX	15.1
-------------------	-------------

ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	105	88 - 110%
	Bromofluorobenzene	103	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

ENVIRONMENTAL LABORATORY

PROJECT MANAGER: R. E. O'NEILL

Analytica Lab I.D.: _____

Company: BUAGG ENGF.
Address:

Phone: 632-1199
Fax: /

Bill To: SAwt
Company:
Address:

Petroleum Hydrocarbons (418.1)	ORGANIC ANALYSES
Gasoline / Diesel (mod. 8015)	
Gasoline (GRO)	
Aromatic HCs <u>BTEX/MTBE</u> (602/8020)	
Chlorinated Hydrocarbons (8010)	
SDWA Volatiles (502.1/503.1)	
Chlorinated Pesticides / PCBs (608 / 8080)	
Herbicides (615 / 8150)	
Volatiles GC/MS (624 / 8240 / 8260)	
Base / Neutral / Acid GC/MS (625 / 8270)	
Polynuclear Aromatic Hydrocarbons (8100)	WATER ANALYSES
TCLP Extraction	
Other (specify):	
Cation / Anion	
Specific Cations (specify):	
Specific Anions (specify):	METALS
BOD / Fecal / Total Coliform	
Solids : TDS / TSS / SS	
Nutrients: NH ₄ ⁺ / NO ₂ ⁻ / NO ₃ ⁻ / TKN	
Oil and Grease	
Other (specify):	
Priority Pollutants	
RCRA Metals (Total)	
RCRA Metals TCLP (1311)	
Other (specify):	

Please Fill Out Thoroughly.

Shaded areas for lab use only

White/Yellow: Analytica
Pink: Client



September 20, 1996

Bob O'Neill
Blagg Engineering, Inc.
PO Box 87
Bloomfield, NM 87413

Dear Mr. O' Neill:

Enclosed are the results for the analysis of the samples received September 23, 1996. The samples were from the Cooper GC 1E location. Analysis for Benzene, Toluene, Ethylbenzene, and Xylenes (BTEX) was performed on the samples, as per the accompanying chain of custody form.

Analysis was performed on the samples according to EPA Method 602, using a Hewlett-Packard 5890 gas chromatograph equipped with an OI Analytical purge and trap (model 4560) and a photoionization detector. Detectable levels of btx analytes were found in the samples, as reported.

Quality control reports appear at the end of the analytical package and can be identified by title. Should you have any questions regarding the analysis, feel free to call.

Sincerely,

A handwritten signature in black ink, appearing to read "Denise A. Bohemier".

Denise A. Bohemier
Lab Director

PURGEABLE AROMATICS

Quality Control Report

Method Blank Analysis

Sample hydrocarbon: Water
Lab ID: MB35327

Report Date: 09/20/96
Date Analyzed: 09/19/96


Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	ND	0.20
Toluene	ND	0.20
Ethylbenzene	ND	0.20
m,p-Xylenes	ND	0.40
o-Xylene	ND	0.20


ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	102	88 - 110%
	Bromofluorobenzene	102	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

Purgeable Aromatics

Duplicate Analysis

Lab ID: 5125Dup
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 09/20/96
Date Sampled: 09/19/96
Date Received: 09/19/96
Date Analyzed: 09/19/96

Target Analyte	Original Conc. (ug/L)	Duplicate Conc. (ug/L)	Acceptance Range (ug/L)
Benzene	1,200	1,200	980 - 1,420
Toluene	1.03	0.88	0 - 2.09
Ethylbenzene	4.52	4.26	1.98 - 6.80
m,p-Xylenes	19.9	18.9	NE
o-Xylene	29.1	25.3	NE

ND - Analyte not detected at the stated detection limit.

NA - Not applicable or not calculated.


NE - Duplicate acceptance range not established by the EPA.

	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
Quality Control:	Trifluorotoluene	108	88 - 110%
	Bromofluorobenzene	103	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

Purgeable Aromatics

Matrix Spike Analysis

Lab ID: 5126Spk
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 09/20/96
Date Sampled: 09/19/96
Date Received: 09/19/96
Date Analyzed: 09/19/96

Target Analyte	Spike Added (ug/L)	Original Conc. (ug/L)	Spiked Sample Conc. (ug/L)	% Recovery	Acceptance Limits (%)
Benzene	10	0.99	10.5	95%	39 - 150
Toluene	10	0.24	10.2	99%	46 - 148
Ethylbenzene	10	ND	10.0	100%	32 - 160
m,p-Xylenes	20	0.45	20.2	99%	NE
o-Xylene	10	ND	10.1	100%	NE

ND - Analyte not detected at the stated detection limit.

NA - Not applicable or not calculated.

NE - Spike acceptance range not established by the EPA.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	106	88 - 110%
	Bromofluorobenzene	102	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

PURGEABLE AROMATICS

Quality Control Report

Method Blank Analysis

Sample hydrocarbon: Water
Lab ID: MB35332

Report Date: 09/25/96
Date Analyzed: 09/24/96


Target Analyte	Concentration (ug/L)	Detection Limit (ug/L)
Benzene	ND	0.50
Toluene	ND	0.50
Ethylbenzene	ND	0.50
m,p-Xylenes	ND	1.00
o-Xylene	ND	0.50

ND - Analyte not detected at the stated detection limit.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	102	88 - 110%
	Bromofluorobenzene	102	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209,
Oct. 1984.

Comments:


Analyst


Review

Purgeable Aromatics

Duplicate Analysis

Lab ID: 5132Dup
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 09/25/96
Date Sampled: 09/23/96
Date Received: 09/23/96
Date Analyzed: 09/24/96

Target Analyte	Original Conc. (ug/L)	Duplicate Conc. (ug/L)	Acceptance Range (ug/L)
Benzene	0.56	0.49	0 - 1.80
Toluene	1.71	1.45	0.34 - 2.83
Ethylbenzene	4.79	3.98	1.98 - 6.80
m,p-Xylenes	8.39	7.25	NE
o-Xylene	3.56	3.04	NE

ND - Analyte not detected at the stated detection limit.

NA - Not applicable or not calculated.

NE - Duplicate acceptance range not established by the EPA.

	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
Quality Control:	Trifluorotoluene	104	88 - 110%
	Bromofluorobenzene	101	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:


Analyst


Review

Purgeable Aromatics

Matrix Spike Analysis

Lab ID: 5132Spk
Sample Matrix: Water
Preservative: Cool, HgCl₂
Condition: Intact

Report Date: 09/25/96
Date Sampled: 09/23/96
Date Received: 09/23/96
Date Analyzed: 09/24/96

Target Analyte	Spike Added (ug/L)	Original Conc. (ug/L)	Spiked Sample Conc. (ug/L)	% Recovery	Acceptance Limits (%)
Benzene	10	0.56	10.9	103%	39 - 150
Toluene	10	1.71	11.5	98%	46 - 148
Ethylbenzene	10	4.79	14.6	98%	32 - 160
m,p-Xylenes	20	8.39	27.9	98%	NE
o-Xylene	10	3.56	13.4	98%	NE

ND - Analyte not detected at the stated detection limit.

NA - Not applicable or not calculated.

NE - Spike acceptance range not established by the EPA.

Quality Control:	<u>Surrogate</u>	<u>Percent Recovery</u>	<u>Acceptance Limits</u>
	Trifluorotoluene	107	88 - 110%
	Bromofluorobenzene	107	86 - 115%

Reference: Method 602.2, Purgeable Aromatics; Federal Register, Vol. 49, No. 209, Oct. 1984.

Comments:



Analyst



Review

BLAGG ENGINEERING, INC.**MONITOR WELL SAMPLING DATA**CLIENT : AMOCO PRODUCTION CO.CHAIN-OF-CUSTODY # : 5112

COOPER GC # 1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ENVIROTECH, INC.Date : June 27, 1997SAMPLER : NJVFilename : 06-27-97.WK3PROJECT MANAGER : NJV

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING TIME	pH	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
2	101.88	77.10	24.78	—	—	—	—	—	—
3	101.28	75.09	26.19	30.00	1130	7.4	2,100	2.00	—
4	101.32	73.59	27.73	30.00	1200	7.3	1,200	1.50	—
5	95.22	72.52	22.70	23.68	1220	7.5	1,300	0.50	—

NOTES : Volume of water purged from well prior to sampling; $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$.(i.e. 2" MW $r = (1/12) \text{ ft}$. $h = 1 \text{ ft}$.) (i.e. 4" MW $r = (2/12) \text{ ft}$. $h = 1 \text{ ft}$.)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 ".MW # 5 - very poor recovery . Collected BTEX samples for MW # 3, # 4, & # 5 only.

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS

Client:	Blagg / Amoco	Project #:	04034-10
Sample ID:	MW #3	Date Reported:	06-25-97
Chain of Custody:	5112	Date Sampled:	06-23-97
Laboratory Number:	B488	Date Received:	06-24-97
Sample Matrix:	Water	Date Analyzed:	06-24-97
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	14.3	1	0.2
Toluene	29.6	1	0.2
Ethylbenzene	97.9	1	0.2
p,m-Xylene	288	1	0.2
o-Xylene	210	1	0.1
Total BTEX	640		

ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	98 %
	Bromofluorobenzene	101 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: Cooper GC #1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS

Client:	Blagg / Amoco	Project #:	04034-10
Sample ID:	MW #4	Date Reported:	06-25-97
Chain of Custody:	5112	Date Sampled:	06-23-97
Laboratory Number:	B489	Date Received:	06-24-97
Sample Matrix:	Water	Date Analyzed:	06-24-97
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	1,215	10	1.8
Toluene	71.7	10	1.7
Ethylbenzene	1,620	10	1.5
p,m-Xylene	2,436	10	2.2
o-Xylene	3,290	10	1.0
Total BTEX	8,633		

ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	99 %
	Bromofluorobenzene	100 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: Cooper GC #1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS

Client:	Blagg / Amoco	Project #:	04034-10
Sample ID:	MW #5	Date Reported:	06-25-97
Chain of Custody:	5112	Date Sampled:	06-23-97
Laboratory Number:	B490	Date Received:	06-24-97
Sample Matrix:	Water	Date Analyzed:	06-24-97
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	1,720	10	1.8
Toluene	635	10	1.7
Ethylbenzene	72.8	10	1.5
p,m-Xylene	435	10	2.2
o-Xylene	530	10	1.0
Total BTEX	3,390		


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	99 %
	Bromofluorobenzene	99 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: Cooper GC #1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

QUALITY ASSURANCE / QUALITY CONTROL DOCUMENTATION

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	QA/QC	Project #:	N/A
Sample ID:	Laboratory Blank	Date Reported:	06-25-97
Laboratory Number:	06-24-BTEX.BLANK	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	06-24-97
Condition:	N/A	Analysis Requested:	BTEX

Parameter	Concentration (ug/L)	Det. Limit (ug/L)
Benzene	ND	0.2
Toluene	ND	0.2
Ethylbenzene	ND	0.2
p,m-Xylene	ND	0.2
o-Xylene	ND	0.1


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	96 %
	Bromofluorobenzene	99 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: QA/QC for samples B486 - B493.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	QA/QC	Project #:	N/A
Sample ID:	Matrix Duplicate	Date Reported:	06-25-97
Laboratory Number:	B487	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	HgCl and Cool	Date Analyzed:	06-24-97
Condition:	Cool and Intact	Analysis Requested:	BTEX-8020

Parameter	Sample Result (ug/L)	Duplicate Result (ug/L)	Percent Diff.	Det. Limit (ug/L)	Dilution Factor
Benzene	ND	ND	0.0%	0.2	1
Toluene	ND	ND	0.0%	0.2	1
Ethylbenzene	ND	ND	0.0%	0.2	1
p,m-Xylene	0.3	0.3	0.0%	0.2	1
o-Xylene	0.1	0.1	0.0%	0.1	1

ND - Parameter not detected at the stated detection limit.

QA/QC Acceptance Criteria:	Parameter	Maximum Difference
----------------------------	-----------	--------------------


8020 Compounds


30 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: QA/QC for samples B486 - B493.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client: QA/QC
Sample ID: Matrix Spike
Laboratory Number: B487
Sample Matrix: Water
Preservative: Cool
Condition: Cool and Intact

Project #: N/A
Date Reported: 06-25-97
Date Sampled: N/A
Date Received: N/A
Date Analyzed: 06-24-97


Parameter	Sample Result (ug/L)	Spike Added (ug/L)	Spiked Sample Result (ug/L)	Det. Limit (ug/L)	Percent Recovery	SW-846 % Rec. Accept. Range
Benzene	ND	50.0	50.2	0.2	100%	39-150
Toluene	ND	50.0	50.1	0.2	100%	46-148
Ethylbenzene	ND	50.0	51.3	0.2	102%	32-160
p,m-Xylene	0.3	100	100	0.2	100%	46-148
o-Xylene	0.1	50.0	50.8	0.1	101%	46-148


ND - Parameter not detected at the stated detection limit.

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: QA/QC for samples B486 - B493.


Analyst


Review

BLAGG ENGINEERING, INC.**MONITOR WELL SAMPLING DATA**CLIENT : AMOCO PRODUCTION CO.CHAIN-OF-CUSTODY # : 5414

COOPER GC # 1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ENVIROTECH, INC.Date : August 22, 1997SAMPLER : JCBFilename : 08-22-97.WK3PROJECT MANAGER : NJV

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING TIME	pH	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
TH A			21.94	24.40	1035	—	—	1.25	—
TH B			23.25	27.50	1050			2.25	—
TH C			20.03	23.50	1105			1.75	—
TH D			20.64	24.00	1130			1.75	—

NOTES : Volume of water purged from well prior to sampling; $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$.
(i.e. 2" MW $r = (1/12) \text{ ft}$. $h = 1 \text{ ft}$.) (i.e. 4" MW $r = (2/12) \text{ ft}$. $h = 1 \text{ ft}$.)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2".

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	TH A	Date Reported:	08-25-97
Chain of Custody:	5414	Date Sampled:	08-22-97
Laboratory Number:	B915	Date Received:	08-22-97
Sample Matrix:	Water	Date Analyzed:	08-25-97
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	ND	1	0.2
Toluene	0.4	1	0.2
Ethylbenzene	1.1	1	0.2
p,m-Xylene	8.5	1	0.2
o-Xylene	4.9	1	0.1
Total BTEX	14.9		


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	98 %
	Bromofluorobenzene	98 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: Cooper 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	TH B	Date Reported:	08-25-97
Chain of Custody:	5414	Date Sampled:	08-22-97
Laboratory Number:	B916	Date Received:	08-22-97
Sample Matrix:	Water	Date Analyzed:	08-25-97
Preservative:	HgCl2 & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	ND	1	0.2
Toluene	11.3	1	0.2
Ethylbenzene	11.1	1	0.2
p,m-Xylene	9.9	1	0.2
o-Xylene	8.7	1	0.1
Total BTEX	41.0		


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	100 %
	Bromofluorobenzene	100 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: Cooper 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	TH C	Date Reported:	08-25-97
Chain of Custody:	5414	Date Sampled:	08-22-97
Laboratory Number:	B917	Date Received:	08-22-97
Sample Matrix:	Water	Date Analyzed:	08-25-97
Preservative:	HgCl2 & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	92.8	1	0.2
Toluene	ND	1	0.2
Ethylbenzene	ND	1	0.2
p,m-Xylene	41.9	1	0.2
o-Xylene	37.2	1	0.1
Total BTEX	172		


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	96 %
	Bromofluorobenzene	96 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: Cooper 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	TH D	Date Reported:	08-25-97
Chain of Custody:	5414	Date Sampled:	08-22-97
Laboratory Number:	B918	Date Received:	08-22-97
Sample Matrix:	Water	Date Analyzed:	08-25-97
Preservative:	HgCl2 & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	10.3	1	0.2
Toluene	2.4	1	0.2
Ethylbenzene	ND	1	0.2
p,m-Xylene	8.2	1	0.2
o-Xylene	3.3	1	0.1
Total BTEX	24.2		


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	99 %
	Bromofluorobenzene	99 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: Cooper 1E.


Analyst


Review

[illegible]

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

QUALITY ASSURANCE / QUALITY CONTROL DOCUMENTATION

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	N/A	Project #:	N/A
Sample ID:	Laboratory Blank	Date Reported:	08-25-97
Laboratory Number:	08-25-BTEX.BLANK	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	08-25-97
Condition:	N/A	Analysis Requested:	BTEX

Parameter	Concentration (ug/L)	Det. Limit (ug/L)
Benzene	ND	0.2
Toluene	ND	0.2
Ethylbenzene	ND	0.2
p,m-Xylene	ND	0.2
o-Xylene	ND	0.1


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	98 %
	Bromofluorobenzene	99 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: QA/QC for samples B915 - B918.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	QA/QC	Project #:	N/A
Sample ID:	Matrix Duplicate	Date Reported:	08-25-97
Laboratory Number:	B915	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	HgCl and Cool	Date Analyzed:	08-25-97
Condition:	Cool and Intact	Analysis Requested:	BTEX-8020

Parameter	Sample Result (ug/L)	Duplicate Result (ug/L)	Percent Diff.	Det. Limit (ug/L)	Dilution Factor
Benzene	ND	ND	0.0%	0.2	1
Toluene	0.4	0.4	0.0%	0.2	1
Ethylbenzene	1.1	1.1	0.0%	0.2	1
p,m-Xylene	8.5	8.3	1.4%	0.2	1
o-Xylene	4.9	4.9	0.0%	0.1	1


ND - Parameter not detected at the stated detection limit.


QA/QC Acceptance Criteria:	Parameter	Maximum Difference
	8020 Compounds	30 %

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: QA/QC for samples B915 - B918.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client: QA/QC
Sample ID: Matrix Spike
Laboratory Number: B915
Sample Matrix: Water
Preservative: Cool
Condition: Cool and Intact

Project #: N/A
Date Reported: 08-25-97
Date Sampled: N/A
Date Received: N/A
Date Analyzed: 08-25-97


Parameter	Sample Result (ug/L)	Spike Added (ug/L)	Spiked Sample Result (ug/L)	Det. Limit (ug/L)	Percent Recovery	SW-846 % Rec. Accept. Range
Benzene	ND	50.0	48.6	0.2	97%	39-150
Toluene	0.4	50.0	49.4	0.2	98%	46-148
Ethylbenzene	1.1	50.0	50.5	0.2	99%	32-160
p,m-Xylene	8.5	100	106	0.2	98%	46-148
o-Xylene	4.9	50.0	53.4	0.1	97%	46-148


ND - Parameter not detected at the stated detection limit.

References: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1994.

Comments: QA/QC for samples B915 - B918.


Analyst


Review

BLAGG ENGINEERING, INC.

MONITOR WELL SAMPLING DATA

CLIENT : AMOCO PRODUCTION CO.

CHAIN-OF-CUSTODY # : 5740

COOPER GC # 1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ENVIROTECH, INC.

Date : April 9, 1998

SAMPLER : N J V

Filename : 04-09-98.WK3

PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING TIME	pH	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	71.62	22.67	26.00	0933	-	-	1.75	-
MW - 3R	97.03	71.44	25.59	34.03	1005	-	-	4.25	-
MW - 5	94.00	70.57	23.43	23.50	-	-	-	-	-
MW - 5R	94.12	-	-	31.00	-	-	-	-	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$
(i.e. 2" MW $r = (1/12) \text{ ft}$. $h = 1 \text{ ft}$.) (i.e. 4" MW $r = (2/12) \text{ ft}$. $h = 1 \text{ ft}$.)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 ".

Collected BTEX & anion / cation samples for MW # 2R & # 3R only .

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	MW # 2R	Date Reported:	04-10-98
Chain of Custody:	5740	Date Sampled:	04-09-98
Laboratory Number:	D092	Date Received:	04-09-98
Sample Matrix:	Water	Date Analyzed:	04-10-98
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	2.4	1	0.2
Toluene	9.9	1	0.2
Ethylbenzene	2.7	1	0.2
p,m-Xylene	13.1	1	0.2
o-Xylene	3.1	1	0.1

Total BTEX 31.2


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	98 %
	Bromofluorobenzene	98 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC # 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	MW # 3R	Date Reported:	04-10-98
Chain of Custody:	5740	Date Sampled:	04-09-98
Laboratory Number:	D093	Date Received:	04-09-98
Sample Matrix:	Water	Date Analyzed:	04-10-98
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	43.3	1	0.2
Toluene	222	1	0.2
Ethylbenzene	8.3	1	0.2
p,m-Xylene	108	1	0.2
o-Xylene	26.6	1	0.1

Total BTEX 410


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	100 %
	Bromofluorobenzene	100 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC # 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW


CATION / ANION ANALYSIS


Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	MW # 2R	Date Reported:	04-10-98
Laboratory Number:	D092	Date Sampled:	04-09-98
Chain of Custody:	5740	Date Received:	04-09-98
Sample Matrix:	Water	Date Extracted:	N/A
Preservative:	Cool	Date Analyzed:	04-10-98
Condition:	Cool & Intact		

Parameter	Analytical Result	Units	Units
pH	6.58	s.u.	
Conductivity @ 25° C	1,200	umhos/cm	
Total Dissolved Solids @ 180C	590	mg/L	
Total Dissolved Solids (Calc)	586	mg/L	
SAR	0.0	ratio	
Total Alkalinity as CaCO3	235	mg/L	
Total Hardness as CaCO3	464	mg/L	
Bicarbonate as HCO3	235	mg/L	3.85 meq/L
Carbonate as CO3	<1	mg/L	0.00 meq/L
Hydroxide as OH	<1	mg/L	0.00 meq/L
Nitrate Nitrogen	0.1	mg/L	0.00 meq/L
Nitrite Nitrogen	<0.001	mg/L	0.00 meq/L
Chloride	46.9	mg/L	1.32 meq/L
Fluoride	0.85	mg/L	0.04 meq/L
Phosphate	0.9	mg/L	0.03 meq/L
Sulfate	202	mg/L	4.21 meq/L
Calcium	185	mg/L	9.23 meq/L
Magnesium	<0.1	mg/L	0.00 meq/L
Potassium	5.03	mg/L	0.13 meq/L
Sodium	2.2	mg/L	0.10 meq/L
Cations			9.46 meq/L
Anions			9.46 meq/L
Cation/Anion Difference			0.01%

Reference: U.S.E.P.A., 600/4-79-020, "Methods for Chemical Analysis of Water and Wastes", 1983
Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Cooper GC # 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

CATION / ANION ANALYSIS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	MW # 3R	Date Reported:	04-10-98
Laboratory Number:	D093	Date Sampled:	04-09-98
Chain of Custody:	5740	Date Received:	04-09-98
Sample Matrix:	Water	Date Extracted:	N/A
Preservative:	Cool	Date Analyzed:	04-10-98
Condition:	Cool & Intact		

Parameter	Analytical Result	Units		Units
pH	7.13	s.u.		
Conductivity @ 25° C	15,600	umhos/cm		
Total Dissolved Solids @ 180C	7,800	mg/L		
Total Dissolved Solids (Calc)	7,780	mg/L		
SAR	26.0	ratio		
Total Alkalinity as CaCO3	346	mg/L		
Total Hardness as CaCO3	1,156	mg/L		
Bicarbonate as HCO3	346	mg/L	5.67	meq/L
Carbonate as CO3	<1	mg/L	0.00	meq/L
Hydroxide as OH	<1	mg/L	0.00	meq/L
Nitrate Nitrogen	21.1	mg/L	0.34	meq/L
Nitrite Nitrogen	0.064	mg/L	0.00	meq/L
Chloride	23.1	mg/L	0.65	meq/L
Fluoride	1.87	mg/L	0.10	meq/L
Phosphate	0.5	mg/L	0.02	meq/L
Sulfate	5,035	mg/L	104.83	meq/L
Calcium	425	mg/L	21.21	meq/L
Magnesium	22.9	mg/L	1.88	meq/L
Potassium	10.1	mg/L	0.26	meq/L
Sodium	2,030	mg/L	88.31	meq/L
Cations			111.66	meq/L
Anions			111.61	meq/L
Cation/Anion Difference			0.04%	

Reference: U.S.E.P.A., 600/4-79-020, "Methods for Chemical Analysis of Water and Wastes", 1983
Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Cooper GC # 1E.

Analyst

Review

(505) 632-0615

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	N/A	Project #:	N/A
Sample ID:	04-10-BTEX QA/QC	Date Reported:	04-10-98
Laboratory Number:	D092	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	04-10-98
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF	C-Cal RF	%Diff	Blank Conc	Detect Limit
		Accept Range 0 - 15%			
Benzene	4.8757E-05	4.9803E-05	2.15%	ND	0.2
Toluene	5.4539E-05	5.5938E-05	2.56%	ND	0.2
Ethylbenzene	6.1355E-05	6.3123E-05	2.88%	ND	0.2
p,m-Xylene	4.9248E-05	5.0771E-05	3.09%	ND	0.2
o-Xylene	5.8524E-05	5.9657E-05	1.94%	ND	0.1


Duplicate Conc. (ug/L)	Sample	Duplicate	%Diff	Accept Limit
Benzene	2.4	2.4	0.0%	0 - 30%
Toluene	9.9	9.9	0.0%	0 - 30%
Ethylbenzene	2.7	2.7	0.0%	0 - 30%
p,m-Xylene	13.1	13.1	0.0%	0 - 30%
o-Xylene	3.1	3.1	0.0%	0 - 30%


Spike Conc. (ug/L)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Limits
Benzene	2.4	50.0	52.3	100%	39 - 150
Toluene	9.9	50.0	59.3	99%	46 - 148
Ethylbenzene	2.7	50.0	52.5	100%	32 - 160
p,m-Xylene	13.1	100.0	112	99%	46 - 148
o-Xylene	3.1	50.0	53.0	100%	46 - 148

ND - Parameter not detected at the stated detection limit.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for samples D092 - D093.


Analyst


Review

BLAGG ENGINEERING, INC.
MONITOR WELL SAMPLING DATA

CLIENT : AMOCO PRODUCTION CO.

CHAIN-OF-CUSTODY # : 6007

COOPER GC # 1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ENVIROTECH, INC.

Date : May 30, 1998

SAMPLER : N J V

Filename : 05-30-98.WK3

PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING	pH TIME	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	71.32	22.97	26.00	-	-	-	-	-
MW - 3R	97.03	71.55	25.48	34.03	0830	7.2	5,900	4.25	-
MW - 5	-	-	-	23.50	-	-	-	-	-
MW - 5R	94.12	64.09	30.03	31.00	0800	7.3	2,500	4.50	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$
(i.e. 2" MW $r = (1/12) \text{ ft}$; $h = 1 \text{ ft}$.) (i.e. 4" MW $r = (2/12) \text{ ft}$; $h = 1 \text{ ft}$.)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 "

Collected BTEX samples for MW # 3R & # 5R. Sampled first bail of MW # 5R .

Redrilled MW # 5 - June 5, 1998 . Dry hole recorded June 5, 1998 @ 2:45 pm .

TD = 24.00 ft. TOC = 1.00 ft. ags . 15 ft. screen, 10 ft. casing .

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client: Blagg / AMOCO
Sample ID: MW #3R
Chain of Custody: 6007
Laboratory Number: D322
Sample Matrix: Water
Preservative: HgCl₂ & Cool
Condition: Cool & Intact

Project #: 04034-10
Date Reported: 06-01-98
Date Sampled: 05-30-98
Date Received: 06-01-98
Date Analyzed: 06-01-98
Analysis Requested: BTEX

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	110	1	0.2
Toluene	81.3	1	0.2
Ethylbenzene	1.5	1	0.2
p,m-Xylene	20.4	1	0.2
o-Xylene	3.8	1	0.1

Total BTEX 217


ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	100 %
	Bromofluorobenzene	100 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC #1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	MW #5R	Date Reported:	06-01-98
Chain of Custody:	6007	Date Sampled:	05-30-98
Laboratory Number:	D323	Date Received:	06-01-98
Sample Matrix:	Water	Date Analyzed:	06-01-98
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	1.1	1	0.2
Toluene	1.1	1	0.2
Ethylbenzene	1.0	1	0.2
p,m-Xylene	1.3	1	0.2
o-Xylene	0.7	1	0.1

Total BTEX **5.2**


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	97 %
	Bromofluorobenzene	97 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: **Cooper GC #1E.**


Analyst


Review

60v7

ENVIROTECH INC.

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	N/A	Project #:	N/A
Sample ID:	06-01-BTEX QA/QC	Date Reported:	06-01-98
Laboratory Number:	D317	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	06-01-98
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF	C-Cal RF	%Diff.	Blank Conc	Detect. Limit
		Accept Range 0 - 15%			
Benzene	1.4863E-02	1.5028E-02	1.11%	ND	0.2
Toluene	2.2878E-02	2.2993E-02	0.50%	ND	0.2
Ethylbenzene	1.0578E-02	1.0663E-02	0.81%	ND	0.2
p,m-Xylene	8.4559E-03	8.5672E-03	1.32%	ND	0.2
o-Xylene	8.7385E-03	8.8357E-03	1.11%	ND	0.1
1,3,5-trimethylbenzene	6.2277E-03	6.2402E-03	0.20%	ND	0.2
1,2,4-trimethylbenzene	7.3319E-03	7.3687E-03	0.50%	ND	0.2


Duplicate Conc. (ug/L)	Sample	Duplicate	%Diff.	Accept Limit
Benzene	3.4	3.3	2.9%	0 - 30%
Toluene	1.6	1.6	0.0%	0 - 30%
Ethylbenzene	3.0	3.0	0.0%	0 - 30%
p,m-Xylene	37.4	36.9	1.3%	0 - 30%
o-Xylene	6.7	6.7	0.0%	0 - 30%


Spike Conc. (ug/L)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Limits
Benzene	3.4	50.0	53.2	100%	39 - 150
Toluene	1.6	50.0	51.5	100%	46 - 148
Ethylbenzene	3.0	50.0	52.9	100%	32 - 160
p,m-Xylene	37.4	100.0	135.2	98%	46 - 148
o-Xylene	6.7	50.0	56.4	99%	46 - 148

ND - Parameter not detected at the stated detection limit.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for samples D317 - D324.


Analyst


Review

BLAGG ENGINEERING, INC.
MONITOR WELL SAMPLING DATA

CLIENT : AMOCO PRODUCTION CO.

CHAIN-OF-CUSTODY # : 6300

COOPER GC # 1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ENVIROTECH, INC.

Date : September 29, 1998

SAMPLER : N J V

Filename : 09-29-98.WK3

PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING	pH TIME	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	74.29	20.00	26.00	-	-	-	-	-
MW - 3R	97.03	75.87	21.16	34.03	1410	7.2	2,900	6.50	-
MW - 5	94.00	72.60	21.40	23.50	-	-	-	-	-
MW - 5R	94.12	72.08	22.04	31.00	1345	7.0	3,200	4.50	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$
(i.e. 2" MW $r = (1/12) \text{ ft}$. $h = 1 \text{ ft}$.) (i.e. 4" MW $r = (2/12) \text{ ft}$. $h = 1 \text{ ft}$.)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 ".

Collected BTEX samples for MW # 3R & # 5R .

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	MW #3R	Date Reported:	10-01-98
Chain of Custody:	6301	Date Sampled:	09-29-98
Laboratory Number:	E001	Date Received:	09-30-98
Sample Matrix:	Water	Date Analyzed:	09-30-98
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	895	1	0.2
Toluene	587	1	0.2
Ethylbenzene	165	1	0.2
p,m-Xylene	686	1	0.2
o-Xylene	233	1	0.1

Total BTEX 2,570


ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	100 %
	Bromofluorobenzene	100 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC #1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	MW #5R	Date Reported:	10-01-98
Chain of Custody:	6301	Date Sampled:	09-29-98
Laboratory Number:	E002	Date Received:	09-30-98
Sample Matrix:	Water	Date Analyzed:	09-30-98
Preservative:	HgCl2 & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	4.7	1	0.2
Toluene	2.3	1	0.2
Ethylbenzene	ND	1	0.2
p,m-Xylene	22.5	1	0.2
o-Xylene	6.7	1	0.1
Total BTEX	36.2		


ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	96 %
	Bromofluorobenzene	96 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC #1E.


Analyst


Review

CHAIN OF CUSTODY RECORD

63U1

Client / Project Name		Project Location		ANALYSIS / PARAMETERS											
BLAGG / Amoco		COOPER GC #1E													
Sampler: NJV		Client No. 04034-10													
Sample No./ Identification	Sample Date	Sample Time	Lab Number	Sample Matrix	No. of Containers	(87X) (1208)									Remarks
MW # 3R	9/29/98	1410	E001	WATER	2	✓									PRESERV. - COOL
MW # 5R	9/29/98	1345	E002	WATER	2	✓									PRESERV. - COOL
Relinquished by: (Signature)		Date		Time		Received by: (Signature)		Date		Time					
[Signature]		9/30/98		0700		[Signature]		9/30/98		0700					
Relinquished by: (Signature)						Received by: (Signature)									
Relinquished by: (Signature)						Received by: (Signature)									
Relinquished by: (Signature)						Received by: (Signature)									
RP COC'S 6300-6301 ENVIROTECH INC. 5796 U.S. Highway 64 Farmington, New Mexico 87401 (505) 632-0615															
Sample Receipt Y N N/A Received Intact ✓ Cool - Ice/Blue Ice ✓															

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	Project #:	N/A
Sample ID:	09-30-BTEX QA/QC	Date Reported:	10-01-98
Laboratory Number:	D996	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	09-30-98
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF:	C-Cal RF:	%Diff.	Blank Conc	Detect. Limit
		Accept. Range 0 - 15%			
Benzene	5.7865E-002	5.8051E-002	0.3%	ND	0.2
Toluene	1.8978E-002	1.9042E-002	0.3%	ND	0.2
Ethylbenzene	2.0822E-002	2.0902E-002	0.4%	ND	0.2
p,m-Xylene	1.6870E-002	1.6955E-002	0.5%	ND	0.2
o-Xylene	1.7776E-002	1.7829E-002	0.3%	ND	0.1


Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff.	Accept Range	Detect. Limit
Benzene	498	504	0.9%	0 - 30%	8.8
Toluene	3,400	3,430	0.9%	0 - 30%	8.4
Ethylbenzene	2,920	2,940	0.7%	0 - 30%	7.6
p,m-Xylene	12,720	12,850	1.0%	0 - 30%	10.8
o-Xylene	6,210	6,310	1.6%	0 - 30%	5.2


Spike Conc. (ug/Kg)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Range
Benzene	498	50.0	542	100%	39 - 150
Toluene	3,400	50.0	3,410	100%	46 - 148
Ethylbenzene	2,920	50.0	2,940	99%	32 - 160
p,m-Xylene	12,720	100	12,580	99%	46 - 148
o-Xylene	6,210	50.0	6,190	99%	46 - 148

ND - Parameter not detected at the stated detection limit.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for samples D996, D998 - E002 and E004 - E007.


Analyst


Review

BLAGG ENGINEERING, INC.**MONITOR WELL SAMPLING DATA**CLIENT : **AMOCO PRODUCTION CO.**

CHAIN-OF-CUSTODY # : 6430

COOPER GC #1E - SEPARATOR PITLABORATORY (S) USED : **ENVIROTECH, INC.****UNIT J, SEC. 15, T29N, R11W**Date : December 18, 1998SAMPLER : N J VFilename : 12-18-98.WK3PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING	pH TIME	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	74.37	19.92	26.00	-	-	-	-	-
MW - 3R	97.03	74.99	22.04	34.03	1100	7.6	6,000	6.00	-
MW - 5	94.00	72.26	21.74	23.50	-	-	-	-	-
MW - 5R	94.12	71.78	22.34	31.00	1025	7.1	3,100	4.25	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$
(i.e. 2" MW $r = (1/12) \text{ ft}$. $h = 1 \text{ ft}$.) (i.e. 4" MW $r = (2/12) \text{ ft}$. $h = 1 \text{ ft}$.)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 "Collected BTEX samples for MW # 3R & # 5R .P & S reclamation system operating @ time of sampling .

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	MW #3 R	Date Reported:	12-22-98
Chain of Custody:	6430	Date Sampled:	12-18-98
Laboratory Number:	E413	Date Received:	12-21-98
Sample Matrix:	Water	Date Analyzed:	12-22-98
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	301	1	0.2
Toluene	44.2	1	0.2
Ethylbenzene	49.9	1	0.2
p,m-Xylene	140	1	0.2
o-Xylene	29.6	1	0.1
Total BTEX	565		


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	97 %
	Bromofluorobenzene	97 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC #1 E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	MW #5 R	Date Reported:	12-22-98
Chain of Custody:	6430	Date Sampled:	12-18-98
Laboratory Number:	E414	Date Received:	12-21-98
Sample Matrix:	Water	Date Analyzed:	12-22-98
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	9.1	1	0.2
Toluene	1.4	1	0.2
Ethylbenzene	0.8	1	0.2
p,m-Xylene	3.6	1	0.2
o-Xylene	0.9	1	0.1

Total BTEX 15.8


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	99 %
	Bromofluorobenzene	99 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC #1 E.


Analyst


Review

6450

ENVIROTECH INC.

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	N/A	Project #:	N/A
Sample ID:	12-22-BTEX QA/QC	Date Reported:	12-22-98
Laboratory Number:	E413	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	12-22-98
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF:	C-Cal RF:	%Diff.	Blank Conc	Detect Limit
		Accept. Range 0 - 15%			
Benzene	3.3006E-002	3.3112E-002	0.32%	ND	0.2
Toluene	1.3687E-002	1.3715E-002	0.20%	ND	0.2
Ethylbenzene	1.7638E-002	1.7712E-002	0.42%	ND	0.2
p,m-Xylene	1.5312E-002	1.5315E-002	0.02%	ND	0.2
o-Xylene	1.5548E-002	1.5595E-002	0.30%	ND	0.1


Duplicate Conc. (ug/L)	Sample	Duplicate	%Diff.	Accept Limit
Benzene	301	301	0.0%	0 - 30%
Toluene	44.2	44.5	0.7%	0 - 30%
Ethylbenzene	49.9	50.3	0.8%	0 - 30%
p,m-Xylene	140	146	4.2%	0 - 30%
o-Xylene	29.6	29.8	0.7%	0 - 30%


Spike Conc. (ug/L)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Limits
Benzene	301	50.0	341	97%	39 - 150
Toluene	44.2	50.0	92.5	98%	46 - 148
Ethylbenzene	49.9	50.0	98.0	98%	32 - 160
p,m-Xylene	140	100.0	234	97%	46 - 148
o-Xylene	29.6	50.0	78.7	99%	46 - 148

ND - Parameter not detected at the stated detection limit.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for samples E413 - E418.


Analyst


Review

BLAGG ENGINEERING, INC.**MONITOR WELL SAMPLING DATA**CLIENT : AMOCO PRODUCTION CO.CHAIN-OF-CUSTODY # : 6612

COOPER GC # 1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ENVIROTECH, INC.Date : February 18, 1999SAMPLER : N J VFilename : 02-18-99.WK4PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING TIME	pH	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	73.33	20.96	26.00	-	-	-	-	-
MW - 3R	97.03	73.41	23.62	34.03	1250	7.3	4,300	5.10	-
MW - 5	-	-	-	23.50	-	-	-	-	-
MW - 5R	94.12	70.20	23.92	31.00	1220	6.9	2,400	3.50	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$
(i.e. 2" MW $r = (1/12) \text{ ft. } h = 1 \text{ ft.}$ (i.e. 4" MW $r = (2/12) \text{ ft. } h = 1 \text{ ft.}$)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 ".Collected BTEX samples for MW # 3R & # 5R .BEI reclamation system operating @ time of sampling .

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	403410
Sample ID:	MW # 3R	Date Reported:	02-19-99
Chain of Custody:	6612	Date Sampled:	02-18-99
Laboratory Number:	E677	Date Received:	02-18-99
Sample Matrix:	Water	Date Analyzed:	02-19-99
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	329	1	0.2
Toluene	125	1	0.2
Ethylbenzene	94.8	1	0.2
p,m-Xylene	204	1	0.2
o-Xylene	54.5	1	0.1
Total BTEX	807		


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	101 %
	Bromofluorobenzene	101 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	403410
Sample ID:	MW # 5R	Date Reported:	02-19-99
Chain of Custody:	6612	Date Sampled:	02-18-99
Laboratory Number:	E678	Date Received:	02-18-99
Sample Matrix:	Water	Date Analyzed:	02-19-99
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	3.0	1	0.2
Toluene	1.8	1	0.2
Ethylbenzene	0.5	1	0.2
p,m-Xylene	3.1	1	0.2
o-Xylene	1.6	1	0.1
Total BTEX	10.0		


ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	98 %
	Bromofluorobenzene	98 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC 1E.


Analyst


Review

6612

X

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	N/A	Project #:	N/A
Sample ID:	02-19-BTEX QA/QC	Date Reported:	02-19-99
Laboratory Number:	E674	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	02-19-99
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF	C-Cal RF	%Diff	Blank Conc	Detect Limit
		Accept. Range 0 - 15%			
Benzene	7.9975E-002	8.0232E-002	0.32%	ND	0.2
Toluene	7.5726E-002	7.5741E-002	0.02%	ND	0.2
Ethylbenzene	5.3049E-002	5.3112E-002	0.12%	ND	0.2
p,m-Xylene	4.6305E-002	4.6314E-002	0.02%	ND	0.2
o-Xylene	4.6122E-002	4.6261E-002	0.30%	ND	0.1

Duplicate Conc. (ug/L)	Sample	Duplicate	%Diff	Accept Limit
Benzene	1.5	1.5	0.0%	0 - 30%
Toluene	1.5	1.4	6.7%	0 - 30%
Ethylbenzene	5.5	5.3	3.6%	0 - 30%
p,m-Xylene	45.7	45.8	0.2%	0 - 30%
o-Xylene	9.5	9.2	3.2%	0 - 30%

Spike Conc. (ug/L)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Limits
Benzene	1.5	50.0	51.5	100%	39 - 150
Toluene	1.5	50.0	51.4	100%	46 - 148
Ethylbenzene	5.5	50.0	55.3	100%	32 - 160
p,m-Xylene	45.7	100.0	143.6	99%	46 - 148
o-Xylene	9.5	50.0	59.0	99%	46 - 148

ND - Parameter not detected at the stated detection limit.

* - Administrative Limits set at 80 - 120%.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for samples E674 - E678.


Analyst


Review

BLAGG ENGINEERING, INC.**MONITOR WELL SAMPLING DATA**CLIENT : AMOCO PRODUCTION CO.CHAIN-OF-CUSTODY # : 6670

COOPER GC # 1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ENVIROTECH, INC.Date : May 27, 1999SAMPLER : N J VFilename : 05-27-99.WK4PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING TIME	pH	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	78.22	16.07	26.00	-	-	-	-	-
MW - 3R	97.03	75.66	21.37	34.03	1005	6.9	1,200	6.25	-
MW - 5	-	-	-	23.50	-	-	-	-	-
MW - 5R	94.12	73.75	20.37	31.00	0925	7.4	1,200	5.25	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$.(i.e. 2" MW $r = (1/12) \text{ ft.}$ $h = 1 \text{ ft.}$) (i.e. 4" MW $r = (2/12) \text{ ft.}$ $h = 1 \text{ ft.}$)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 ".Collected BTEX samples for MW # 3R & # 5R .BEI reclamation system not operating @ time of sampling .

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	403410
Sample ID:	MW # 3R	Date Reported:	05-27-99
Chain of Custody:	6670	Date Sampled:	05-27-99
Laboratory Number:	F408	Date Received:	05-27-99
Sample Matrix:	Water	Date Analyzed:	05-27-99
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	628	10	1.8
Toluene	733	10	1.7
Ethylbenzene	106	10	1.5
p,m-Xylene	281	10	2.2
o-Xylene	112	10	1.0

Total BTEX 1,860


ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	98 %
	Bromofluorobenzene	98 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC # 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	403410
Sample ID:	MW # 5R	Date Reported:	05-27-99
Chain of Custody:	6670	Date Sampled:	05-27-99
Laboratory Number:	F409	Date Received:	05-27-99
Sample Matrix:	Water	Date Analyzed:	05-27-99
Preservative:	HgCl2 & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	20.3	1	0.2
Toluene	22.7	1	0.2
Ethylbenzene	2.1	1	0.2
p,m-Xylene	20.2	1	0.2
o-Xylene	10.6	1	0.1

Total BTEX 75.9

ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	101 %
	Bromofluorobenzene	101 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC # 1E.


Analyst


Review

66/0

Client / Project Name						Project Location							ANALYSIS / PARAMETERS										
BLAGE / Amoco						COOPER GC #1E																	
Sampler:						NJV	Client No.																
						04034-10																	
Sample No./ Identification		Sample Date	Sample Time	Lab Number	Sample Matrix	No. of Containers	BTEX (g/L)											Remarks					
MW # 3R		5/27/99	1005	F408	WATER	2	✓											BOTH SAMPLES PRESERV. HgCl ₂ & COOL					
MW # 5R		5/27/99	0925	F409	WATER	2	✓																
Relinquished by: (Signature) <i>Melvin V. J.</i>				Date 5/27/99	Time 11:14	Received by: (Signature) <i>Dennis R. O'Brien</i>			Date 5.27.99			Time 11:14											
Relinquished by: (Signature) _____							Received by: (Signature) _____																
Relinquished by: (Signature) _____							Received by: (Signature) _____																
ENVIROTECH INC.																							
5796 U.S. Highway 64 Farmington, New Mexico 87401 (505) 632-0615																							

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	N/A	Project #:	N/A
Sample ID:	05-27-BTEX QA/QC	Date Reported:	05-27-99
Laboratory Number:	F398	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	05-27-99
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF	C-Cal RF	%Diff Accept Range 0 - 15%	Blank Conc	Detect Limit
Benzene	1.6360E-002	1.6412E-002	0.32%	ND	0.2
Toluene	1.7563E-002	1.7566E-002	0.02%	ND	0.2
Ethylbenzene	7.1313E-003	7.1398E-003	0.12%	ND	0.2
p,m-Xylene	8.5740E-003	8.5758E-003	0.02%	ND	0.2
o-Xylene	7.9281E-003	7.9520E-003	0.30%	ND	0.1

Duplicate Conc. (ug/L)	Sample	Duplicate	%Diff	Accept Limit
Benzene	78.9	79.0	0.1%	0 - 30%
Toluene	22.0	22.2	0.9%	0 - 30%
Ethylbenzene	51.6	52.1	1.0%	0 - 30%
p,m-Xylene	207	216	4.4%	0 - 30%
o-Xylene	66.9	67.4	0.7%	0 - 30%

Spike Conc. (ug/L)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Limits
Benzene	78.9	50.0	128	99%	39 - 150
Toluene	22.0	50.0	72.0	100%	46 - 148
Ethylbenzene	51.6	50.0	102	100%	32 - 160
p,m-Xylene	207	100.0	305	99%	46 - 148
o-Xylene	66.9	50.0	117	100%	46 - 148


ND - Parameter not detected at the stated detection limit.

* - Administrative Limits set at 80 - 120%.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for samples F398 - F400, F405 - F406 and F408 - F409.


Analyst


Review

BLAGG ENGINEERING, INC.
MONITOR WELL SAMPLING DATA

CLIENT : AMOCO PRODUCTION CO.

CHAIN-OF-CUSTODY # : 6698

COOPER GC # 1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ENVIROTECH, INC.

Date : August 23, 1999

SAMPLER : N J V

Filename : 08-23-99.WK4

PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING TIME	pH	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	79.68	14.61	26.00	-	-	-	-	-
MW - 3R	97.03	78.70	18.33	34.03	0945	7.0	1,100	7.75	-
MW - 5	-	-	-	23.50	-	-	-	-	-
MW - 5R	94.12	76.19	17.93	31.00	0905	7.0	1,600	6.50	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$.
(i.e. 2" MW $r = (1/12) \text{ ft. } h = 1 \text{ ft.}$ (i.e. 4" MW $r = (2/12) \text{ ft. } h = 1 \text{ ft.}$)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 ".

Collected BTEX samples for MW # 3R & # 5R . DTW @ # 3R = 22.7 ft. during collection .

BEI reclamation system running, but not operating @ time of sampling .

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	403410
Sample ID:	MW #3R	Date Reported:	08-24-99
Chain of Custody:	6698	Date Sampled:	08-23-99
Laboratory Number:	F965	Date Received:	08-23-99
Sample Matrix:	Water	Date Analyzed:	08-24-99
Preservative:	HgCl2 & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	270	1	0.2
Toluene	33.7	1	0.2
Ethylbenzene	85.4	1	0.2
p,m-Xylene	215	1	0.2
o-Xylene	74.0	1	0.1
Total Xylene	289		
Total BTEX	678		


ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	97 %
	Bromofluorobenzene	97 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC #1 E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	403410
Sample ID:	MW #5R	Date Reported:	08-24-99
Chain of Custody:	6698	Date Sampled:	08-23-99
Laboratory Number:	F964	Date Received:	08-23-99
Sample Matrix:	Water	Date Analyzed:	08-24-99
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	1.0	1	0.2
Toluene	2.4	1	0.2
Ethylbenzene	0.2	1	0.2
p,m-Xylene	8.6	1	0.2
o-Xylene	2.7	1	0.1
Total Xylene	11.3		
Total BTEX	14.9		


ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	96 %
	Bromofluorobenzene	96 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC #1 E.


Analyst


Review

669

ENVIROTECH INC.

5796 U.S. Highway 64
Farmington, New Mexico 87401
(505) 632-0615

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	N/A	Project #:	N/A
Sample ID:	08-24-BTEX QA/QC	Date Reported:	08-24-99
Laboratory Number:	F964	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	08-24-99
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF:	C-Cal RF:	%Diff.	Blank Conc	Detect. Limit
		Accept. Range 0 - 15%			
Benzene	3.6219E-001	3.6335E-001	0.32%	ND	0.2
Toluene	2.7867E-002	2.7872E-002	0.02%	ND	0.2
Ethylbenzene	4.1931E-002	4.1981E-002	0.12%	ND	0.2
p,m-Xylene	3.6569E-002	3.6576E-002	0.02%	ND	0.2
o-Xylene	3.1955E-002	3.2051E-002	0.30%	ND	0.1

Duplicate Conc. (ug/L)	Sample	Duplicate	%Diff.	Accept Limit
Benzene	1.0	1.0	0.0%	0 - 30%
Toluene	2.4	2.4	0.0%	0 - 30%
Ethylbenzene	0.2	0.2	0.0%	0 - 30%
p,m-Xylene	8.6	8.9	3.5%	0 - 30%
o-Xylene	2.7	2.7	0.0%	0 - 30%

Spike Conc. (ug/L)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Limits
Benzene	1.0	50.0	51.1	100%	39 - 150
Toluene	2.4	50.0	52.5	100%	46 - 148
Ethylbenzene	0.2	50.0	50.2	100%	32 - 160
p,m-Xylene	8.6	100.0	109	100%	46 - 148
o-Xylene	2.7	50.0	52.8	100%	46 - 148

ND - Parameter not detected at the stated detection limit.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for samples F964 - F969.

Analyst

Review

BLAGG ENGINEERING, INC.**MONITOR WELL SAMPLING DATA**CLIENT : AMOCO PRODUCTION CO.CHAIN-OF-CUSTODY # : 7448

COOPER GC #1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ENVIROTECH, INC.Date : December 6, 1999SAMPLER : N J VFilename : 12-06-99.WK4PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING TIME	pH	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	80.64	13.65	26.00	-	-	-	-	-
MW - 3R	97.03	79.21	17.82	34.03	1050	7.1	1,200	8.00	-
MW - 5	-	-	-	23.50	-	-	-	-	-
MW - 5R	94.12	77.07	17.05	31.00	1130	7.0	1,800	7.00	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$.
(i.e. 2" MW $r = (1/12) \text{ ft.}$ $h = 1 \text{ ft.}$) (i.e. 4" MW $r = (2/12) \text{ ft.}$ $h = 1 \text{ ft.}$)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 ".Collected BTEX samples for MW #3R & #5R. DTW @ #3R = 20.0 ft. during collection.BEI reclamation system not operating @ time of sampling.

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	403410
Sample ID:	MW # 3R	Date Reported:	12-07-99
Chain of Custody:	7448	Date Sampled:	12-06-99
Laboratory Number:	G542	Date Received:	12-06-99
Sample Matrix:	Water	Date Analyzed:	12-06-99
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	103	1	0.2
Toluene	410	1	0.2
Ethylbenzene	98.5	1	0.2
p,m-Xylene	786	1	0.2
o-Xylene	219	1	0.1
Total Xylene	1,010		
Total BTEX	1,620		

ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	96 %
	Bromofluorobenzene	96 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC # 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	403410
Sample ID:	MW # 5R	Date Reported:	12-07-99
Chain of Custody:	7448	Date Sampled:	12-06-99
Laboratory Number:	G543	Date Received:	12-06-99
Sample Matrix:	Water	Date Analyzed:	12-06-99
Preservative:	HgCl ₂ & Cool	Analysis Requested:	BTEX
Condition:	Cool & Intact		

Parameter	Concentration (ug/L)	Dilution Factor	Det. Limit (ug/L)
Benzene	5.4	1	0.2
Toluene	ND	1	0.2
Ethylbenzene	ND	1	0.2
p,m-Xylene	25.1	1	0.2
o-Xylene	25.8	1	0.1
Total Xylene	50.9		
Total BTEX	56.3		

ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	98 %
	Bromofluorobenzene	98 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: Cooper GC # 1E.


Analyst


Review

7448

ENVIROTECH INC.

5796 U.S. Highway 64
Farmington, New Mexico 87401
(505) 632-0615

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	N/A	Project #:	N/A
Sample ID:	12-06-BTEX QA/QC	Date Reported:	12-07-99
Laboratory Number:	G538	Date Sampled:	N/A
Sample Matrix:	Water	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	12-06-99
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF:	C-Cal RF:	%Diff.	Blank Conc	Detect. Limit
		Accept. Range 0 - 15%			
Benzene	1.0021E+000	1.0054E+000	0.32%	ND	0.2
Toluene	6.8221E-001	6.8234E-001	0.02%	ND	0.2
Ethylbenzene	6.1562E-002	6.1636E-002	0.12%	ND	0.2
p,m-Xylene	5.6170E-002	5.6181E-002	0.02%	ND	0.2
o-Xylene	5.1027E-002	5.1180E-002	0.30%	ND	0.1

Duplicate Conc. (ug/L)	Sample	Duplicate	%Diff.	Accept Limit
Benzene	42.7	41.1	3.7%	0 - 30%
Toluene	119	119	0.0%	0 - 30%
Ethylbenzene	113	110	2.8%	0 - 30%
p,m-Xylene	1,100	1,080	1.8%	0 - 30%
o-Xylene	540	524	2.9%	0 - 30%

Spike Conc. (ug/L)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Limits
Benzene	42.7	50.0	93.0	100%	39 - 150
Toluene	119	50.0	172	102%	46 - 148
Ethylbenzene	113	50.0	165	101%	32 - 160
p,m-Xylene	1,100	100.0	1,200	100%	46 - 148
o-Xylene	540	50.0	600	102%	46 - 148

ND - Parameter not detected at the stated detection limit.

* - Administrative level set at 80 - 120.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for samples G538 - G545.

Analyst

Review

BLAGG ENGINEERING, INC.
MONITOR WELL SAMPLING DATA

CLIENT : BP AMOCO

CHAIN-OF-CUSTODY # : 10361

COOPER GC #1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ON - SITE TECH.

Date : February 24, 2000

SAMPLER : N J V

Filename : 02-24-00.WK4

PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING TIME	pH	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	75.64	18.65	26.00	-	-	-	-	-
MW - 3R	97.03	75.41	21.62	34.03	0900	7.6	2,500	6.25	-
MW - 5	-	-	-	23.50	-	-	-	-	-
MW - 5R	94.12	72.46	21.66	31.00	0850	7.6	1,000	4.75	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$.
(i.e. 2" MW $r = (1/12) \text{ ft.}$ $h = 1 \text{ ft.}$) (i.e. 4" MW $r = (2/12) \text{ ft.}$ $h = 1 \text{ ft.}$)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2"

Collected BTEX samples from MW #3R & #5R . BEI reclamation system operating @
time of sampling . Collected true DTW measurements on 2 / 25 / 00 . DTW decreased
between 3.80 - 5.00 ft. since last sampling event (12 / 06 / 99) .

OFF: (505) 325-5667



LAB: (505) 325-1556

ANALYTICAL REPORT

Date: 01-Mar-00

Client:	Blagg Engineering	Client Sample Info:	Cooper GC #1E
Work Order:	0002054	Client Sample ID:	MW #3R
Lab ID:	0002054-01A	Matrix:	AQUEOUS
Project:	BP Amoco- Cooper GC #1E	Collection Date:	2/24/2000 9:00:00 AM
		COC Record:	10361

Parameter	Result	PQL	Qual	Units	DF	Date Analyzed
AROMATIC VOLATILES BY GC/PID		SW8021B		Analyst: DM		
Benzene	290	5		µg/L	10	2/29/2000
Toluene	790	5		µg/L	10	2/29/2000
Ethylbenzene	130	5		µg/L	10	2/29/2000
m,p-Xylene	1200	10		µg/L	10	2/29/2000
o-Xylene	220	5		µg/L	10	2/29/2000

Qualifiers:

PQL - Practical Quantitation Limit

ND - Not Detected at Practical Quantitation Limit

J - Analyte detected below Practical Quantitation Limit

B - Analyte detected in the associated Method Blank

S - Spike Recovery outside accepted recovery limits

R - RPD outside accepted recovery limits

E - Value above quantitation range

Surr: - Surrogate

1 of 1

P.O. BOX 2606 • FARMINGTON, NM 87499

- TECHNOLOGY BLENDING INDUSTRY WITH THE ENVIRONMENT -

OFF: (505) 325-5667



LAB: (505) 325-1556

ANALYTICAL REPORT

Date: 01-Mar-00

Client:	Blagg Engineering	Client Sample Info:	Cooper GC #1E
Work Order:	0002054	Client Sample ID:	MW #5R
Lab ID:	0002054-02A	Matrix:	AQUEOUS
Project:	BP Amoco- Cooper GC #1E	Collection Date:	2/24/2000 8:50:00 AM
		COC Record:	10361

Parameter	Result	PQL	Qual	Units	DF	Date Analyzed
AROMATIC VOLATILES BY GC/PID		SW8021B		Analyst: DM		
Benzene	ND	0.5		µg/L	1	2/29/2000
Toluene	ND	0.5		µg/L	1	2/29/2000
Ethylbenzene	ND	0.5		µg/L	1	2/29/2000
m,p-Xylene	ND	1		µg/L	1	2/29/2000
o-Xylene	ND	0.5		µg/L	1	2/29/2000

Qualifiers:	PQL - Practical Quantitation Limit	S - Spike Recovery outside accepted recovery limits
	ND - Not Detected at Practical Quantitation Limit	R - RPD outside accepted recovery limits
	J - Analyte detected below Practical Quantitation Limit	E - Value above quantitation range
	B - Analyte detected in the associated Method Blank	Surr: - Surrogate

1 of 1

P.O. BOX 2606 • FARMINGTON, NM 87499

- TECHNOLOGY BLENDING INDUSTRY WITH THE ENVIRONMENT -

TECHNOLOGIES, LTD.

612 E. Murray Dr. • P.O. Box 2606 • Farmington, NM 87499
LAB: (505) 325-5667 • FAX: (505) 327-1496

Date: 2/24/20

Page: 1 of 1[illegible]

On Site Technologies, LTD.

Date: 01-Mar-00

CLIENT: Blagg Engineering
Work Order: 0002054
Project: BP Amoco- Cooper GC #1E

QC SUMMARY REPORT

Method Blank

Sample ID: MB1	Batch ID: GC-1_000229	Test Code: SW8021B	Units: µg/L	Analysis Date: 2/29/2000	Prep Date:
Client ID:	0002054	Run ID: GC-1_000229A		SeqNo: 24671	
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC LowLimit HighLimit RPD Ref Val %RPD RPDLimit Qual
Benzene	.0873	0.5			J
Ethylbenzene	.0742	0.5			J
m,p-Xylene	.2172	1			J
Methyl tert-Butyl Ether	ND	1			
o-Xylene	.0814	0.5			J
Toluene	.1879	0.5			J

Qualifiers: ND - Not Detected at the Reporting Limit
 J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
 R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

On Site Technologies, LTD.

Date: 01-Mar-00

CLIENT: Blagg Engineering
Work Order: 0002054
Project: BP Amoco- Cooper GC #1E

QC SUMMARY REPORT

Sample Matrix Spike

Sample ID: 0002054-01AMS		Batch ID: GC-1_000229		Test Code: SW8021B		Units: µg/L		Analysis Date 2/29/2000		Prep Date:		
Client ID: MW #3R	0002054	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	SeqNo: 24672	%RPD	RPDLimit	Qual
Analyte												
Benzene		687	5	400	288.1	99.7%	73	126				
Ethylbenzene		531.7	5	400	134.6	99.3%	88	113				
m,p-Xylene		1964	10	800	1178	98.3%	83	112				
Methyl tert-Butyl Ether		402	10	400	0	100.5%	81	125				
o-Xylene		619.8	5	400	223.8	99.0%	93	110				
Toluene		1200	5	400	787	103.3%	76	126				

Sample ID: 0002054-01AMSD		Batch ID: GC-1_000229	Test Code: SW8021B	Units: µg/L	Analysis Date 2/29/2000		Prep Date:				
Client ID: MW #3R	0002054	Run ID: GC-1_000229A			SeqNo: 24673						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	661.9	5	400	288.1	93.4%	73	126	687	3.7%	6	
Ethylbenzene	513.1	5	400	134.6	94.6%	88	113	531.7	3.6%	5	
m,p-Xylene	1894	10	800	1178	89.5%	83	112	1964	3.6%	7	
Methyl tert-Butyl Ether	393.2	10	400	0	98.3%	81	125	402	2.2%	9	
o-Xylene	620.4	5	400	223.8	99.2%	93	110	619.8	0.1%	6	
Toluene	1156	5	400	787	92.3%	76	126	1200	3.8%	6	

Qualifiers: ND - Not Detected at the Reporting Limit
J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

On Site Technologies, LTD.

Date: 01-Mar-00

CLIENT: Blagg Engineering
Work Order: 0002054
Project: BP Amoco- Cooper GC #1E

QC SUMMARY REPORT

Laboratory Control Spike - generic

Sample ID: LCS WATER		Batch ID: GC-1_000229	Test Code: SW8021B	Units: µg/L	Analysis Date 2/29/2000		Prep Date:				
Client ID:	0002054	Run ID:	GC-1_000229A		SeqNo:	24670					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	39.59	0.5	40	0.0873	98.8%	89	112				
Ethylbenzene	40.28	0.5	40	0.0742	100.5%	93	112				
m,p-Xylene	76.5	1	80	0.2172	95.4%	88	108				
Methyl tert-Butyl Ether	39.41	1	40	0	98.5%	87	115				
o-Xylene	40.09	0.5	40	0.0814	100.0%	93	112				
Toluene	40.02	0.5	40	0.1879	99.6%	92	111				

Qualifiers: ND - Not Detected at the Reporting Limit
J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

On Site Technologies, LTD.

Date: 01-Mar-00

CLIENT: Blagg Engineering
Work Order: 0002054
Project: BP Amoco- Cooper GC #1E

QC SUMMARY REPORT

Continuing Calibration Verification Standard

Sample ID: CCV1 BTEX_0001		Batch ID: GC-1_000229	Test Code: SW8021B	Units: µg/L	Analysis Date 2/29/2000		Prep Date:				
Client ID:	0002054	Run ID:	GC-1_000229A		SeqNo: 24665						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	19.78	0.5	20	0	98.9%	85	115				
Ethylbenzene	20.37	0.5	20	0	101.9%	85	115				
m,p-Xylene	38.43	1	40	0	96.1%	85	115				
Methyl tert-Butyl Ether	20.01	1	20	0	100.0%	85	115				
o-Xylene	20.25	0.5	20	0	101.2%	85	115				
Toluene	19.98	0.5	20	0	99.9%	85	115				
1,4-Difluorobenzene	89.73	0	100	0	89.7%	80	105				
4-Bromochlorobenzene	90.01	0	100	0	90.0%	78	108				
Fluorobenzene	88.26	0	100	0	88.3%	78	108				

Sample ID: CCV2 BTEX_0001		Batch ID: GC-1_000229	Test Code: SW8021B	Units: µg/L	Analysis Date 2/29/2000		Prep Date:				
Client ID:		0002054	Run ID:	GC-1_000229A	SeqNo:	24666					
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	19.1	0.5	20	0	95.5%	85	115				
Ethylbenzene	19.64	0.5	20	0	98.2%	85	115				
m,p-Xylene	36.94	1	40	0	92.3%	85	115				
Methyl tert-Butyl Ether	19.41	1	20	0	97.0%	85	115				
o-Xylene	19.59	0.5	20	0	98.0%	85	115				
Toluene	19.28	0.5	20	0	96.4%	85	115				
1,4-Difluorobenzene	89.93	0	100	0	89.9%	80	105				
4-Bromochlorobenzene	90.04	0	100	0	90.0%	78	108				
Fluorobenzene	88.09	0	100	0	88.1%	78	108				

Qualifiers: ND - Not Detected at the Reporting Limit
J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

QC SUMMARY REPORT
Continuing Calibration Verification Standard

CLIENT: Blagg Engineering
Work Order: 0002054
Project: BP Amoco-Cooper GC #1E

Sample ID: CCV3 BTEX_0001		Batch ID: GC-1_000229	Test Code: SW8021B	Units: µg/L	Analysis Date 2/29/2000		Prep Date:
Client ID: 0002054		Run ID: GC-1_000229A	PQL	SPK value	SPK Ref Val	%REC	SeqNo: 24667
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit
Benzene	38.44	0.5	40	0	96.1%	85	115
Ethylbenzene	38.91	0.5	40	0	97.3%	85	115
m,p-Xylene	73.62	1	80	0	92.0%	85	115
Methyl tert-Butyl Ether	39.67	1	40	0	99.2%	85	115
o-Xylene	38.98	0.5	40	0	97.5%	85	115
Toluene	38.82	0.5	40	0	97.0%	85	115
1,4-Difluorobenzene	89.07	0	100	0	89.1%	80	105
4-Bromochlorobenzene	90.83	0	100	0	90.8%	78	108
Fluorobenzene	87.69	0	100	0	87.7%	78	108

Sample ID: CCV4 BTEX_0001		Batch ID: GC-1_000229	Test Code: SW8021B	Units: µg/L	Analysis Date 2/29/2000		Prep Date:
Client ID: 0002054		Run ID: GC-1_000229A	PQL	SPK value	SPK Ref Val	%REC	SeqNo: 24668
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit
Benzene	20.78	0.5	20	0	103.9%	85	115
Ethylbenzene	21.36	0.5	20	0	106.8%	85	115
m,p-Xylene	40.26	1	40	0	100.6%	85	115
Methyl tert-Butyl Ether	17.61	1	20	0	88.1%	85	115
o-Xylene	21.27	0.5	20	0	106.3%	85	115
Toluene	20.96	0.5	20	0	104.8%	85	115
1,4-Difluorobenzene	88.96	0	100	0	89.0%	80	105
4-Bromochlorobenzene	88	0	100	0	88.0%	78	108
Fluorobenzene	88.46	0	100	0	88.5%	78	108

Qualifiers: ND - Not Detected at the Reporting Limit
J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

CLIENT: Blagg Engineering
Work Order: 0002054
Project: BP Amoco- Cooper GC #1E

QC SUMMARY REPORT
 Continuing Calibration Verification Standard

Sample ID: CCV5 BTEX_0001		Batch ID: GC-1_000229	Test Code: SW8021B	Units: µg/L	Analysis Date 2/29/2000			Prep Date:				
Client ID:		0002054	Run ID:	GC-1_000229A		SeqNo:	24669					
Analyte		Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene		20.23	0.5	20	0	101.2%	85	115				
Ethylbenzene		20.81	0.5	20	0	104.1%	85	115				
m,p-Xylene		39.26	1	40	0	98.2%	85	115				
Methyl tert-Butyl Ether		20.94	1	20	0	104.7%	85	115				
o-Xylene		20.83	0.5	20	0	104.2%	85	115				
Toluene		20.48	0.5	20	0	102.4%	85	115				
1,4-Difluorobenzene		90.04	0	100	0	90.0%	80	105				
4-Bromochlorobenzene		88.66	0	100	0	88.7%	78	108				
Fluorobenzene		88.26	0	100	0	88.3%	78	108				

Qualifiers: ND - Not Detected at the Reporting Limit
 J - Analyte detected below quantitation limits
 S - Spike Recovery outside accepted recovery limits
 R - RPD outside accepted recovery limits
 B - Analyte detected in the associated Method Blank

On Site Technologies, LTD.

Date: 01-Mar-00

CLIENT: Blagg Engineering
Work Order: 0002054
Project: BP Amoco- Cooper GC #1E
Test No: SW8021B

QC SUMMARY REPORT SURROGATE RECOVERIES

Aromatic Volatiles by GC/PID

Sample ID	14FBZ	4BCBZ	FLBZ
0002054-01A	88	88.9	87.9
0002054-01AMS	88.3	89.1	87.2
0002054-01AMSD	87.8	88.6	86.2
0002054-02A	90.1	89.9	89.1
0002055-01A	91.1	89.6	90.4
0002055-02A	89.7	87.8	88.9
0002055-03A	89.7	89.7	89.5
0002055-04A	90	89.7	90.8
0002055-05A	90.8	89.7	89.1
0002055-06A	89.5	88.6	89.4
0002058-01A	89.8	89.4	89.7
0002059-01A	90	90.7	89
0002059-02A	89.5	90	88.8
0002059-03A	90.8	90.6	88.7
0002059-04A	89.4	89.2	88.6
0002059-05A	90.4	90.1	88.9
0002059-06A	90.1	90.4	89.1
0002063-01A	87.5	86.6	86.8
CCV1 BTEX_00010	89.7	90	88.2
CCV2 BTEX_00010	89.9	90	88.1
CCV3 BTEX_00010	89.1	90.8	87.7
CCV4 BTEX_00010	89	88	88.5
CCV5 BTEX_00010	90	88.7	88.2
LCS WATER	89.1	89.9	87.8
MBI	90	88.9	89.3

Acronym	Surrogate	QC Limits
14FBZ	= 1,4-Difluorobenzene	80-105
4BCBZ	= 4-Bromochlorobenzene	78-108
FLBZ	= Fluorobenzene	78-108

* Surrogate recovery outside acceptance limits

BLAGG ENGINEERING, INC.**MONITOR WELL SAMPLING DATA**CLIENT : BP AMOCOCHAIN-OF-CUSTODY # : 10583

COOPER GC #1E - SEPARATOR PIT
UNIT J, SEC. 15, T29N, R11W

LABORATORY (S) USED : ON - SITE TECH.Date : May 15, 2000SAMPLER : N J VFilename : 05-15-00.WK4PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING TIME	pH	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	78.17	16.12	26.00	-	-	-	-	-
MW - 3R	97.03	76.54	20.49	34.03	1520	7.2	6,600	6.75	-
MW - 5R	94.12	73.82	20.30	31.00	1445	7.2	1,200	5.25	-

NOTES : Volume of water purged from well prior to sampling: $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$.(i.e. 2" MW $r = (1/12) \text{ ft. } h = 1 \text{ ft.}$ (i.e. 4" MW $r = (2/12) \text{ ft. } h = 1 \text{ ft.}$)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 ".Collected BTEX samples from MW # 3R & # 5R . BEI reclamation system operating @time of sampling . Collected true DTW measurements on 5 / 19 / 00 .

OFF: (505) 325-5667
FAX: (505) 327-1496



LAB: (505) 325-1556
FAX: (505) 327-1496

ANALYTICAL REPORT

Date: 22-May-00

Client:	Blagg Engineering	Client Sample Info:	Cooper GC #1E
Work Order:	0005032	Client Sample ID:	MW #3R
Lab ID:	0005032-01A	Matrix:	AQUEOUS
Project:	BP Amoco - Cooper GC #1E	Collection Date:	5/15/2000 3:20:00 PM
		COC Record:	10583

Parameter	Result	PQL	Qual	Units	DF	Date Analyzed
AROMATIC VOLATILES BY GC/PID		SW8021B		Analyst: DM		
Benzene	140	5		µg/L	10	5/20/2000
Toluene	110	5		µg/L	10	5/20/2000
Ethylbenzene	8.3	5		µg/L	10	5/20/2000
m,p-Xylene	480	10		µg/L	10	5/20/2000
o-Xylene	160	5		µg/L	10	5/20/2000

Qualifiers: PQL - Practical Quantitation Limit
ND - Not Detected at Practical Quantitation Limit
J - Analyte detected below Practical Quantitation Limit
B - Analyte detected in the associated Method Blank

S - Spike Recovery outside accepted recovery limits
R - RPD outside accepted recovery limits
E - Value above quantitation range
Surr: - Surrogate

P.O. BOX 2606 • FARMINGTON, NM 87499

- TECHNOLOGY BLENDING INDUSTRY WITH THE ENVIRONMENT -

OFF: (505) 325-5667
FAX: (505) 327-1496



LAB: (505) 325-1556
FAX: (505) 327-1496

ANALYTICAL REPORT

Date: 22-May-00

Client:	Blagg Engineering	Client Sample Info:	Cooper GC #1E
Work Order:	0005032	Client Sample ID:	MW #5R
Lab ID:	0005032-02A	Matrix:	AQUEOUS
Project:	BP Amoco - Cooper GC #1E	Collection Date:	5/15/2000 2:45:00 PM
		COC Record:	10583

Parameter	Result	PQL	Qual	Units	DF	Date Analyzed
AROMATIC VOLATILES BY GC/PID		SW8021B		Analyst: DM		
Benzene	ND	0.5		µg/L	1	5/20/2000
Toluene	ND	0.5		µg/L	1	5/20/2000
Ethylbenzene	ND	0.5		µg/L	1	5/20/2000
m,p-Xylene	ND	1		µg/L	1	5/20/2000
o-Xylene	ND	0.5		µg/L	1	5/20/2000

Qualifiers:

PQL - Practical Quantitation Limit

ND - Not Detected at Practical Quantitation Limit

J - Analyte detected below Practical Quantitation Limit

B - Analyte detected in the associated Method Blank

S - Spike Recovery outside accepted recovery limits

R - RPD outside accepted recovery limits

E - Value above quantitation range

Surr: - Surrogate

1 of 1

P.O. BOX 2606 • FARMINGTON, NM 87499

- TECHNOLOGY BLENDING INDUSTRY WITH THE ENVIRONMENT -

CHAIN OF CUSTODY RECORD

0
1
2
3
4
5
6
7
8
9

Page: _____ of _____

Distribution:	White - On Site	Yellow - LAB	Pink - Sampler	Goldenrod - Client
---------------	-----------------	--------------	----------------	--------------------

On Site Technologies, LTD.

Date: 22-May-00

CLIENT: Blagg Engineering
Work Order: 0005032
Project: BP Amoco - Cooper GC #1E

QC SUMMARY REPORT
Method Blank

Sample ID: MB1	Batch ID: GC-1_000520	Test Code: SW8021B	Units: µg/L	Analysis Date 5/20/2000	Prep Date:
Client ID:	0005032	Run ID: GC-1_000520A		SeqNo: 27838	
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC LowLimit HighLimit RPD Ref Val %RPD RPDLimit Qual
Benzene	ND	0.5			
Ethylbenzene	ND	0.5			
m,p-Xylene	ND	1			
Methyl tert-Butyl Ether	ND	1			
o-Xylene	ND	0.5			
Toluene	.0893	0.5			J

Qualifiers: ND - Not Detected at the Reporting Limit
J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

1 of 1

On Site Technologies, LTD.

Date: 22-May-00

CLIENT: Blagg Engineering
 Work Order: 0005032
 Project: BP Amoco - Cooper GC #1E

QC SUMMARY REPORT

Sample Matrix Spike

Sample ID: 0005022-03AMS		Batch ID: GC-1_000520		Test Code: SW8021B		Units: µg/L		Analysis Date 5/20/2000		Prep Date:	
Client ID:		0005032		Run ID:		GC-1_000520A		SeqNo: 27839			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	6560	25	2000	4300	113.0%	73	126				
Ethylbenzene	2252	25	2000	120	106.6%	88	113				
m,p-Xylene	4980	50	4000	1000	99.5%	83	112				
Methyl tert-Butyl Ether	2174	50	2000	0	108.7%	81	125				
o-Xylene	2250	25	2000	170	104.0%	93	110				
Toluene	4377	25	2000	2300	103.8%	76	126				

Sample ID: 0005022-03AMSD		Batch ID: GC-1_000520		Test Code: SW8021B		Units: µg/L		Analysis Date 5/20/2000		Prep Date:	
Client ID:		0005032		Run ID:		GC-1_000520A		SeqNo: 27840			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	6404	25	2000	4300	105.2%	73	126	6560	2.4%	6	
Ethylbenzene	2201	25	2000	120	104.1%	88	113	2252	2.3%	5	
m,p-Xylene	4874	50	4000	1000	96.8%	83	112	4980	2.2%	7	
Methyl tert-Butyl Ether	2155	50	2000	0	107.8%	81	125	2174	0.9%	9	
o-Xylene	2207	25	2000	170	101.5%	93	110	2250	1.9%	6	
Toluene	4271	25	2000	2300	98.5%	76	126	4377	2.5%	6	

Qualifiers: ND - Not Detected at the Reporting Limit
 J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
 R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

On Site Technologies, LTD.

Date: 22-May-00

CLIENT: Blagg Engineering
 Work Order: 0005032
 Project: BP Amoco - Cooper GC #IE

QC SUMMARY REPORT

Laboratory Control Spike - generic

Sample ID: LCS WATER		Batch ID: GC-1_000520		Test Code: SW8021B		Units: µg/L		Analysis Date 5/20/2000		Prep Date:	
Client ID:		0005032		Run ID:		GC-1_000520A		SeqNo: 27837			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	42.46	0.5	40	0	106.1%	89	112				
Ethylbenzene	42.76	0.5	40	0	106.9%	93	112				
m,p-Xylene	79.8	1	80	0	99.7%	88	108				
Methyl tert-Butyl Ether	43.17	1	40	0	107.9%	87	115				
o-Xylene	42.04	0.5	40	0	105.1%	93	112				
Toluene	42.16	0.5	40	0.0893	105.2%	92	111				

Qualifiers: ND - Not Detected at the Reporting Limit
 J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
 R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

On Site Technologies, LTD.

Date: 22-May-00

CLIENT: Blagg Engineering
Work Order: 0005032
Project: BP Amoco - Cooper GC #1E

QC SUMMARY REPORT

Continuing Calibration Verification Standard

Sample ID: CCV1 BTEX_0004		Batch ID: GC-1_000520	Test Code: SW8021B		Units: µg/L		Analysis Date 5/20/2000			Prep Date:			
Client ID:		0005032	Run ID:	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Analyte	Result												
Benzene	22.59			0.5	20	0	112.9%	85	115				
Ethylbenzene	22.45			0.5	20	0	112.3%	85	115				
m,p-Xylene	41.89			1	40	0	104.7%	85	115				
Methyl tert-Butyl Ether	22.37			1	20	0	111.8%	85	115				
o-Xylene	22.1			0.5	20	0	110.5%	85	115				
Toluene	21.9			0.5	20	0	109.5%	85	115				
1,4-Difluorobenzene	88.27			0	100	0	88.3%	80	105				
4-Bromochlorobenzene	94.25			0	100	0	94.3%	78	108				
Fluorobenzene	84.19			0	100	0	84.2%	78	108				

Sample ID: CCV2 BTEX_0004		Batch ID: GC-1_000520	Test Code: SW8021B	Units: µg/L		Analysis Date 5/20/2000		Prep Date:			
Client ID:		0005032	Run ID:	GC-1_000520A	SeqNo: 27835						
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	21.55	0.5	20	0	107.7%	85	115				
Ethylbenzene	21.85	0.5	20	0	109.2%	85	115				
m,p-Xylene	40.65	1	40	0	101.6%	85	115				
Methyl tert-Butyl Ether	22.5	1	20	0	112.5%	85	115				
o-Xylene	21.57	0.5	20	0	107.8%	85	115				
Toluene	21.37	0.5	20	0	106.9%	85	115				
1,4-Difluorobenzene	87.86	0	100	0	87.9%	80	105				
4-Bromochlorobenzene	95.32	0	100	0	95.3%	78	108				
Fluorobenzene	83.48	0	100	0	83.5%	78	108				

Qualifiers: NID - Not Detected at the Reporting Limit
J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

CLIENT: Blagg Engineering

Work Order: 0005032

Project: BP Amoco - Cooper GC #1E

QC SUMMARY REPORT

Continuing Calibration Verification Standard

Sample ID: CCV3 BTEX_0004	Batch ID: GC-1_000520	Test Code: SW8021B	Units: µg/L	Analysis Date: 5/20/2000	Prep Date:
Client ID: 0005032	Run ID: GC-1_000520A	PQL	SPK value	SeqNo: 27836	
Analyte	Result		SPK Ref Val	LowLimit	HighLimit
Benzene	41.16	0.5	40	85	115
Ethylbenzene	41.2	0.5	40	85	115
m,p-Xylene	76.73	1	80	85	115
Methyl tert-Butyl Ether	43.95	1	40	85	115
o-Xylene	40.74	0.5	40	85	115
Toluene	40.75	0.5	40	85	115
1,4-Difluorobenzene	87.67	0	100	80	105
4-Bromochlorobenzene	94.93	0	100	78	108
Fluorobenzene	83.13	0	100	78	108
		%REC	RPD Ref Val	%RPD	RPDLimit
		102.9%			
		103.0%			
		95.9%			
		109.9%			
		101.9%			
		101.9%			
		87.7%			
		94.9%			
		83.1%			

Qualifiers:

ND - Not Detected at the Reporting Limit

S - Spike Recovery outside accepted recovery limits

B - Analyte detected in the associated Method Blank

J - Analyte detected below quantitation limits

R - RPD outside accepted recovery limits

On Site Technologies, LTD.

Date: 22-May-00

CLIENT: Blagg Engineering
 Work Order: 0005032
 Project: BP Amoco - Cooper GC #1E
 Test No: SW8021B

QC SUMMARY REPORT SURROGATE RECOVERIES

Aromatic Volatiles by GC/PID

Sample ID	14FBZ	4BCBZ	FLBZ
0005018-01A	86.2	96.2	81.3
0005020-04A	88.4	93.9	84.4
0005022-01A	88.8	94.4	84.4
0005022-03A	86.6	95.1	82.1
0005022-03AMS	86.4	95.4	82.3
0005022-03AMSD	86.3	95.4	82.2
0005022-06A	83.2	93.4	79.3
0005022-08A	87.5	92.8	83.1
0005023-01A	86.5	94.1	82.6
0005031-01A	87	94.3	83.8
0005031-02A	87.8	94.7	83.9
0005031-03A	87.9	95.1	83.8
0005031-04A	87.6	94.6	83.7
0005032-01A	88	95	83.5
0005032-02A	88	94.6	84
0005036-01A	88.3	94.9	84.6
0005036-02A	88.3	95.1	84.1
0005036-03A	85.1	93.1	81.6
0005036-04A	88.3	95.1	84.2
0005036-05A	87.7	94.9	83.5
0005049-03A	87.6	92.9	83.3
0005049-05A	88.5	95	84.5
CCV1 BTEX_00040	88.3	94.2	84.2
CCV2 BTEX_00040	87.8	95.3	83.5
CCV3 BTEX_00040	87.7	94.9	83.1
LCS WATER	87.7	95	83
MBI	88.5	92.1	83.8

Acronym	Surrogate	QC Limits
14FBZ	= 1,4-Difluorobenzene	80-105
4BCBZ	= 4-Bromochlorobenzene	78-108
FLBZ	= Fluorobenzene	78-108

* Surrogate recovery outside acceptance limits

BLAGG ENGINEERING, INC.

MONITOR WELL SAMPLING DATA

CLIENT : BP AMOCO

CHAIN-OF-CUSTODY # : 10773

COOPER GC #1E - SEPARATOR PIT

LABORATORY (S) USED : ON - SITE TECH.

UNIT J, SEC. 15, T29N, R11W

Date : November 28, 2000

SAMPLER : N J V

Filename : 11-28-00.WK4

PROJECT MANAGER : N J V

WELL #	WELL ELEV. (ft)	WATER ELEV. (ft)	DEPTH TO WATER (ft)	TOTAL DEPTH (ft)	SAMPLING TIME	pH	CONDUCT (umhos)	VOLUME PURGED (gal.)	FREE PRODUCT (ft)
MW - 2R	94.29	81.62	12.67	26.00	-	-	-	-	-
MW - 3R	97.03	81.47	15.56	34.03	1100	7.6	900	9.00	-
MW - 5R	94.12	78.81	15.31	31.00	-	-	-	-	-

NOTES : Volume of water purged from well prior to sampling; $V = \pi \times r^2 \times h \times 7.48 \text{ gal./ft}^3 \times 3 \text{ (wellbores)}$.

(i.e. 2" MW $r = (1/12) \text{ ft}$. $h = 1 \text{ ft}$.) (i.e. 4" MW $r = (2/12) \text{ ft}$. $h = 1 \text{ ft}$.)

Ideally a minimum of three (3) wellbore volumes:

1.25 " well diameter = 0.19 gallons per foot of water (or 24 oz.).

2 bails per foot - small teflon bailer.

3 bails per foot - 3 / 4 " teflon bailer.

2.00 " well diameter = 0.49 gallons per foot of water.

4.00 " well diameter = 1.95 gallons per foot of water.

Comments or note well diameter if not standard 2 ".

Collected BTEX samples from MW #3R only . BEI reclamation system operating @

time of sampling .

OFF: (505) 325-5667
FAX: (505) 327-1496



LAB: (505) 325-1556
FAX: (505) 327-1496

ANALYTICAL REPORT

Date: 15-Dec-00

Client:	Blagg Engineering	Client Sample Info:	Cooper GC #1E
Work Order:	0011047	Client Sample ID:	MW #3R
Lab ID:	0011047-01A	Matrix:	AQUEOUS
Project:	BP - Cooper GC #1E	Collection Date:	11/28/2000 11:00:00 AM
		COC Record:	10773

Parameter	Result	PQL	Qual	Units	DF	Date Analyzed
AROMATIC VOLATILES BY GC/PID		SW8021B		Analyst: DC		
Benzene	220	5		µg/L	10	12/5/2000
Toluene	880	5		µg/L	10	12/5/2000
Ethylbenzene	74	5		µg/L	10	12/5/2000
m,p-Xylene	800	10		µg/L	10	12/5/2000
o-Xylene	210	5		µg/L	10	12/5/2000


Qualifiers:	PQL - Practical Quantitation Limit	S - Spike Recovery outside accepted recovery limits
	ND - Not Detected at Practical Quantitation Limit	R - RPD outside accepted recovery limits
	J - Analyte detected below Practical Quantitation Limit	E - Value above quantitation range
	B - Analyte detected in the associated Method Blank	Surr: - Surrogate

1 of 1

P.O. BOX 2606 • FARMINGTON, NM 87499

EMAIL: ONSITE@ONSITELTD.COM

- TECHNOLOGY BLENDING INDUSTRY WITH THE ENVIRONMENT -



CHAIN OF CUSTODY RECORD

Date: 11/28/00

Page: 1 of 1

612 E. Murray Dr. • P.O. Box 2606 • Farmington, NM 87499
LAB: (505) 325-5667 • FAX: (505) 327-1496

Purchase Order No.:		Project No.	
Name: JEFF BLACC		Title:	
Company: BLACC ENGINEERING, INC.		Company: SAME	
Address:		Mailing Address:	
City, State, Zip:		City, State, Zip:	
Telephone No. 632-1199		Telephone No. 632-3903	
FAX No. 632-1199		FAX No. 632-3903	
PROJECT LOCATION: BP - COOPER GC #1E		ANALYSIS REQUESTED	
SAMPLER'S SIGNATURE: <i>John V. [Signature]</i>		LAB ID	
SAMPLE IDENTIFICATION		Containers	
DATE	TIME	MATRIX	PRES.
11/28/00	1100	WATER	1515
MW # 3R		2	
Relinquished by: <i>John V. [Signature]</i>		Received by: <i>John V. [Signature]</i>	
Date/Time		Date/Time	
11/28/00 1100		11/28/00 1515	
Relinquished by:		Received by:	
Date/Time		Date/Time	
Relinquished by:		Received by:	
Date/Time		Date/Time	
Method of Shipment:		Rush	
		24-48 Hours	
		10 Working Days	
		By Date	
Authorized by:		Special Instructions / Remarks:	
(Client Signature Must Accompany Request)			

On Site Technologies, LTD.

Date: 15-Dec-00

CLIENT: Blagg Engineering
Work Order: 0011047
Project: BP - Cooper GC #IE

QC SUMMARY REPORT

Method Blank

Sample ID: MB1	Batch ID: GC-1_001205	Test Code: SW8021B	Units: µg/L	Analysis Date 12/5/2000	Prep Date:						
Client ID:	0011047	Run ID: GC-1_001205A		SeqNo: 33206							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	ND	0.5									J
Ethylbenzene	.0771	0.5									J
m,p-Xylene	.2174	1									J
Methyl tert-Butyl Ether	ND	1									J
o-Xylene	.2053	0.5									J
Toluene	ND	0.5									

Qualifiers: ND - Not Detected at the Reporting Limit
 J - Analyte detected below quantitation limits
 S - Spike Recovery outside accepted recovery limits
 R - RPD outside accepted recovery limits
 B - Analyte detected in the associated Method Blank

On Site Technologies, LTD.

Date: 15-Dec-00

CLIENT: Blagg Engineering
Work Order: 0011047
Project: BP - Cooper GC #1E

QC SUMMARY REPORT

Sample Matrix Spike

Sample ID: 0012002-03AMS		Batch ID: GC-1_001205		Test Code: SW8021B		Units: µg/L		Analysis Date 12/5/2000		Prep Date:	
Client ID: 0011047		Run ID: GC-1_001205A		SeqNo: 33207							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	1939	25	2000	0	97.0%	88	112				
Ethylbenzene	1968	25	2000	41.32	96.4%	86	113				
m,p-Xylene	4855	50	4000	1051	95.1%	85	108				
Methyl tert-Butyl Ether	1964	50	2000	0	98.2%	86	117				
o-Xylene	2031	25	2000	75.36	97.8%	92	110				
Toluene	1974	25	2000	0	98.7%	88	116				

Sample ID: 0012002-03AMSD		Batch ID: GC-1_001205		Test Code: SW8021B		Units: µg/L		Analysis Date 12/5/2000		Prep Date:	
Client ID: 0011047		Run ID: GC-1_001205A		SeqNo: 33208							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	1950	25	2000	0	97.5%	88	112	1939	0.5%	6	
Ethylbenzene	1980	25	2000	41.32	96.9%	86	113	1968	0.6%	6	
m,p-Xylene	4890	50	4000	1051	96.0%	85	108	4855	0.7%	6	
Methyl tert-Butyl Ether	1998	50	2000	0	99.9%	86	117	1964	1.7%	7	
o-Xylene	2051	25	2000	75.36	98.8%	92	110	2031	1.0%	6	
Toluene	1989	25	2000	0	99.5%	88	116	1974	0.8%	6	

Qualifiers: ND - Not Detected at the Reporting Limit
 J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
 R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

On Site Technologies, LTD.

Date: 15-Dec-00

CLIENT: Blagg Engineering
 Work Order: 0011047
 Project: BP - Cooper GC #1E

QC SUMMARY REPORT

Laboratory Control Spike - generic

Sample ID: LCS WATER	Batch ID: GC-1_001205	Test Code: SW8021B	Units: µg/L	Analysis Date 12/5/2000	Prep Date:
Client ID: 0011047	Run ID: GC-1_001205A	PQL	SPK value	SeqNo: 33205	
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC
Benzene	38.45	0.5	40	0	96.1%
Ethylbenzene	38.65	0.5	40	0.0771	96.4%
m,p-Xylene	77.64	1	80	0.2174	96.8%
Methyl tert-Butyl Ether	38.91	1	40	0	97.3%
o-Xylene	39.21	0.5	40	0.2053	97.5%
Toluene	39.05	0.5	40	0	97.6%
				HighLimit	RPD Ref Val
				96	111
				96	111
				92	105
				93	113
				97	110
				97	109
				%RPD	RPDLimit
					Qual

Qualifiers: ND - Not Detected at the Reporting Limit
 J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
 R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

On Site Technologies, LTD.

CLIENT: Blagg Engineering
 Work Order: 0011047
 Project: BP - Cooper GC #1E

Date: 15-Dec-00

QC SUMMARY REPORT

Continuing Calibration Verification Standard

Sample ID: CCV1 BTEX_0010		Batch ID: GC-1_001205		Test Code: SW8021B		Units: µg/L		Analysis Date 12/5/2000		Prep Date:	
Client ID: 0011047		Run ID: GC-1_001205A		SeqNo: 33202							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	20.34	0.5	20	0	101.7%	85	115				
Ethylbenzene	21.73	0.5	20	0	108.7%	85	115				
m,p-Xylene	42.14	1	40	0	105.3%	85	115				
Methyl tert-Butyl Ether	20.24	1	20	0	101.2%	85	115				
o-Xylene	20.94	0.5	20	0	104.7%	85	115				
Toluene	20.71	0.5	20	0	103.5%	85	115				
1,4-Difluorobenzene	73.54	0	80	0	91.9%	70	130				
4-Bromochlorobenzene	80.05	0	80	0	100.1%	70	130				
Fluorobenzene	73.2	0	80	0	91.5%	70	130				

Sample ID: CCV2 BTEX_0010		Batch ID: GC-1_001205		Test Code: SW8021B		Units: µg/L		Analysis Date 12/5/2000		Prep Date:	
Client ID: 0011047		Run ID: GC-1_001205A		SeqNo: 33203							
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	19.51	0.5	20	0	97.6%	85	115				
Ethylbenzene	19.8	0.5	20	0	99.0%	85	115				
m,p-Xylene	39.72	1	40	0	99.3%	85	115				
Methyl tert-Butyl Ether	19.93	1	20	0	99.7%	85	115				
o-Xylene	20.17	0.5	20	0	100.9%	85	115				
Toluene	19.77	0.5	20	0	98.9%	85	115				
1,4-Difluorobenzene	73.34	0	80	0	91.7%	70	130				
4-Bromochlorobenzene	82.12	0	80	0	102.7%	70	130				
Fluorobenzene	73.54	0	80	0	91.9%	70	130				

Qualifiers: ND - Not Detected at the Reporting Limit
 J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits
 R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

CLIENT: Blagg Engineering
Work Order: 0011047
Project: BP - Cooper GC #1E

QC SUMMARY REPORT

Continuing Calibration Verification Standard

Sample ID: CCV3 BTEX_0010		Batch ID: GC-1_001205		Test Code: SW8021B		Units: µg/L		Analysis Date 12/5/2000		Prep Date:	
Client ID:		0011047		Run ID:		GC-1_001205A		SeqNo: 33204			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	RPD Ref Val	%RPD	RPDLimit	Qual
Benzene	40.45	0.5	40	0	101.1%	85	115				
Ethylbenzene	40.3	0.5	40	0	100.8%	85	115				
m,p-Xylene	80.27	1	80	0	100.3%	85	115				
Methyl tert-Butyl Ether	41.06	1	40	0	102.7%	85	115				
o-Xylene	40.79	0.5	40	0	102.0%	85	115				
Toluene	40.68	0.5	40	0	101.7%	85	115				
1,4-Difluorobenzene	72.99	0	80	0	91.2%	70	130				
4-Bromochlorobenzene	82.48	0	80	0	103.1%	70	130				
Fluorobenzene	73.06	0	80	0	91.3%	70	130				

Qualifiers:

NID - Not Detected at the Reporting Limit

J - Analyte detected below quantitation limits

S - Spike Recovery outside accepted recovery limits

R - RPD outside accepted recovery limits

B - Analyte detected in the associated Method Blank

2 of 2

CLIENT: Blagg Engineering
Work Order: 0011047
Project: BP - Cooper GC #1E
Test No: SW8021B

QC SUMMARY REPORT SURROGATE RECOVERIES

Aromatic Volatiles by GC/PID

Sample ID	14FBZ	4BCBZ	FLBZ
0011047-01A	91.1	102	90.4
0011048-01A	90.2	98.1	89.6
0011048-02A	92.4	99.9	92.4
0011048-03A	92.3	101	94.2
0011048-04A	91.3	100	91.8
0011049-01A	93.7	103	92.6
0011049-02A	92	100	92.3
0011049-03A	91.5	99.6	91.8
0011049-04A	91.9	100	91
0011050-01A	88.1	96	87.6
0011050-02A	91.9	101	91.2
0011050-03A	89.2	99.6	92.3
0011050-04A	93.4	103	92.3
0012001-01A	91.2	101	91.6
0012002-01A	92.5	102	92.4
0012002-02A	92.8	102	93.1
0012002-03AMS	90.9	104	91.2
0012002-03AMSD	91	104	91
CCV1 BTEX_00100	91.9	100	91.5
CCV2 BTEX_00100	91.7	103	91.9
CCV3 BTEX_00100	91.2	103	91.3
LCS WATER	91	96.4	91.2
MBI	92.5	95.4	92.2

Acronym	Surrogate	QC Limits
14FBZ	= 1,4-Difluorobenzene	70-130
4BCBZ	= 4-Bromochlorobenzene	70-130
FLBZ	= Fluorobenzene	70-130

* Surrogate recovery outside acceptance limits

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / Amoco	Project #:	04034-10
Sample ID:	2 @ 23'	Date Reported:	08-11-97
Laboratory Number:	B796	Date Sampled:	08-06-97
Chain of Custody No:	5137	Date Received:	08-08-97
Sample Matrix:	Soil	Date Extracted:	08-11-97
Preservative:	Cool	Date Analyzed:	08-11-97
Condition:	Cool and Intact	Analysis Requested:	8015 TPH


Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	1,470	0.2
Diesel Range (C10 - C28)	51.6	0.1
Total Petroleum Hydrocarbons	1,520	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Comments: Cooper GC #1E Dehy Pit.


Analyst


Review

CHAIN OF CUSTODY RECORD

[illegible]

ENVIROTECH INC.

5796 U.S. Highway 64-3014

Farmington, New Mexico 87401

(505) 632-0615

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

QUALITY ASSURANCE / QUALITY CONTROL DOCUMENTATION

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA Method 8015 Modified Nonhalogenated Volatile Organic Total Petroleum Hydrocarbons

Quality Assurance Report


Client:	QA/QC	Project #:	N/A
Sample ID:	Laboratory Blank	Date Reported:	08-11-97
Laboratory Number:	08-11-TPH.BLANK	Date Sampled:	N/A
Sample Matrix:	Methylene Chloride	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	08-11-97
Condition:	N/A	Analysis Requested:	TPH


Parameter	Concentration (mg/L)	Det. Limit (mg/L)
Gasoline Range C5 - C10	ND	0.2
Diesel Range C10 - C28	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Comments: QA/QC for samples B796 - B797.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons Quality Assurance Report

Client:	QA/QC	Project #:	N/A
Sample ID:	Matrix Duplicate	Date Reported:	08-11-97
Laboratory Number:	B796	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	Cool	Date Analyzed:	08-11-97
Condition:	Cool and Intact	Analysis Requested:	TPH


Parameter	Sample Result (mg/Kg)	Duplicate Result (mg/Kg)	Percent Difference
Gasoline Range (C5 - C10)	1,470	1,400	5.0%
Diesel Range (C10 - C28)	51.6	50.4	2.5%
Total Petroleum Hydrocarbons	1,520	1,450	4.9%


ND - Parameter not detected at the stated detection limit.

QA/QC Acceptance Criteria:	Parameter	Max Difference
	Petroleum Hydrocarbons	30%

References: Method 8015, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Comments: QA/QC for samples B796 - B797.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Hydrocarbons Total Petroleum Hydrocarbons Quality Assurance Report

Client:	QA/QC	Project #:	N/A
Sample ID:	Matrix Spike	Date Reported:	08-11-97
Laboratory Number:	B796	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Analysis Requested:	TPH	Date Analyzed:	08-11-97
Condition:	N/A		

Parameter	Sample Result (mg/kg)	Spike Added (mg/kg)	Spiked Sample Result (mg/kg)	Det. Limit (mg/kg)	Percent Recovery
Gasoline Range (C5 - C10)	1,470	250	1,670	0.2	97%
Diesel Range (C10 - C28)	51.6	250	300	0.1	99%
Total Petroleum Hydrocarbons	1,520	500	1,970	0.2	98%

ND - Parameter not detected at the stated detection limit.


QA/QC Acceptance Criteria:	Parameter	Acceptance Range
----------------------------	-----------	------------------


Petroleum Hydrocarbons

75 - 125%

References: Method 8015, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Comments: QA/QC for samples B796 - B797.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons


Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	SPG - 1	Date Reported:	10-09-97
Laboratory Number:	C226	Date Sampled:	10-02-97
Chain of Custody No:	5417	Date Received:	10-07-97
Sample Matrix:	Soil	Date Extracted:	10-07-97
Preservative:	Cool	Date Analyzed:	10-08-97
Condition:	Cool and Intact	Analysis Requested:	8015 TPH


Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	15.1	0.1
Total Petroleum Hydrocarbons	15.1	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Comments: **Cooper GC #1E Stockpile.**
Grab sample.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons


Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	SPC - 1	Date Reported:	10-09-97
Laboratory Number:	C227	Date Sampled:	10-02-97
Chain of Custody No:	5417	Date Received:	10-07-97
Sample Matrix:	Soil	Date Extracted:	10-07-97
Preservative:	Cool	Date Analyzed:	10-08-97
Condition:	Cool and Intact	Analysis Requested:	8015 TPH


Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	13.8	0.1
Total Petroleum Hydrocarbons	13.8	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Comments: **Cooper GC #1E Stockpile.**
5 pt. composite.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons


Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	SPG - 2	Date Reported:	10-09-97
Laboratory Number:	C228	Date Sampled:	10-07-97
Chain of Custody No:	5417	Date Received:	10-07-97
Sample Matrix:	Soil	Date Extracted:	10-07-97
Preservative:	Cool	Date Analyzed:	10-08-97
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	78.1	0.1
Total Petroleum Hydrocarbons	78.1	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Comments: **Cooper GC #1E Stockpile.**
Grab sample.


Analyst


Review

ENVIROTECH INC.
5796 U.S. Highway 64-3014
Farmington, New Mexico 87401
(505) 632-0615

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

QUALITY ASSURANCE / QUALITY CONTROL DOCUMENTATION

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA Method 8015 Modified Nonhalogenated Volatile Organic Total Petroleum Hydrocarbons

Quality Assurance Report


Client:	QA/QC	Project #:	N/A
Sample ID:	Laboratory Blank	Date Reported:	10-09-97
Laboratory Number:	10-07-TPH.BLANK	Date Sampled:	N/A
Sample Matrix:	Methylene Chloride	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	10-08-97
Condition:	N/A	Analysis Requested:	TPH


Parameter	Concentration (mg/L)	Det. Limit (mg/L)
Gasoline Range C5 - C10	ND	0.2
Diesel Range C10 - C28	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Comments: QA/QC for samples C225 - C228.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons Quality Assurance Report

Client:	QA/QC	Project #:	N/A
Sample ID:	Matrix Duplicate	Date Reported:	10-09-97
Laboratory Number:	C225	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	Cool	Date Analyzed:	10-08-97
Condition:	Cool and Intact	Analysis Requested:	TPH


Parameter	Sample Result (mg/Kg)	Duplicate Result (mg/Kg)	Percent Difference
Gasoline Range (C5 - C10)	ND	ND	0.0%
Diesel Range (C10 - C28)	196	191	2.5%
Total Petroleum Hydrocarbons	196	191	2.5%


ND - Parameter not detected at the stated detection limit.

QA/QC Acceptance Criteria:	Parameter	Max Difference
	Petroleum Hydrocarbons	30%

References: Method 8015, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Comments: QA/QC for samples C225 - C228.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Hydrocarbons Total Petroleum Hydrocarbons Quality Assurance Report

Client:	QA/QC	Project #:	N/A
Sample ID:	Matrix Spike	Date Reported:	10-09-97
Laboratory Number:	C225	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Analysis Requested:	TPH	Date Analyzed:	10-08-97
Condition:	N/A		


Parameter	Sample Result (mg/kg)	Spike Added (mg/kg)	Spiked Sample Result (mg/kg)	Det. Limit (mg/kg)	Percent Recovery
Gasoline Range (C5 - C10)	ND	250	249	0.2	100%
Diesel Range (C10 - C28)	196	250	443	0.1	99%
Total Petroleum Hydrocarbons	196	500	692	0.2	100%


ND - Parameter not detected at the stated detection limit.

QA/QC Acceptance Criteria:	Parameter	Acceptance Range
	Petroleum Hydrocarbons	75 - 125%

References: Method 8015, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992.

Comments: QA/QC for samples C225 - C228.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons


Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	AS - 8 @ 20'	Date Reported:	04-06-98
Laboratory Number:	D077	Date Sampled:	04-03-98
Chain of Custody No:	5738	Date Received:	04-06-98
Sample Matrix:	Soil	Date Extracted:	04-06-98
Preservative:	Cool	Date Analyzed:	04-06-98
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	273	0.2
Diesel Range (C10 - C28)	8.7	0.1
Total Petroleum Hydrocarbons	282	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: Cooper GC # 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / AMOCO	Project #:	04034-10
Sample ID:	AS - 8 @ 20'	Date Reported:	04-06-98
Laboratory Number:	D077	Date Sampled:	04-03-98
Chain of Custody:	5738	Date Received:	04-06-98
Sample Matrix:	Soil	Date Analyzed:	04-06-98
Preservative:	Cool	Date Extracted:	04-06-98
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	1,420	17.5
Toluene	60,960	16.7
Ethylbenzene	47,660	15.2
p,m-Xylene	75,960	21.6
o-Xylene	73,400	10.4
Total BTEX	259,400	


ND - Parameter not detected at the stated detection limit.


Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene	97 %
	Bromofluorobenzene	97 %

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.

Comments: Cooper GC # 1E.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

Client:	QA/QC	Project #:	N/A
Sample ID:	04-06-TPH QA/QC	Date Reported:	04-06-98
Laboratory Number:	D077	Date Sampled:	N/A
Sample Matrix:	Methylene Chloride	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	04-06-98
Condition:	N/A	Analysis Requested:	TPH

Calibration	I-Cal Date	I-Cal RF:	C-Cal RF:	% Difference	Accept. Range
Gasoline Range C5 - C10	03-27-98	5.6544E-04	5.6456E-04	0.16%	0 - 15%
Diesel Range C10 - C28	03-27-98	5.4387E-04	5.4331E-04	0.10%	0 - 15%

Blank Conc. (mg/L - mg/Kg)	Concentration	Detection Limit
Gasoline Range C5 - C10	ND	0.2
Diesel Range C10 - C28	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2


Duplicate Conc. (mg/Kg)	Sample	Duplicate	% Difference	Accept. Range
Gasoline Range C5 - C10	273	271	0.8%	0 - 30%
Diesel Range C10 - C28	8.7	8.7	0.0%	0 - 30%


Spike Conc. (mg/Kg)	Sample	Spike Added	Spike Result	% Recovery	Accept. Range
Gasoline Range C5 - C10	273	250	523	100%	75 - 125%
Diesel Range C10 - C28	8.7	250	260	100%	75 - 125%

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste SW-846, USEPA, December 1996.

Comments: QA/QC for samples D077 - D079.


Analyst


Review

ENVIROTECH LABS

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

EPA METHOD 8021 AROMATIC VOLATILE ORGANICS QUALITY ASSURANCE REPORT

Client:	N/A	Project #:	N/A
Sample ID:	04-06-BTEX QA/QC	Date Reported:	04-06-98
Laboratory Number:	D077	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	04-06-98
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-Cal RF:	C-Cal RF:	%Diff.	Blank Conc	Detect. Limit
		Accept. Range 0 - 15%			
Benzene	6.8842E-05	7.1785E-05	4.3%	ND	0.2
Toluene	7.5643E-05	7.8386E-05	3.6%	ND	0.2
Ethylbenzene	8.8155E-05	9.1637E-05	4.0%	ND	0.2
p,m-Xylene	6.5684E-05	6.7715E-05	3.1%	ND	0.2
o-Xylene	8.7047E-05	9.0580E-05	4.1%	ND	0.1


Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff.	Accept Range	Detect. Limit
Benzene	1,420	1,400	1.4%	0 - 30%	17.5
Toluene	60,960	59,920	1.7%	0 - 30%	16.7
Ethylbenzene	47,660	46,890	1.6%	0 - 30%	15.2
p,m-Xylene	75,960	74,820	1.5%	0 - 30%	21.6
o-Xylene	73,400	72,710	0.9%	0 - 30%	10.4

Spike Conc. (ug/Kg)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Range
Benzene	1,420	50.0	1,470	100%	39 - 150
Toluene	60,960	50.0	61,010	100%	46 - 148
Ethylbenzene	47,660	50.0	47,710	100%	32 - 160
p,m-Xylene	75,960	100.0	76,060	100%	46 - 148
o-Xylene	73,400	50.0	73,450	100%	46 - 148

ND - Parameter not detected at the stated detection limit.

References: Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, December 1996.
Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments: QA/QC for sample D077.


Analyst


Review

PC

ENVIROTECH Inc.

5796 US HWY. 64, FARMINGTON, NM 87401
(505) 632-0615

PIT NO: C4949

C.O.C. NO: 3149
11-1-93

FIELD REPORT: CLOSURE VERIFICATION

JOB No 92140
PAGE No 2 of 3

LOCATION: LEASE COOPER GC WELL # 1E QD: NW/4, SE/4 (J)
SEC: 15 TWP: 29 N RNG: 11 W BM: Nm CNTY: SJ ST: NM PIT: TANKS
CONTRACTOR: PAUL VELASCO'S W. OF SEP.
EQUIPMENT USED: EXCAVATOR

DATE STARTED: 10-29-93
DATE FINISHED: 11-1-93

ENVIRONMENTAL
SPECIALIST: RED

SOIL REMEDIATION: QUANTITY: EXCAVATION APPROX. 50' DIA X 25' DEEP.
DISPOSAL FACILITY: LANDFARMING AT COOPER #1 / CROUCH MESA
LAND USE: FARMING/ RESIDENTIAL
SURFACE CONDITIONS: EXCAVATION CONTINUING

FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY _____ FEET _____ FROM WELLHEAD.
EXCAVATION APPROX. 25' DEEP - BOTTOM INTO WATER TABLE - HEAVY HYDROCARBON
ODOR IN BOTTOM. EAST SIDE OF EXCAVATION BREAKS INTO SEPARATE EXCAVATION.
BOTTOM IN WATER - RECOMMEND EXCAVATE BOTTOM INTO WATER TABLE.
TO BE CONTINUED: - SIDEWALLS APPEAR TO BE CLEANING UP -
11-1-93: WATER IN EXCAVATION BOTTOM APPEARS CONTAMINATED.

FIELD 418.1 CALCULATIONS

SAMPLE I.D.	LAB No.	WEIGHT (g)	mL. FREON	DILUTION	READING	CALC. ppm

DEPTH TO GROUNDWATER:
NEAREST WATER SOURCE:
NEAREST SURFACE WATER:
NMOED PUMPING SCORE:
NMOED TSP CLOSURE STD:

SCALE



0 FEET

PIT PERIMETER

OVM RESULTS


SAMPLE ID	FIELD HEADSPACE PID (ppm)
10-29-93	
6 NS @ 10'	7.7
7 WS @ 15'	105
8 SS @ 20'	120
9 C @ 20'	O.R.
	72000
11-1-93	
10 WS @ 15'	32
11 SS @ 12'	12.8
	LAB
12 B @ 20' WATER - BTEX	
	LAB
10	418.1

PIT PROFILE

SEE PAGE 1

TRAVEL NOTES: CALLOUT: 10-28-93 ONSITE: 10-29-93 0800
11-1-93 1030

TRAVEL NOTES: DATE: 11-5-93 ONSITE: 11-5-93 1300 HRS.



ENVIROTECH LABS

5796 US HIGHWAY 64-3014 • FARMINGTON, NEW MEXICO 87401
PHONE: (505) 632-0615 • FAX: (505) 632-1865

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS

Client:	Amoco	Project #:	92140
Sample ID:	12 B @ 20'	Date Reported:	11-02-93
Laboratory Number:	6427	Date Sampled:	11-01-93
Sample Matrix:	Water	Date Received:	11-01-93
Preservative:	HgCl and Cool	Date Analyzed:	11-01-93
Condition:	Cool and Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/L)	Det. Limit (ug/L)
Benzene	12,900	1.0
Toluene	6,200	1.0
Ethylbenzene	720	1.0
p,m-Xylene	3,290	1.0
o-Xylene	2,140	1.0

SURROGATE RECOVERIES:	Parameter	Percent Recovery
	Trifluorotoluene	98 %
	Bromofluorobenzene	98 %

Method: Method 5030A, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992


Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1986

ND - Parameter not detected at the stated detection limit.

Comments: Cooper GC # 1E Separator Pit C4949

David L. Cramer
Analyst

Maris D. Young
Review



ENVIROTECH LABS

5796 US HIGHWAY 64-3014 • FARMINGTON, NEW MEXICO 87401
PHONE: (505) 632-0615 • FAX: (505) 632-1865

EPA METHOD 8020 AROMATIC VOLATILE ORGANICS

Client:	Amoco	Project #:	92140
Sample ID:	13 B @ 20'	Date Reported:	11-09-93
Laboratory Number:	6438	Date Sampled:	11-05-93
Sample Matrix:	Water	Date Received:	11-05-93
Preservative:	HgCl & Cool	Date Analyzed:	11-08-93
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/L)	Det. Limit (ug/L)
Benzene	8,200	10.0
Toluene	16,400	25.0
Ethylbenzene	373	10.0
p,m-Xylene	5,100	20.0
o-Xylene	1,480	15.0

SURROGATE RECOVERIES:	Parameter	Percent Recovery
	Trifluorotoluene	95 %
	Bromofluorobenzene	99 %

Method: Method 5030, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA, July 1992

Method 8020, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846, USEPA, Sept. 1986

ND - Parameter not detected at the stated detection limit.

Comments: Cooper GC #1E Separator Pit C4949

Kevin L. Ciemer
Analyst

Morris D. Young
Review