

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
LG-5582

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL GAS WELL OTHER

Name of Operator
The Desana Corporation

Address of Operator
600 Bldg of the Southwest, Midland, Texas 79701

Location of Well
UNIT LETTER M 660 FEET FROM THE West LINE AND 660 FEET FROM
THE south LINE, SECTION 36 TOWNSHIP 5-N RANGE 30-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
4602.1 GL

7. Unit Agreement Name

8. Farm or Lease Name
Wichita-State

9. Well No.
1

10. Field and Pool, or Wildcat
Wildcat

12. County
Quay

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASINGS <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-20-86 Circ hole w/10.0 ppg salt gel mud. Set CIBP @ 2050'. Cap w/30' cmt (2sx). Shot csg @ 1600' - will not work free. Shot csg @ 1500' - would not work free. Shot csg. @ 1000'. Pulled csg. Ran tbg to 1050'. Spotted 80sx cmt. @ 1050' (Inside 4-1/2" csg. & up in 8-5/8" csg.). Spotted 15sx cmt plug from 60' to surface.

Note: All cmt plugs are Class "C" mixed @ 14.6 ppg.
4-22-86 Weld on plate & Installed dry hole marker. Well P & A 4-22-86.
Covered up pits and cleaned up location.

Location is ready for inspection.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED K. V. Tholstrom TITLE Operations Manager DATE May 27, 1986

APPROVED BY K. V. Tholstrom TITLE DISTRICT SUPERVISOR DATE 10-31-86

CONDITIONS OF APPROVAL, IF ANY: