

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		✓
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease  
 State  Fee   
 5. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
 USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tom L. Ingram	8. Farm or Lease Name Gihon
3. Address of Operator P. O. Box 1757, Roswell, NM 88201	9. Well No. #1
4. Location of Well UNIT LETTER <u>G</u> <u>2970</u> FEET FROM THE <u>South</u> LINE AND <u>1814</u> FEET FROM THE <u>East</u> LINE, SECTION <u>31</u> TOWNSHIP <u>13-N</u> RANGE <u>30-E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4028 GR	12. County San Miguel

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUS AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Called David Catanach (NMOCD) @ 4:45 p.m., 10-15-86  
 Plan to P & A as follows:  
 25 sx cmt plug @ 2515 Top of Yeso  
 25 sx cmt plug @ 2000 Top of San Andres  
 25 sx cmt plug @ 1090 Top of Santa Rosa  
 26 sx cmt plug @ 398'-498' 50' above & 50' below 8 5/8" csg shoe  
 10 sx cmt plug @ surface

Mud laden drilling fluid to be placed between all plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Joseph L. Ingram TITLE Engineer DATE 10-16-86  
 APPROVED BY Ray E. Johnson TITLE DISTRICT SUPERVISOR DATE 10-20-86  
 CONDITIONS OF APPROVAL, IF ANY: