

FORM 1025

HALLIBURTON LOCATION

BILLED ON
TICKET NO. 766 719

FIELD _____ SEC. 16 TWP. 4N RNG. 1E COUNTY CLATSOP STATE OR

	NEW USED	WEIGHT	SIZE	FROM	TO	MAXIMUM PER ALLOWABLE
CASING	U	54	8 1/2	2	430	
LINER						
DRILLING	U	155	3 1/2	5.8	7080	
OPEN HOLE						SHOTS/FT.
PERFORATIONS						
PERFORATIONS						
PERFORATIONS						

CALLER OUT	ON LOCATION	JOB STARTED	JOB COMPLETED
4-22-84	4-22-84	4-22-84	4-26-84
DATE	DATE	DATE	DATE
TIME 7:30	TIME 1:00	TIME 1:15	TIME 12:48

TYPE AND SIZE	QTY.	MAKE
FLOAT COLLAR		
FLOAT SHOE		
GUIDE SHOE		
CENTRALIZERS		
BOTTOM PLUG		
TOP PLUG		
HEAD DRAINER	1	W. J. C.
PACKER		
OTHER		

[illegible]

TREAT. FLUID _____ DENSITY _____ LB/GAL.-API⁰
DISPL. FLUID _____ DENSITY _____ LB/GAL.-API⁰
PROP. TYPE _____ SIZE _____ LB.
PROP. TYPE _____ SIZE _____ LB.
ACID TYPE _____ %
ACID TYPE _____ %
ACID TYPE _____ %
SURFACTANT TYP. _____ IN
NE AGENT TYPE _____ GAL. _____ IN
FLUID LOSS ADD. TYPE _____ GAL.-LB. _____ IN
GELLING AGENT TYPE _____ GAL.-LB. _____ IN
FRIC. RED. AGENT TYPE _____ GAL.-LB. _____ IN
BREAKER TYPE _____ GAL.-LB. _____ IN
BLOCKING AGENT TYPE _____ GAL.-LB. _____
PERFPAC BALLS TYPE _____ QTY. _____
OTHER _____
OTHER _____

DEPARTMENT CRIM
DESCRIPTION OF JOB PT4
JOB DONE THRU: TUBING ☒ CASING ☐ ANNULUS ☐ TEG./ANN. ☐
CUSTOMER REPRESENTATIVE X W. C. Wald
HALLIBURTON OPERATOR W. C. Wald COPIES REQUESTED 1

1	2	3	4	5	6	7	8	9
STAGE	NUMBER OF SACKS	TYPE	API CLASS	BRAND	BULK SACKED	ADDITIVES	YIELD CU.FT./SK.	MIXED LBS./GAL.
1	50	REG	C	200	0		1.32	11.5
2	50	REG	C	200	0		1.32	11.5
3	50	REG	C	200	0		1.32	11.5
4	50	REG	C	200	0	2000-112	1.32	14.5
5	50	REG	C	200	0	2000-112	1.32	10.5
6	50	REG	C	200	0		1.32	11.5
7	50	REG	C	200	0		1.32	11.5

PRESSURES IN PSI
 CIRCULATING _____ DISPLACEMENT _____
 BREAKDOWN _____ MAXIMUM _____
 AVERAGE _____ FRACTURE GRADIENT _____
 SHUT-IN: INSTANT _____ 5-MIN. _____ 15-MIN. _____
 HYDRAULIC HORSEPOWER
 ORDERED _____ AVAILABLE _____ USED _____
 AVERAGE RATES IN BPM
 TREATING _____ DISPL. _____ OVERALL _____
 CEMENT LEFT IN PIPE

SUMMARY **VOLUMES**

PRESLUSH: SBL-GAL. 100 TYPE 100

LOAD & SHDN: SBL-GAL. 100 PAD: SBL-GAL. 100

TREATMENT: SBL-GAL. 100 DISPL: SBL-GAL. 100

CEMENT SLURRY: SBL-GAL. 100

TOTAL VOLUME: SBL-GAL. 100

REMARKS

Water Temp 48° F

CUSTOMER