

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103
Revised June 10, 2003

WELL API NO.

30-015-32801

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

K-3977

7. Lease Name or Unit Agreement Name

Yates State

8. Well Number

2

RECEIVED

MAY 03 2004

9. OGRID Number

115970

OOB-ARTESIA

10. Pool name or Wildcat

Burton Flat - Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Unit Petroleum Company

3. Address of Operator

P.O. Box 702500 Tulsa, OK 74170

4. Well Location

Unit Letter M: 1310 feet from the South line and 1310 feet from the West line

Section 10

Township 21S

Range 27E

NMPM Eddy

County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3268' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/4/04 Drilled 8 3/4" hole to 11,375'. Ran DLL/GR CDN/GR open hole logs. Ran 39 jts 5 1/2" 20# N-80, 171 jts 17# N-80, and 55 jts 20# N-80 casing to 11,375'.

1/5/04 Cemented casing with 800 sx 50:50 Poz "H" + 2% D20 + 5% BWOW D44 + 0.2% D65 + 0.2% D46 mixed @ 14.2 ppg and 1.33 ft3/sk. Bumped the plug and floats held. Set the slips and rigged down. TOC @ 7900'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

District Engineer

DATE 1-7-04

Type or print name Kelly Ryan

E-mail address:

Telephone No. 918-493-7700

This space for State use)

APPROVED BY

FOR RECORDS ONLY

DATE MAY 04 2004

Conditions of approval, if any: