

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised June 10, 2003

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-33147
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Carlsbad
8. Well Number 1
9. OGRID Number 115970
10. Pool name or Wildcat Dublin Ranch - Morrow

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other

RECEIVED

2. Name of Operator
Unit Petroleum Company

MAY 07 2004

3. Address of Operator
P.O. Box 702500 Tulsa, OK 74170-2500

OCD-ARTESIA

4. Well Location

Unit Letter A: 660 feet from the North line and 660 feet from the East line

Section 32 Township 22S Range 28E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3019' Gr

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4-25-04 Spud well @ 6:00 AM 4-25-4.

4-26-04 Drill 17 1/2" hole to 440'. Ran 10 jts 13 3/8" H-40 48# casing to TD. Cemented with 450 sx Class "C" + 2% CaCl + 1/4# flocele mixed @ 15 ppg and 1.34 ft3/sk. Circulated 46 sx cement to pits. WOC 34 hours.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kelly Ryan TITLE District Engineer DATE 5/3/04

Type or print name Kelly Ryan
(This space for State use)

E-mail address:

Telephone No. 918-493-7700

APPROVED BY FOR RECORDS ONLY

DATE MAY 17 2004

Conditions of approval, if any: