

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.
30-015-33338

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
B-8617

7. Lease Name or Unit Agreement Name:
Mule Train 16 State

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

RECEIVED

2. Name of Operator
Yates Drilling Company

MAY 25 2004

3. Address of Operator
105 South 4th St., Artesia, NM 88210

OCC-ARTESIA

8. Well No.
2

9. Pool name or Wildcat
Empire Penn

4. Well Location

Unit Letter N : 660 feet from the N line and 1520 feet from the W line

Section 16 Township 17S Range 28E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3552' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPLETION ☐	CASING TEST AND CEMENT JOB ☒	
OTHER: ☐		OTHER: ☐	

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/16/2004 TD 10,253'.

5/19/2004 Ran 240 jts. 5 1/2" casing, as follows:

54 jts. 17#, L-80 2301.81'
43 jts. 17#, J-55 1815.73'
103 jts. 15.5#, J-55 4418.38'
25 jts. 17#, J-55 1068.62'
15 jts. 17#, L-80 649.78'

Float shoe set at 10,253'. Float collar set at 10,210.62'. Bottom marker set at 7951.19'-7931.10'. Top marker set at 6135.46'-6155.50'. Cemented with 1480 sxs. "C" 35:65:6 + 5% salt + 1/4# Celloflake +. 03% FL-52. (yld 2.09, wt 12.5). Tailed in with 1375 sxs. "C" 15:61:11 + .06% FL-52+ 1% BA-10 + 3% (yld 13.2, wt 1.61). PD at 2:26 PM, 5-19-2004. Bumped plug to 2519 psi for 10 mins., float and casing held okay. Circulated 100 sxs. Note: Ran centralizers on jts. #1,10,20,30,40,50,60,70,80,90,100,110,120,130,140,150,160,170,180 and 190.

Rig released at 9:00 PM, 5-19-2004. Waiting on completion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Karen J. Leishman TITLE Engineering Tech. DATE 5/24/2004

Type or print name Karen J. Leishman

Telephone No. 505-748-8463

(This space for State use)

APPROVED BY FOR RECORDS ONLY TITLE

Conditions of approval, if any:

DATE

MAY 31 2004