Form 3160-5

## OII Cons. TERIOR N.M. DIV-Dist. 2 UNITED STATES

FORM APPROVED OMB NO. 1004-0135

(August 1999)		OF THE INTERIOR	19.101. DIV-1		Expires:	November 30, 2	000	
BUREAU OF LAND MANAGEMEN 301 W. Grand Avenue sundry notices and reports on Avenue NM 88210  Do not use this form for proposals to drill or to re-enter an					Lease Serial No.     NM025503     If Indian, Allottee or Tribe Name			
abandoned well. Use Form 3160-3 (APD) for such proposals.  SUBMIT IN TRIPLICATE - Other instructions on reverse sine CEIVED						7. If Unit or CA/Agreement, Name and/or No		
1. Type of Well  Oil Well X Gas Well Other  2. Name of Operator OXY USA WTP Limited Partnership  3a. Address P.O. Box 50250, Midland, TX 79710-  4. Location of Well (Footage, Sec., T., R., M., or Survey 760 FSL 2020 FEL SWSE(0)) Sec 26		MAY 2.8 2014  192463  3b. Phone No. (include area code) 432-685-5717  Description)		8. Well Name and No. OXY Pal Federal 1  9. API Well No. 30-015-33651 33364  10. Field and Pool, or Explorator, Area Undsg. Hackberry Morrow, N.				
					Eddy	NM NM		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPO					ORT, OR OTHE	ER DATA		
TYPE OF SUBMI		TYPE OF ACTION						
Notice of Intent  X Subsequent Report  Final Abandonment Notice		Acidize Alter Casing Casing Repair Change Plans Convert to Injection	ther Casing Fracture Treat Reclama sing Repair New Construction Recomp ange Plans Plug and Abandon Tempora		ete X Other Spud.		oud	
13. Describe Proposed or Com If the proposal is to deepen Attach the Bond under whi following completion of the testing has been completed determined that the final sit	directionally or recomple ich the work will be perfe e involved operations. If l. Final Abandonment No.	ete horizontally, give substantially, give substantially or provide the Bonthe operation results in a potices shall be filed only	surface locations and meas ad No. on file with BLM/I multiple completion or re-	ured and true versi BIA. Required sub completion in a ne- luding reclamation	cal depths of all posequent reports show interval, a Form	ertinent markers a nall be filed within 3 3 160-4 shall be eleted, and the ope	and zones. n 30 days filed once	
See Attached					LES BABYAI	04		
14 I hereby certify that the foreg	oing is true and correct		Title	_=_=			<del></del>	
14 I hereby certify that the foregoing is true and correct Name (Printed Typed) David Stewart			Sr. Regulatory Analyst					
W. Cat			Date 5/21/04					

THIS SPACE FOR FEDERAL OR STATE OFFICE USE Date Title Approved by Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, ficutious or fraudulent statements or representations as to any matter within its jurisdiction.

## **OXY PAL FEDERAL #1**

05/14/2004 CMIC: BOWKER

LOCATION STAKED BY JOHN WEST SURVEYORS AT 760' FSL, 2020' FEL, SECTION 26, T18S, R30E, EDDY CTY NM. BUILT ROAD & LOCATION. DUG & LINED RESERVE PITS. SET 20" CONDUCTOR AT 40' & CEMENTED W/ REDI-MIX. MIRU PATTERSON 508. HELD PRE SPUD SAFETY MEETING & RIG INSPECTION. SPUDED 17 1/2" HOLE AT 10:00 PM 5-13-04. DRILLING F/ 40' TO 109' & LOST RETURNS. BUILD & PUMP LCM PILLS. REGAIN CIRCULATION, DRILLING TO 140'. RESET ROATARY TABLE AT REPORT TIME. DON W/ BLM NOTIFIED OF SPUD AT 3:30 PM MST 5-13-04.

05/15/2004 CMIC: LANGE

RESET ROTARY TABLE.DRILLING F/ 140' TO 150'. LOST RETURNS, MIX & PUMP 2 LCM PILLS, REGAINED CIRCULATION. DRILLING F/ 150' TO 181' LOST RETURNS, MIX & PUMP LCM PILL. DRILLING F/ 181' TO 184'. GROUND CRACKING FROM CELLAR OUT TO PIPE RACKS & F/ CELLAR OUT TO MUD TANKS. FLUID COMING OUT OF CRACKS AND UP CELLAR. MIX & PUMP GW-27 & LCM PILL. DRILLING W/ RETURNS F/ 184' TO 560' W/ SURVEYS. PUT LEVEL ON SUB TO WATCH FOR ANY SETTLING, SUB STAYING LEVEL. CRACKS ARE NOT SEEPING FLUID, STILL HAVE MUD COMING UP AROUND CONDUCTOR PIPE.

05/16/2004 CMIC: BOWKER

DRILLING F/ 560' TO 645'. PUMP SWEEP & CIRCULATE OUT OF HOLE. POOH TO RUN CASING. RU CASING CREW & RUN CASING. HIT HARD BRIDGE AT 577', COULD NOT GET THRU IT. TALKED W/ PAUL SCHWARTZ & JIM AMOS W/ BLM, THEY AGRRED TO LET US CEMENT THE CASING AT 577'. RU HALLIBURTON & CEMENT CASING W/ 150 SX THIXOTROPIC, 360 SX HALLIBURTON LITE TAILED W/ 250 SX PREMIUM PLUS. DISPLACED W/ 90 BBLS FW. BUMPED PLUG W/ 600 PSI AT 2:15 PM 4-15-04. CIRCULATED 175 SX TO RESERVE. WOC 6 HOURS. CUT OFF CONDUCTOR & CASING & WELD ON STARTING HEAD. TESTED HEAD TO 500 PSI OK. NIPPLE UP BOPE AT REPORT TIME. PAUL SCHWARTZ W/ BLM NOTIFIED & WITNESSED CEMENT JOB.

05/17/2004 CMIC: BOWKER

FINISH NIPPLE UP BOPE. PU BHA & TRIP IN HOLE. TAG CEMENT. TEST CASING & BOPE TO 500 PSI. DRILL CEMENT & BAFFLE PLATE. DRILLING AHEAD W/NO PROBLEMS AT REPORT TIME.

05/18/2004 CMIC: LANGE

DRILLING F/ 1372' TO 1990' W/ SURVEYS. NO PROBLEMS AT REPORT TIME.

05/19/2004 CMIC: LANGE

DRILLING F/ 1990' TO 2490' W/ SURVEYS. NO PROBLEMS AT REPORT TIME.

05/20/2004 CMIC: BOWKER

DRILLED TO 2817' AND CRACKED SUCTION LINE ON PUMP. POOH WITH BIT TO CASING. REPAIRED SUCTION LINE. TBIH WITH BIT. DRILLING AHEAD AT REPORT TIME WITH NO PROBLEMS.

05/21/2004 CMIC: BOWKER

DRILLING AHEAD WITH NO PROBLEMS.

