State of New Mexico Energy, Minerals and Natural Resources Department

S

<u>DISTRICT I</u> P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION	N DIVISION	WELL API NO.	
	2040 Pacheco St. Santa Fe NM 87	75,066 17 18 19 20 21 2	30-015-32537	
<u>DISTRICT II</u> P.O. Drawer DD, Artesia, NM 88210	20	A SE	sIndicate Type of Lease	
DISTRICT III	7273	}************************************	2)	STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410	dense dense dense dense	RECFIVED	State Oil & Gas Lease N GV-5010-1	NO.
SUNDRY NOTICES AND REPORTS ON WELLSOD - ARTESIA			A service of the service of the	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEREN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR REMIT"			ViLease Name or Unit Agreement Name	
	01) FOR SUCH PROPOSALS.)	<u> </u>	Esperanza 11 State	e Com
iType of Well: OIL GAS WELL WELL WELL	OTHER			
2Name of Operator	/	,	₃Weil No.	
Mewbourne Oil Company 14744 3Address of Operator	/		2 Pool name or Wildcat	
PO Box 5270, Hobbs, NM 88241			Burton Flat Morrow	
Well Location	eet From The South	Line and 1650		East Line
Unit Letter J 1900 Fe	eet From The South	Line and1550	Feet From The	Line
Section 11	C 000 E 7 N F 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Range 27E	NMPM	Eddy County
And the second s	₁₀Elevation (Show whether DF, 3259'	RKB, RT, GR, etc.		
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OF		LUG AND ANBANDONMENT
PULL OR ALTER CASING CASING TEST AND CEME				EGO AND ANDANDONNETT
OTHER:		OTHER:		
¹² Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.				
02-02-03Spud 17 1/2" hole. TD'ed @ 423'. Ran 423' of 13 3/8" 48# H-40 ST/C csg. Cemented w/ 250 sks BJ Lite 'C' Poz				
w/ additives. Mixed @ 12.5 #/g & 1.97 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl				
28 sks to pit. WOC 18 hrs. Test BOP to 500 psi. OK. Drill out w/ 12 1/4" bit.				
02-08-02TD'ed 12 1/4" hole @ 2630'. Ran 2630' of 8 5/8" 32# J-55 ST/C csg. Cemented w/ 200 sks Thic-Set 'H' . Mixed @ 14.6 #/g & 1.52 yd. 900 sks 65/35/6 'C' Poz w/ additives. Mixed @ 12.4 #/g & 2.09 yd. Tailed w/ 200 sks 'C' w/ 2%				
CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 76 sks to pit. WOC 18 hrs. Test BOP to 2500 psi, OK, Drilled out w/				
7 7/8" bit. Will test BOP equipment with 3rd party on trip before Wolfcamp.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE	тп	_{LE} District Manager		DATE 02-17-03
TYPE OF PRINT NAME N.M. YOUR				
TYPE OR PRINT NAME N.M. Young (This space for State Use)				
	MONTAL SCORES BY TIM W	. Cum		erb 9 4 200 2
APPROVED BY	STRICT H SUPERVIOR	'LE		FEB 21 2003
CONDITIONS OF APPROVAL IF ANY				