


file

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410



# OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-015 - 32607
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	Lease Name or Unit Agreement Name Otis 14
Name of Operator Mewbourne Oil Company 14744	Well No. 1
Address of Operator PO Box 5270, Hobbs, New Mexico 88241	Pool name or Wildcat East Carlsbad Morrow
Well Location Unit Letter I Feet From The South Line and 660 Feet From The East Line Section 14 Township 22S Range 27E NMPM Eddy County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 3062' GL	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

02-14-03...MI & spud 17 1/2" hole. TD'ed @ 377'. Ran 377' of 13 3/8" H-40 48# STC csg. Cement w/ 200 sks BJ Lite w/ additives. Mixed @ 12.5 #/g w/ 1.97 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Circd 70 sks to pit. WOC 18 hrs. Test csg & BOPE to 1000 psi. OK. Drill out w/ 12 1/4" bit.

02-20-03...TD'ed 12 1/4" hole @ 2620'. Ran 2620' of 9 5/8" J & N-80 40# STC csg. Cement w/ 850 sks BJ Lite w/ additives. Mixed @ 12.4 #/g w/ 2.09 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Circd 98 sks to pit. WOC 18 hrs. Test csg & BOPE to 2000 psi. OK. Drill out w/ 8 3/4" bit.

Will test BOPE as required on trip before Wolfcamp.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE TITLE District Manager DATE 02-22-03

TYPE OR PRINT NAME N.M. Young TELEPHONE NO.

(This space for State Use)

APPROVED BY TITLE District Supervisor DATE FEB 26 2003

CONDITIONS OF APPROVAL IF ANY: