CONDITIONS OF APPROVAL

State of New Mexico Energy, Minerals and Natural Resources Department

DATE 3-31-03

DISTRICT I OIL CONSERVATION DIVISION P.O. Box 1980, Hobbs, NM 88240 WELL API NO. 2040 Pacheco St. Santa Fe, NM 875057526272820 30-015-32620 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 sIndicate Type of Lease FEE X STATE State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUC BACKINGO A 7 Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR REPMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: Harroun 15 WELL XX «Well No. 2Name of Operator Pogo Producing Company 14 3Address of Operator Pool name or Wildcat Box 10340, Midland, TX 79702-7340 4Well Location : 660__ Feet From The North Unit Letter 750 Line and Feet From The West 15 Section 245 Township Range **NMPM** Eddy County 10Elevation (Show whether DF, RKB, RT, GR, etc.) 29301 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON PERFORM REMEDIAL WORK REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ANBANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER: OTHER: a2Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed Spud & Set Surface Csg - MIRU Patterson #54. Spud well @ 19:30 hrs 02/14/03. Drld 17-1/2" hole to 577'. TD reached @ 09:45 hrs 02/15/03. Ran 13 jts 13-3/8" 48# H-40 STC csg. Cmt'd w/ 470 sks 35:65 POZ C @ 12.8 ppg followed by 200 sks Cl "C" + 2% CaCl2 @ 14.8 ppg. Circ 41 sks to surface. Plug down @ 18:30 hrs 02/15/03. WOC 20-1/2 hrs. Make cut-off. Install WH. NU BOP's & test to 1000# ok. Intermediate Csg - Drld 11" hole to 2878'. TD reached @ 00:45 hrs 02/20/03. Ran 65 jts 8-5/8" 32# J-55 STC csg. Cmt'd w/ 750 sks 35:65 POZ @ 12.5 ppg followed by 200 sks Cl "C" + 2% CaCl2 @ 14.8 ppg. Plug down @ 11:45 hrs 02/20/03. Circ 188 sks to surface. WOC 25 hrs. Make cutoff. Install WH. NU BOP's & test to 3000# ok. TD & Prod Csg - Drld 7-7/8" hole to 8000'. TD reached @ 19:00 hrs 02/28/03. Logged well w/ Baker Atlas. Ran 180 jts 5-1/2" 15.5# & 17# J-55 LTC csg. Cmt'd 1st stage w/ 665 sks Cl "C" + additives @ 14.09 ppg. Circ 48 sks to surface. Cmt'd 2nd stage w/ 950 sks Cl "C" + additives @ 14.09 ppg. Ran CBL 03/08/03. TOC @ 1300'. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE DATE <u>03/27/</u>03 πιε Sr. Operation Tech Cathy Tomberlin TYPE OR PRINT NAME (915)685-8100 TELEPHONE NO. (This space for State Use)

TITLE