

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised May 08, 2003

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-015-32818

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

EDSEL'S WAND WAVER FEE

8. Well Number

1

9. OGRID Number

14049

10. Pool name or Wildcat

BLACK RIVER; MORROW

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

RECEIVED

2. Name of Operator

MARBOB ENERGY CORPORATION

AUG 23 2004

3. Address of Operator

PO BOX 227, ARTESIA, NM 88211-0227

4. Well Location

Unit Letter 5 : 1650 feet from the NORTH line and 660 feet from the WEST line

Section 6 Township 24S Range 28E NMPM County EDDY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3096' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ADD PAY ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

ADD PAY IN THE MORROW AND/OR THE ATOKA ZONES AS FOLLOWS:

PERF THE MIDDLE MORROW @ 12400-38' (72 SHOTS). ACIDIZE W/ 1250 GAL CLAY SAFE H
ACID. SWAB/FLOW TEST. IF DECISION MADE TO FRAC, FRAC DOWN CSG W/ 25K# SAND.
PERF THE UPPER MORROW @ 12244-56' (66 SHOTS). ACIDIZE W/ 750 GAL CLAY SAFE H
ACID. SWAB/FLOW TEST. IF DECISION MADE TO FRAC, FRAC DOWN CSG W/ 25K# SAND.
SET CIPR 4 25' CMT @ 12300'. PERF THE ATOKA @ 11705-07' (30 SHOTS). ACIDIZE
W/ 500 GAL CLAY SAFE H ACID. SWAB/FLOW TEST.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Diana J. Cannon TITLE PRODUCTION ANALYST DATE 8/20/04

Type or print name DIANA J. CANNON

Telephone No. (505) 748-3303

(This space for State use)

APPROVED BY TIM W. GUM
DISTRICT II SUPERVISOR

DATE AUG 24 2004

Conditions of approval, if any: Open. To submit CLOS CLOS for recompletion to Atoka