Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR

35.54

FORM APPROVED OM B No. 1004-0137

Expires: March 31, 2007		
5. Lease Serial 1	√o.	
ND40 2 7	57	

AUG 23 2004

ALEXIS C. SWOBODA

Date

BUREAU OF LAND MANAGEMENT		5. Lease Serial No.
SUNDRY NOTICES AND REPORTS OF	NM92757	
Do not use this form for proposals to drill or a abandoned well. Use Form 3160-3 (APD) for su	6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE- Other instructions on	7. If Unit or CA/Agreement, Name and/or No.	
1. Type of Well X Oil Well Gas Well Other		8. Well Name and No.
2. Name of Operator McCabe Energy, Inc.		Willow Lake Federal "20" #1 9. API Well No.
	o. (include area code)	30-015-33209
P.O. Box 3816, Midland, TX 79702 (432	10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Willow Lake	
		11. County or Parish, State
1910' FNL & 1838' FEL, Sec. 20, T-24-S,	R-28-E, NMP	M Eddy County, NM
12. CHECK APPROPRIATE BOX(ES) TO INDICATE	NATURE OF NOTIC	E, REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTIO	N
Acidize Deepen	Production	on (Start/Resume) Water Shut-Off
Notice of Intent Alter Casing Fracture Tr	eat Reclama	tion Well Integrity
X Subsequent Report Casing Repair New Const	truction Recompl	ete XOther <u>Drilling</u>
Change Plans Plug and A	bandon Tempora	rily Abandon <u>operations</u>
Final Abandonment Notice Convert to Injection Plug Back	Water D	
If the proposal is to deepen directionally or recomplete horizontally, give subsurfa Attach the Bond under which the work will be performed or provide the Bond No following completion of the involved operations. If the operation results in a mult testing has been completed. Final Abandonment Notices shall be filed only after a determined that the site is ready for final inspection.)	on file with BLM/BIA. Tiple completion or recomp	Required subsequent reports shall be filed within 30 days sletion in a new interval, a Form 3160-4 shall be filed once
3/6/04 Ran used 8 5/8" casing as follows:	1.20'	ALIC 9. 4. 2004
1-8 5/8" Guide shoe		AUG 2 4 2004
	∆ ∩ 59'	
1-8 5/8", 32#, K-55, 8rd, lt&c	40.59' 1.30'	OGD-ARTESIA
1-8 5/8" Float collar	1.30'	
1-8 5/8" Float collar 63-8 5/8", 32#, K-55, 8rd, It&c	1.30' <u>2426.91'</u>	
1-8 5/8" Float collar 63-8 5/8", 32#, K-55, 8rd, It&c Total	1.30' <u>2426.91'</u> 2526.91'	OGD-ARTESIA
1-8 5/8" Float collar 63-8 5/8", 32#, K-55, 8rd, It&c Total Set @2522.00'	1.30' <u>2426.91'</u> 2526.91' salt + 1/4# Cello	OGD-ARTESIA flake followed by 150 sxs Class
1-8 5/8" Float collar 63-8 5/8", 32#, K-55, 8rd, lt&c Total Set @2522.00' Cmt with 930 sxs 35:65:6 Class "C" + 5%	1.30' <u>2426.91'</u> 2526.91' salt + 1/4# Cello	OCD-ARTESIA Flake followed by 150 sxs Class axs to surface.
1-8 5/8" Float collar 63-8 5/8", 32#, K-55, 8rd, lt&c Total Set @2522.00' Cmt with 930 sxs 35:65:6 Class "C" + 5%	1.30' <u>2426.91'</u> 2526.91' salt + 1/4# Cello	OCD-ARTESIA Flake followed by 150 sxs Class axs to surface.
1-8 5/8" Float collar 63-8 5/8", 32#, K-55, 8rd, lt&c Total Set @2522.00' Cmt with 930 sxs 35:65:6 Class "C" + 5% "C" + 1% CaCl2. Plug down @ 8:30 AM 3 Note: Used 12 centralizers. One in middle	1.30' <u>2426.91'</u> 2526.91' salt + 1/4# Cello	OCD-ARTESIA Flake followed by 150 sxs Class axs to surface.
1-8 5/8" Float collar 63-8 5/8", 32#, K-55, 8rd, lt&c Total Set @2522.00' Cmt with 930 sxs 35:65:6 Class "C" + 5%	1.30' <u>2426.91'</u> 2526.91' salt + 1/4# Cello	OCD-ARTESIA Flake followed by 150 sxs Class axs to surface.
1-8 5/8" Float collar 63-8 5/8", 32#, K-55, 8rd, lt&c Total Set @2522.00' Cmt with 930 sxs 35:65:6 Class "C" + 5% "C" + 1% CaCl2. Plug down @ 8:30 AM 3 Note: Used 12 centralizers. One in middle	1.30' <u>2426.91'</u> 2526.91' salt + 1/4# Cello	OCD-ARTESIA Flake followed by 150 sxs Class axs to surface.
1-8 5/8" Float collar 63-8 5/8", 32#, K-55, 8rd, lt&c Total Set @2522.00' Cmt with 930 sxs 35:65:6 Class "C" + 5% "C" + 1% CaCl2. Plug down @ 8:30 AM 3 Note: Used 12 centralizers. One in middle 3rd collar thereafter.	1.30' 2426.91' 2526.91' salt + 1/4 Cello 3/5/04. Circ 55 s. e of shoe joint, o	OCD-ARTESIA Flake followed by 150 sxs Class axs to surface.
1-8 5/8" Float collar 63-8 5/8", 32#, K-55, 8rd, lt&c Total Set @2522.00' Cmt with 930 sxs 35:65:6 Class "C" + 5% "C" + 1% CaCl2. Plug down @ 8:30 AM 3 Note: Used 12 centralizers. One in middle 3rd collar thereafter. 14. Thereby certify that the foregoing is true and correct Name (Printed/Typed)	1.30' 2426.91' 2526.91' salt + 1/4 Cello 3/5/04. Circ 55 s. e of shoe joint, o	flake followed by 150 sxs Class xs to surface. ne first collar, then one every

Title

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United R States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or

certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.