Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOROUS. BUREAU OF LAND MANAGEMENT OF LAND MANAGEMENT

PURM APPROVE	D.
OM B No. 1004-01	37
Expires: March 31,	
124010111111111111111111111111111111111	

SUNDRY	NOTICES				NM 93	
Do not use the abandoned we	nis form for eli. Use For	proposals m 3160 - 3 (PUNTS)ON M BBittl , dx kg re (APD) for such ,	roposals	6. If Indian	n, Allottee or Tribe Name
SUBMIT IN TR	IPLICATE-	Other inst			7. If Unit o	r CA/Agreement, Name and/or No.
Type of Well Oil Well	✓ Gas Well	Other	F	IECEIVED -		
	<u></u>			OCT 1 8 2004		me and No. Federal #1
Name of Operator Nadel and G	ussman Permis	an, LLC Suite 5	ens	D-ARTESIA	9. API W	
a. Address 601 N. Marienfeld Midland, Texas 79705		3b. Phone No. (include area code) 432-682-4429		30-015-33594 10. Field and Pool, or Exploratory Area		
J. Location of Well (Footage, Sec., T., R., M., or Survey Description) 780' FSL & 810' FEL UL P Sec. 30 T20S -R23E				Chester 96542		
			11. County	1. County or Parish, State		
					Eddy	County, NM
12. CHECK A	PPROPRIATE	BOX(ES) TO	INDICATE NATI	JRE OF NOTICE, I	REPORT, O	R OTHER DATA
TYPE OF SUBMISSION			Т	YPE OF ACTION		
7 57 67 444	Acidize		Deepen	Production (S	tart/Resume)	Water Shut-Off
Notice of Intent	Alter Ca	ŭ	Fracture Treat	Reclamation		Well Integrity Other CMT, Pred. CSG
Subsequent Report	Change	-	New Construction Plug and Abandon		bandon	- One
Final Abandonment Notice		to Injection	☐ Plug Back	Water Disposa		
If the proposal is to deepen dire Attach the Bond under which it following completion of the in- testing has been completed. Fit determined that the site is ready 10/08/04 Rig up casing or	ectionally or reconthe work will be p volved operations inal Abandonment y for final inspect	mplete horizontal performed or proving in the operation it Notices shall be iton.)	lly, give subsurface loca ride the Bond No. on fil n results in a multiple co e filed only after all requ LT&C. Wash 8904	tions and measured and to e with BLM/BIA. Requi impletion or recompletion irements, including rectar to 8919° FC @ 8,831°	rue vertical depli ired subsequent in a new interv mation, have be . Circ. cmt w	ths of all pertinent markers and zone reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has 1/400sx 35/65 poz H + 6%D20 +
If the proposal is to deepen dire Attach the Bond under which it following completion of the in- testing has been completed. Fi determined that the site is ready 10/08/04 Rig up casing or 5%D44 + .2%D167 + .2%	ectionally or reconthe work will be provided operations in al Abandonment of final inspect rew and run 5 1 4 1065 + .2% 1064	mplete horizontal performed or provise. If the operation at Notices shall be aion.) 1/2" 17# P-110 +.1%D13 12.2	lly, give subsurface loca ride the Bond No. on fil a results in a multiple co e filed only after all requ LT&C. Wash 8904' Density 2.14 yield.	tions and measured and to e with BLM/BIA. Requi impletion or recompletion irements, including reclar to 8919° FC @ 8,831° Tail w/ 1078xx PVL + :	rue vertical depi ired subsequent i in a new interv mation, have be . Circ. cmt w 2%D44 +(BW	ths of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has // 400sx 35/65 poz H + 6%D20 +
If the proposal is to deepen dire. Attach the Bond under which it following completion of the intesting has been completed. Fi determined that the site is ready 10/08/04 Rig up casing cr 5%D44 + .2%D167 + .2%D46 + .2%D13 13#Density	ectionally or reconthe work will be provided operations in al Abandonment of final inspect rew and run 5 1 4 1065 + .2% 1064	mplete horizontal performed or provise. If the operation at Notices shall be aion.) 1/2" 17# P-110 +.1%D13 12.2	lly, give subsurface loca ride the Bond No. on fil a results in a multiple co e filed only after all requ LT&C. Wash 8904' Density 2.14 yield.	tions and measured and to e with BLM/BIA. Requi impletion or recompletion irements, including reclar to 8919° FC @ 8,831° Tail w/ 1078xx PVL + :	rue vertical depi ired subsequent in a new interv mation, have be . Circ. cmt w 2%D44 +(BW rocate pipe. S	ths of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has 4/400sx 35/65 poz H + 6%D20 + 4/OW) +.2%D65 +.2%D167 +.2% Set slips 125K test well head
If the proposal is to deepen dire. Attach the Bond under which it following completion of the intesting has been completed. Fi determined that the site is ready 10/08/04 Rig up casing cr 5%D44 + .2%D167 + .2%D46 + .2%D13 13#Density	ectionally or reconthe work will be provided operations in al Abandonment of final inspect rew and run 5 1 4 1065 + .2% 1064	mplete horizontal performed or provise. If the operation at Notices shall be aion.) 1/2" 17# P-110 +.1%D13 12.2	lly, give subsurface loca ride the Bond No. on fil a results in a multiple co e filed only after all requ LT&C. Wash 8904' Density 2.14 yield.	tions and measured and to e with BLM/BIA. Requi impletion or recompletion irements, including reclar to 8919° FC @ 8,831° Tail w/ 1078xx PVL + :	rue vertical depi ired subsequent in a new interv mation, have be . Circ. cmt w 2%D44 +(BW rocate pipe. S	ths of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has // 400sx 35/65 poz H + 6%D20 + //OW) +.2%D65 +.2%D167 +.2%
If the proposal is to deepen dire Attach the Bond under which it following completion of the in- testing has been completed. Fi determined that the site is ready 10/08/04 Rig up casing or 5%D44 + .2%D167 + .2% D46 + .2%D13 13#Density	ectionally or reconthe work will be provided operations in al Abandonment of final inspect rew and run 5 1 4 1065 + .2% 1064	mplete horizontal performed or provise. If the operation at Notices shall be aion.) 1/2" 17# P-110 +.1%D13 12.2	lly, give subsurface loca ride the Bond No. on fil a results in a multiple co e filed only after all requ LT&C. Wash 8904' Density 2.14 yield.	tions and measured and to e with BLM/BIA. Requi impletion or recompletion irements, including reclar to 8919° FC @ 8,831° Tail w/ 1078xx PVL + :	rue vertical depi ired subsequent in a new interv mation, have be . Circ. cmt w 2%D44 +(BW rocate pipe. S	ths of all pertinent markers and zones reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has 4 400sx 35/65 poz H + 6%D20 + 70W) + 2%D65 + 2%D167 + .2% Set slips 125K test well head
If the proposal is to deepen dire. Attach the Bond under which it following completion of the intesting has been completed. Fi determined that the site is ready 10/08/04 Rig up casing cr 5%D44 + .2%D167 + .2%D46 + .2%D13 13#Density	ectionally or reconthe work will be provided operations in al Abandonment of final inspect rew and run 5 1 4 1065 + .2% 1064	mplete horizontal performed or provise. If the operation at Notices shall be aion.) 1/2" 17# P-110 +.1%D13 12.2	lly, give subsurface loca ride the Bond No. on fil a results in a multiple co e filed only after all requ LT&C. Wash 8904' Density 2.14 yield.	tions and measured and to e with BLM/BIA. Requi impletion or recompletion irements, including reclar to 8919° FC @ 8,831° Tail w/ 1078xx PVL + :	rue vertical depi ired subsequent in a new interv mation, have be . Circ. cmt w 2%D44 +(BW rocate pipe. S	ths of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has 4/400sx 35/65 poz H + 6%D20 + 4/OW) +.2%D65 +.2%D167 +.2% Set slips 125K test well head
If the proposal is to deepen dire Attach the Bond under which it following completion of the in- testing has been completed. Fi determined that the site is ready 10/08/04 Rig up casing or 5%D44 + .2%D167 + .2% D46 + .2%D13 13#Density	ectionally or reconthe work will be provided operations in al Abandonment of final inspect rew and run 5 1 4 1065 + .2% 1064	mplete horizontal performed or provise. If the operation at Notices shall be aion.) 1/2" 17# P-110 +.1%D13 12.2	lly, give subsurface loca ride the Bond No. on fil a results in a multiple co e filed only after all requ LT&C. Wash 8904' Density 2.14 yield.	tions and measured and to e with BLM/BIA. Requi impletion or recompletion irements, including reclar to 8919° FC @ 8,831° Tail w/ 1078xx PVL + :	rue vertical depired subsequent in a new intervention, have be Circ. cmt w 2%D44 +(BW recate pipe. S	ths of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has d 400sx 35/65 poz H + 6%D20 + VOW) +.2%D65 +.2%D167 +.2* Set slips 125K test well head PTED FOR RECORI OCT 1 4 2004
If the proposal is to deepen dire Attach the Bond under which it following completion of the in- testing has been completed. Fi determined that the site is ready 10/08/04 Rig up casing or 5%D44 + .2%D167 + .2% D46 + .2%D13 13#Density	ectionally or reconthe work will be provided operations in al Abandonment of final inspect rew and run 5 1 4 1065 + .2% 1064	mplete horizontal performed or provise. If the operation at Notices shall be aion.) 1/2" 17# P-110 +.1%D13 12.2	lly, give subsurface loca ride the Bond No. on fil a results in a multiple co e filed only after all requ LT&C. Wash 8904' Density 2.14 yield.	tions and measured and to e with BLM/BIA. Requi impletion or recompletion irements, including reclar to 8919° FC @ 8,831° Tail w/ 1078xx PVL + :	rue vertical depired subsequent in a new intervention, have be Circ. cmt w 2%D44 +(BW recate pipe. S	ths of all pertinent markers and zones reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has 4 400sx 35/65 poz H + 6%D20 + 70W) + 2%D65 + 2%D167 + .2% Set slips 125K test well head
If the proposal is to deepen dire. Attach the Bond under which it following completion of the intesting has been completed. Fi determined that the site is ready 10/08/04 Rig up casing cr 5%D44 + .2%D167 + .2%D46 + .2%D13 13#Density 2,500# ok.	ectionally or reconthe work will be provided operations in al Abandonmen y for final inspect rew and run 5 1 a D65 + .2% D64 7 1.41 yield 7.7 1	mplete horizontal performed or prov s. If the operation at Notices shall be ion.) 1/2" 17# P-110 +.1%D13 12.2 BPM bump plu	lly, give subsurface loca ride the Bond No. on fil a results in a multiple co e filed only after all requ LT&C. Wash 8904' Density 2.14 yield.	tions and measured and to e with BLM/BIA. Requi impletion or recompletion irements, including reclar to 8919° FC @ 8,831° Tail w/ 1078xx PVL + :	rue vertical depired subsequent in a new intervention, have be Circ. cmt w 2%D44 +(BW recate pipe. S	ths of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has d 400sx 35/65 poz H + 6%D20 + VOW) +.2%D65 +.2%D167 +.2* Set slips 125K test well head PTED FOR RECORI OCT 1 4 2004
If the proposal is to deepen dire. Attach the Bond under which it following completion of the intesting has been completed. Fi determined that the site is ready 10/08/04 Rig up casing cr 5%D44 + .2%D167 + .2%D46 + .2%D13 13#Density 2,500# ok.	ectionally or reconthe work will be provided operations in al Abandonmen y for final inspect rew and run 5 1 a D65 + .2% D64 7 1.41 yield 7.7 1	mplete horizontal performed or prov s. If the operation at Notices shall be ion.) 1/2" 17# P-110 +.1%D13 12.2 BPM bump plu	lly, give subsurface locaride the Bond No. on file results in a multiple coeffield only after all requirements. Wash 8904' Density 2.14 yield. 'eg 202 BBL FW held	tions and measured and to e with BLM/BIA. Requi impletion or recompletion irements, including reclar to 8919° FC @ 8,831° Tail w/ 1078xx PVL + :	rue vertical depired subsequent in a new intervention, have be Circ. cmt w 2%D44 +(BW recate pipe. S	ths of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has d 400sx 35/65 poz H + 6%D20 + VOW) +.2%D65 +.2%D167 +.2* Set slips 125K test well head PTED FOR RECORI OCT 1 4 2004
If the proposal is to deepen dire Attach the Bond under which it following completion of the in- testing has been completed. Fi determined that the site is ready 10/08/04 Rig up casing cr 5%D44 + .2%D167 + .2% D46 + .2%D13 13#Density 2,500# ok. 4. I hereby certify that the fore Name (Printed/Typed)	ectionally or reconthe work will be provided operations in al Abandonmen y for final inspect rew and run 5 1 a D65 + .2% D64 7 1.41 yield 7.7 1	mplete horizontal performed or prov s. If the operation at Notices shall be ion.) 1/2" 17# P-110 +.1%D13 12.2 BPM bump plu	lly, give subsurface locaride the Bond No. on file results in a multiple coeffield only after all requirements. Wash 8904' Density 2.14 yield. 'eg 202 BBL FW held	tions and measured and to e with BLM/BIA. Requimpletion or recompletion irements, including rectar to 8919° FC @ 8,831° Tail w/ 1078sx PVL + ok. Good circ. Recipi	rue vertical depired subsequent in a new intervention, have be Circ. cmt w 2%D44 +(BW recate pipe. S	ths of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has d 400sx 35/65 poz H + 6%D20 + VOW) +.2%D65 +.2%D167 +.2* Set slips 125K test well head PTED FOR RECORI OCT 1 4 2004
If the proposal is to deepen dire Attach the Bond under which it following completion of the int testing has been completed. Fit determined that the site is ready 10/08/04 Rig up casing or 5%D44 + .2%D167 + .2% D46 + .2%D13 13#Density 2,500# ok. 4. I hereby certify that the fore Name (Printed/Typed) Josh Fernau	ectionally or reconthe work will be produced operations and Abandonmen y for final inspect rew and run 5 1 4 1 4 1 yield 7.7 1 1 4 1 yield 7.7 1 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	mplete horizontal cerformed or prov s. If the operation t Notices shall be ion.) 1/2" 17# P-110 +.1%D13 12.2 BPM bump plu	lly, give subsurface locaride the Bond No. on fit in results in a multiple confidence of filed only after all requirements. Wash 8904' Density 2.14 yield. 'Ing 202 BBL FW held	tions and measured and to e with BLM/BIA. Requimpletion or recompletion irements, including rectar to 8919° FC @ 8,831° Tail w/ 1078sx PVL + ok. Good circ. Recipi	rue vertical depired subsequent in a new intervention, have be Circ. cmt w 2%D44 +(BW rocate pipe. S	ths of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has d 400sx 35/65 poz H + 6%D20 + VOW) +.2%D65 +.2%D167 +.2* Set slips 125K test well head PTED FOR RECORI OCT 1 4 2004
Attach the Bond under which it following completion of the intesting has been completed. Fit determined that the site is ready 10/08/04 Rig up casing cr 5%D44 + .2%D167 + .2%D46 + .2%D13 13#Density 2,500# ok. 4. I hereby certify that the fore Name (Printed/Typed) Josh Fernau	ectionally or reconthe work will be produced operations and Abandonmen y for final inspect rew and run 5 1 4 1 4 1 yield 7.7 1 1 4 1 yield 7.7 1 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	mplete horizontal cerformed or prov s. If the operation t Notices shall be ion.) 1/2" 17# P-110 +.1%D13 12.2 BPM bump plu	lly, give subsurface locaride the Bond No. on fit in results in a multiple confidence of filed only after all requirements. Wash 8904' Density 2.14 yield. 'Ing 202 BBL FW held	tions and measured and to e with BLM/BIA. Requimpletion or recompletion irements, including reclar to 8919' FC @ 8,831' Fail w/ 1078sx PVL + ok. Good circ. Recipi	rue vertical depired subsequent in a new intervention, have be Circ. cmt w 2%D44 +(BW rocate pipe. S	ths of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once en completed, and the operator has d 400sx 35/65 poz H + 6%D20 + VOW) +.2%D65 +.2%D167 +.2* Set slips 125K test well head PTED FOR RECORI OCT 1 4 2004