

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

| |
|---|
| WELL API NO. 30-005-63660 |
| 5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 6. State Oil & Gas Lease No. |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other ☐

RECEIVED

2. Name of Operator
Primero Operating, Inc.

SEP 03 2004

3. Address of Operator
PO Box 1433, Roswell, NM 88202

OOD-ARTESIA

4. Well Location

Unit Letter D : 990 feet from the North line and 660 feet from the West line

Section 17 Township 10S Range 29E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3894 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Commenced Drilling operations on June 7, 2004. Drilled a 12 1/4" hole to 558'. Ran 8 5/8" casing equipped with insert float, and Texas pattern shoe to TD. Cemented casing with 350 sx Class C cement w/ 2% CaCl, circulating 257 sx to pit. Tested casing to 900 psi and it held OK. Drilled out of 8 5/8" on June 23 and drilled a 7 7/8" hole to 2957'. Logged hole w/ CNL Density and Induction log. RIH w/ 4 1/2" 10.5# J-55 casing equipped with Texas pattern shoe, insert float and 5 centralizers. Cement Casing with 200 sx 50/50 poz cement w/ 5# salt. Plug down at 3:23pm 7/5/04.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE President DATE 9/2/04

Type or print name Phelps White Telephone No. 505 622 1001
(For State use)

APPROVED BY [Signature] TITLE FOR RECORDS ONLY DATE SEP 14 2004
Conditions of approval, if any: